



Introducing the RQGIS package

Jannes Muenchow

2017-08-09

Installing QGIS



- **Follow** the steps described in `vignette(install_guide, package = "RQGIS")`!

Installing QGIS



- **Follow** the steps described in `vignette(install_guide, package = "RQGIS")`!
- Windows users: Use the [OSGeo-network-installer](#) (also described in the vignette)!

Installing RQGIS



You can either install the developer...

```
devtools::install_github("jannes-m/RQGIS")
```

Installing RQGIS



You can either install the developer...

```
devtools::install_github("jannes-m/RQGIS")
```

... or the CRAN version

```
install.packages("RQGIS")
```

Installing RQGIS



You can either install the developer...

```
devtools::install_github("jannes-m/RQGIS")
```

... or the CRAN version

```
install.packages("RQGIS")
```

For more information and a short introduction by example refer to:

<https://github.com/jannes-m/RQGIS>


RQGIS by example



To introduce the RQGIS package, let's find the intersection between two polygons. For this we create two polygons using the `sf`-package.

```
library("sf")
coords_1 <-
  matrix(data =
    c(0, 0, 1, 0, 1, 1, 0, 1, 0, 0),
    ncol = 2, byrow = TRUE)
coords_2 <-
  matrix(data =
    c(-0.5, -0.5, 0.5, -0.5, 0.5,
      0.5, -0.5, 0.5, -0.5, -0.5),
    ncol = 2, byrow = TRUE)

poly_1 <- st_polygon(list((coords_1))) %>%
  st_sfc(crs = 4326) %>%
  st_sf
poly_2 <- st_polygon(list((coords_2))) %>%
  st_sfc(crs = 4326) %>%
  st_sf
plot(poly_1, xlim = c(-1, 1), ylim = c(-1, 1))
plot(poly_2, add = TRUE)
```



Want to learn more about `sf` and geocomputation with R



```
vignette(package = "sf")
```


Want to learn more about `sf` and geocomputation with R



```
vignette(package = "sf")
```

And there's a new book to appear but you can already read it online:

<http://robinlovelace.net/geocompr/>

Find a QGIS algorithm



Now we would like to know which QGIS geoalgorithm we can use for this task. We assume that the word `intersec` will be part of the short description of the searched geoalgorithm

```
library("RQGIS")  
find_algorithms("intersec", name_only = TRUE)
```

```
## [1] "qgis:intersection"          "qgis:lineintersections"  
## [3] "saga:fuzzyintersectionand"  "saga:intersect"  
## [5] "saga:linepolygonintersection" "saga:polygonlineintersection"
```

How to use it



To find out the parameter names and corresponding default values, use `get_usage`.

```
get_usage("qgis:intersection")
```

```
## ALGORITHM: Intersection  
## INPUT <ParameterVector>  
## INPUT2 <ParameterVector>  
## OUTPUT <OutputVector>
```

How to use it



To find out the parameter names and corresponding default values, use `get_usage`.

```
get_usage("qgis:intersection")
```

```
## ALGORITHM: Intersection  
##      INPUT <ParameterVector>  
##      INPUT2 <ParameterVector>  
##      OUTPUT <OutputVector>
```

Here, we only have three function arguments, and automatic parameter collection is not necessary, but when I first looked at...

```
get_usage("grass7:r.slope.aspect")
```



```
ALGORITHM: r.slope.aspect - Generates raster layers of slope, aspect,
elevation <ParameterRaster>
format <ParameterSelection>
precision <ParameterSelection>
-a <ParameterBoolean>
zscale <ParameterNumber>
min_slope <ParameterNumber>
GRASS_REGION_PARAMETER <ParameterExtent>
GRASS_REGION_CELLSIZE_PARAMETER <ParameterNumber>
slope <OutputRaster>
aspect <OutputRaster>
pcurvature <OutputRaster>
tcurvature <OutputRaster>
dx <OutputRaster>
dy <OutputRaster>
dxx <OutputRaster>
dyy <OutputRaster>
dxy <OutputRaster>

format(Format for reporting the slope)
  0 - degrees
  1 - percent
precision(Type of output aspect and slope layer)
  0 - FCELL
  1 - CELL
  2 - DCELL
```



But looking at the QGIS GUI.



r.slope.aspect - Generates raster layers of slope, aspect, curvatures and partial derivatives from a... ? X

Parameters Log Help Run as batch process...

Elevation
[Dropdown menu] ...

Format for reporting the slope
degrees [Dropdown menu]

Type of output aspect and slope layer
CELL [Dropdown menu]

Multiplicative factor to convert elevation units to meters
1,000000 [Spin box] ...

Minimum slope val. (in percent) for which aspect is computed
0,000000 [Spin box] ...

GRASS GIS 7 region extent (xmin, xmax, ymin, ymax)
[Leave blank to use min covering extent] ...

GRASS GIS 7 region cellsize (leave 0 for default)
0,000000 [Spin box] ...

Slope
[Save to temporary file] ...

0%

Run Close

Convenience function

get_args_man



```
params <- get_args_man(alg = "grass7:r.slope.aspect")
params[1:10]
```

```
## $elevation
## [1] "None"
##
## $format
## [1] "0"
##
## $precision
## [1] "0"
##
## $`-a`
## [1] "True"
##
## $zscale
## [1] "1.0"
```

```
## $min_slope
## [1] "0.0"
##
## $GRASS_REGION_PARAMETER
## [1] "\"None\""
##
## $GRASS_REGION_CELL_SIZE_PARAMETER
## [1] "0.0"
##
## $slope
## [1] "None"
##
## $aspect
## [1] "None"
```

Access the online help



By the way, use `open_help` to access the online help and possibly find out more about a specific gealgorithm:

```
library("RQGIS")  
open_help(alg = "grass7:r.slope.aspect")
```



GRASS GIS manual: r.slope.aspect - Mozilla Firefox

File Edit View History Bookmarks Tools Help

GitHub - jannes-m/RQGIS... GRASS GIS manual: r.slope...

https://grass.osgeo. Search

Google Web of Science Google Scholar metacoon Friedolin Bookmarks



[Table of contents](#)

NAME

r.slope.aspect - Generates raster maps of slope, aspect, curvatures and partial derivatives from an elevation raster map. Aspect is calculated counterclockwise from east.

KEYWORDS

[raster](#), [terrain](#), [aspect](#), [slope](#), [curvature](#)

SYNOPSIS


```
r.slope.aspect
r.slope.aspect --help
r.slope.aspect [-a] elevation=name [slope=name] [aspect=name]
[format=string] [precision=string] [pcurvature=name]
[tcurvature=name] [dx=name] [dy=name] [dxx=name] [dyy=name]
```



Back to our use case



We have created two polygons using `sf`, and would like to find the intersection between the two.



Back to our use case



We also know the name of the geoalgorithm (`qgis:intersection`), and its parameters

```
## ALGORITHM: Intersection
## INPUT <ParameterVector>
## INPUT2 <ParameterVector>
## OUTPUT <OutputVector>
```

Back to our use case



We also know the name of the geoalgorithm (`qgis:intersection`), and its parameters

```
## ALGORITHM: Intersection
##      INPUT <ParameterVector>
##      INPUT2 <ParameterVector>
##      OUTPUT <OutputVector>
```

Hence, we have to specify `INPUT`, `INPUT2` and `OUTPUT`. We can do so using R named arguments.

Run QGIS from within R



```
int <- run_qgis("qgis:intersection",  
               INPUT = poly_1,  
               INPUT2 = poly_2,  
               OUTPUT = "out.shp",  
               load_output = TRUE)
```

```
## $OUTPUT  
## [1] "C:\\Users\\pi37pat\\AppData\\Local\\Temp\\RtmpUtxtgA/out.shp"
```

Spatial objects as inputs



```
int <- run_qgis("qgis:intersection",  
               INPUT = poly_1,  
               INPUT2 = poly_2,  
               OUTPUT = "out.shp",  
               load_output = TRUE)
```

Load QGIS output into R




```
int <- run_qgis("qgis:intersection",  
               INPUT = poly_1,  
               INPUT2 = poly_2,  
               OUTPUT = "out.shp",  
               load_output = TRUE)
```

Visualizing the result



```
plot(poly_1, xlim = c(-1, 1),  
      ylim = c(-1, 1))  
plot(poly_2, add = TRUE)  
plot(int, col = "lightblue",  
      add = TRUE)
```



Your turn



1. Let us (together) reproduce the `qgis:intersection` example (download code).

Your turn



1. Let us (together) reproduce the `qgis:intersection` example (download code).
2. Since we could also use `sf` to do the intersection (see also task 3), we will now compute the SAGA wetness index - an gealgorithm unavailalbe in R.
Calculate the SAGA wetness index of `data(dem)` using RQGIS. If you are faster than the others or if you have trouble using SAGA, calculate the slope, the aspect (and the curvatures) of `data(dem)` using GRASS through RQGIS.

Your turn



1. Let us (together) reproduce the `qgis:intersection` example (download code).
2. Since we could also use `sf` to do the intersection (see also task 3), we will now compute the SAGA wetness index - an gealgorithm unavailalbe in R.
Calculate the SAGA wetness index of `data(dem)` using RQGIS. If you are faster than the others or if you have trouble using SAGA, calculate the slope, the aspect (and the curvatures) of `data(dem)` using GRASS through RQGIS.
3. If you are faster than the others, calculate the intersection of `poly_1` and `poly_2` with the help of `sf`, SAGA and/or GRASS (hint: `overlay` and `open_help`).