

# Introduction to R

Maximilian Kasy

Fall 2019

# Agenda

- ▶ Comparison of R to its alternatives
- ▶ Ressources for learning R
- ▶ Installing R
- ▶ An introductory R session

# Why R?

- ▶ Most popular environment in statistics and machine learning communities.
- ▶ Open source, fast growing ecosystem.
- ▶ Packages for almost everything:
  - ▶ Data processing and cleaning
  - ▶ Data visualization
  - ▶ Interactive web-apps
  - ▶ Typesetting, writing articles and slides
  - ▶ The newest machine learning routines
  - ▶ ...
- ▶ Accomplishes the things you might be used to doing in Stata (data processing, fitting standard models) and those you might be used to doing in Matlab (numerical programming).
- ▶ High level language that (mostly) avoids having to deal with technicalities.

## Alternatives to R

- ▶ **Stata** (proprietary): Most popular statistical software in economics, easy to use for standard methods, not a good programming language.
- ▶ **Matlab** (proprietary): Numerical programming environment, matrix based. Programming in (base) R is quite similar to Matlab.
- ▶ **Python** (open): General purpose programming language, standard in industry, not targeted toward data analysis and statistics, but lots of development for machine learning. More overhead to write relative to R.
- ▶ **Julia** (open): New language for numerical programming, fast, increasingly popular in macro / for solving complicated structural models, not geared toward data analysis.

# Installing R, RStudio, and tidyverse

- ▶ **Install R:**

<https://cran.rstudio.com/>

- ▶ **Install RStudio:**

<https://www.rstudio.com/products/rstudio/download/>

- ▶ **Install tidyverse** packages: Type in RStudio terminal

```
install.packages("tidyverse")
```

- ▶ You will often install other packages using this command.

# Resources for learning R

- ▶ **An Introduction to R**

Complete introduction to base R. My recommended place to get started.

<https://cran.r-project.org/doc/manuals/r-release/R-intro.pdf>

- ▶ **R for Data Science**

Introduction to data analysis using R, focused on the tidyverse packages. If your goal is to find a substitute for Stata, start here.

<http://r4ds.had.co.nz/>

- ▶ **Advanced R**

In-depth discussion of programming in R. Read later, if you want to become a good R programmer.

<https://adv-r.hadley.nz/>

# Resources for data visualization in R

- ▶ **Data Visualization - A Practical Introduction**

Textbook on data visualization, using ggplot2. <http://socviz.co/>

- ▶ **ggplot2 - Elegant Graphics for Data Analysis**

In depth discussion of R-package for data vizualization.

<http://moderngraphics11.pbworks.com/f/ggplot2-Book09hWickham.pdf>

- ▶ **An Economist's Guide to Visualizing Data**

Guidelines for good visualizations (not R-specific).

<https://pubs.aeaweb.org/doi/pdfplus/10.1257/jep.28.1.209>

- ▶ **A Layered Grammar of Graphics**

The theory behind ggplot2.

[https://byrneslab.net/classes/biol607/readings/wickham\\_layered-grammar.pdf](https://byrneslab.net/classes/biol607/readings/wickham_layered-grammar.pdf)

## Resources for learning extensions to R

- ▶ **Programming interactive R-apps using Shiny**

Useful if you want to make your methods easy to use for people not familiar with R, or want to include interactive visualizations in web-pages.

<https://shiny.rstudio.com/articles/>

- ▶ **Markdown**

A lightweight markup language.

<https://www.markdownguide.org/>

- ▶ **R markdown** Integrate code and output into typeset documents and slides. These slides are written in R markdown. <https://rmarkdown.rstudio.com/lesson-1.html>

- ▶ **RStudio Cheat Sheets**

Cheatsheets for numerous packages.

<https://www.rstudio.com/resources/cheatsheets/>



## A sample session in R

- ▶ Please type the commands on the following slides in your RStudio terminal.
- ▶ This session is based on [https://en.wikibooks.org/wiki/R\\_Programming/Sample\\_Session](https://en.wikibooks.org/wiki/R_Programming/Sample_Session)
- ▶ R can be used as a simple calculator and we can perform any simple computation.

```
# Sample Session
```

```
# This is a comment
```

```
2 # print a number
```

```
2+3 # perform a simple calculation
```

```
log(2) # natural log
```

## A sample session in R

- R can be used as a simple calculator and we can perform any simple computation.

```
# Sample Session  
# This is a comment  
2 # print a number
```

```
## [1] 2
```

```
2+3 # perform a simple calculation
```

```
## [1] 5
```

```
log(2) # natural log
```

```
## [1] 0.6931472
```

## Numeric and string objects.

```
x = 2 # store an object
```

```
x # print this object
```

```
(x = 3) # store and print an object
```

```
x = "Hello" # store a string object
```

```
x
```

## Numeric and string objects.

```
x = 2 # store an object  
x # print this object
```

```
## [1] 2
```

```
(x = 3) # store and print an object
```

```
## [1] 3
```

```
x = "Hello" # store a string object  
x
```

```
## [1] "Hello"
```

## Vectors.

```
#store a vector  
Height =  
  c(168, 177, 177, 177, 178, 172, 165, 171, 178, 170)  
Height[2] # Print the second component  
  
# Print the second, the 3rd, the 4th and 5th component  
Height[2:5]  
  
(obs = 1:10) # Define a vector as a sequence (1 to 10)
```

## Vectors.

```
#store a vector
Height =
  c(168, 177, 177, 177, 178, 172, 165, 171, 178, 170)
Height[2] # Print the second component

## [1] 177

# Print the second, the 3rd, the 4th and 5th component
Height[2:5]

## [1] 177 177 177 178

(obs = 1:10) # Define a vector as a sequence (1 to 10)

## [1] 1 2 3 4 5 6 7 8 9 10
```

## Vectors 2

```
Weight = c(88, 72, 85, 52, 71, 69, 61, 61, 51, 75)
```

```
# Performs a simple calculation using vectors
```

```
BMI = Weight/((Height/100)^2)
```

```
BMI
```

## Vectors 2

```
Weight = c(88, 72, 85, 52, 71, 69, 61, 61, 51, 75)
```

```
# Performs a simple calculation using vectors
```

```
BMI = Weight/((Height/100)^2)
```

```
BMI
```

```
## [1] 31.17914 22.98190 27.13141 16.59804 22.40879 23.32342 22.40588
```

```
## [8] 20.86112 16.09645 25.95156
```



## Vectors 3

- ▶ We can also describe the vector with **length()**, **mean()** and **var()**.

```
length(Height)
```

```
mean(Height) # Compute the sample mean
```

```
var(Height)
```

## Vectors 3

- We can also describe the vector with **length()**, **mean()** and **var()**.

```
length(Height)
```

```
## [1] 10
```

```
mean(Height) # Compute the sample mean
```

```
## [1] 173.3
```

```
var(Height)
```

```
## [1] 22.23333
```

## Matrices.

```
M = cbind(obs,Height,Weight,BMI) # Create a matrix  
typeof(M) # Give the type of the matrix  
  
class(M) # Give the class of an object  
  
is.matrix(M) # Check if M is a matrix  
  
dim(M) # Dimensions of a matrix
```

## Matrices.

```
M = cbind(obs,Height,Weight,BMI) # Create a matrix  
typeof(M) # Give the type of the matrix
```

```
## [1] "double"
```

```
class(M) # Give the class of an object
```

```
## [1] "matrix"
```

```
is.matrix(M) # Check if M is a matrix
```

```
## [1] TRUE
```

```
dim(M) # Dimensions of a matrix
```

```
## [1] 10 4
```


## Simple plotting

- ▶ For “quick and dirty” plots, use **plot**.
- ▶ For more advanced and attractive data visualizations, use **ggplot**.

```
plot(Height,Weight,ylab="Weight",xlab="Height")
```

## Simple plotting

```
plot(Height,Weight,ylab="Weight",xlab="Height")
```



## Dataframes (tibbles)

- ▶ **tibbles** are modernized versions of **dataframes**.
- ▶ Technically: Lists of vectors (with names).
- ▶ Can have different datatypes in different vectors.

```
library(tibble) # Load the tidyverse tibble package  
mydat = as_tibble(M) # Creates a dataframe  
names(mydat) # Give the names of each variable  
  
summary(mydat) # Descriptive Statistics
```

# Dataframes

```
library(tibble) # Load the tidyverse tibble package
mydat = as_tibble(M) # Creates a tibble
names(mydat) # Give the names of each variable
```

```
## [1] "obs"      "Height" "Weight" "BMI"
```

```
summary(mydat) # Descriptive Statistics
```

##	obs	Height	Weight	BMI
##	Min. : 1.00	Min. :165.0	Min. :51.00	Min. :16.10
##	1st Qu.: 3.25	1st Qu.:170.2	1st Qu.:61.00	1st Qu.:21.25
##	Median : 5.50	Median :174.5	Median :70.00	Median :22.70
##	Mean : 5.50	Mean :173.3	Mean :68.50	Mean :22.89
##	3rd Qu.: 7.75	3rd Qu.:177.0	3rd Qu.:74.25	3rd Qu.:25.29
##	Max. :10.00	Max. :178.0	Max. :88.00	Max. :31.18



## Reading and writing data

- ▶ There are many routines for reading and writing files.
- ▶ Tidyverse versions are in the readr package.

```
library(readr) #load the tidyverse readr package  
write_csv(mydat, "my_data.csv")  
mydat2=read_csv("my_data.csv")  
mydat2
```

## Reading and writing data

```
library(readr) #load the tidyverse readr package  
write_csv(mydat, "my_data.csv")  
mydat2=read_csv("my_data.csv")
```

```
## Parsed with column specification:  
## cols(  
##   obs = col_double(),  
##   Height = col_double(),  
##   Weight = col_double(),  
##   BMI = col_double()  
## )
```

## Reading and writing data

```
mydat2
```

```
## # A tibble: 10 x 4
##      obs Height Weight  BMI
##    <dbl> <dbl> <dbl> <dbl>
##  1     1    168     88  31.2
##  2     2    177     72  23.0
##  3     3    177     85  27.1
##  4     4    177     52  16.6
##  5     5    178     71  22.4
##  6     6    172     69  23.3
##  7     7    165     61  22.4
##  8     8    171     61  20.9
##  9     9    178     51  16.1
## 10    10    170     75  26.0
```

## Special characters in R

- ▶ **NA**: Not Available (i.e. missing values)
- ▶ **NaN**: Not a Number (e.g.  $0/0$ )
- ▶ **Inf**: Infinity
- ▶ **-Inf**: Minus Infinity. For instance  $0$  divided by  $0$  gives a **NaN**, but  $1$  divided by  $0$  gives **Inf**.

$0/0$

$1/0$

## Special characters in R

- ▶ **NA**: Not Available (i.e. missing values)
- ▶ **NaN**: Not a Number (e.g.  $0/0$ )
- ▶ **Inf**: Infinity
- ▶ **-Inf**: Minus Infinity. For instance 0 divided by 0 gives a **NaN**, but 1 divided by 0 gives **Inf**.

```
0/0
```

```
## [1] NaN
```

```
1/0
```

```
## [1] Inf
```

## Working directory

We can define a working directory. Note for Windows users : R uses slash ("/") in the directory instead of backslash ("").

```
setwd("~/Desktop") # Sets working directory  
getwd() # Returns current working directory  
  
dir() # Lists the content of the working directory
```

## Defining functions

- ▶ Whenever you program something more involved, you should use functions.
- ▶ R makes it easy to provide default arguments.

```
example_function = function(a, b=2) {  
  r=a/b  
  return(r)  
}
```

```
example_function(3)
```

```
example_function(3,4)
```

## Defining functions

```
example_function = function(a, b=2) {  
  r=a/b  
  return(r)  
}
```

```
example_function(3)
```

```
## [1] 1.5
```

```
example_function(3,4)
```

```
## [1] 0.75
```



## Linear regressions

- ▶ R makes it easy to fit linear regressions and other models
- ▶ The objects returned contain coefficients, residuals, fitted values, etc.

```
example_regression = lm(Height ~ Weight + BMI, mydat)
```

```
summary(example_regression)
```

## Linear regressions

```
example_regression = lm(Height ~ Weight + BMI, mydat)
summary(example_regression)
```

```
##
## Call:
## lm(formula = Height ~ Weight + BMI, data = mydat)
##
## Residuals:
```

##	Min	1Q	Median	3Q	Max
##	-1.0168	-0.5849	-0.1534	0.4682	1.4380

```
##
## Coefficients:
```

##		Estimate	Std. Error	t value	Pr(> t )	
##	(Intercept)	174.24291	1.68433	103.45	2.08e-12	***
##	Weight	1.20911	0.08745	13.83	2.45e-06	***
##	BMI	-3.65895	0.23993	-15.25	1.26e-06	***

```
## ---
```

## Some further important commands

- ▶ Look up the help files for the following commands:

```
map()  
ggplot()
```