



header	a logical value indicating whether the file contains the names of the variables as its first line. If missing, the value is determined from the file format: <code>header</code> is set to <code>TRUE</code> if and only if the first row contains one fewer field than the number of columns.
--------	--

header	a logical value indicating whether the file contains the names of the variables as its first line. If missing, the value is determined from the file format: <code>header</code> is set to <code>TRUE</code> if and only if the first row contains one fewer field than the number of columns.
--------	--

<code>sep</code>	the field separator character. Values on each line of the file are separated by this character. If <code>sep = " "</code> (the default for <code>read.table</code> ) the separator is ‘white space’, that is one or more spaces, tabs, newlines or carriage returns.
------------------	--

header	a logical value indicating whether the file contains the names of the variables as its first line. If missing, the value is determined from the file format: <code>header</code> is set to <code>TRUE</code> if and only if the first row contains one fewer field than the number of columns.
sep	the field separator character. Values on each line of the file are separated by this character. If <code>sep = " "</code> (the default for <code>read.table</code> ) the separator is ‘white space’, that is one or more spaces, tabs, newlines or carriage returns.

<code>na.strings</code>	a character vector of strings which are to be interpreted as <u>NA</u> values. Blank fields are also considered to be missing values in logical, integer, numeric and complex fields. Note that the test happens <i>after</i> white space is stripped from the input, so <code>na.strings</code> values may need their own white space stripped in advance.
-------------------------	---

header	a logical value indicating whether the file contains the names of the variables as its first line. If missing, the value is determined from the file format: <code>header</code> is set to <code>TRUE</code> if and only if the first row contains one fewer field than the number of columns.
sep	the field separator character. Values on each line of the file are separated by this character. If <code>sep = " "</code> (the default for <code>read.table</code> ) the separator is ‘white space’, that is one or more spaces, tabs, newlines or carriage returns.
<code>na.strings</code>	a character vector of strings which are to be interpreted as <u>NA</u> values. Blank fields are also considered to be missing values in logical, integer, numeric and complex fields. Note that the test happens <i>after</i> white space is stripped from the input, so <code>na.strings</code> values may need their own white space stripped in advance.

stringsAsFactors	logical: should character vectors be converted to factors? Note that this is overridden by <code>as.is</code> and <code>colClasses</code> , both of which allow finer control.
------------------	--



header	a logical value indicating whether the file contains the names of the variables as its first line. If missing, the value is determined from the file format: <code>header</code> is set to <code>TRUE</code> if and only if the first row contains one fewer field than the number of columns.
sep	the field separator character. Values on each line of the file are separated by this character. If <code>sep = " "</code> (the default for <code>read.table</code> ) the separator is ‘white space’, that is one or more spaces, tabs, newlines or carriage returns.
<code>na.strings</code>	a character vector of strings which are to be interpreted as <u>NA</u> values. Blank fields are also considered to be missing values in logical, integer, numeric and complex fields. Note that the test happens <i>after</i> white space is stripped from the input, so <code>na.strings</code> values may need their own white space stripped in advance.
<code>stringsAsFactors</code>	logical: should character vectors be converted to factors? Note that this is overridden by <code>as.is</code> and <code>colClasses</code> , both of which allow finer control.

<code>strip.white</code>	logical. Used only when <code>sep</code> has been specified, and allows the stripping of leading and trailing white space from unquoted <code>character</code> fields ( <code>numeric</code> fields are always stripped). See <a href="#">scan</a> for further details (including the exact meaning of ‘white space’), remembering that the columns may include the row names.
--------------------------	--

header	a logical value indicating whether the file contains the names of the variables as its first line. If missing, the value is determined from the file format: header is set to TRUE if and only if the first row contains one fewer field than the number of columns.
sep	the field separator character. Values on each line of the file are separated by this character. If sep = " " (the default for read.table) the separator is ‘white space’, that is one or more spaces, tabs, newlines or carriage returns.
na.strings	a character vector of strings which are to be interpreted as <u>NA</u> values. Blank fields are also considered to be missing values in logical, integer, numeric and complex fields. Note that the test happens <i>after</i> white space is stripped from the input, so na.strings values may need their own white space stripped in advance.
stringsAsFactors	logical: should character vectors be converted to factors? Note that this is overridden by as.is and colClasses, both of which allow finer control.
strip.white	logical. Used only when sep has been specified, and allows the stripping of leading and trailing white space from unquoted character fields (numeric fields are always stripped). See <u>scan</u> for further details (including the exact meaning of ‘white space’), remembering that the columns may include the row names.



"Details": more details than you usually need about how the function does what it does



## Details

This function is the principal means of reading tabular data into **R**.

Unless `colClasses` is specified, all columns are read as character columns and then converted using [type.convert](#) to logical, integer, numeric, complex or (depending on `as.is`) factor as appropriate. Quotes are (by default) interpreted in all fields, so a column of values like "42" will result in an integer column.

A field or line is 'blank' if it contains nothing (except whitespace if no separator is specified) before a comment character or the end of the field or line.

If `row.names` is not specified and the header line has one less entry than the number of columns, the first column is taken to be the row names. This allows data frames to be read in from the format in which they are printed. If `row.names` is specified and does not refer to the first column, that column is discarded from such files.

The number of data columns is determined by looking at the first five lines of input (or the whole input if it has less than five lines), or from the length of `col.names` if it is specified and is longer. This could conceivably be wrong if `fill` or `blank.lines.skip` are true, so specify `col.names` if necessary (as in the 'Examples').

`read.csv` and `read.csv2` are identical to `read.table` except for the defaults. They are intended for reading 'comma separated value' files (`' .csv '`) or