

Introduction to \mathcal{R}

Sessions 3: Data management

Dag Tanneberg¹

Potsdam Center for Quantitative Research
University of Potsdam, Germany
October 11/12, 2018

¹Chair of Comparative Politics, UP dag.tanneberg@uni-potsdam.de

Introduction

Outline

- 1 Introduction
- 2 Sequential Execution
- 3 Iterative Execution
- 4 Conditional Execution
- 5 Summary

Sequential Execution

Sequential Execution

- Run a script
 - step by step;
 - from start to end.

```
A <- "Well"
B <- "hello there."
paste(A, B, sep = ", ")
rm(A B) # Explain the error.
```

Iterative Execution

A.k.a. Looping

- Execute statement(s) repeatedly
 - a. over a set of values
 - b. as long as some condition holds
 - c. until an abort condition is met
- Includes: for, while, and repeat
- Typical use-case: transform several variables

for()-Loops²

- repeats statements for each element on an input set

```
# Generic example
for (VALUE in THAT) { # Do THIS for each VALUE in THAT
  THIS
}

# A first working example
for (value in c("Waiting", "for", "statistics.")) {
  print(value)
}
```

- for() creates an object called VALUE
- reassigns VALUE for each element in the set THIS

²People don't like for(). For alternatives see <https://bit.ly/2IEbeGj>.

for()-Loops, contd.

- `for()` returns nothing unless told to³
- Save the output to an object
- Good practice:
 - Execute on a set of integers
 - Index both object and storage simultaneously

```
words <- c("So", "how's", "looping", "so", "far?")  
chr <- vector("character", length = length(words))  
for (i in 1:length(words)){  
  chr[i] <- words[i]  
}
```

³“for loops are like Las Vegas: what happens in a for loop stays in a for loop”
(Gorrelmund 2014: 164).

While()-Loops

- Rerun statement(s) as long as some condition is TRUE
- Condition should be a logical test
- Remember “Groundhog Day”
 - Include a change of condition in the while()'s body!

```
k <- 0
while (k < 20) {
  k <- k + 1
  print("Still running")
}
```

- Returns anything unless told to

Repeat()-Statements

- Reruns statement(s) until meets **break**

```
chr <- "All work and no play makes Jack a dull boy"
k <- 0
repeat {
  print(chr)
  k <- k + 1
  if (k > 100) break
}
```

But...

How do we tell \mathcal{R} to execute some code conditionally?

Conditional Execution

if()-Statements

else()-Statements

Summary