CHAPTER

24

ELECTRICAL POWER



CHAPTER 24 ELECTRICAL POWER

Subje	ct/Page	Date	Subject/Page	Date	Subject/Page	Date
24-EF	FECTIVE	PAGES				
	1	Feb 05/2016				
	2	BLANK				
24-C0	ONTENTS	3				
0	1	Feb 05/2016				
	2	BLANK				
24-10	-01					
	1	Aug 05/2014				
	2	Aug 05/2014				
	3	Aug 05/2014				
	4	Aug 05/2014				
	5	Aug 05/2014				
	6	BLANK				
24-10						
	1	Aug 05/2014				
	2	Aug 05/2014				
24-20						
R	1	Feb 05/2016				
R	2	Feb 05/2016				
24-30		1 00 00/2010				
2.00	1	Aug 05/2015				
	2	Aug 05/2015				
24-30		7 tag 00/2010				
2100	1	Aug 05/2014				
	2	BLANK				
24-30		DEAINI				
24 00	1	Aug 05/2014				
24-30	2 -04	BLANK				
24-30	1	Aug 05/2015				
	2	Aug 05/2015 Aug 05/2015				
	3	Aug 05/2015 Aug 05/2015				
	4	Aug 05/2015 Aug 05/2015				
24-40		Aug 00/2010				
2,40	1	Aug 05/2014				
	2	Aug 05/2014				

A = Added, R = Revised, D = Deleted, O = Overflow

24-EFFECTIVE PAGES



CHAPTER 24 ELECTRICAL POWER

SUBJECT	TITLE	PART NO.
24	ELECTRICAL POWER	
24-10-01	JACK ADAPTER - VARIABLE SPEED CONSTANT FREQUENCY (VSCF) AND INTEGRATED DRIVE GENERATOR (IDG)	C24002-31, -39, -77, -78
24-10-02	PRESSURE TEST EQUIPMENT - ENGINE GENERATORS	J24015-1
24-20-01	POWER DISTRIBUTION PANEL (PDP)- REMOVAL AND INSTALLATION EQUIPMENT	C24004-1, -43
24-30-01	TRAY ASSEMBLY - BATTERY, REMOVAL AND INSTALLATION	C24003-1
24-30-02	TEST BOX - P5-4 PANEL, AC SYSTEM GENERATOR AND APU MODULE	C24005
24-30-03	TEST BOX - P5-5 GENERATOR DRIVE AND STANDBY POWER	C24006
24-30-04	BATTERY INSPECTION GAUGE TOOL	J24016-1
24-40-01	WEAR GAUGE SET - PLUG AND RECEPTACLE, GROUND POWER	F70284-1

24-CONTENTS



PART NUMBER: C24002-31, -39, -77, -78

NAME: JACK ADAPTER - VARIABLE SPEED CONSTANT FREQUENCY (VSCF)

AND INTEGRATED DRIVE GENERATOR (IDG)

AIRPLANE MAINTENANCE: YES

AMM 24-11-11

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The C24002-31 (option) or C24002-39 (preferred) variable speed constant

frequency (VSCF) and integrated drive generator (IDG) jack adapters are

only used on 737-300 thru -500 airplanes equipped with a VSCF

generator.

The C24002-77 (option) or C24002-78 (option) variable speed constant frequency and integrated drive generator jack adapters are used on

737-600 thru -900 airplanes.

C24002-31 or -39 is used in conjunction with a customer-furnished, low-profile, transmission jack (such as Hein-Werner No. 54 or No. 62 or Milwaukee No. 3000 transmission jack). C24002-31 or -39 is used to remove or install the variable speed constant frequency (VSCF) generator/

converter.

The C24002-77 or -78 are used in conjunction with a customer-furnished, low-profile, transmission jack (such as a Hein-Werner NO. 54 or NO. 62, Lincoln W93718 or the Milwaukee 3000). C24002-77 or -78 is used to remove or install the integrated drive generator on all 737-600 thru -900

airplanes.

C24002-77 is recommended when the customer-furnished, transmission

jack is used on floors that are not smooth finished concrete.

 ${\tt C24002-78}\ is\ recommended\ when\ the\ customer-furnished,\ transmission$

jack is used on floors that are smooth finished concrete.

Refer to the current C24002 tool drawing and AMM 24-11-11 for complete

usage instructions.

The C24002-31, -39, -77 and -78 variable speed constant frequency and

integrated drive generator jack adapter consist of:

C24002-31			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	VSCF ADAPTER ASSEMBLY	C24002-32	
1	STORAGE BOX		

C24002-39			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	JACK ADAPTER ASSEMBLY	C24002-68	
1	STORAGE BOX		

24-10-01



C24002-77			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	JACK ADAPTER ASSEMBLY	C24002-79	
1	STORAGE BOX		

C24002-78			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	JACK ADAPTER ASSEMBLY	C24002-80	
1	STORAGE BOX		

WEIGHT: 43 lbs (20 kg)


DIMENSIONS: 11 x 14 x 14 inches (279 x 356 x 356 mm)

NOTE: C24002-77 supersedes C24002-40 and C24002-45.

C24002-78 supersedes C24002-41.

C24002-39 replaces C24002-31 for future procurement.






C24002-31 and -39 VSCF Usage Figure 1

24-10-01

Page 3 Aug 05/2014






C24002-77 and -78 IDG Usage and Components Figure 2 (Sheet 1 of 2)

24-10-01


Page 4 Aug 05/2014





C24002-79 JACK ADAPTER ASSEMBLY (SLIDING BASE)





C24002-80 JACK ADAPTER ASSEMBLY (FIXED BASE)



2079203 S0000436305_V2

C24002-77 and -78 IDG Usage and Components Figure 2 (Sheet 2 of 2)

24-10-01

Page 5 Aug 05/2014



PART NUMBER: J24015-1

NAME: PRESSURE TEST EQUIPMENT - ENGINE GENERATORS

AIRPLANE MAINTENANCE: YES

AMM 24-11-00

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The J24015-1 engine generators pressure test equipment is used on all

737 airplanes.

J24015 applies compressed air or nitrogen to the integrated drive generator (IDG), constant speed drive (CSD) or variable speed, constant frequency (VSCF) oil system through the pressure fill fitting. The pressure is monitored for a pressure decrease. A continuous decrease in pressure

indicates a leak in the system.

Refer to AMM 24-11-00 and the current J24015 drawing for complete

usage instructions.


The J24015-1 engine generators pressure test equipment consists of:

J24015-1		
QUANTITY	NOMENCLATURE	PART NUMBER
1	PRESSURE TEST ASSEMBLY	J24015-4
1	STORAGE BOX	

WEIGHT: 21 lbs (10 kg)

DIMENSIONS: 12 x 15 x 18 inches (305 x 381 x 457 mm)





1564802 S0000290188_V2

Engine Generators Pressure Test Equipment Figure 1

24-10-02

Page 2 Aug 05/2014



PART NUMBER: C24004-1, -43

NAME: POWER DISTRIBUTION PANEL (PDP)- REMOVAL AND INSTALLATION

EQUIPMENT

AIRPLANE MAINTENANCE: YES

AMM 24-21-21

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The C24004-1 (option) and C24004 -43 (preferred) power distribution

panel are used on all 737-600 thru -900 airplanes.

C24004 is used to remove or install the power distribution panels (PDP P91 left and P92 right) on the E2-1 (left) and E3-1 (right) equipment shelves. C24004 includes handles to attach to the PDP's for lifting.

C24004 also includes a teflon topped, portable shelf to slide the PDP's out of the airplane. The shelf includes a leg for positioning and stability.

Refer to AMM 24-21-21 and the current C24004 drawing for complete

usage instructions.

C24004-1 and -43 consist of:

C24004-1			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	BASE ASSEMBLY	C24004-2	
2	HANDLE ASSEMBLY	C24004-5	
1	STORAGE BOX		

C24004-43			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	BASE ASSEMBLY	C24004-44	
2	HANDLE ASSEMBLY	C24004-5	
1	STORAGE BOX		


WEIGHT: 17 lbs (7.7 kg)

DIMENSIONS: 4 x 22 x 45 inches (102 x 559 x 1143 mm)

NOTE: C24004-43 replaces C24004-1 for future procurement.

24-20-01





Removal and Installation Equipment, Power Distribution Panel Figure 1

24-20-01



PART NUMBER: C24003-1

NAME: TRAY ASSEMBLY - BATTERY, REMOVAL AND INSTALLATION

AIRPLANE MAINTENANCE: YES

AMM 24-31-11

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The C24003-1 tray assembly is used on all 737 airplanes except 737-100

thru -500 airplanes.

C24003 is inserted underneath the main battery (and auxiliary battery, if installed). The battery is slid from the battery compartment and removed without damage to the access panel seal on the deck forward of the

battery compartment.

Refer to AMM 24-31-11 and the current C24003 drawing for complete

usage instructions.


C24003-1 consists of:

	C24003-1			
QUANTITY	NOMENCLATURE	PART NUMBER		
1	TRAY ASSEMBLY	C24003-2		
1	STORAGE BOX			

WEIGHT: 9 lbs (4 kg)

DIMENSIONS: 1 x 15 x 25 inches (25 x 381 x 635 mm)





Battery Removal and Installation Tray Assembly Figure 1

24-30-01

Page 2 Aug 05/2015



PART NUMBER: C24005

NAME: TEST BOX - P5-4 PANEL, AC SYSTEM GENERATOR AND APU

MODULE

AIRPLANE MAINTENANCE: NO

COMPONENT MAINTENANCE: YES

CMM 31-37-31

USAGE & DESCRIPTION: C24005 drawing has been transferred to BAE Systems and will no longer

be revised by Boeing. C24005 inclusion in the 737 ITEM is for information

and historical purposes only.

C24005 is used on all 737 airplanes equipped with P5-4 Module

Assembly. See CMM 31-37-31.



PART NUMBER: C24006

NAME: TEST BOX - P5-5 GENERATOR DRIVE AND STANDBY POWER

AIRPLANE MAINTENANCE: NO

COMPONENT MAINTENANCE: YES

CMM 31-10-41

USAGE & DESCRIPTION: C24006 drawing has been transferred to BAE Systems and will no longer

be revised by Boeing. C24006 inclusion in the 737 ITEM is for information

and historical purposes only.

C24006 is used on all 737 airplanes equipped with P5-5 module assembly.

See CMM 31-10-41.



PART NUMBER: J24016-1

NAME: BATTERY INSPECTION GAUGE TOOL

AIRPLANE MAINTENANCE: YES

AMM 24-31-11, AMM 24-31-12

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The J24016-1 battery inspection gauge tool is used on all 737 airplanes.

J24016 includes a two-ended, cylindrical, probe test tool. One end is machined to a 0.3850+/-0.0002 inch cylinder; the other end is machined to

a 0.3700+/-0.0002 inch cylinder.

J24016 is used to test two different types of battery connector power contacts to meet MS25182 requirements. The battery connector is generically identified as MS25182-2 and mates with the main and APU

batteries.

Both ends of J24016 are used to test power contacts of the spiral spring type (manufactured by Elcon). The 0.3850-inch end tests the resiliency of expansion to an oversized pin. The 0.3700-inch end checks for proper contact to a worn or undersized pin. The 0.3700-inch end of J24016 is used to test power contacts of the longitudinal spring type (manufactured by Rebling Plastics). The 0.3700-inch end checks for proper contact to a worn or undersized pin.

Refer to AMM 24-31-11, AMM 24-31-12 and the current J24016 drawing

for complete usage instructions.

J24016-1 consists of:


J24016-1			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	BATTERY INSPECTION GAUGE ASSEMBLY	J24016-2	
1	FORCE SCALE	J24016-3	
1	STORAGE BOX		

WEIGHT: 2 lbs (1 kg)

DIMENSIONS: 2 x 2 x 7 inches (51 x 51 x 178 mm)

24-30-04






Battery Gauge Inspection Tool Figure 1 (Sheet 1 of 3)

24-30-04






Battery Gauge Inspection Tool Figure 1 (Sheet 2 of 3)

24-30-04


Page 3 Aug 05/2015





J24016-2 BATTERY INSPECTION GAUGE ASSEMBLY





2037959 S0000410185_V3

Battery Gauge Inspection Tool Figure 1 (Sheet 3 of 3)

24-30-04

Page 4 Aug 05/2015



PART NUMBER: F70284-1

NAME: WEAR GAUGE SET - PLUG AND RECEPTACLE, GROUND POWER

AIRPLANE MAINTENANCE: YES

AMM 24-41-11

COMPONENT MAINTENANCE: NO

USAGE & DESCRIPTION: The F70284-1 wear gauge set is used on all 737 airplanes.

F70284 is used to check for wear on the pins and sockets of the ground

power plug and receptacle.

When used on the ground power plug's sockets, F70284 measures a minimum disengagement force of 10 pounds (4.5 kg) for each large socket

and 5 pounds (2.3 kg) for each small socket.

When used on the airplane's ground power receptacle, the F70284 acts as a go/no-go gauge by fitting over the receptacle pins. The receptacle pins

are worn if the gauge will fit over the pins.

Refer to AMM 24-41-11 and to the current F70284 drawing for complete

usage instructions.


F70284-1 consists of:

F70284-1			
QUANTITY	NOMENCLATURE	PART NUMBER	
1	WEAR GAUGE	F70284-2	
1	WEAR GAUGE	F70284-3	
1	INSTRUMENT SCALE	IN-25	
1	STORAGE BOX		

DIMENSIONS: 13 x 7 x 4 inches (330 x 179 x 102 mm)

NOTE: F70284 supersedes SE24-4001.





M52627 S0006831469_V3

Ground Power Plug and Receptacle Wear Gauge Set Figure 1

24-40-01

Page 2 Aug 05/2014