

CSE 417T: Homework 3

Due: March 19 (Friday), 2021

Notes:

- Please submit your homework via Gradescope and check the [submission instructions](#).
- There will be two submission links for homework 3: one for report and the other for code. **Your score will be based on the report.** The code you submit is only used for checking the correctness and for running plagiarism checkers.
- Make sure you **specify the pages for each problem correctly**. You **will not get points** for problems that are not correctly connected to the corresponding pages.
- Homework is due **by 11:59 PM on the due date**. Remember that you may not use more than 2 late days on any one homework, and you only have a budget of 5 in total.
- Please keep in mind the collaboration policy as specified in the course syllabus. If you discuss questions with others you **must** write their names on your submission, and if you use any outside resources you **must** reference them. **Do not look at each others' writeups, including code.**
- There are 4 problems on 2 pages in this homework.

Problems:

1. (40 points) The weight decay regularizer is also called L_2 regularizer, since $\vec{w}^T \vec{w}$ is the square of the 2-norm of the weight vector $\|\vec{w}\|_2 = \sqrt{\sum_{i=0}^d w_i^2}$. Another common regularizer is called L_1 regularizer, since 1-norm ($\|\vec{w}\|_1 = \sum_{i=0}^d |w_i|$) is used as the regularizer.

Below are the definitions of the two regularizations¹:

- L_1 regularization: $E_{aug}(\vec{w}) = E_{in}(\vec{w}) + \lambda \|\vec{w}\|_1$
- L_2 regularization: $E_{aug}(\vec{w}) = E_{in}(\vec{w}) + \lambda \vec{w}^T \vec{w}$

(a) Answer LFD Problem 4.8.

(b) Similar to Problem 4.8, derive the update rule of gradient descent for minimizing the augmented error with L_1 regularizer.

Note that the gradient of 1-norm is not well-defined at 0. To address this issue, we can utilize the *subgradient* idea defined as follows:

$$\frac{\partial}{\partial w_i} \|\vec{w}\|_1 = \begin{cases} +1 & \text{if } w_i > 0 \\ \text{any value in } [-1, 1] & \text{if } w_i = 0 \\ -1 & \text{if } w_i < 0 \end{cases}$$

¹When applying these regularizations to linear regression, they are called Ridge Regression (L_2 regularizer) and Lasso Regression (L_1 regularizer) respectively.

To simplify the discussion, we let $\frac{\partial}{\partial w_i} \|\vec{w}\|_1 = 0$ when $w_i = 0$. Please write down the update rule of gradient descent for L_1 regularization. (You can define a $\text{sign}()$ function that returns $+1, 0, -1$ when the input is positive, zero, negative, respectively).

Note for implementation: we can use *truncated* gradient [1] when implementing L_1 regularizer. Let $\vec{w}'(t+1) \leftarrow \vec{w}(t) - \eta \nabla E_{\text{in}}(\vec{w}(t))$ be the update rule of gradient descent without regularization. The update rule for L_1 regularization should be in the form of

$$\vec{w}(t+1) \leftarrow \vec{w}'(t+1) + \text{additional term}$$

The additional term represents the effect of L_1 regularization compared with no regularization. Truncated gradient works as follows: At each step t , you first perform the update as what you derive above. Then for each dimension i , if $w_i(t+1)$ and $w'_i(t+1)$ have different signs and when $w'_i(t+1) \neq 0$, we set the update $w_i(t+1)$ to 0 (i.e., we *truncate* the update if the additional term makes the new weight change signs).

- (c) Update your implementation of logistic regression in HW2 to include the L_1 and L_2 regularizers (use truncated gradient for L_1 regularizer). Conduct the following experiment and include the results in your report. Also submit the updated python implementation (feel free to update the function headers and/or define new functions).

You will be working with digits dataset, classifying whether a digit belongs to $\{1, 6, 9\}$ (labeled as -1) or $\{0, 7, 8\}$ (labeled as $+1$). The TA (Guanghui Yu) has pre-processed the data, which you can download below.

<http://chienjuho.com/courses/cse417t/hw3/hw3.html>

Examine different regularization strengths $\lambda = 0, 0.0001, 0.001, 0.005, 0.01, 0.05, 0.1$ for both L_1 and L_2 regularizations. Train your models on the training set. For each trained model, report (1) the classification error on the test set and (2) the number of 0s in your learned weight vector. Describe your observations and the property of the L_1 regularizer.

For the other parameters, please use the following. Normalize the features. Set learning rate $\eta = 0.01$. The maximum number of iterations is 10^4 . Terminate learning if the magnitude of every element of the gradient (of E_{in}) is less than 10^{-6} . When calculating classification error, classify the data using a cutoff probability of 0.5.

Note on code efficiency: While we don't grade on your code efficiency, you are encouraged to check out *vectorization* (if you haven't done so in your homework 2) to speed up your code. There will be very significant differences in terms of running time.

2. (15 points) LFD **Exercise** (not Problem) 4.5
3. (25 points) LFD Problem 4.25 (a) to (c)
4. (20 points) LFD Problem 5.4. The problem makes a simplifying definition: a stock is called "profitable" if it went up half of the days (and whether a stock goes up or down in a day is a random draw from a distribution that associates with how good that stock is). While this definition of "profitable" might not be accurate in practice, please use it for your discussion.

References

- [1] John Langford, Lihong Li, and Tong Zhang. Sparse online learning via truncated gradient. *Journal of Machine Learning Research*, 10:777801, 2009.