

PowerGlow Panel Light

Product Features

- Long LED life: 50,000 hours
- Flicker-free
- No UV or IR light radiation
- High CRI
- Homogeneous flood illumination
- Slim profile.
- Corrosion-resistant aluminium finishing
- Comes with replaceable power supply



IN-PA3C06 – Metallic silver border

Typical Applications

- Recessed lighting
- Bedrooms and kitchens
- Office corridors and lobbies
- Retail store lighting
- Commercial Lighting
- Mood lighting/General lighting



**IN-PA3S04 – Matt white border
with glass trim**

Product Specifications

Light Source	High Power SMD LED chips	Max. Depth	26mm (round) 88mm (square)
Power Consumption	12W or 18W (round) 7W (square)	Beam Angle	> 120° wide angle coverage
Input Voltage	AC 100-240V	Illumination	> 800 lm @ 1m (for 18W model)
Forward Current	375mA to 450mA	Operating Temperature	-20°C to 45°C
Optics	Frosted anti-glare cover	Colour	Warm white (3000K) or Cool white (6000K)
Model No. (hole cutout size)	IN-PA3C06 - 12W (160mm – 6 inch diameter) IN-PA3C08 - 18W (210mm – 8 inch diameter) IN-PA3S04 - 7W (112mm – 4 inch diameter)		
Usage	Replacement for standard recessed PLC lighting. For indoor use only. Non-dimmable.		

Warranty

One (1) year warranty subject to terms and conditions of use.