

# STaR: Self-Taught Reasoner

## Bootstrapping Reasoning With Reasoning

Aniket Tiwari(MDS202308), Kironmoy Roy(MDS202332)

**Instructor:** Pranabendu Misra(CMI), Dinesh Kirthivasan(Kantar)

Chennai Mathematical Institute

19 May 2025

# Outline

1. Introduction
2. Methodology
3. Algorithm and Implementation
4. Results
5. Discussion
6. Conclusion & Broader Impact

# The Reasoning Challenge

## Current Approaches:

- **Manual rationales**  
(Expensive, unscalable)

# The Reasoning Challenge

## Current Approaches:

- **Manual rationales**  
(Expensive, unscalable)
- **Few-shot CoT**  
(Limited accuracy)

# The Reasoning Challenge

## Current Approaches:

- **Manual rationales**  
(Expensive, unscalable)
- **Few-shot CoT**  
(Limited accuracy)
- **Direct fine-tuning**  
(No reasoning)

# The Reasoning Challenge

## Current Approaches:

- **Manual rationales**  
(Expensive, unscalable)
- **Few-shot CoT**  
(Limited accuracy)
- **Direct fine-tuning**  
(No reasoning)

## Research Question


Can models teach themselves  
to reason better?

# Understanding the STaR Algorithm

The STaR algorithm introduces a loop-based mechanism that allows a language model to generate and refine its reasoning capabilities over time through rationale generation and iterative learning.

## STaR: Self-Taught Reasoner

< = Self-Taught Reasoner




# Understanding the STaR Algorithm

The STaR algorithm introduces a loop-based mechanism that allows a language model to generate and refine its reasoning capabilities over time through rationale generation and iterative learning.

- Creates step-by-step explanations (rationales)

## STaR: Self-Taught Reasoner

< = Self-Taught Reasoner






# Understanding the STaR Algorithm

The STaR algorithm introduces a loop-based mechanism that allows a language model to generate and refine its reasoning capabilities over time through rationale generation and iterative learning.

- Creates step-by-step explanations (rationales)
- Continuously improves by learning from generated data

## STaR: Self-Taught Reasoner

< = Self-Taught Reasoner




# Understanding the STaR Algorithm

The STaR algorithm introduces a loop-based mechanism that allows a language model to generate and refine its reasoning capabilities over time through rationale generation and iterative learning.

- Creates step-by-step explanations (rationales)
- Continuously improves by learning from generated data
- Combines rationale generation with rationalization


## STaR: Self-Taught Reasoner

< = Self-Taught Reasoner




# The STaR Process

## 1. Starting Point: Begins with a Question




# The STaR Process

1. Starting Point: Begins with a Question
2. Rationale Generation: Model generates reasoning + answer
  - Correct: Added to training data
  - Incorrect: Given correct answer as hint



# The STaR Process

1. Starting Point: Begins with a Question
2. Rationale Generation: Model generates reasoning + answer
  - Correct: Added to training data
  - Incorrect: Given correct answer as hint
3. Feedback Loop: Rationales used to fine-tune model



## Example: Correct Answer

**Question:** "What is the best way to carry a small dog?"

**Choices:** (a) Swimming pool (b) Basket (c) Dog show (d) Backyard (e) Own home

## Example: Correct Answer

**Question:** "What is the best way to carry a small dog?"

**Choices:** (a) Swimming pool (b) Basket (c) Dog show (d) Backyard (e) Own home

Model Output (Correct)

**Rationale:** "Baskets are portable and designed to hold items. Other options are not for carrying."

**Answer:** (b) Basket

## Example: Correct Answer

**Question:** "What is the best way to carry a small dog?"

**Choices:** (a) Swimming pool (b) Basket (c) Dog show (d) Backyard (e) Own home

Model Output (Correct)

**Rationale:** "Baskets are portable and designed to hold items. Other options are not for carrying."

**Answer:** (b) Basket

- Correct answer/rationale added to training data



## Example: Correct Answer

**Question:** “What is the best way to carry a small dog?”

**Choices:** (a) Swimming pool (b) Basket (c) Dog show (d) Backyard (e) Own home

Model Output (Correct)

**Rationale:** “Baskets are portable and designed to hold items. Other options are not for carrying.”

**Answer:** (b) Basket

- Correct answer/rationale added to training data
- Reinforces valid reasoning paths

## Example: Incorrect Answer Handling

### Initial Incorrect Output

**Rationale:** “Dog show has space for movement.”

**Answer:** (c) Dog show

# Example: Incorrect Answer Handling

## Initial Incorrect Output

**Rationale:** "Dog show has space for movement."

**Answer:** (c) Dog show

## Correction Process

- Provide hint: Correct answer is (b) Basket

# Example: Incorrect Answer Handling

## Initial Incorrect Output

**Rationale:** "Dog show has space for movement."

**Answer:** (c) Dog show

## Correction Process

- Provide hint: Correct answer is (b) Basket
- Model generates new rationale supporting basket

# Example: Incorrect Answer Handling

## Initial Incorrect Output

**Rationale:** "Dog show has space for movement."

**Answer:** (c) Dog show

## Correction Process

- Provide hint: Correct answer is (b) Basket
- Model generates new rationale supporting basket
- New rationale added to training data

# Example: Incorrect Answer Handling

## Initial Incorrect Output

**Rationale:** "Dog show has space for movement."

**Answer:** (c) Dog show

## Correction Process

- Provide hint: Correct answer is (b) Basket
- Model generates new rationale supporting basket
- New rationale added to training data
- Model fine-tuned to avoid similar mistakes

# STaR without Rationalization

---

## Algorithm 1 Rationale Generation Bootstrapping (STaR without rationalization)

---

**Input  $M$ :** a pretrained LLM; dataset  $\mathcal{D} = \{(x_i, y_i)\}_{i=1}^D$  (w/ few-shot prompts)

- 1:  $M_0 \leftarrow M$  # Copy the original model
  - 2: **for**  $n$  in  $1 \dots N$  **do** # Outer loop
  - 3:    $(\hat{r}_i, \hat{y}_i) \leftarrow M_{n-1}(x_i) \quad \forall i \in [1, D]$  # Perform rationale generation
  - 4:    $\mathcal{D}_n \leftarrow \{(x_i, \hat{r}_i, y_i) \mid i \in [1, D] \wedge \hat{y}_i = y_i\}$  # Filter rationales using ground truth answers
  - 5:    $M_n \leftarrow \text{train}(M, \mathcal{D}_n)$  # Finetune the original model on the correct solutions - inner loop
-

# STaR Algorithm

---

## Algorithm 2 STaR

---

**Input**  $M$ : a pretrained LLM; dataset  $\mathcal{D} = \{(x_i, y_i)\}_{i=1}^D$  (w/ few-shot prompts)

- 1:  $M_0 \leftarrow M$  # Copy the original model
  - 2: **for**  $n$  in  $1 \dots N$  **do** # Outer loop
  - 3:    $(\hat{r}_i, \hat{y}_i) \leftarrow M_{n-1}(x_i) \quad \forall i \in [1, D]$  # Perform rationale generation
  - 4:    $(\hat{r}_i^{\text{rat}}, \hat{y}_i^{\text{rat}}) \leftarrow M_{n-1}(\text{add\_hint}(x_i, y_i)) \quad \forall i \in [1, D]$  # Perform rationalization
  - 5:    $\mathcal{D}_n \leftarrow \{(x_i, \hat{r}_i, y_i) \mid i \in [1, D] \wedge \hat{y}_i = y_i\}$  # Filter rationales using ground truth
  - 6:    $\mathcal{D}_n^{\text{rat}} \leftarrow \{(x_i, \hat{r}_i^{\text{rat}}, y_i) \mid i \in [1, D] \wedge \hat{y}_i \neq y_i \wedge \hat{y}_i^{\text{rat}} = y_i\}$  # Filter rationalized rationales
  - 7:    $M_n \leftarrow \text{train}(M, \mathcal{D}_n \cup \mathcal{D}_n^{\text{rat}})$  # Finetune on correct solutions
-



# Technical Implementation

## Mathematical Formulation

Treat as latent variable model:

$$p_M(y|x) = \sum_r p(r|x)p(y|x, r)$$

$$\nabla J = \sum_i \mathbb{E}_{r,y} [\mathbb{I}(y_i = \hat{y}_i) \cdot \nabla \log p_M(\hat{y}_i, \hat{r}_i | x_i)]$$



# Technical Implementation

## Mathematical Formulation

Treat as latent variable model:

$$p_M(y|x) = \sum_r p(r|x)p(y|x, r)$$

$$\nabla J = \sum_i \mathbb{E}_{r,y} [\mathbb{I}(y_i = \hat{y}_i) \cdot \nabla \log p_M(\hat{y}_i, \hat{r}_i | x_i)]$$

- Base model: GPT-J (6B parameters)
- Batch size: 8 sequences  $\times$  1024 tokens
- Learning rate: 1e-6 (Adam optimizer)
- TPU-v3 hardware



# CommonsenseQA Results


Method	CQA Dev Set Accuracy (%)	Train Data Used (%)
GPT-3 Direct Finetuned(175B)	73.0	100
Few-shot Direct GPT-J	20.9	~0
Few-shot CoT GPT-J	36.6	~0
Few-shot CoT LaMDA 137B	55.6	~0
GPT-J Direct Finetuned	60.0	100
STaR without rationalization	68.8	69.7
STaR with rationalization	<b>72.5</b>	86.7

# CommonsenseQA Results

Method	CQA Dev Set Accuracy (%)	Train Data Used (%)
GPT-3 Direct Finetuned(175B)	73.0	100
Few-shot Direct GPT-J	20.9	~0
Few-shot CoT GPT-J	36.6	~0
Few-shot CoT LaMDA 137B	55.6	~0
GPT-J Direct Finetuned	60.0	100
STaR without rationalization	68.8	69.7
STaR with rationalization	<b>72.5</b>	86.7

## Key Observations

- STaR achieves 72.5% accuracy vs. GPT-3's 73.0%




# CommonsenseQA Results

Method	CQA Dev Set Accuracy (%)	Train Data Used (%)
GPT-3 Direct Finetuned(175B)	73.0	100
Few-shot Direct GPT-J	20.9	~0
Few-shot CoT GPT-J	36.6	~0
Few-shot CoT LaMDA 137B	55.6	~0
GPT-J Direct Finetuned	60.0	100
STaR without rationalization	68.8	69.7
STaR with rationalization	<b>72.5</b>	<b>86.7</b>

## Key Observations

- STaR achieves 72.5% accuracy vs. GPT-3's 73.0%
- Uses only 86.7% training data (78.2% generation + 8.5% rationalization)




# CommonsenseQA Results

Method	CQA Dev Set Accuracy (%)	Train Data Used (%)
GPT-3 Direct Finetuned(175B)	73.0	100
Few-shot Direct GPT-J	20.9	~0
Few-shot CoT GPT-J	36.6	~0
Few-shot CoT LaMDA 137B	55.6	~0
GPT-J Direct Finetuned	60.0	100
STaR without rationalization	68.8	69.7
STaR with rationalization	<b>72.5</b>	<b>86.7</b>

## Key Observations

- STaR achieves 72.5% accuracy vs. GPT-3's 73.0%
- Uses only 86.7% training data (78.2% generation + 8.5% rationalization)
- Outperforms LaMDA (137B params) with just 6B params



# GSM8K Results (Math Word Problems)

Method	Test Accuracy (%)	Train Data Used (%)
Few-shot Direct GPT-J	3.0	~0
Few-shot CoT GPT-J	3.1	~0
GPT-J Direct Finetuned	5.8	100
STaR without rationalization	10.1	25.0
STaR with rationalization	<b>10.7</b>	28.7

# GSM8K Results (Math Word Problems)

Method	Test Accuracy (%)	Train Data Used (%)
Few-shot Direct GPT-J	3.0	~0
Few-shot CoT GPT-J	3.1	~0
GPT-J Direct Finetuned	5.8	100
STaR without rationalization	10.1	25.0
STaR with rationalization	<b>10.7</b>	28.7

- STaR achieves 2-3 $\times$  improvement over baselines



# GSM8K Results (Math Word Problems)

Method	Test Accuracy (%)	Train Data Used (%)
Few-shot Direct GPT-J	3.0	~0
Few-shot CoT GPT-J	3.1	~0
GPT-J Direct Finetuned	5.8	100
STaR without rationalization	10.1	25.0
STaR with rationalization	<b>10.7</b>	28.7

- STaR achieves 2-3 $\times$  improvement over baselines
- Uses only 25–28% of training data

# GSM8K Results (Math Word Problems)

Method	Test Accuracy (%)	Train Data Used (%)
Few-shot Direct GPT-J	3.0	~0
Few-shot CoT GPT-J	3.1	~0
GPT-J Direct Finetuned	5.8	100
STaR without rationalization	10.1	25.0
STaR with rationalization	<b>10.7</b>	28.7

- STaR achieves 2-3 $\times$  improvement over baselines
- Uses only 25–28% of training data
- Rationalization provides modest gains in this domain

# Simpler Solutions by the Model: GSM8K Solutions

Q: A van is delivering 180 bottles of drinks to a neighborhood, and each bottle contains either cider or beer or a mixture of two. Out of the 180 bottles, 40 contain only cider, 80 contain only beer, and the rest are a mixture of the two drinks. If the delivery man gives half the number of each bottle of drink to the first house, how many bottles does the first house get?

*Human (Ground truth from GSM8K dataset):*

The total number of bottles containing cider or beer is  $40+80 = 120$ .  
 If the number of bottles in the van was 180, then  $180-120 = 60$  contains a mixture of the two drinks.  
 At the first house, the delivery man dropped  $1/2 \times 40 = 20$  bottles.  
 There were also  $1/2 \times 80 = 40$  bottles of beer that the delivery man gave to the first house.  
 Together, the first house received  $40+20 = 60$  bottles of cider and beer.  
 The total number of bottles that had a mixture of the two drinks that were dropped at the first house is  $1/2 \times 60 = 30$ .  
 The first house got  $60+30 = 90$  bottles of all types of drinks.  
 #### 90

*STaR (on GPT-J):*

The delivery man gives half the number of each bottle of drink to the first house.  
 So he gives  $180/2 = 90$  bottles of drink to the first house.  
 #### 90


Fig: Example problem in the training set where STaR derives significantly simpler solution than the ground truth.

# Why STaR is a Game-Changer?


## Core Innovations

### ■ Human-like learning:

Generate → Verify → Improve cycle



(a) Without rationalization




(b) With rationalization

# Why STaR is a Game-Changer?


## Core Innovations

### ■ Human-like learning:

Generate → Verify → Improve cycle  
Learns from both correct/incorrect  
outputs



(a) Without rationalization



(b) With rationalization

# Why STaR is a Game-Changer?


## Core Innovations

### ■ Human-like learning:


Generate → Verify → Improve cycle  
Learns from both correct/incorrect outputs

### ■ Mathematical edge:

Explores  $p(r|x, y)$  space not  $p(r|x)$



(a) Without rationalization



(b) With rationalization

# Why STaR is a Game-Changer?


## Core Innovations

### ■ Human-like learning:


Generate → Verify → Improve cycle  
Learns from both correct/incorrect outputs

### ■ Mathematical edge:

Explores  $p(r|x, y)$  space not  $p(r|x)$   
Stronger training signals



(a) Without rationalization



(b) With rationalization

# Why STaR is a Game-Changer?

## Core Innovations

### Human-like learning:


Generate → Verify → Improve cycle  
Learns from both correct/incorrect outputs

### Mathematical edge:


Explores  $p(r|x, y)$  space not  $p(r|x)$   
Stronger training signals

### AI Development

Faster training of models



(a) Without rationalization



(b) With rationalization



# Why STaR is a Game-Changer?

## Core Innovations

### Human-like learning:


Generate  $\rightarrow$  Verify  $\rightarrow$  Improve cycle  
Learns from both correct/incorrect outputs

### Mathematical edge:


Explores  $p(r|x, y)$  space not  $p(r|x)$   
Stronger training signals

### AI Development

Faster training of models  
Less human-labeled data needed



(a) Without rationalization



(b) With rationalization

# Why STaR is a Game-Changer?

## Core Innovations

### ■ Human-like learning:


Generate → Verify → Improve cycle  
Learns from both correct/incorrect outputs

### ■ Mathematical edge:


Explores  $p(r|x, y)$  space not  $p(r|x)$   
Stronger training signals

### ■ AI Development

Faster training of models  
Less human-labeled data needed



(a) Without rationalization



(b) With rationalization

## Results

- +35% accuracy over few-shot

# Why STaR is a Game-Changer?

## Core Innovations

### Human-like learning:

Generate → Verify → Improve cycle  
Learns from both correct/incorrect outputs

### Mathematical edge:


Explores  $p(r|x, y)$  space not  $p(r|x)$   
Stronger training signals

### AI Development

Faster training of models  
Less human-labeled data needed

## Results

- +35% accuracy over few-shot



- Matches models 30x larger
- Reverse-engineers solutions
- Prevents learning plateaus

# Human-Evaluated Test Prompts

Comparing Few-Shot vs. STaR vs. Human Rationales

## Evaluation Methodology

- 50 questions correctly answered by both models
- 20 crowdworkers ranked rationales (1=best, 3=worst)
- Examples shown with sources shuffled

# Human-Evaluated Test Prompts

Comparing Few-Shot vs. STaR vs. Human Rationales

## Evaluation Methodology

- 50 questions correctly answered by both models
- 20 crowdworkers ranked rationales (1=best, 3=worst)
- Examples shown with sources shuffled

## Sample Question

**Q:** What should you do to become a good writer?

**Choices:** (a) word sentence (b) own animal (c) read newspaper (d) catch cold (e) study literature

# Human-Evaluated Test Prompts

Comparing Few-Shot vs. STaR vs. Human Rationales

## Evaluation Methodology

- 50 questions correctly answered by both models
- 20 crowdworkers ranked rationales (1=best, 3=worst)
- Examples shown with sources shuffled

## Sample Question

**Q:** What should you do to become a good writer?

**Choices:** (a) word sentence (b) own animal (c) read newspaper (d) catch cold (e) study literature

1. (STaR) "Literature develops writing skills..."
2. (Few-Shot) "The answer must help writing..."
3. (Human) "Studying literature gives writing skills..."

# Human-Evaluated Test Prompts

Comparing Few-Shot vs. STaR vs. Human Rationales

## Evaluation Methodology

- 50 questions correctly answered by both models
- 20 crowdworkers ranked rationales (1=best, 3=worst)
- Examples shown with sources shuffled

## Sample Question

**Q:** What should you do to become a good writer?

**Choices:** (a) word sentence (b) own animal (c) read newspaper (d) catch cold (e) study literature

1. (STaR) "Literature develops writing skills..."
2. (Few-Shot) "The answer must help writing..."
3. (Human) "studying literature gives writing skills..."

STaR rationales were preferred 30% over few-shot and 74% over human with  $p < 0.01$

# Key Limitations and Challenges

Major Limitations	Ethical Challenges
<ul style="list-style-type: none"><li>■ Requires human examples to start</li><li>■ Struggles with math reasoning</li><li>■ Slow processing speed</li><li>■ Needs careful tuning</li></ul>	<ul style="list-style-type: none"><li>■ Accountability for errors unclear</li><li>■ Potential for hidden biases</li><li>■ Autonomous learning risks</li></ul>



# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization

# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization
- Achieves performance of models **30× larger** with less human data

# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization
- Achieves performance of models **30× larger** with less human data
- Creates more **transparent & explainable** AI decisions

# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization
- Achieves performance of models **30× larger** with less human data
- Creates more **transparent & explainable** AI decisions

## Transformative Potential

- **Applications:** More explainable healthcare/legal/education decisions

# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization
- Achieves performance of models **30× larger** with less human data
- Creates more **transparent & explainable** AI decisions

## Transformative Potential

- **Applications:** More explainable healthcare/legal/education decisions
- **Ethics:** Built-in rationale generation enables bias detection

# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization
- Achieves performance of models **30× larger** with less human data
- Creates more **transparent & explainable** AI decisions

## Transformative Potential

- **Applications:** More explainable healthcare/legal/education decisions
- **Ethics:** Built-in rationale generation enables bias detection
- **Future Research:** Inspires new RL methods (STaR-RL), ReSTaR, Q-STaR etc.

# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization
- Achieves performance of models **30× larger** with less human data
- Creates more **transparent & explainable** AI decisions

## Transformative Potential

- **Applications:** More explainable healthcare/legal/education decisions
- **Ethics:** Built-in rationale generation enables bias detection
- **Future Research:** Inspires new RL methods (STaR-RL), ReSTaR, Q-STaR etc.

# Conclusion & Broader Impact

## Key Contributions

- First framework for **self-improving reasoning** via rationalization
- Achieves performance of models **30× larger** with less human data
- Creates more **transparent** & **explainable** AI decisions

## Transformative Potential

- **Applications:** More explainable healthcare/legal/education decisions
- **Ethics:** Built-in rationale generation enables bias detection
- **Future Research:** Inspires new RL methods (STaR-RL), ReSTaR, Q-STaR etc.

General framework for creating more capable, efficient, and trustworthy AI systems



End

Thank You!