
DOKUMENTACIJA

Sadržaj

Uvod	5
Korišćeni jezici	5
Domen	5
Opis funkcionalnosti	6
Template	6
Organizacija	7
sitemap.xml	7
Organizacija stranica	9
Izgled stranica i opis njihovih funkcionalnosti:	9
main/login.blade.php	9
main/register.blade.php	10
Izgled dela sajta za autorizovanog korisnika:	10
main/home.blade.php	10
products/index.blade.php	12
cart/index.blade.php	13
orders/orderFrom.blade.php	14
orders/index.blade.php	14
main/contact.blade.php	15
main/author.blade.php	16
Izgled dela sajta za administratora	17
admin/home.blade.php	17
admin/orders/index.blade.php	18
admin/messages/index.blade.php	18
admin/users/index.blade.php	19
admin/products/index.blade.php	20
admin/products/update.blade.php	20
admin/products/insert.blade.php	21
Kodovi	22
Views	22
Components	23
Fixed	26

Layouts.....	30
Routes.....	78
web.php.....	78
Middleware	81
Admin.php	81
UserLoggedIn.php.....	82
User.php	82
Models.....	83
ActivitiesModel.php	84
Category.php	84
Color.php	85
Discount.php	85
Material.php.....	86
Message.php	86
MessageModel.php.....	87
Order.php	88
OrdersModel.php	88
Price.php.....	89
Product.php	90
ProductModel.php	91
Role.php.....	95
Users.php.....	96
UserModel.php.....	96
Providers.....	97
AppServiceProvider.php.....	97
Rules	99
Address.php.....	99
EmailUnique.php	100
Password.php	101
ProductName.php	102
ProductNameUnique.php.....	103
UserFullName.php.....	104
Requests	105

AddToCartRequest.php	106
MessageAdminRequest.php.....	106
OrderFormRequest.php	107
ProductInsertRequest.php	108
ProductUpdateReuquest.php.....	109
RegisterUserRequest.php.....	110
UserRequest.php.....	111
Helpers.....	112
ActivityLogger.php.....	112
Controllers	113
AdminController.php.....	113
AuthorController.php	117
CartController.php.....	118
ContactController.php.....	120
HomeController.php.....	121
LoginController.php.....	122
MainController.php	123
OrdersController.php	124
ProductsController.php	127
ProductsInsertController.php.....	128
ProductsUpdateController.php	130
RegisterController.php	135
Assets.....	136
css/style.css	137
js/main.js	145
Database.....	154

Uvod

Korišćeni jezici

Markup jezici: HTML, XML

Stilski jezik: CSS

Skript jezik: JavaScript

Framework: Bootstrap, Laravel

Biblioteke: jQuery

Domen

Aplikacija je namenja prodaji nameštaja. Autorizovani korisnici mogu da kupuju proizvode i imaju pregled narudžbina. Pored kupovine imaju mogućnost da kontaktiraju administratora ukoliko je to potrebno. Administratori imaju mogućnost da unesu nov proizvod, izmene ga i obrišu. Takođe administratori upravljaju korisnicima i njihovim narudžbinama. Na početnoj stranici admin panela nalazi se ispis svih aktivnosti korisnika. Korisnici se sami registruju. Neautorizovani korisnici nemaju pristup sadržaju sajta.

Opis funkcionalnosti

- Responsive sajt, Bootstrap
- Dodavanje naloga, logovanje na isti
- Upravljanje proizvodima kao administrator (dodavanje proizvoda, njihovo brisanje i izmena)
- Upravljanje porudžbinama kao korisnik i kao administrator
- Upravljanje korisnicima kao administrator (izmena uloge, izmena statusa naloga i brisanje naloga)
- Dohvatanje proizvoda, narudžbina, aktivnosti, korisnika i poruka iz baze
- Aktivnosti korisnika (posećenost svake stranice, logovanje tog dana)
- Slanje poruka administratoru
- Ispis poruka administratoru
- Filter proizvoda, sortiranje i pretraga
- Dodavanje proizvoda u korpu
- Ispis porudžbina korisnicima
- Straničenje poruka, porudžbina, aktivnosti i korisnika
- Optimalna organizacija view-a
- Validacija grešaka
- Upotreba komponenata
- Middleware
- Upotreba ajax-a na određenim delovima sajta

Template

Nije korišćen template, samostalno pisan kod

Organizacija

sitemap.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<urlset xmlns="http://www.sitemaps.org/schemas/sitemap/0.9">
  <url>
    <loc>http://127.0.0.1:8000/login</loc>
    <lastmod>2023-01-25</lastmod>
    <changefreq>never</changefreq>
    <priority>0.4</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/home-user</loc>
    <lastmod>2023-01-25</lastmod>
    <changefreq>yearly</changefreq>
    <priority>0.2</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/products</loc>
    <lastmod>2023-01-25</lastmod>
    <changefreq>daily</changefreq>
    <priority>1</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/cart</loc>
    <lastmod>2023-01-25</lastmod>
    <changefreq>daily</changefreq>
    <priority>0.9</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/orders</loc>
    <lastmod>2023-01-25</lastmod>
    <changefreq>weekly</changefreq>
    <priority>0.7</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/order-form</loc>
    <lastmod>2023-01-25</lastmod>
    <changefreq>never</changefreq>
    <priority>0.1</priority>
  </url>
  <url>
    <loc>http://127.0.0.1:8000/contact</loc>
    <lastmod>2023-01-25</lastmod>
    <changefreq>never</changefreq>
    <priority>0.1</priority>
  </url>
</urlset>
```

```
</url>
<url>
  <loc>http://127.0.0.1:8000/author</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>never</changefreq>
  <priority>0.1</priority>
</url>
<url>
  <loc>http://127.0.0.1:8000/register</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>never</changefreq>
  <priority>0.3</priority>
</url>
<url>
  <loc>http://127.0.0.1:8000/home-admin</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>daily</changefreq>
  <priority>0.9</priority>
</url>
<url>
  <loc>http://127.0.0.1:8000/products-admin</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>weekly</changefreq>
  <priority>0.7</priority>
</url>
<url>
  <loc>http://127.0.0.1:8000/products-insert-form</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>yearly</changefreq>
  <priority>0.5</priority>
</url>
<url>
  <loc>http://127.0.0.1:8000/products-update</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>yearly</changefreq>
  <priority>0.5</priority>
</url>
<url>
  <loc>http://127.0.0.1:8000/orders-admin</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>weekly</changefreq>
  <priority>0.7</priority>
</url>
<url>
  <loc>http://127.0.0.1:8000/messages</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>daily</changefreq>
  <priority>0.8</priority>
</url>
```



```
<url>
  <loc>http://127.0.0.1:8000/users</loc>
  <lastmod>2023-01-25</lastmod>
  <changefreq>daily</changefreq>
  <priority>0.8</priority>
</url>

</urlset>
```

Organizacija stranica

Izgled stranica i opis njihovih funkcionalnosti:

main/login.blade.php



Login

Email:


Password:

Don't have an account? [Register here](#)

Copyright © Dreamy | Furniture shop

Stranica koja se inicijalno prikazuje korisniku. Prikazana je forma za logovanje, gde se unosi email i lozinka korisnika. Ukoliko korisnik nema nalog mora se registrovati. Nakon logovanja korisnik se preusmerava na početnu stranicu u odnosu na njegovu ulogu. Za logovanje je korišćena sesija.

main/register.blade.php



The screenshot shows the registration page for 'Dreamy Furniture shop'. At the top center is the 'Dreamy' logo, which consists of a stylized chair icon and the word 'Dreamy'. Below the logo is a white rectangular form with a thin red border. The form is titled 'Register' in a red, italicized serif font. It contains four input fields: 'First name:', 'Last name:', 'Email:', and 'Password:'. Each field is a simple white rectangle with a thin red border. Below the 'Password:' field is a red 'Submit' button. At the bottom center of the page, below the form, is a small copyright notice: 'Copyright © Dreamy| Furniture shop'.

Stranica za registrovanje korisnika. Korisnik unosi podatke u formu (ime, prezime i parametre za logovanje: email, password). Ukoliko je uspešno registrovan preusmerava se na login formu.


Izgled dela sajta za autorizovanog korisnika:

main/home.blade.php



U odnosu koji je korisnik uzlogovan prikazuje se njegove ime i prezime u delu navigacije u desnom uglu.

What do we offer?



Lamps

We offer a different range of lamps, variety in color, shape and light intensity
Light your home with our lamps


Blok gde su prikazane kategorije ispisan je kao komponenta koja se vrti u petlji. Podaci su izvučeni iz baze i smešteni u HomeController.



[Home](#) [Products](#) [Cart](#) [Orders](#) [Contact](#) [Author](#) [Logout](#)

Pera Perić

Need help with room design, here are some ideas?



Call us: +381 123 4567

Email us: dreamy@gmail.com

Visit us at: Zira, Belgrade

Dream big !



About
Small business furniture shop


Documentation


Find us
    

Copyright © Dreamy Furniture shop

Svaki blok je zapravo jedna komponenta koja se vrti u petlji. Podaci u ovom bloku su dohvaćeni iz HomeController-a gde su napisani kao niz.

products/index.blade.php

[Home](#) [Products](#) [Cart](#) [Orders](#) [Contact](#) [Author](#) [Logout](#) *Pera Perić*

Categories

☐ Lamp

☐ Table

☐ Armchair

☐ Sofa

☐ Nightstand

Colors


Product status

Sort by price Choose

Show discounts Choose

Search by name:

Filter




Idanas
Material:wood
85\$
Black / Nightstand

✖ Out of stock

Free shipping

Holiday discount




Lack
Material:wood
13.93\$ ~~16.72\$~~
Pink / Nightstand

PURCHASE

✔ In stock

Free shipping

Spring Cleaning




Ekero
Material:leather
566.55\$ ~~602.71\$~~
White / Armchair

PURCHASE

✔ In stock

Free shipping

Holiday discount



Landskrona
Material:leather
1764.68\$ ~~2229.07\$~~
Yellow / Sofa

PURCHASE

✔ In stock

Free shipping

<

1

2

3

4

>

Stranica za prikaz proizvoda korisnicima. Sa leve strane se nalazi blok za filter i sortiranje proizvoda. Proizvodi se mogu sortirati po ceni opadajuće i rajuće. Filter je moguć na osnovu kategorije, boje, materijala, statusa, akcije i naziva proizvoda. Svi filteri i paginacija su usklađeni. Ukoliko ne postoji proizvod za određeni filter ispisuje se poruka.

Proizvodi su ispisani pomoću komponente i izvučeni iz baze. Klikom na dugme **PURCHASE** proizvod se dodaje u korpu i korisniku se ispisuje poruka da je proizvod dodat u korpu.

12

cart/index.blade.php




Ukoliko korisnik nije dodao ništa u korpu ispisaće se poruka da je korpa prazna.



Ispis proizvoda iz korpe korisnika. Podaci iz korpe su smešteni u sesiju. Moguće je izmeniti kolučinu proizvoda ili ga izbaciti iz korpe klikom na dugme **Remove**. Klikom na dugme **Remove all** briše se cela sesija. Dugme **Checkout** preusmerava korisnika na formu za napravljenu porudžbinu. Cella funkcionalnot korpe je obavljena pomoću ajax-a.

orders/orderFrom.blade.php

 [Home](#) [Products](#) [Cart](#) [Orders](#) [Contact](#) [Author](#) [Logout](#) *Pera Perić*

Order form

Address:*

Payment type:*

Choose


Delivery: *

☐ Home address ☐ The post office

Submit

Nakon klika na dugme **Checkout** na stranici **Cart** korisnik se preusmerava na formu za porudžbinu. Potrebno je uneti adresu, način isporuke i način plaćanja. Klikom na dugme **Submit** korisnik se preusmerava na stranicu **Orders** i njegova porudžbina se upisuje u bazu. Sesija za korpu se tada briše.

orders/index.blade.php

 [Home](#) [Products](#) [Cart](#) [Orders](#) [Contact](#) [Author](#) [Logout](#) *Pera Perić*

My orders


Address	Quantity	Total	Payment type	Delivery method	Created at		
Ljubice Luković 15, Beograd 11000	2	378.02 \$	card	address	2023-01-21 12:41:01	Show	Cancel

Call us: +381 123 4567


Email us: dreamy@gmail.com


Visit us at: Zira, Belgrade

Dream big !




About
Small business furniture shop

Documentation


Find us



Copyright © Dreamy| Furniture shop

Ispis porudžbina korisnika koje su izvučene iz baze. Korisnik je u mogućnosti da otkaže porudžbnu klikom na dugme **Cancel**. Korišćen ajax za brisanje narudžbine. Paginacija je primenjena




Klikom na dugme **Show** prikazuje se modal sa stavkama iz narudžbine. Korišćen ajax.


main/contact.blade.php




Na stranici **Contact** korisnik je u mogućnosti da pošalje poruku administratoru. Korisnik bira iz padajuće liste kom administratoru želi da se obrati. Poruka se upisuje u bazu i ispisuje na admin panelu.


main/author.blade.php


 [Home](#) [Products](#) [Cart](#) [Orders](#) [Contact](#) [Author](#) [Logout](#) *Pera Perić*




My name is Anica Radenković
Here's something about me
Date of birth: 14.02.2002
Status: Student
Place of study: ICT College
Module: Web programming
Title after graduation: Professional Engineer of Electrical Engineering and Computing
Objective: Acquiring adequate knowledge, expertise and skills to work in creative places in the field of programming
[My portfolio](#)

 Call us: +381 123 4567


 Email us: dreamy@gmail.com


 Visit us at: Zira, Belgrade

Dream big !

*Dreamy*

About
Small business furniture shop

Documentation


Find us


Stranica o autoru sajta.

Izgled dela sajta za administratora

admin/home.blade.php

Mika Mikic

Dashboard

Orders

Products

Customers

Messages

Dashboard

3 customers

Active

3 orders

Total orders

9 products

In stock

4 products

Out of stock

Name

Choose

Users

Choose

Filter

Submit

Name	User	Date	Data
Login	mika.mikic@gmail.com	2023-01-25 19:11:00	user=mika.mikic@gmail.com
Logout	pera.peric@gmail.com	2023-01-25 19:10:54	user=pera.peric@gmail.com
Login	pera.peric@gmail.com	2023-01-25 19:09:33	user=pera.peric@gmail.com
Logout	mika.mikic@gmail.com	2023-01-25 19:09:16	user=mika.mikic@gmail.com
Login	mika.mikic@gmail.com	2023-01-25 19:09:08	user=mika.mikic@gmail.com
Logout	pera.peric@gmail.com	2023-01-25 19:07:47	user=pera.peric@gmail.com

Na početnoj stranici admin panela izlistane su aktivnosti korisnika. Stavke koje se zabeleže su akcija koja se desila, korisnik koji je obavio tu akciju, datum kada je zabeležena i podaci vezani za akciju. Omogućeno je filtriranje aktivnosti po nazivu i korisniku. Filter i paginacija su usklađeni.

admin/orders/index.blade.php

Mika Mikic

Sign out

Dashboard

Orders

Products

Customers

Messages

Orders

User

Payment type

Delivery method

Filter

Choose

Choose

Choose

Submit

User	Address	Quantity	Total	Payment type	Delivery method	Created at		
anica02@gmail.com	Ljubice Luković 15, Beograd 11000	2	529.37 \$	card	address	2023-01-25 14:41:09	Show	Remove
anica02@gmail.com	Ljubice Luković 15, Beograd 11000	2	1996.68 \$	cash	postOffice	2023-01-23 17:30:20	Show	Remove
pera.peric@gmail.com	Ljubice Luković 15, Beograd 11000	2	378.02 \$	card	address	2023-01-21 12:41:01	Show	Remove

Prikaz svih narudžbina korisnika iz baze. Omogućeno je brisanje narudžbine i pregled pojedinih stavki. Filtriranje narudžbina po korisniku, načinu plaćanja i načinu dostave. Filter i paginacija su usklađeni.

admin/messages/index.blade.php

Mika Mikic

Sign out

Dashboard

Orders

Products

Customers

Messages

Messages

Email

Filter

Choose

Submit

User	Message	Created at	
pera.peric@gmail.com	My friends account was blocked, the email is mare99@gmail.com	2023-01-25 19:07:45	Delete
pera.peric@gmail.com	Are there new products coming soon?	2023-01-25 19:06:57	Delete

Ispis poruka namenjenim određenom administratoru. Omogućeno brisanje poruke. Filter po korisničkom email-u. Filter i paginacija usklađeni.

admin/users/index.blade.php

The screenshot shows a web application interface for managing users. On the left is a sidebar with the user's name 'Mika Mikic' and a 'Sign out' button. The sidebar contains links to Dashboard, Orders, Products, Customers, and Messages. The main content area is titled 'Users' and features three dropdown filters for Email, Role, and Active status, with a 'Submit' button. Below the filters is a table with columns: First name, Last name, Email, Id_role, Active, Created at, Edit, and Delete. The table contains four rows of user data.

First name	Last name	Email	Id_role	Active	Created at	Edit	Delete
Anica	Radenković	anica02@gmail.com	2	1	2023-01-21 14:53:00	Edit	Delete
Marko	Marković	mare9@gmail.com	2	1	2022-12-11 19:13:24	Edit	Delete
Pera	Perić	pera.peric@gmail.com	2	1	2022-12-11 15:36:26	Edit	Delete
Mika	Mikic	mika.mikic@gmail.com	1	1	2022-12-11 15:35:21	Edit	Delete

Stranica namenjena ispisu korisnika iz baze. Omogućeno je brisanje i izmena korisničkih naloga. Filter korisnika po email-u, ulozi i statusu naloga. Klikom na dugme **Edit** prikazuje se modal sa formom za izmenu naloga korisnika.

This screenshot shows the same user management interface as the previous one, but with a modal window open for editing a user. The modal is titled 'User' and displays the email 'User: anica02@gmail.com'. It contains two dropdown menus: 'Account status' (set to 'Active') and 'Role' (set to 'User'). There is an 'Edit' button at the bottom of the form and a 'Close' button at the bottom right of the modal. The background table and filters are visible but dimmed.

Moguća izmena statusa naloga i uloge. Prikaz podataka putem ajax-a.

admin/products/index.blade.php

Mika Mikic

Sign out

Dashboard

Orders

Products

Customers

Messages

INSERT NEW PRODUCT

Products

Discount

Choose

Category

Choose





Status

Choose

Name

Filter

Submit

Image	Name	Status	Color	Category	Material	Price	Discount name	Discount	Created at		
	Idanas	0	Black	Nightstand	wood	85 \$			2023-01-23	<div>EDIT</div>	<div>DELETE</div>
	Lack	1	Pink	Nightstand	wood	16.72 \$	Holiday discount	13.93 \$		<div>EDIT</div>	<div>DELETE</div>
	Ekerö	1	White	Armchair	leather	602.71 \$	Spring Cleaning	566.55 \$		<div>EDIT</div>	<div>DELETE</div>
	Landskrona	1	Yellow	Sofa	leather	2229.07 \$	Holiday discount	1764.68 \$		<div>EDIT</div>	<div>DELETE</div>

<

1

2

3

4

>

Stranica za upravljanje proizvodima. Proizvode je moguće izmeniti, obrisati i dodati nov. Filter proizvoda po tipu popustu, kategoriji, statusu i nazivu. Filter i paginacija su usklađeni. Klikom na dugme **Edit** učitava se stranica sa formom za izmenu proizvoda. Klikom na dugme **INSERT NEW PRODUCT** učitava se forma za unos novog proizvoda.

admin/products/update.blade.php

Mika Mikic

Sign out

Dashboard

Orders

Products

Customers

Messages

Update product

Name:

Idanas

Color:

Black

Category:

Nightstand

Material:

wood

Price:

85

Product status:

☐ In stock

☒ Out of stock

Discount type:

Choose

Discount price:

Product image:

Moguća je izmena naziva, boje, kategorije, materijala, cene, statusa, tipa popusta, cene popusta i slike. Validacija unosa.

admin/products/insert.blade.php

Mika Mikic

Sign out

Dashboard

Orders

Products

Customers

Messages

Insert new product

Name:*

Price:*

Color:*

Choose

Category:*

Choose

Material:*

Choose

Discount type:

Choose

Discount price:

Product image:*

Choose File


No file chosen

Submit

Stranica za unos novog proizvoda. Nakon validacije podaci se upisuju u bazu. Za proizvod se unose sledeći parametri: naziv, cena, boja, kategorija, materijal, tip popusta, cena popusta i slika proizvoda.

Kodovi

Views



Components

card.blade.php

```
<div class="row top-margin borderCards cardP col-12 ml-1">
    <div class="col-sm-4 border-right">
        
    </div>
    <div class="col-sm-8">
        <div class="description text-left">
            <h3 class="font-italic text-center">{{ $title }}s</h3>
            <h4 class="mt-5">{{ $description1 }}</h4>
            <h5 class="">{{ $description2 }}</h5>

        </div>
    </div>
</div>
```

cart-row.blade.php

```
<div class="row" class="cartItems" id="cartItem_{{ $idProd }}">
    <div class="col-12 col-sm-3 text-center">
        
    </div>
    <div class="col-12 col-sm-3 text-center rowItem font-weight-bold
colorRottenCherry">
        <div class="col text-center font-weight-bold colorMint font18">
            <p>Name</p>
        </div>
        <p>{{ $name }}</p>
    </div>
    <div class="col-12 col-sm-2 text-center rowItem font-weight-bold
colorRottenCherry">
        <div class="col text-center font-weight-bold colorMint font18">
            <p>Quantity</p>
        </div>
        @if($discount)
            <input type="number" onchange="changeQuantity(
{{ $idProd }},{{ $discount }},{{ count(session()->get('cart')) }},this
)" value="{{ session()->get('cart')[ $idProd ] }}" style="width:
6em" />
```

```

        @else
        <input type="number" onchange="changeQuantity(
        {{ $idProd }}, {{ $price }}, {{ count(session()->get('cart')) }}, this
        )" value="{{ session()->get('cart')[$idProd] }}" style="width:
6em" />
        @endif
    </div>

    <div class="col-12 col-sm-2 text-center rowItem font-weight-bold
colorRottenCherry">
        <div class="col text-center font-weight-bold colorMint font18">
            <p>Price</p>
        </div>
        @if($discount)
            <p id="price_{{ $idProd }}">{{ number_format((float)$discount
* session()->get('cart')[$idProd], 2, '.', ''). " $" }}</p>
        @else
            <p id="price_{{ $idProd }}">{{
number_format((float)$price * session()->get('cart')[$idProd], 2, '.',
''). " $" }}</p>
        @endif
    </div>
    <div class="col-12 col-sm-2 text-center rowItem ">
        <div class="col text-center font-weight-bold ">
            <p></p>
        </div>
        <button onclick="removeFromCart('{{ $idProd }})" class="colorMint
btn removeButton py-1 px-1">Remove</button>
    </div>
</div>

```

room-card.blade.php

```

<div class="col-12 col-sm-6 col-lg-3 mb-3">
    <div class="card bg-dark text-white cardRoom">
        
    </div>
</div>

```


product.blade.php

```
<div class="col-12 col-sm-6 col-lg-4 col-xl-3 product">
    <div class="card mb-5 py-3 px-4 text-center cardWidth">
        <div>
            @if(!empty($discountPrice))
                <div class="text-left pl-2 {{$discountStyle}}">
                    <h5 class="py-1 font-italic">{{$discountName}}</h5>
                </div>
            @else
                <div></div>
            @endif
        </div>

        
        <div class="card-body text-left">
            <h4 class="card-title">{{ ucfirst(trans($name)) }}</h4>
            <h5 class="card-text">Material:{{$material}}</h5>
            @if(!empty($discountPrice))
                <h5 class="card-text"> {{$discountPrice}}$
&nbsp;<s>{{$price}}$</s></h5>
            @else
                <h5 class="card-text"> {{$price}}$</h5>
            @endif

            <h6 class="card-text">{{$color}} / {{$category}}</h6>

            @if($status==1)
                <div class="row text-right">

                    <div class="col-5 col-sm-6 col-xl-5 ">
                        <button type="button"
onclick="addToCart({{$prodId}})" class="btn btnProduct colorMint font-
weight-bold">
                            PURCHASE
                        </button>
                    </div>

                </div>

                <div class="col-12 mt-3">
                    <p class="card-text inStock text-right"><i
class="fas fa-check-circle"></i> In stock</p>
                </div>
            @endif
        </div>
    </div>
```

```

        <div class="col-12 mt-3">
            <p class="card-text inStock text-right">Free
shipping</p>
        </div>

        @elseif($status==0)

            <div class="col-12 mt-3">
                <p class="card-text outStock text-right"><i
class="fas fa-times-circle"></i> Out of stock</p>
            </div>
            <div class="col-12 mt-3">
                <p class="card-text inStock text-right">Free
shipping</p>
            </div>
        @endif

    </div>
</div>
</div>

```

Fixed

head.blade.php

```

<head>
    <title>@yield("title")</title>
    <meta charset="UTF-8"/>
    @yield("csrf-token")
    <meta name="viewport" content="width=device-width, initial-
scale=1.0"/>
    <meta name="keywords" content="@yield("keywords")"/>
    <meta name="description" content="@yield("description")"/>
    <link rel="shortcut icon" href="{{asset("assets/img/logo1.png")}}"/>

    <script src="https://kit.fontawesome.com/ce9a3cdf18.js"
crossorigin="anonymous"></script>
    <script src="https://cdn.jsdelivr.net/npm/feather-
icons@4.28.0/dist/feather.min.js"></script>
    <script src="{{ asset("assets/js/jquery.js") }}"></script>
    <link rel="stylesheet"

```

```

href="https://cdn.jsdelivr.net/npm/bootstrap@4.6.1/dist/css/bootstrap.min
.css" integrity="sha384-
zCbKRCUGaJDkqS1kPbPd7TveP5iyJE0EjAuZQTgFLD2ylzuqKfdKlfG/eSrtxUkn"
crossorigin="anonymous">
    <link rel="canonical"
href="https://getbootstrap.com/docs/4.6/examples/dashboard/">
    <link href="{{asset('assets/css/dashboard.css')}}" rel="stylesheet">
    <link type="text/css" rel="stylesheet"
href="{{asset('assets/css/style.css')}}" />

    <link
href="https://cdnjs.cloudflare.com/ajax/libs/toastr.js/2.0.1/css/toastr.c
ss" rel="stylesheet" />
</head>

```

header.blade.php

```

<header class="@yield('header_class')">
    <div class="container">

        <nav class="navbar navbar-expand-lg navbar-light">
            <a class="navbar-brand2" href="{{route('home-user')}}"></a>

            <button class="navbar-toggler" type="button" data-
toggle="collapse" data-target="#navbarTogglerDemo02" aria-
controls="navbarTogglerDemo02" aria-expanded="false" aria-label="Toggle
navigation">

                <span class="navbar-toggler-icon"></span>
            </button>
            <div class="collapse navbar-collapse"
id="navbarTogglerDemo02">
                <ul class="navbar-nav m-auto mt-lg-0 text-center
colorRottenCherry" id="navigation">

                    @if(session()->has('user'))

                        <li class="nav-item"><a class="nav-
link" href="{{route('home-user')}}">Home</a></li>
                        <li class="nav-item"><a class="nav-
link" href="{{route('products')}}">Products</a></li>
                        <li class="nav-item"><a class="nav-link"
href="{{route('cart')}}">Cart</a></li>
                        <li class="nav-item"><a class="nav-

```

```

link" href="{{route('orders')}}">Orders</a></li>
                                <li class="nav-item"><a class="nav-
link" href="{{route('contact')}}">Contact</a></li>
                                <li class="nav-item"><a class="nav-
link" href="{{route('author')}}">Author</a></li>

                                <li class="nav-item"><a class="nav-link"
href="{{route('logout')}}">Logout</a></li>
                                @endif
                                </ul>
                                <h3 class="font-weight-bold font-italic
colorRottenCherry">{{session()->get('user')->first_name." " .session()-
>get('user')->last_name}}</h3>
                                </div>

                                </nav>

                                </div>
</header>

```

footer.blade.php

```

<footer>
    <div class="container-fluid">
        <div id="footer">
            <div class="row mb-5 ">
                <div class="col-12 col-sm-6 col-lg-3 mb-2 text-center">
                    <p class="footerCol py-1"><i class="fas fa-phone-alt
"></i> Call us: +381 123 4567</p>
                </div>
                <div class="col-12 col-sm-6 col-lg-3 mb-2 text-center">
                    <p class="footerCol py-1"><i class="fas fa-envelope
"></i> Email us: dreamy@gmail.com</p>
                </div>
                <div class="col-12 col-sm-6 col-lg-3 mb-2 text-center">
                    <p class="footerCol py-1"><i class="fas fa-map-
marker-alt"></i> Visit us at: <a href="https://g.page/golden-tulip-zira-
belgrade?share" target="_blank" class="text-decoration-none colorWhite">
Zira, Belgrade</a></p>
                </div>
                <div class="col-12 col-sm-6 col-lg-3 mb-2 text-center">
                    <p class="footerCol py-1"><i> Dream big !</p>
                </div>
            </div>
        </div>
    </div>

```

```

        <div class="col-12 col-sm-6 col-lg-3 text-center">
            
        </div>
        <div class="col-12 col-sm-6 col-lg-3 text-center
colorRottenCherry">
            <h4 class="font-italic font-weight-bold">About</h4>
            <h5 class="font-weight-bold">Small business furniture
shop</h5>
        </div>
        <div class="col-12 col-sm-6 col-lg-3 text-center
colorRottenCherry">
            <h4 class="font-italic font-weight-
bold">Documentation</h4>
            <a href="Documentation/Documentation.pdf"
target="_blank" class="colorRottenCherry font18"><i class="fas fa-file-
alt"></i></a>
        </div>
        <div class="col-12 col-sm-6 col-lg-3 text-center
colorRottenCherry">
            <h4 class="font-italic font-weight-bold">Find us</h4>
            <div id="socialN">
                @foreach($links as $link)
                    <a href="{{ $link['href'] }}" target="_blank"
class="colorRottenCherry fontSI mr-2"><i
class="{{ $link['icon'] }}"></i></a>
                @endforeach
            </div>
        </div>
    </div>
</div>
<div class="row">
    <div class="col-12 text-center colorRottenCherry">
        <h6 class="font-weight-bold">Copyright &copy; Dreamy|
Furniture shop</h6>
    </div>
</div>

</div>
</div>
</footer>

```

scripts.blade.php

```

<script>
    const baseUrl = "{{url('/')}}";
    const token="{{csrf_token()}}";

</script>

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.6.1/dist/js/bootstrap.bundle.min.js" integrity="sha384-
fQybjgWLrvvRgtW6bFlB7jaZrFsaBXjsOMm/tB9LTS58ONXgqbR9W8oWht/amnpF"
crossorigin="anonymous"></script>

<script>window.jQuery || document.write('<script
src="{{asset('assets/js/jquery.slim.min.js')}}"></script>')</script><scr
ipt src="{{asset('assets/js/bootstrap.bundle.min.js')}}"
crossorigin="anonymous"></script>

<script type="text/javascript"
src="{{asset('assets/js/main.js')}}"></script>
<script
src="https://cdnjs.cloudflare.com/ajax/libs/toastr.js/2.0.1/js/toastr.js"
></script>

```

banner.blade.php

```

<div class="container-fluid">
    <div id="banner">
        <div id="apperText">
            <div class="row">
                <div class="col-12">
                    <div id="motto" class="centering text-center
colorRottenCherry">
                        <h2 class="font-weight-bold font-italic">DECORATE
YOUR HOME</h2>
                    </div>
                </div>
            </div>
        </div>
    </div>
</div>

```

Layouts

layout.blade.php

```
<!DOCTYPE html>
<html>
@include('fixed.head')

<body>
@include('fixed.header')
@yield('banner')
@yield('content')

@include('fixed.footer')
@include('fixed.scripts')
</body>
</html>
```

form.blade.php

```
<!DOCTYPE html>
<html>
@include('fixed.head')

<body>
<div class="container-fluid text-center mt-5">
    
</div>
@yield('content')
<footer>
    <div class="container-fluid">
        <div class="row">
            <div class="col-12 text-center colorRottenCherry">
                <h6 class="font-weight-bold">Copyright &copy; Dreamy|
Furniture shop</h6>
            </div>
        </div>
    </div>
</footer>

@include('fixed.scripts')
</body>
</html>
```

admin.blade.php

```

<!DOCTYPE html>
<html>
@include('fixed.head')

<body>
<nav class="navbar navbar-dark sticky-top backgroundNav flex-md-nowrap p-0 shadow">
    <a class="navbar-brand col-md-3 col-lg-2 mr-0 px-3 font26">{{session()->get('user')->first_name." " .session()->get('user')->last_name}}</a>
    <button class="navbar-toggler position-absolute d-md-none collapsed" type="button" data-toggle="collapse" data-target="#sidebarMenu" aria-controls="sidebarMenu" aria-expanded="false" aria-label="Toggle navigation">
        <span class="navbar-toggler-icon"></span>
    </button>

    <ul class="navbar-nav px-3">
        <li class="nav-item text-nowrap">
            <a class="nav-link font-weight-bold colorWhite font18" href="{{route('logout')}}">Sign out</a>
        </li>
    </ul>
</nav>

<div class="container-fluid">
    <div class="row">
        <nav id="sidebarMenu" class="col-md-3 col-lg-2 d-md-block bg-light sidebar collapse">
            <div class="sidebar-sticky pt-3">
                <ul class="nav flex-column">
                    <li class="nav-item">
                        <a class="nav-link active" href="{{route('home-admin')}}">
                            <svg xmlns="http://www.w3.org/2000/svg" width="24" height="24" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-linejoin="round" class="feather feather-home"><path d="M3 9l9-7 9 7v11a2 2 0 0 1-2 2H5a2 2 0 0 1-2 2z"></path><polyline points="9 22 9 12 15 12 15 22"></polyline></svg>
                            Dashboard <span class="sr-only">(current)</span>
                        </a>
                    </li>
                    <li class="nav-item">
                        <a class="nav-link" href="{{route('orders-admin')}}">
                            <svg xmlns="http://www.w3.org/2000/svg" width="24" height="24" viewBox="0 0 24 24" fill="none"

```



```

stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-
linejoin="round" class="feather feather-file"><path d="M13 2H6a2 2 0 0 0-
2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V9z"></path><polyline points="13 2
13 9 20 9"></polyline></svg>
      Orders
    </a>
  </li>
  <li class="nav-item">
    <a class="nav-link" href="{{route('products-
admin')}}">
      <svg xmlns="http://www.w3.org/2000/svg"
width="24" height="24" viewBox="0 0 24 24" fill="none"
stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-
linejoin="round" class="feather feather-shopping-cart"><circle cx="9"
cy="21" r="1"></circle><circle cx="20" cy="21" r="1"></circle><path d="M1
1h4l2.68 13.39a2 2 0 0 0 2 1.61h9.72a2 2 0 0 0 2-1.61L23
6H6"></path></svg>
      Products
    </a>
  </li>
  <li class="nav-item">
    <a class="nav-link" href="{{route('users')}}">
      <svg xmlns="http://www.w3.org/2000/svg"
width="24" height="24" viewBox="0 0 24 24" fill="none"
stroke="currentColor" stroke-width="2" stroke-linecap="round" stroke-
linejoin="round" class="feather feather-users"><path d="M17 21v-2a4 4 0 0
0-4-4H5a4 4 0 0 0-4 4v2"></path><circle cx="9" cy="7"
r="4"></circle><path d="M23 21v-2a4 4 0 0 0-3-3.87"></path><path d="M16
3.13a4 4 0 0 1 0 7.75"></path></svg>
      Customers
    </a>
  </li>

  <li class="nav-item">
    <a class="nav-link" href="{{route('show-
messages')}}">
      <i class="fas fa-inbox feather feather-bar-
chart-2"></i>
      Messages
    </a>
  </li>
</ul>

</div>
</nav>
<main role="main" class="col-md-9 ml-sm-auto col-lg-10 px-md-
4"><div class="chartjs-size-monitor"><div class="chartjs-size-monitor-

```

```

expand"><div class=""></div></div><div class="chartjs-size-monitor-
shrink"><div class=""></div></div></div>
        @yield('content')
    </main>
</div>
</div>

<div>
    <div id="twoseven-ext-tab-media-modal" class="twoseven-ext-tab-media-
modal" style="display: none;">
        <!-- Modal content -->
        <div class="twoseven-ext-tab-media-modal-content">
            <div class="iframe-container" style="height: 100%; width:
100%;">
                <span class="close">x</span>
            </div>
        </div>
    </div></div>
<include('fixed.scripts')
</body>

</html>

```

Pages

cart/index.blade.php

```

@extends('layouts.layout')
@section('header_class')
    fixed-top
@endsection
@section('csrf-token')
    <meta name="csrf-token" content="{{ csrf_token() }}">
@endsection
@section('title')
    Dreamy | Cart
@endsection
@section('keywords')
    products, lamp, table, armchair, sofa, nightstand, sort, purchase,
discount
@endsection
@section('description')
    Dreamy furniture store, your cart
@endsection
@section('content')

```

```

<div class="container border-top marginTB2">
  <div class="row">
    <div class="col-12 py-5">
      <h3 class="font-weight-bold font-italic text-center
colorRottenCherry">Cart status</h3>
      <div id="cartStatus">
        @if(empty($cartItems))
          <div class="col-12">
            <p class="alert-danger my-5 text-center py-2
font-weight-bold">Cart is empty</p>
          </div>
        @else
          @foreach($cartItems as $cart)
            <x-cart-row :idProd="$cart->idProd"
:image="$cart->img_src" :alt="$cart->img_alt" :name="$cart->name"
:price="$cart->price" :discount="$cart->discount" >

              </x-cart-row>
            <hr/>
          @endforeach
        @endif
      </div>
    <div class="row my-4">
      <div class="col-6 text-center font18">
        <p>Remove all from cart</p>
        <a href="{{route('remove-all')}}" class="btn
removeButton colorMint py-1 px-1 font18">Remove all</a>
      </div>
      <div class="col-6 text-center font18">
        <p>Go to checkout</p>
        <a href="{{route('checkout')}}" class="btn
removeButton colorMint py-1 px-1 font18">Checkout</a>
      </div>
    </div>
  </div>
  <!--<div class="col-12 col-md-3 text-center col-lg-4 py-5"
id="cart">
    
  </div-->
</div>
</div>

```

```
@endsection
```

products/index.blade.php

```
@extends('layouts.layout')
@section('csrf-token')
    <meta name="csrf-token" content="{{ csrf_token() }}">
@endsection
@section('header_class')
    fixed-top
@endsection
@section('title')
    Dreamy | Products
@endsection
@section('keywords')
    products, lamp, table, armchair, sofa, nightstand, sort, purchase,
discount
@endsection
@section('description')
    Dreamy furniture store, where you can purchase furniture with a good
discount
@endsection
@section('content')
    <div class="container-fluid marginTop">
        <hr/>
    </div>

    <div class="container-fluid my-5">
        @if (session('error'))
            <div class="alert alert-danger">
                <p>{{session('error')}}</p>
            </div>
        @endif
        <div class="row">

            <div class="col-12 col-sm-3 col-lg-2 mb-5 ">
                <div id="filterP">
                    <form action="{{route('products')}}" method="GET">

                        <div id="filter">
                            <ul>
                                <li class="active">
                                    <h5 class="filterC py-1 pl-2 font-weight-
bold pointer">Categories</h5>
                                    <ul class="list-group mb-2 pointer">
```

```

id="categories" >

                                @foreach($data['categoryId']
as $cat)
                                @if(session()-
>has('category'))
                                <li class="list-
group-item borderLi">

<input type="checkbox" value="{{ $cat->id }}" name="chCat[]" class="chCat"
id="{{ $cat->id }}"

@for($i=0;$i <= count(session()->get('category')); $i++)

@if(session()->get('category.'.$i)==$cat->id)

checked

@endif

@endfor
                                />

                                {{ $cat->name }}

                                </li>
                                @else
                                <li class="list-group-item
borderLi">

                                <input type="checkbox"
value="{{ $cat->id }}" name="chCat[]" class="chCat" id="{{ $cat->id }}">
                                {{ $cat->name }}
                                </li>
                                @endif
                                @endforeach
                                </ul>
                                </li>
                                <li>
                                <h5 class="filterC py-1 pl-2 font-weight-
bold pointer">Colors</h5>
                                <ul class="list-group mb-2 pointer"
id="colors">

                                @foreach($data['colors'] as $col)
                                @if(session()->has('color'))
                                <li class="list-group-item
borderLi">

                                <input type="checkbox"
value="{{ $col->id }}" name="chCol[]" class="chCol" id="{{ $col->id }}"

```

```

count(session()->get('color')); $i++)
@for($i=0;$i <=
>get('color.'.$i)==$col->id)
checked
@endif
@endfor
/> {{$col->color}}
</li>
@else
<li class="list-group-item
borderLi">
<input type="checkbox"
value="{{$col->id}}" name="chCol[]" class="chCol" id="{{$col->id}}">
{{$col->color}}
</li>
@endif
@endforeach
</ul>
</li>
<li>
<h5 class="filterC py-1 pl-2 font-weight-
bold pointer">
Product status </h5>
<ul class="list-group pointer">
<li class="list-group-item borderLi">
<input type="radio" name="status" @if(session()->has('status') &&
session()->get('status')=='1') checked @endif class="radioS" value="1" />
In stock</li>
<li class="list-group-item borderLi">
<input type="radio" name="status" @if(session()->has('status') &&
session()->get('status')=='0') checked @endif class="radioS" value="0" />
Out of stock</li>
</ul>
</li>
</ul>
</div>
<div class="col mb-3" id="priceHtml">
<label class="font-weight-bold font18
colorRottenCherry">Sort by price</label>
<select name="priceSort" class="font18"
id="priceSort">
<option value="0">Choose</option>
<option value="1" @if(session()-
>has('priceSort') && session()->get('priceSort')=='1') selected @endif
>Price descending</option>
<option value="2" @if(session()-

```

```

>has('priceSort') && session()->get('priceSort')== '2') selected @endif
>Price growing</option>
    </select>
  </div>

  <div class="col mb-3" id="dicountHtml">
    <label class="colorRottenCherry font18 font-
weight-bold">Show dicounts</label>
    <select name="discountFilter" class="font18"
id="discountFilter">
      <option value="0">Choose</option>
      @foreach($data['discounts'] as $dis)
        @if(session()->has('discount') &&
session()->get('discount')== $dis->id)
          <option value="{{ $dis->id }}"
selected>{{ $dis->name }}</option>
        @else
          <option value="{{ $dis->id }}">{{ $dis-
>name }}</option>
        @endif
      @endforeach
    </select>
  </div>

  <div class="col mb-3">
    <div class="form-inline">
      <input type="search" name="keyword" id="find"
placeholder="Search by name.." value="@if(session()->has('keyword'))
{{session()->get('keyword')}} @endif"/>
    </div>
  </div>

  <div class="col">
    <button class="btn btnFilter"
type="submit">Filter</button>
  </div>

</form>
</div>

<div class="col-12 col-sm-9 col-lg-10">
  <div class="row" id="products">

    @forelse ($model as $prod)
      <x-product
        :name="$prod->productName"

```

```

                :price="$prod->price"
                :color="$prod->color"
                :category="$prod->category"
                :prodId="$prod->prodId"
                :imgAlt="$prod->imgAlt"
                :imgSrc="$prod->imgSrc"
                :discountName="$prod->discountName"
                :discountStyle="$prod->css"
                :discountPrice="$prod->discountPrice"
                :status="$prod->status"
                :material="$prod->material"
            >
        </x-product>
    @empty
        <div class="col-12">
            <p class="alert-danger my-5 text-center py-2
font-weight-bold">No products were found</p>
        </div>
    @endforelse
</div>

    <div class="col-12">
        {{ $model->links("pagination::bootstrap-4") }}
    </div>

</div>
</div>
</div>
@endsection

```

orders/index.blade.php

```

@extends('layouts.layout')
@section('csrf-token')
    <meta name="csrf-token" content="{{csrf_token()}}">
@endsection
@section('title')
    Dreamy | Orders
@endsection
@section('keywords')
    address, total, quantity, payment type, delivery method
@endsection

```



```

@section('description')
    Dreamy furniture store, your orders
@endsection
@section('header_class')
    fixed-top
@endsection
@section('content')
    <div class="container-fluid border-top marginTB2">
        <div class="row">
            <div class="col-12 py-5">
                <h3 class="font-weight-bold font-italic text-center
colorRottenCherry">My orders</h3>
                <div id="orderStatus">
                    @if(count($data['orders'])==0)
                        <div class="col-12">
                            <p class="alert-danger my-5 text-center py-2
font-weight-bold">You haven't purchased anything</p>
                        </div>
                    @else
                        <div class="container-fluid">
                            <div class="col-12 table-responsive ">
                                <table class="table table-striped
table-bordered">
                                    <thead>
                                        <tr>
                                            <th scope="col" class="text-
center">Address</th>
                                            <th scope="col" class="text-
center">Quantity</th>
                                            <th scope="col" class="text-
center">Total</th>
                                            <th scope="col" class="text-
center">Payment type</th>
                                            <th scope="col" class="text-
center">Delivery method</th>
                                            <th scope="col" class="text-
center">Created at</th>
                                            <th scope="col" class="text-
center"></th>
                                            <th scope="col" class="text-
center"></th>
                                        </tr>
                                    </thead>
                                    <tbody id="ordersTr">
                                        @foreach($data['orders'] as
$order)
                                            <tr id="orderId_{{$order-

```

```

<id}}">
center">{{ $order->address }}</td>
center"> {{ $order->quantity}} </td>
center">{{ $order->total. " $"}}</td>
center">{{ $order->payment_type}}</td>
center">{{ $order->delivery_method}}</td>
center">{{ $order->created_at}}</td>
center"><button type="button" data-id="{{ $order->id }}" class="colorMint
btn btnSubmit font-weight-bold py-1 px-1 btnShowOrderItems" data-
toggle="modal" data-target=".bd-example-modal-lg">
Show
</button>
<!-- Modal -->
<div class="modal
fade bd-example-modal-lg" tabindex="-1" role="dialog" aria-
labelledby="myLargeModalLabel" aria-hidden="true">
<div
class="modal-dialog modal-lg">
<div
class="modal-content">
<div
class="modal-header">
<h5
class="modal-title" id="exampleModalLongTitle">Order items</h5>
<button type="button" class="close" data-dismiss="modal" aria-
label="Close">
<span aria-hidden="true">&times;</span>
</button>
</div>
<div
class="modal-body">
<table class="table table-borderless tableBg">
<thead>
<tr class="borderBottom">

```

```

<th scope="col" >Product</th>

<th scope="col">Name</th>

<th scope="col">Quantity</th>

<th scope="col" >Price</th>

</tr>

</thead><tbody id="orderItems">

</tbody></table>

</div>
<div
class="modal-footer">

<button type="button" class="colorMint btn btnSubmit font-weight-bold py-
1 px-1" data-dismiss="modal">Close</button>

</div>
</div>
</div>
</div>
</td>

<td class="col-1 text-
center"><button onclick="deleteOrder('{{ $order->id }})' " class="colorMint
btn btnSubmit font-weight-bold py-1 px-1 ">Cancel</button></td>

</tr>

@endforeach
</tbody>
</table>

</div>
</div>

@endif

</div>
</div>
<div class="col-12">

{{ $data['orders']->links("pagination::bootstrap-4") }}

```

```

        </div>
    </div>
</div>

@endsection

```

orders/orderForm.blade.php

```

@extends('layouts.layout')

@section('title')
    Dreamy | Order form
@endsection
@section('keywords')
    address, payment type, delivery method
@endsection
@section('description')
    Dreamy furniture store, order form
@endsection
@section('content')
    <div class="container-fluid border-top my-5">
        <div class="row">
            <div class="col-12 col-md-8 col-lg-5 py-5 m-auto">
                <h2 class="font-weight-bold font-italic text-center mb-3
colorRottenCherry">Order form</h2>
                @if (session('error'))
                    <div class="alert alert-danger">
                        <p>{{session('error')}}</p>
                    </div>
                @endif
                <form action="{{route('order-form-submit')}}"
method="POST" name="formOrder" enctype="multipart/form-data">
                    @csrf
                    <div class="col mb-3">
                        <label class="font-weight-bold colorRottenCherry
font18 ">Address:*</label>
                        <input type="text" name="address" class="form-
control" value="{{old('addres')}}" placeholder="Dimitrija Tucovića 12,
Beograd 11000"/>
                        @error('address')
                            <div class="alert alert-danger">
                                {{ $message }}
                            </div>
                        @enderror
                    </div>

                    <div class="col mb-3">
                        <label class="font-weight-bold colorRottenCherry

```



```

@extends('layouts.layout')

@section('csrf-token')
    <meta name="csrf-token" content="{{ csrf_token() }}">
@endsection

@section('title')
    Dreamy | Furniture store
@endsection

@section('keywords')
    products, furniture, lamps, tables, armchairs, sofas
@endsection

@section('description')
    Dreamy furniture store, here to help you decorate your home with our
    furniture
@endsection

@section('header_class')
    fixed-top
@endsection
@section('banner')
    @include('fixed.banner')
@endsection

@section('content')
    <div class="container my-5">
        <div class="row">
            <h2 class="centering border-bottom font-italic">What do we
offer?</h2>
            </div>
            <div id="productDes">

                @foreach($data['categoryId'] as $cat)

                    <x-card
                        :image="$cat->img_src"
                        :imageAlt="$cat->name"
                        :title="$cat->name"
                        :description1="$cat->description1"
                        :description2="$cat->description2"
                        :idCat="$cat->id"
                    ></x-card>

                @endforeach
            </div>
        </div>
    </div>

```

```

        <div class="container-fluid mt-5">
            <div class="row my-5 col-12">
                <h2 class="centering border-bottom font-italic">Need help
with room design, here are some ideas?</h2>
            </div>
            <div id="rooms-Gallery">
                <div class="row my-5" id="room">
                    @foreach($data['rooms'] as $room)
                        <x-room-card
                            :src="$room['src']"
                            :alt="$room['alt']"
                        ></x-room-card>
                    @endforeach
                </div>
            </div>
        </div>
    @endsection

```

main/contact.blade.php

```

@extends('layouts.layout')

@section('title')
    Dreamy | Contact
@endsection
@section('keywords')
    products, lamp, table, armchair, sofa, nightstand, sort, purchase,
discount
@endsection
@section('description')
    Dreamy furniture store, contact admin
@endsection
@section('content')
    <div class="container-fluid marginTop5 px-5 ">
        <div class="row">
            <div class="col-12 col-md-8 col-lg-4 py-5 m-auto"
id="loginForm">
                <h2 class="font-weight-bold font-italic text-center mb-3
colorRottenCherry">Send message to admin</h2>
                @if (session('error'))
                    <div class="alert alert-danger">
                        <p>{{session('error')}}</p>
                    </div>
                @elseif(session('success'))
                    <div class="alert alert-success">
                        <p>{{session('success')}}</p>
                    </div>
                @endif
            </div>
        </div>
    </div>

```

```

        <form action="{{route('message')}}" method="POST"
name="formLogin" enctype="multipart/form-data">
            @csrf
            <div class="col-6 mb-3">
                <label class="font-weight-bold colorRottenCherry
font18">Admin:</label>
                <select name="admin" class="form-control">
                    <option value="">Choose</option>
                    @foreach($admins as $a)
                        <option value="{{ $a->id }}">{{ $a-
>email}}</option>
                    @endforeach
                </select>
            </div>
            <div class="col mb-3">
                <label class="font-weight-bold colorRottenCherry
font18">Message:</label>
                <textarea name="message" class="form-control"
id="messageAdmin">

                    </textarea>
                    @error('message')
                    <div class="alert alert-danger">
                        {{ $message }}
                    </div>
                    @enderror
                </div>

                <div class="col text-center mt-2 ">
                    <button type="submit" class="btn btnSubmit
colorMint font-weight-bold font18 ">Submit</button>
                </div>
            </form>
        </div>
    </div>
</div>
@endsection

```

main/author.blade.php


```

@extends('layouts.layout')
@section('title')
    Dreamy | Author
@endsection
@section('keywords')
    products, cart, author, store
@endsection
@section('description')
    Dreamy furniture store, something about our author
@endsection

@section('content')
    <div class="container my-4">
        <div class="row">
            <div class="col-12 col-lg-6 text-center mb-3" id="authorImg">
                
            </div>
            <div class="col-12 col-lg-6">
                <div class="card py-3 px-4" id="authorText">
                    <div class="card-body">
                        <h4 class="card-title">My name is Anica
Radenković</h4>
                        <h6 class="card-subtitle mb-2 text-muted">Here's
something about me</h6>
                        <p class="card-text fontSize">Date of birth:
14.02.2002</p>
                        <p class="card-text fontSize">Status: Student</p>
                        <p class="card-text fontSize">Place of study: ICT
College</p>
                        <p class="card-text fontSize">Module: Web
programming</p>
                        <p class="card-text fontSize">Title after
graduation: Professional Engineer of Electrical Engineering and
Computing</p>
                        <p class="card-text fontSize">Objective:
Acquiring adequate knowledge, expertise and skills to work in creative
places in the field of programming</p>
                        <a
href="https://anica02.github.io/portfolioWebPage/" class="card-link
fontSize" target="_blank">My portfolio</a>
                    </div>
                </div>
            </div>
        </div>
    </div>
@endsection

```

```
@extends('layouts.form')

@section('title')
    Dreamy | Login
@endsection
@section('keywords')
    login, email, password, account, register
@endsection
@section('description')
    Dreamy furniture store, login
@endsection
@section('content')
    <div class="container-fluid marginTop5 px-5 ">
        <div class="row">
            <div class="col-12 col-md-8 col-lg-4 py-5 m-auto"
id="loginForm">
                <h2 class="font-weight-bold font-italic text-center mb-3
colorRottenCherry">Login</h2>
                @if (session('error'))
                    <div class="alert alert-danger">
                        <p>{{session('error')}}</p>
                    </div>
                @elseif(session('success'))
                    <div class="alert alert-danger">
                        <p>{{session('success')}}</p>
                    </div>
                @endif
                <form action="{{route('login')}}" method="POST"
name="formLogin" enctype="multipart/form-data">
                    @csrf
                    <div class="col mb-3">
                        <label class="font-weight-bold colorRottenCherry
font18">Email:</label>
                        <input type="email" name="email" class="form-
control" value="{{old('email')}}" />
                    </div>
                    <div class="col mb-3">
                        <label class="font-weight-bold colorRottenCherry
font18">Password:</label>
                        <input type="password" name="password"
class="form-control" value="{{old('password')}}" />
                    </div>
                    <div class="col-12">
                        <a class="colorMint font18 font-weight-bold
register" href="{{route('register')}}">Don't have an account? Register
```

```

here </a>
        </div>
        <div class="col text-center mt-2 ">
            <button type="submit" class="btn btnSubmit
colorMint font-weight-bold font18 " >Submit</button>
        </div>
    </form>
</div>
</div>
</div>

@endsection

```

main/register.blade.php

```

@extends('layouts.form')

@section('title')
    Dreamy | Register
@endsection
@section('keywords')
    register, name, email ,password
@endsection
@section('description')
    Dreamy furniture store, create your account
@endsection
@section('content')
    <div class="container-fluid marginTop3 px-5">
        <div class="row">
            <div class="col-12 col-md-8 col-lg-4 py-5 m-auto"
id="loginForm">
                <h2 class="font-weight-bold font-italic text-center mb-3
colorRottenCherry">Register</h2>
                @if (session('error'))
                    <div class="alert alert-danger">
                        <p>{{session('error')}}</p>
                    </div>
                @endif
                <form action="{{route('register-post')}}" method="POST"
name="formRegister" enctype="multipart/form-data">
                    @csrf

                    <div class="col mb-3">
                        <label class="font-weight-bold colorRottenCherry
font18">First name:</label>
                        <input type="text" name="firstName" class="form-

```

```

control" value="{{old('firstName')}}" />
                @error('firstName')
                <div class="alert alert-danger">
                    {{$message}}
                </div>
            @enderror
        </div>
        <div class="col mb-3">
            <label class="font-weight-bold colorRottenCherry
font18">Last name:</label>
            <input type="text" name="lastName" class="form-
control" value="{{old('lastName')}}" />
                @error('lastName')
                <div class="alert alert-danger">
                    {{$message}}
                </div>
            @enderror
        </div>

        <div class="col mb-3">
            <label class="font-weight-bold colorRottenCherry
font18">Email:</label>
            <input type="email" name="email" class="form-
control" value="{{old('email')}}" />
                @error('email')
                <div class="alert alert-danger">
                    {{$message}}
                </div>
            @enderror
        </div>
        <div class="col mb-3">
            <label class="font-weight-bold colorRottenCherry
font18">Password:</label>
            <input type="text" name="password" class="form-
control" value="{{old('password')}}" />
                @error('password')
                <div class="alert alert-danger">
                    {{$message}}
                </div>
            @enderror
        </div>
        <div class="col text-center ">
            <button type="submit" class="btn btnSubmit
colorMint font-weight-bold font18 " >Submit</button>
        </div>
    </form>
</div>
</div>

```

```
</div>

@endsection
```

admin/home.blade.php

```
@extends('layouts.admin')
@section('title')
    Dreamy | Admin panel
@endsection
@section('keywords')

@endsection
@section('description')
    Dreamy furniture store, admin panel
@endsection
@section('content')

    <h1 class="h2 colorBlue">Dashboard</h1>
    <div class="d-flex justify-content-between flex-wrap flex-md-nowrap
align-items-center pt-3 pb-2 mb-3 border-bottom">

        <div class="container">
            <div class="row align-items-center g-4 mb-5">
                <div class="col-12 col-md-auto">
                    <div class="d-flex align-items-center"><i class="fas
fa-users stat"></i>
                        <div class="ms-3 colorBlue">
                            <h4 class="mb-0">{{ $data['users'] }}
customers</h4>
                            <p class="text-800 fs--1 mb-0">Active</p>
                        </div>
                    </div>
                </div>
                <div class="col-12 col-md-auto">
                    <div class="d-flex align-items-center"><i class="fas
fa-clock stat"></i>
                        <div class="ms-3 colorBlue">
                            <h4 class="mb-0">{{ $data['orders'] }}
orders</h4>
                            <p class="text-800 fs--1 mb-0">Total
orders</p>
                        </div>
                    </div>
                </div>
            </div>
        </div>

    </div>
```

```

        <div class="col-12 col-md-auto">
            <div class="d-flex align-items-center"><i class="fas
fa-store stat"></i>
                <div class="ms-3 colorBlue">
                    <h4 class="mb-0">{{ $data['inStock'] }}
products</h4>
                    <p class="text-800 fs--1 mb-0">In stock</p>
                </div>
            </div>
        </div>
        <div class="col-12 col-md-auto">
            <div class="d-flex align-items-center"><i class="fas
fa-store-slash stat"></i>
                <div class="ms-3 colorBlue">
                    <h4 class="mb-0">{{ $data['outOfStock'] }}
products</h4>
                    <p class="text-800 fs--1 mb-0">Out of
stock</p>
                </div>
            </div>
        </div>
    </div>
</div>
<div class="container-fluid my-3">
    <div class="row">
        <div class="col-12 py-5">
            <h3 class="font-weight-bold font-italic text-center
colorBlue">User activities</h3>
            <form action="{{ route('home-admin') }}" method="GET">
                <div class="row mt-3">
                    <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
                        <p class="font-weight-bold mb-3 colorBlue
font18">Name</p>
                        <select name="nameAc" class="form-control">
                            <option value="" >Choose</option>
                            @foreach($data['acNames'] as $name)
                                @if(session()->has('nameAc') &&
session()->get('nameAc')== $name->name)
                                    <option value="{{ $name->name }}"
selected >{{ $name->name }}</option>
                                @else
                                    <option value="{{ $name->name }}"
>{{ $name->name }}</option>
                                @endif
                            @endforeach
                        </select>

```

```

        </div>
        <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
            <p class="font-weight-bold mb-3 colorBlue
font18" >Users</p>
            <select name="userAc" class="form-control">
                <option value="" >Choose</option>
                @foreach($data['acUsers'] as $user)
                    @if(session()->has('userAc') &&
session()->get('userAc')==>$user->user)
                        <option value="{{>$user->user}}"
selected>{{>$user->user}}</option>
                    @else
                        <option value="{{>$user->
user}}">{{>$user->user}}</option>
                    @endif
                @endforeach
            </select>
        </div>
        <div class="col-12 col-sm-6 col-lg-4 col-xl-3">
            <p class="font-weight-bold mb-3 colorBlue
font18">Filter</p>
            <button type="submit" class="btn btnSubmit
colorMint font-weight-bold font18" >Submit</button>
        </div>
    </div>

    </form>

    <div id="messages" class="mt-5">
        @if(count($activities)!=0)
            <div class="col-12 table-responsive">
                <table class="table">
                    <thead>
                        <tr>
                            <th scope="col">Name</th>
                            <th scope="col">User</th>
                            <th scope="col">Date</th>
                            <th scope="col">Data</th>
                        </tr>
                    </thead>
                    <tbody id="activitiesTR">
                        @foreach($activities as $a)
                            <tr>
                                <td>{{>$a->name}}</td>
                                <td>{{>$a->user}}</td>
                                <td>{{>$a->date}}</td>
                                <td>{{>$a->request_data}}</td>
                            </tr>
                        @endforeach
                    </tbody>
                </table>
            </div>
        </if>
    </div>

```

```

                </tbody>
            </table>
        </div>
        @else
            <div class="col-12">
                <p class="alert-danger my-5 text-center py-2
font-weight-bold">No activities</p>
            </div>
        @endif
    </div>
    <div class="col-12">
        {{ $activities->links("pagination::bootstrap-4") }}
    </div>
</div>
</div>
</div>
@endsection

```

admin/messages/index.blade.php

```

@extends('layouts.admin')
@section('csrf-token')
    <meta name="csrf-token" content="{{ csrf_token() }}">
@endsection
@section('title')
    Dreamy | Messages
@endsection
@section('keywords')
    message, admin, user, email
@endsection
@section('description')
    Dreamy furniture store, your messages
@endsection

@section('content')
    <div class="container-fluid my-3 ">
        <div class="row">
            <div class="col-12 py-5">
                <h3 class="font-weight-bold font-italic text-center
colorBlue">Messages</h3>
                <form action="{{route("show-messages")}}" method="GET">

```



```

                </tr>
            @endforeach
        </tbody>
    </table>
</div>
    @else
        <div class="col-12">
            <p class="alert-danger my-5 text-center py-2
font-weight-bold">No messages</p>
        </div>
    @endif
</div>
<div class="col-12">
    {{ $messages->links("pagination::bootstrap-4") }}
</div>
</div>
</div>
</div>
@endsection

```

admin/orders/index.blade.php

```

@extends('layouts.admin')
@section('csrf-token')
    <meta name="csrf-token" content="{{csrf_token()}}">
@endsection
@section('title')
    Dreamy | Orders
@endsection
@section('keywords')
    address, quantity, total, user, payment type, delivery method,
@endsection
@section('description')
    Dreamy furniture store, orders
@endsection

@section('content')
    <div class="container-fluid border-top marginTB2">
        <div class="row">
            <div class="col-12 py-5">
                <h3 class="font-weight-bold font-italic text-center
colorRottenCherry mb-5">Orders</h3>
                <form action="{{route("orders-admin")}}" method="GET">
                    <div class="row mb-5">
                        <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
                            <p class="font-weight-bold mb-3 colorBlue

```

```

font18" >User</p>
        <select name="user0" class="form-control">
            <option value="" >Choose</option>
            @foreach( $data['emails'] as $user)
                @if(session()->has('user0') &&
session()->get('user0')==>id_user)
                    <option value="{{>id_user}}" selected>{{>email}}</option>
                @else
                    <option value="{{>id_user}}">{{>email}}</option>
                @endif
            @endforeach
        </select>
    </div>
    <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
        <p class="font-weight-bold mb-3 colorBlue
font18" >Payment type</p>
        <select name="paymentU" class="form-control">
            <option value="" >Choose</option>
            <option value="card" @if(session()-
>has('paymentU') && session()->get('paymentU')=="card") selected @endif
>Card</option>
            <option value="cash" @if(session()-
>has('paymentU') && session()->get('paymentU')=="cash") selected @endif
>Cash</option>
        </select>
    </div>
    <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
        <p class="font-weight-bold mb-3 colorBlue
font18" >Delivery method</p>
        <select name="deliveryU" class="form-
control">
            <option value="" >Choose</option>
            <option value="address" @if(session()-
>has('deliveryU') && session()->get('deliveryU')=="address") selected
@endif >Home address</option>
            <option value="postOffice" @if(session()-
>has('deliveryU') && session()->get('deliveryU')=="postOffice") selected
@endif >Post office</option>
        </select>
    </div>
    <div class="col-12 col-sm-6 col-lg-4 col-xl-3">
        <p class="font-weight-bold mb-3 colorBlue
font18">Filter</p>
        <button type="submit" class="btn btnSubmit
colorMint font-weight-bold font18" >Submit</button>
    </div>

```

```

        </div>

    </form>
    <div id="orderStatus">
        @if(count($model)==0)
        <div class="col-12">
            <p class="alert-danger my-5 text-center py-2
font-weight-bold">No orders had been made</p>
        </div>
        @else
            <div class="container-fluid">
                <div class="col-12 table-responsive ">
                    <table class="table table-striped table-
bordered">
                        <thead>
                            <tr>
                                <th scope="col" class="text-
center">User</th>
                                <th scope="col" class="text-
center">Address</th>
                                <th scope="col" class="text-
center">Quantity</th>
                                <th scope="col" class="text-
center">Total</th>
                                <th scope="col" class="text-
center">Payment type</th>
                                <th scope="col" class="text-
center">Delivery method</th>
                                <th scope="col" class="text-
center">Created at</th>
                                <th scope="col" class="text-
center"></th>
                                <th scope="col" class="text-
center"></th>
                            </tr>
                        </thead>
                        <tbody id="ordersTr">
                            @foreach($model as $order)
                                @foreach($data['users'] as $user)
                                    @if($order->id_user==$user-
>id)
                                        <tr id="orderId_{{ $order-
>id }}">
                                            <td class="col-2 text-
center">{{ $user->email }}</td>
                                            <td class="col-3 text-
center">{{ $order->address }}</td>
                                            <td class="col-1 text-
center">{{ $order->quantity }} </td>

```

```

center">{{ $order->total. " $"}}</td>
center">{{ $order->payment_type}}</td>
center">{{ $order->delivery_method}}</td>
center">{{ $order->created_at}}</td>
center"><button type="button" data-id="{{ $order->id }}" class="colorMint
btn btnSubmit font-weight-bold py-1 px-1 btnShowOrderItemsAdmin" data-
toggle="modal" data-target=".bd-example-modal-lg">
Show
</button>
<!-- Modal -->
<div class="modal fade
bd-example-modal-lg" tabindex="-1" role="dialog" aria-
labelledby="myLargeModalLabel" aria-hidden="true">
<div class="modal-
dialog modal-lg">
<div
class="modal-content">
<div
class="modal-header">
<h5
class="modal-title" id="exampleModalLongTitle">Order items</h5>
<button
type="button" class="close" data-dismiss="modal" aria-label="Close">
<span
aria-hidden="true">&times;</span>
</button>
</div>
<div
class="modal-body">
<table
class="table table-borderless tableBg">
<thead>
<tr
class="borderBottom">
<th scope="col">Product</th>
<th scope="col">Name</th>
<th scope="col">Quantity</th>

```

```

<th scope="col" >Price</th>
</tr>

</thead><tbody id="orderItems">

</tbody></table>

</div>
<div
class="modal-footer">
<button
type="button" class="colorMint btn btnSubmit font-weight-bold py-1 px-1"
data-dismiss="modal">Close</button>
</div>
</div>
</div>
</div>
</td>

<td class="col-1 text-
center"><button onclick="deleteOrderAdmin({{$order->id}})"
class="colorMint btn btnSubmit font-weight-bold py-1 px-1"
">Remove</button></td>

</tr>
@endif
@endforeach
@endforeach
</tbody>
</table>

</div>
</div>

@endif

</div>
<div class="col-12">
{{ $model->links("pagination::bootstrap-4") }}
</div>
</div>
</div>
</div>
@endsection

```

admin/users/index.blade.php

```

@extends('layouts.admin')
@section('csrf-token')

```

```

    <meta name="csrf-token" content="{{csrf_token()}}">
@endsection
@section('title')
    Dreamy | Users
@endsection
@section('keywords')
    first name, lats name, email, active, Id_role
@endsection
@section('description')
    Dreamy furniture store, users
@endsection

@section('content')
    <div class="container-fluid border-top marginTB2">
        <div class="row">
            <div class="col-12 py-5">
                <h3 class="font-weight-bold font-italic text-center
colorRottenCherry mb-5">Users</h3>
                <form action="{{route('users')}}" method="GET">
                    <div class="row mb-5">
                        <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
                            <p class="font-weight-bold mb-3 colorBlue
font18" >Email</p>

                            <select name="emailU" class="form-control">
                                <option value="" >Choose</option>
                                @foreach( $data['emails'] as $user)
                                    @if(session()->has('emailU') &&
session()->get('emailU')==>email)
                                        <option value="{{>$user->email}}"
selected>{{>$user->email}}</option>
                                    @else
                                        <option value="{{>$user->
>email}}">{{>$user->email}}</option>
                                    @endif
                                @endforeach
                            </select>
                        </div>
                        <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
                            <p class="font-weight-bold mb-3 colorBlue
font18" >Role</p>

                            <select name="roleU" class="form-control">
                                <option value="" >Choose</option>
                                @foreach( $data['roles'] as $role)
                                    @if(session()->has('roleU') &&
session()->get('roleU')==>$role->id)
                                        <option value="{{>$role->id}}"
selected>{{>$role->role}}</option>
                                    @else
                                        <option value="{{>$role->

```

```

>id}}">{{$role->role}}</option>
                                @endif
                                @endforeach
                                </select>
                                </div>
                                <div class="col-12 col-sm-6 col-lg-4 col-xl-3 ">
                                <p class="font-weight-bold mb-3 colorBlue
font18" >Active</p>
                                <select name="statusU" class="form-control">
                                <option value="" >Choose</option>
                                <option value="0" @if(session()-
>has('statusU') && session()->get('statusU')==0") selected @endif
>Inactive</option>
                                <option value="1" @if(session()-
>has('statusU') && session()->get('statusU')==1") selected @endif
>Active</option>
                                </select>
                                </div>
                                <div class="col-12 col-sm-6 col-lg-4 col-xl-3">
                                <p class="font-weight-bold mb-3 colorBlue
font18">Filter</p>
                                <button type="submit" class="btn btnSubmit
colorMint font-weight-bold font18" >Submit</button>
                                </div>
                                </div>
                                </form>
                                <div id="orderStatus">
                                @if(count($model)==0)
                                <div class="col-12">
                                <p class="alert-danger my-5 text-center py-2
font-weight-bold">No users had been found</p>
                                </div>
                                @else
                                <div class="container-fluid">
                                <div class="col-12 table-responsive ">
                                <table class="table table-striped table-
bordered">
                                <thead>
                                <tr>
                                <th scope="col" class="text-
center">First name</th>
                                <th scope="col" class="text-
center">Last name</th>
                                <th scope="col" class="text-
center">Email</th>
                                <th scope="col" class="text-
center">Id_role</th>

```



```

center">Active</th>
center">Created at</th>
center"></th>
center"></th>

<tr>
</thead>
<tbody id="ordersTr">
@foreach($model as $user)
    <tr id="userId_{{$user->id}}">
        <td class="col-2 text-
center">{{ $user->first_name }}</td>
        <td class="col-1 text-
center"> {{ $user->last_name}} </td>
        <td class="col-3 text-
center">{{ $user->email}}</td>
        <td class="col-1 text-
center">{{ $user->id_role}}</td>
        <td class="col-1 text-
center">{{ $user->active}}</td>
        <td class="col-3 text-
center">{{ $user->created_at}}</td>
        <td class="col-1 text-
center"><button type="button" data-id="{{$user->id}}" class="colorMint
btn btnSubmit font-weight-bold py-1 px-1 btnShowUserParam" data-
toggle="modal" data-target=".bd-example-modal-lg">
            Edit
        </button>

        <!-- Modal -->
        <div class="modal fade
bd-example-modal-lg" tabindex="-1" role="dialog" aria-
labelledby="myLargeModalLabel" aria-hidden="true">
            <div class="modal-
dialog modal-lg">
                <div
class="modal-content">
                    <div
class="modal-header">
                        <h5
class="modal-title" id="exampleModalLongTitle">User</h5>
                        <button
type="button" class="close" data-dismiss="modal" aria-label="Close">
                            <span
aria-hidden="true">&times;</span>
                        </button>

```

```

</div>
<div
class="modal-body">
    @if
    ($errors->any())
    <div
class="alert alert-danger">
    <ul>
    @foreach ($errors->all() as $error)
    <li>{{ $error }}</li>
    @endforeach
    </ul>
    </div>
    @endif
    <form
action="{{route('edit-user')}}" method="POST">
    @csrf
    @method('PATCH')
    <div
id="user">
    </div>
    </form>
    </div>
    <div
class="modal-footer">
    <button
type="button" class="colorMint btn btnSubmit font-weight-bold py-1 px-1"
data-dismiss="modal">Close</button>
    </div>
    </div>
    </div>
    </div>
    </td>
    <td class="col-1 text-
center"><button onclick="deleteUser('{{ $user->id }}'" class="colorMint btn
btnSubmit font-weight-bold py-1 px-1 ">Delete</button></td>
    </tr>

```

```

                                @endforeach
                                </tbody>
                            </table>

                            </div>
                        </div>

                        @endif
                    </div>
                    <div class="col-12">
                        {{ $model->links("pagination::bootstrap-4") }}
                    </div>
                </div>
            </div>
        </div>
    </div>

@endsection

```

admin/products/index.blade.php

```

@extends('layouts.admin')
@section('csrf-token')
    <meta name="csrf-token" content="{{csrf_token()}}">
@endsection
@section('title')
    Dreamy | Products
@endsection
@section('keywords')
    image, name, status, color, category, material, price, discount name,
    discount
@endsection
@section('description')
    Dreamy furniture store, products
@endsection

@section('content')
    <div class="container-fluid border-top marginTB2">
        <div class="row">
            <div class="col-12 py-5">
                <a class="btn btnProduct colorMint font-weight-bold
text-center" href="{{route('products-form')}}">
                    INSERT NEW PRODUCT
                </a>
                <h3 class="font-weight-bold font-italic text-center
colorRottenCherry mb-5">Products</h3>
                <form action="{{route('products-admin')}}" method="GET">
                    <div class="row mb-5">

```



```

        <div class="col-12 col-sm-6 col-lg-4 col-xl-2">
            <p class="font-weight-bold mb-3 colorBlue
font18">Name</p>
                <input type="search" name="nameP" class="btn
btnSubmit colorMint font-weight-bold font18 form-control"
value="@if(session()->has('nameP')){{session()->get('nameP')}}@endif" >
                </div>
            <div class="col-12 col-sm-6 col-lg-4 col-xl-2">
                <p class="font-weight-bold mb-3 colorBlue
font18">Filter</p>
                    <button type="submit" class="btn btnSubmit
colorMint font-weight-bold font18" >Submit</button>
                </div>
            </div>

        </form>
        <div id="orderStatus">
            @if(count($model)==0)
                <div class="col-12">
                    <p class="alert-danger my-5 text-center py-2
font-weight-bold">No products where found</p>
                </div>
            @else
                <div class="container-fluid">
                    <div class="col-12 table-responsive ">
                        <table class="table table-striped table-
bordered">
                            <thead>
                                <tr>
                                    <th scope="col" class="text-
center">Image</th>
                                    <th scope="col" class="text-
center">Name</th>
                                    <th scope="col" class="text-
center">Status</th>
                                    <th scope="col" class="text-
center">Color</th>
                                    <th scope="col" class="text-
center">Category</th>
                                    <th scope="col" class="text-
center">Material</th>
                                    <th scope="col" class="text-
center">Price</th>
                                    <th scope="col" class="text-
center">Discount name</th>
                                    <th scope="col" class="text-
center">Discount</th>
                                    <th scope="col" class="text-
center">Created at</th>

```

```

center"></th>
center"></th>
</tr>
</thead>
<tbody id="ordersTr">
@foreach($model as $product)
    <tr id="orderId_{{$product->prodId}}">
        <td class="col-2 text-center">imgAlt}}"></td>
        <td class="col-1 text-center"> {{ $product->productName}} </td>
        <td class="col-1 text-center">{{$ $product->status}}</td>
        <td class="col-1 text-center">{{$ $product->color}}</td>
        <td class="col-1 text-center">{{$ $product->category}}</td>
        <td class="col-1 text-center">{{$ $product->material}}</td>
        <td class="col-1 text-center">{{$product->price}} $</td>
        <td class="col-2 text-center">{{$product->discountName}}</td>
        @if($product->discountPrice)
            <td class="col-1 text-center">
                @else
                <td class="col-1 text-center">
                @endif
            <td class="col-2 text-center">
                <td class="col-1 text-center">
                <a type="button" class="btn btnCart btnProduct colorMint font-weight-bold" href="{{route("update-product-form", [ "id" => $product->prodId])}}">
                    EDIT
                </a>
            </td>
            <td class="col-1 text-center"> <form action="{{route("product-delete", [ "id" => $product->

```

```

>prodId]]}}" method="POST">
                                @csrf
                                <button type="submit"
class="btn btnProduct colorMint font-weight-bold">
                                DELETE
                                </button>
                                </form></td>
                                </tr>
                                @endforeach
                                </tbody>
                                </table>
                                </div>
                                </div>
                                @endif
                                </div>
                                <div class="col-12">
                                {{ $model->links("pagination::bootstrap-4") }}
                                </div>
                                </div>
                                </div>
                                </div>
                                </div>
                                @endsection

```

admin/products/insert.blade.php

```

@extends('layouts.admin')

@section('title')
    Dreamy | Insert new product
@endsection
@section('keywords')
    products, color, material, price, category, image, discount price,
discount type
@endsection
@section('description')
    Dreamy furniture store, insert product
@endsection
@section('content')
    <div class="container-fluid border-top">
        <div class="row">
            <div class="col-12 col-md-8 col-lg-5 py-5 m-auto">
                <h2 class="font-weight-bold font-italic text-center mb-3
colorRottenCherry">Insert new product</h2>

```

```

        @if (session('error'))
            <div class="alert alert-danger">
                <p>{{session('error')}}</p>
            </div>
        @endif
        <form action="{{route('products-post')}}" method="POST"
name="formInsertProduct" enctype="multipart/form-data">
            @csrf
            <div class="col mb-3">
                <label class="font-weight-bold colorRottenCherry
font18 ">Name:*</label>
                <input type="text" name="name" class="form-control"
value="{{old('name')}}" />
                @error('name')
                <div class="alert alert-danger">
                    {{ $message }}
                </div>
                @enderror
            </div>
            <div class="col mb-3">
                <label class="font-weight-bold colorRottenCherry
font18">Price:*</label>
                <input type="number" name="price" class="form-
control" value="{{old('price')}}" />
                @error('price')
                <div class="alert alert-danger">
                    {{ $message }}
                </div>
                @enderror
            </div>
            <div class="col mb-3">
                <label class="font-weight-bold colorRottenCherry
font18">Color:*</label>
                <select name="color" class="form-control">
                    <option value="0">Choose</option>
                    @foreach($data['colors'] as $color)
                        <option value="{{ $color->id }}"
@if(old('color')== $color->id) selected @endif>{{ $color->color}}</option>
                    @endforeach
                </select>
                @error('color')
                <div class="alert alert-danger">
                    {{ $message }}
                </div>
                @enderror
            </div>
            <div class="col mb-3">
                <label class="font-weight-bold colorRottenCherry
font18">Category:*</label>

```



```

        <select name="category" class="form-control">
            <option value="0">Choose</option>
            @foreach($data['categories'] as $cat)
                <option value="{{ $cat->id }}"
@if(old('category')== $cat->id) selected @endif>{{ $cat->name }}</option>
            @endforeach
        </select>
        @error('category')
        <div class="alert alert-danger">
            {{ $message }}
        </div>
        @enderror
    </div>
    <div class="col mb-3">
        <label class="font-weight-bold colorRottenCherry
font18">Material: *</label>
        <select name="material" class="form-control">
            <option value="0">Choose</option>
            @foreach($data['materials'] as $mat)
                <option value="{{ $mat->id }}"
@if(old('material')== $mat->id) selected @endif>{{ $mat->name }}</option>
            @endforeach
        </select>
        @error('material')
        <div class="alert alert-danger">
            {{ $message }}
        </div>
        @enderror
    </div>
    <div class="col mb-3">
        <label class="colorRottenCherry font18 font-weight-
bold">Discount type: </label>
        <select name="discountFilter" class="font18 form-
control" id="discountFilter">
            <option value="0">Choose</option>
            @foreach($data['discounts'] as $dis)
                <option value="{{ $dis->id }}"
@if(old('discountFilter')== $dis->id) selected @endif>{{ $dis-
>name }}</option>
            @endforeach
        </select>
        @error('discountFilter')
        <div class="alert alert-danger">
            {{ $message }}
        </div>
        @enderror
    </div>
    <div class="col mb-3">
        <label class="font-weight-bold colorRottenCherry

```

```

font18">Discount price:</label>
        <input type="text" name="discountPrice" class="form-
control"
                value="{{old('discountPrice')}}"
            />
        @error('discountPrice')
        <div class="alert alert-danger">
            {{$message}}
        </div>
        @enderror
    </div>
    <div class="col mb-3">
        <label class="font-weight-bold colorRottenCherry
font18">Product image:*</label>
        <input type="file" name="image" class="form-
control"/>
        @error('image')
        <div class="alert alert-danger">
            {{$message}}
        </div>
        @enderror
    </div>
    <div class="col text-center ">
        <button type="submit" class="btn btnSubmit colorMint
font-weight-bold font18 " >Submit</button>
    </div>
</form>
</div>
</div>
</div>
</div>
@endsection

```

admin/products/update.blade.php

```

@extends('layouts.admin')

@section('title')
    Dreamy | Update product
@endsection
@section('keywords')
    name, color, material, category, price, status, discount type,
    discount price, image
@endsection
@section('description')
    Dreamy furniture store, edit product
@endsection
@section('content')

```

```

<div class="container-fluid border-top">
  <div class="row">
    <div class="col-12 col-md-8 col-lg-5 py-5 m-auto">
      <h2 class="font-weight-bold font-italic text-center mb-3 colorRottenCherry">Update product</h2>
      @if (session("error"))
        <div class="alert alert-danger">
          <p>{{session("error")}}</p>
        </div>
      @endif
      <form action="{{route('update-product-patch',[ "id" =>
$product->id]) }}" method="post" enctype="multipart/form-
data"name="formUpdateProduct">
        @csrf
        @method("PATCH")
        <div class="col mb-3">
          <label class="font-weight-bold colorRottenCherry
font18 ">Name:</label>
          <input type="text" name="name" class="form-
control" value="{{ $product->name }}" />
          @error('name')
            <div class="alert alert-danger">
              {{ $message }}
            </div>
          @enderror
        </div>
        <div class="col mb-3">
          <label class="font-weight-bold colorRottenCherry
font18">Color:</label>
          <select name="color" class="form-control">
            <option value="0">Choose</option>
            @foreach($data['colors'] as $color)
              <option value="{{ $color->id }}"
@if($product->id_color== $color->id) selected @endif>{{ $color->
color }}</option>
            @endforeach
          </select>
          @error('color')
            <div class="alert alert-danger">
              {{ $message }}
            </div>
          @enderror
        </div>
        <div class="col mb-3">
          <label class="font-weight-bold colorRottenCherry
font18">Category:</label>
          <select name="category" class="form-control">
            <option value="0">Choose</option>
            @foreach($data['categories'] as $cat)

```

```

                                <option value="{{ $cat->id }}"
@if($product->id_category== $cat->id) selected @endif>{{ $cat-
>name}}</option>
                                @endforeach
                                </select>
                                @error('category')
                                <div class="alert alert-danger">
                                    {{ $message }}
                                </div>
                                @enderror
                            </div>
                            <div class="col mb-3">
                                <label class="font-weight-bold colorRottenCherry
font18">Material:</label>
                                <select name="material" class="form-control">
                                    <option value="0">Choose</option>
                                    @foreach($data['materials'] as $mat)
                                        <option value="{{ $mat->id }}" @if($product-
>id_material== $mat->id) selected @endif>{{ $mat->name}}</option>
                                    @endforeach
                                </select>
                                @error('material')
                                <div class="alert alert-danger">
                                    {{ $message }}
                                </div>
                                @enderror
                            </div>
                            <div class="col mb-3">
                                <label class="font-weight-bold colorRottenCherry
font18">Price:</label>
                                <input type="text" name="price" class="form-
control" value="{{ $productPrice->price }}" />
                                @error('price')
                                <div class="alert alert-danger">
                                    {{ $message }}
                                </div>
                                @enderror
                            </div>
                            <div class="col mb-3">
                                <label class="font-weight-bold colorRottenCherry
font18">Product status:</label>
                                <ul class="list-group pointer">
                                    <li class="list-group-item borderLi"> <input
type="radio" name="status" class="radioS" value="1" @if($product-
>status=='1') checked @endif /> In stock</li>
                                    <li class="list-group-item borderLi"> <input
type="radio" name="status" class="radioS" value="0" @if($product-
>status=='0') checked @endif/> Out of stock</li>
                                </ul>

```

```

                @error('status')
                <div class="alert alert-danger">
                    {{$message}}
                </div>
            @enderror
        </div>
        <div class="col mb-3">
            <label class="colorRottenCherry font18 font-
weight-bold">Discount type: </label>
            <select name="discountFilter" class="font18 form-
control" id="discountFilter">
                <option value="0">Choose</option>
                @foreach($data['discounts'] as $dis)
                    <option value="{{ $dis->id }}"
@if(!empty($productDiscount->id_discount) && $productDiscount-
>id_discount== $dis->id) selected @endif>{{$dis->name}}</option>
                @endforeach
            </select>
            @error('discountFilter')
            <div class="alert alert-danger">
                {{$message}}
            </div>
            @enderror
        </div>
        <div class="col mb-3">
            <label class="font-weight-bold colorRottenCherry
font18">Discount price:</label>
            <input type="text" name="discountPrice"
class="form-control" @if(!empty($productDiscount->discount))
value="{{ $productDiscount->discount }}" @endif/>
            @error('discountPrice')
            <div class="alert alert-danger">
                {{$message}}
            </div>
            @enderror
        </div>
        <div class="col mb-3">
            <label class="font-weight-bold colorRottenCherry
font18">Product image:</label>
            <input type="file" name="pImage" class="form-
control"/>
            @error('pImage')
            <div class="alert alert-danger">
                {{$message}}
            </div>
            @enderror
        </div>
        <div class="col text-center ">
            <button type="submit" class="btn btnSubmit

```

```

colorMint font-weight-bold font18 " >Submit</button>
        </div>
    </form>
</div>
</div>
</div>
@endsection

```

Routes

web.php

```

Route::middleware(['loggedIn'])->group(function () {
    Route::get('/logout', [\App\Http\Controllers\LoginController::class,
"logout"] )->name('logout');
});

Route::middleware(['user'])->group(function () {

    Route::get('/home-user',
[\App\Http\Controllers\HomeController::class, "index"])->name('home-
user');

Route::get('/products', [\App\Http\Controllers\ProductsController::class,
"index"] )->name('products');
    Route::post('/add-to-
cart', [\App\Http\Controllers\CartController::class, "add"] )->name('add-
to-cart');
    Route::get('/cart', [\App\Http\Controllers\CartController::class,
"index"] )->name('cart');

    Route::patch("/cart", [\App\Http\Controllers\CartController::class,
"update"]);
    Route::delete("/remove-item",
[\App\Http\Controllers\CartController::class, "remove"]);
    Route::get("/remove-all",
[\App\Http\Controllers\CartController::class, "removeAll"])-

```

```

>name('remove-all');

Route::get('/contact', [\App\Http\Controllers\ContactController::class,
"index"] )->name('contact');

Route::get("/orders", [\App\Http\Controllers\OrdersController::class,
"index"])->name('orders');
Route::get('/order-
form', [\App\Http\Controllers\OrdersController::class, "orderForm"] )-
>name('checkout');
Route::post('/order-form-
submit', [\App\Http\Controllers\OrdersController::class,
"orderFormSubmit"] )->name('order-form-submit');
Route::post('/order-
pag', [\App\Http\Controllers\OrdersController::class, "paginationOrder"]
)->name('order-pag');

Route::delete('/delete-
order', [\App\Http\Controllers\OrdersController::class, "deleteOrder"] )-
>name('delete-order');
Route::delete('/delete-order-
item', [\App\Http\Controllers\OrdersController::class, "deleteOrderItem"]
)->name('delete-order-item');
Route::post('/show-order-
items', [\App\Http\Controllers\OrdersController::class, "showOrderItems"]
)->name('show-order-items');

Route::post('/message', [\App\Http\Controllers\ContactController::class,
"message"] )->name('message');

Route::get('/author', [\App\Http\Controllers\AuthorController::class,
"index"] )->name('author');

});

Route::middleware(['admin']->group(function () {

Route::get('/home-admin',
[\App\Http\Controllers\AdminController::class, "index"])->name('home-
admin');

Route::get('/products-
admin', [\App\Http\Controllers\AdminController::class, "products"] )-
>name('products-admin');
Route::get('/products-insert-
form', [\App\Http\Controllers\ProductsInsertController::class, "show"] )-
>name('products-form');
Route::post('/products-

```

```

insert', [\App\Http\Controllers\ProductsInsertController::class, "insert"]
)->name('products-post');

    Route::get('/products-
update/{id}', [\App\Http\Controllers\ProductUpdateController::class,
"show"] )->name('update-product-form');
    Route::patch('/products-
update/{id}', [\App\Http\Controllers\ProductUpdateController::class,
"update"] )->name('update-product-patch');
    Route::post('/product-
post/{id}', [\App\Http\Controllers\ProductUpdateController::class,
"delete"] )->name('product-delete');

    Route::get("/orders-admin",
[\App\Http\Controllers\AdminController::class, "orders"])->name('orders-
admin');
    Route::delete('/delete-order-
admin', [\App\Http\Controllers\AdminController::class, "deleteOrder"] )-
>name('delete-order-admin');
    Route::delete('/delete-order-item-
admin', [\App\Http\Controllers\AdminController::class, "deleteOrderItem"]
)->name('delete-order-item-admin');
    Route::post('/show-order-items-
admin', [\App\Http\Controllers\AdminController::class, "showOrderItems"]
)->name('show-order-items-admin');

    Route::get('/users', [\App\Http\Controllers\AdminController::class,
"users"])->name('users');
    Route::delete('/delete-user',
[\App\Http\Controllers\AdminController::class, "deleteUser"])-
>name('delete-user');
    Route::post('/show-user-param',
[\App\Http\Controllers\AdminController::class, "showUserParam"])-
>name('show-user-param');
    Route::patch('/edit-user',
[\App\Http\Controllers\AdminController::class, "editUser"])->name('edit-
user');

    Route::get('/messages', [\App\Http\Controllers\AdminController::class,
"messages"] )->name('show-messages');
    Route::post('/message-
pag', [\App\Http\Controllers\AdminController::class, "paginationMsg"] )-
>name('message-pag');
    Route::delete('/delete-
msg', [\App\Http\Controllers\AdminController::class, "deleteMsg"] )-
>name('delete-msg');
});

```



```

Route::get('/login', [\App\Http\Controllers\LoginController::class,
"index"] )->name('login-form');
Route::post('/login', [\App\Http\Controllers\LoginController::class,
"login"] )->name('login');

Route::get('/register', [\App\Http\Controllers\RegisterController::class,
"register"] )->name('register');
Route::post('/register', [\App\Http\Controllers\RegisterController::class,
"post"] )->name('register-post');

```

Middleware

Admin.php

```

<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class Admin
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request):
(\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return
\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if($request->session()->has("user") && $request->session()-
>get("user")->id_role==1) {
            return $next($request);
        }
        else{

            return redirect()->route("login-form");
        }
    }
}

```

```

    }

}

}

```

UserLoggedIn.php

```

<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class UserLoggedIn
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request): (\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if($request->session()->has("user")){
            return $next($request);
        }
        else{
            return redirect()->route("login-form");
        }
    }
}

```

User.php

```

<?php

```

```

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;

class User
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure(\Illuminate\Http\Request):
     * (\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse)  $next
     * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
     */
    public function handle(Request $request, Closure $next)
    {
        if($request->session()->has("user") && $request->session()-
>get("user")->id_role==2) {
            return $next($request);
        }
        else{
            return redirect()->route("login-form");
        }
    }
}

```

Models

ActivitiesModel.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class ActivitiesModel extends Model
{
    use HasFactory;

    function searchActivities(Request $request){
        $query=DB::table('activities');

        if($request->has("nameAc") && $request->get('nameAc')!=""){
            $query = $query->where('name', '=', $request->get("nameAc"));
            $request->session()->put("nameAc",$request->get("nameAc") );
        }

        if($request->has("userAc") && $request->get('userAc')!=""){
            $query = $query->where('user', '=', $request->get("userAc"));
            $request->session()->put("userAc",$request->get("userAc") );
        }
        $perPage = 10;
        $query=$query->orderByDesc('id');
        $query=$query->select(['id', 'name', 'date', 'request_data',
        'user']);

        return $query->paginate($perPage)->withQueryString();
    }
}
```

Category.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Category extends Model
{
    use HasFactory;

    public $timestamps = false;

    public function products()
    {
        return $this->hasMany(Products::class);
    }
}

```

Color.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Color extends Model
{
    use HasFactory;

    public $timestamps = false;

    public function products()
    {
        return $this->hasMany(Product::class);
    }
}

```

Discount.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Discount extends Model
{
    use HasFactory;

    public function prices()
    {
        return $this->belongsToMany(Price::class, 'discount_price',
'id_discount', 'id_price');
    }
}

```

Material.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Material extends Model
{
    use HasFactory;

    public $timestamps = false;

    public function products()
    {
        return $this->hasMany(Product::class);
    }
}

```

Message.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Message extends Model
{
    use HasFactory;
    protected $fillable = ["user", "message"];
    protected $table="messages";
}

```

MessageModel.php

```

<?php

namespace App\Models;

use Illuminate\Http\Request;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Facades\DB;

class MessageModel
{
    use HasFactory;

    function searchMessages(Request $request){
        $query=DB::table('messages')->where('id_admin', '=', session()->get('user')->id);

        if($request->has("emailMsg") && $request->get("emailMsg")!=" "){
            $query = $query->where('user', '=', $request->get("emailMsg"));
            $request->session()->put("emailMsg",$request->get("emailMsg"));
        }

        $perPage = 5;
        $query=$query->orderByDesc('id');

        $query=$query->select(['id', 'message', 'created_at', 'user']);
    }
}

```

```

        return $query->paginate($perPage)->withQueryString();
    }
}

```

Order.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Order extends Model
{
    use HasFactory;

    protected $fillable = ['id_user', 'address', 'quantity',
'total', 'payment_type', 'delivery_method'];

    public function users()
    {
        return $this->belongsTo(User::class);
    }
}

```

OrdersModel.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

```



```

use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class OrdersModel extends Model
{
    use HasFactory;

    function searchOrders(Request $request){
        $query=DB::table('orders')
            ->whereExists(function ($query) {
                $query->select(DB::raw(1))
                    ->from('order_items')
                    ->whereColumn('order_items.id_order', 'orders.id');
            });

        if($request->has("userO") && $request->get('userO')!=""){
            $query = $query->where('id_user', '=', $request-
>get("userO"));
            $request->session()->put("userO",$request->get("userO") );
        }

        if($request->has("paymentU") && $request->get('paymentU')!=""){
            $query = $query->where('payment_type', '=', $request-
>get("paymentU"));
            $request->session()->put("paymentU",$request->get("paymentU")
);
        }

        if($request->has("deliveryU") && $request->get('deliveryU')!=""){
            $query = $query->where('delivery_method', '=', $request-
>get("deliveryU"));
            $request->session()->put("deliveryU",$request-
>get("deliveryU") );
        }

        $perPage = 5;
        $query=$query->orderByDesc('id');
        $query=$query->select(['id', 'id_user', 'created_at', 'total',
'quantity', 'payment_type', 'delivery_method', 'address']);

        return $query->paginate($perPage)->withQueryString();
    }
}

```

Price.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Price extends Model
{
    use HasFactory;

    protected $table="price";
    protected $fillable =['id_product', 'price', 'id', 'old'];
    public function products()
    {
        return $this->hasMany(Product::class);
    }

    public function discounts()
    {
        return $this->belongsToMany(Discount::class, 'discount_price',
'id_price', 'id_discount');
    }

    public function orders()
    {
        return $this->hasMany(Order::class);
    }
}

```

Product.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Product extends Model
{
    use HasFactory;
    protected $fillable = ["name", "img_src", "img_alt", "status",
'id_color", "id_category", "id_material"];
    public function color()

```

```

    {
        return $this->belongsTo(Color::class);
    }

    public function orders()
    {
        return $this->hasMany(Order::class);
    }

    public function category()
    {
        return $this->belongsTo(Category::class);
    }

    public function price()
    {
        return $this->belongsTo(Price::class);
    }

    public function material()
    {
        return $this->belongsTo(Material::class);
    }
}

```

ProductModel.php

```

<?php

namespace App\Models;

use Illuminate\Http\Request;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Support\Facades\DB;

class ProductModel
{
    use HasFactory;

    public $price=[
        "1" => ["price", "desc"],
    ]
}

```

```

        "2" => ["price", "asc"],
    ];

    public function search(Request $request) {

        $query =Product::join('colors', 'products.id_color', '=',
'colors.id')
            ->join('categories', 'products.id_category', '=',
'categories.id')
            ->join('price', 'products.id', '=', 'price.id_product')
            ->join('materials', 'materials.id', '=',
'products.id_material')
            ->leftjoin('discount_price', 'price.id', '=',
'discount_price.id_price')
            ->leftjoin('discounts', 'discount_price.id_discount', '=',
'discounts.id')
            ->where('discount_price.old', '=', 0)
            ->orWhere('discount_price.old', '=', NULL)
            ->whereNull('price.old')
            ->whereNull('products.old')

        ;

        if($request->has("chCat")){
            $query = $query->whereIn("products.id_category", $request-
>get("chCat"));

            $request->session()->put("category",$request->get("chCat") );

        }
        if($request->has("chCol")){
            $query = $query->whereIn("products.id_color", $request-
>get("chCol"));

            $request->session()->put("color",$request->get("chCol") );

        }

        if($request->has("discountFilter") && $request-
>get('discountFilter')!="0") {
            $query = $query->where('discounts.id', 'like', $request-
>get("discountFilter"));

            $request->session()->put("discount",$request-
>get("discountFilter") );

        }

        if($request->has("status")){
            $query = $query->where('products.status', '=', $request-
>get("status"));

            $request->session()->put("status",$request->get("status") );

```

```

    }

    if($request->has("keyword") && !empty($request->get("keyword")))
    {
        $v = $request->get("keyword");
        $query = $query->where("products.name", 'like', '%' . $v .
        '%');
        $request->session()->put("keyword",$request->get("keyword")
    );
    }

    if($request->has("priceSort") && $request->get('priceSort')!='0')
    {
        $sort = $this->getOrderBy($request,"priceSort", $this->
        >price);
        $query = $query->orderBy($sort[0], $sort[1]);
        $request->session()->put("priceSort",$request->
        >get("priceSort") );
    }

    $perPage = 4;
    $query=$query->orderByDesc('products.id');

    $query=$query->select(['materials.name as material','products.id
    as prodId','products.name as productName', 'products.status as status',
    'products.img_src as imgSrc', 'products.img_alt as imgAlt', 'colors.color
    as color', 'categories.name as category', 'price.price as price',
    'discounts.name as discountName', 'discounts.css_style as css',
    'discount_price.discount as discountPrice']);

    return $query->paginate($perPage)->withQueryString();

}

public function searchProducts(Request $request) {

    $query =Product::join('colors', 'products.id_color', '=',
    'colors.id')
        ->join('categories', 'products.id_category', '=',
    'categories.id')
        ->join('price', 'products.id', '=', 'price.id_product')
        ->join('materials', 'materials.id', '=',
    'products.id_material')
        ->leftjoin('discount_price', 'price.id', '=',
    'discount_price.id_price')
        ->leftjoin('discounts', 'discount_price.id_discount', '=',
    'discounts.id')
        ->where('discount_price.old', '=', 0)
        ->orWhere('discount_price.old', '=', NULL)
        ->whereNull('price.old')

```

```

        ->whereNull('products.old')
    ;

    if($request->has("discountP") && $request->get('discountP')!="")
    {
        $query = $query->where('discounts.id', 'like', $request-
>get("discountP"));
        $request->session()->put("discountP",$request-
>get("discountP") );
    }
    if($request->has("categoryP") && $request->get('categoryP')!="")
    {
        $query = $query->where('categories.id', 'like', $request-
>get("categoryP"));
        $request->session()->put("categoryP",$request-
>get("categoryP") );
    }
    if($request->has("statusP") && $request->get('statusP')!="") {
        $query = $query->where('products.status', '=', (int)$request-
>get("statusP"));
        $request->session()->put("statusP",$request->get("statusP")
);
    }

    if($request->has("nameP") && !empty($request->get("nameP"))) {
        $v = $request->get("nameP");
        $query = $query->where("products.name", 'like', $v );
        $request->session()->put("nameP",$request->get("nameP") );
    }

    $perPage = 4;
    $query=$query->orderByDesc('products.id');

    $query=$query->select(['products.created_at as
createdAt','materials.name as material','products.id as
prodId','products.name as productName', 'products.status as status',
'products.img_src as imgSrc', 'products.img_alt as imgAlt', 'colors.color
as color', 'categories.name as category', 'price.price as price',
'discounts.name as discountName', 'discounts.css_style as css',
'discount_price.discount as discountPrice']);

    return $query->paginate($perPage)->withQueryString();
}

private function getOrderby(Request $request, $sortName,$array) {

    $defaultSort = $array["1"];

```

```

        if($request->has($sortName) && is_numeric($request->get($sortName))) {
            if(isset($array[$request->get($sortName)])) {
                $sort = $array[$request->get($sortName)];
                if($sort) {
                    $defaultSort = $sort;
                }
            }
        }
        return $defaultSort;
    }

    public function getProductsByID($ids) {
        return DB::table("products")->join('price', 'products.id', '=', 'price.id_product')->leftJoin('discount_price', 'price.id', '=', 'discount_price.id_price')->whereIn("products.id", $ids)->whereNull('price.old')->whereNull('discount_price.old')->select("products.id as idProd", "name", "img_src", "img_alt", "price", "price.id as id_price", "discount")->get();
    }
}

```

Role.php

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Role extends Model
{
    use HasFactory;
    public $timestamps = false;
    public function users()
    {
        return $this->hasMany(User::class);
    }
}

```

Users.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Users extends Model
{
    use HasFactory;
    protected $fillable = ["first_name", "last_name", "email",
"password"];
    protected $table='users';

    public function role()
    {
        return $this->belongsTo(Role::class);
    }
}
```

UserModel.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class UserModel extends Model
{
    use HasFactory;

    function searchUsers(Request $request){
        $query=DB::table('users');

        if($request->has("emailU") && $request->get('emailU')!=""){
```



```

        $query = $query->where('email', '=', $request-
>get("emailU"));
        $request->session()->put("emailU",$request->get("emailU") );
    }
    if($request->has("roleU") && $request->get('roleU')!=""){
        $query = $query->where('id_role', '=', (int)$request-
>get("roleU"));
        $request->session()->put("roleU",$request->get("roleU") );
    }
    if($request->has("statusU") && $request->get('statusU')!=""){
        $query = $query->where('active', '=', (int)$request-
>get("statusU"));
        $request->session()->put("statusU",$request->get("statusU")
);
    }
    $perPage = 5;
    $query=$query->orderByDesc('id');
    $query=$query->select(['id', 'first_name', 'created_at',
'last_name', 'email', 'id_role', 'active']);

    return $query->paginate($perPage)->withQueryString();
}
}

```

Providers

AppServiceProvider.php

```

<?php

namespace App\Providers;

use App\Models\Menu;
use Illuminate\Pagination\Paginator;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\View;
use Illuminate\Support\ServiceProvider;

class AppServiceProvider extends ServiceProvider
{
    /**
     * Register any application services.
     *
     * @return void
     */
}

```

```

    */
private $menu;
private $links = [

    [
        "icon"=>"fab fa-instagram-square",
        "href"=>"https://www.instagram.com/_sweetheart55_/"
    ],
    [
        "icon"=>"fab fa-twitter-square",
        "href"=>"https://twitter.com/anika99black"
    ],
    [
        "icon"=>"fab fa-linkedin",
        "href"=>"https://www.linkedin.com/in/anica-
radenkovi%C4%87-9519b3206/"
    ],
    [
        "icon"=>"fab fa-facebook-square",
        "href"=>"https://www.facebook.com/anica.radenkovic96/"
    ],
    [
        "icon"=>"fab fa-github-square",
        "href"=>"https://github.com/anica02"
    ]
];

public function register()
{
    //
}

/**
 * Bootstrap any application services.
 *
 * @return void
 */
public function boot()
{
    View::share('links', $this->links);

    Paginator::useBootstrapFour();
}
}

```

Rules

Address.php

```
<?php

namespace App\Rules;

use Illuminate\Contracts\Validation\InvokableRule;

class Address implements InvokableRule
{
    /**
     * Create a new rule instance.
     *
     * @return void
     */
    private $address;
    public function __construct($address)
    {
        $this->address=$address;
    }

    /**
     * Determine if the validation rule passes.
     *
     * @param string $attribute
     * @param mixed $value
     * @return bool
     */
    public function __invoke($attribute, $value, $fail)
    {
        $regAddress='/^[A-ZČĆŠĐŽ]{1}[a-zčćšđž]{2,15}(\s[A-ZČĆŠĐŽ]{1}[a-zčćšđž]{0,15})*\s[\d]{1,5}(\s[A-ZČĆŠĐŽ]{1}[a-zčćšđž]{2,15})*,(\s[A-ZČĆŠĐŽ]{1}[a-zčćšđž]{2,10})+\s[\d]{5}$/' ;

        if(!preg_match($regAddress,$value)) {
            $fail("Password length has to be at least 8 character and has to contain at least one uppercase letter, one lowercase, one number and one special character");
        }
    }

    /**
     * Get the validation error message.
     */
}
```

```

        * @return string
        */
    public function message()
    {
        return 'The validation error message.';
    }
}

```

EmailUnique.php

```

<?php

namespace App\Rules;

use App\Models\User;
use Illuminate\Contracts\Validation\InvokableRule;
use Illuminate\Contracts\Validation\Rule;
use Illuminate\Support\Facades\DB;

class EmailUnique implements InvokableRule
{
    /**
     * Create a new rule instance.
     *
     * @return void
     */
    private $email;
    public function __construct($email)
    {
        $this->email=$email;
    }

    /**
     * Determine if the validation rule passes.
     *
     * @param string $attribute
     * @param mixed $value
     * @return bool
     */
    public function __invoke($attribute, $value, $fail)
    {
        $count = User::select('id')->where("email",'like',$value)->first();

        if($count) {
            $fail("Email is already taken");
        }
    }
}

```

```

    }
}

/**
 * Get the validation error message.
 *
 * @return string
 */
public function message()
{
    return 'The validation error message.';
}
}

```

Password.php

```

<?php

namespace App\Rules;

use Illuminate\Contracts\Validation\InvokableRule;
use Illuminate\Contracts\Validation\Rule;

class Password implements InvokableRule
{
    /**
     * Create a new rule instance.
     *
     * @return void
     */
    private $password;
    public function __construct($password)
    {
        $this->password=$password;
    }

    /**
     * Determine if the validation rule passes.
     *
     * @param string $attribute
     * @param mixed $value
     * @return bool
     */
    public function __invoke($attribute, $value, $fail)
    {
        $regPass="/^(?=.*[a-zčćđžš])(?=.*[A-

```

```

ZČČĐŽŠ]) (?=.*\d) (?=.*[@$!%*?]) ([A-ZČČĐŽŠa-zččđžš\d@$!%*?]){8,}$/"';

        if(!preg_match($regPass,$value)) {
            $fail("Password length has to be at least 8 character and has
to contain at least one uppercase letter, one lowercase, one number and
one special character");
        }
    }
}

/**
 * Get the validation error message.
 *
 * @return string
 */
public function message()
{
    return 'The validation error message.';
}
}

```

ProductName.php

```

<?php

namespace App\Rules;

use Illuminate\Contracts\Validation\Rule;
use Illuminate\Contracts\Validation\InvokableRule;

class ProductName implements InvokableRule
{
    /**
     * Create a new rule instance.
     *
     * @return void
     */
    private $name;
    public function __construct($name)
    {
        $this->name=$name;
    }

    /**
     * Determine if the validation rule passes.
     *
     * @param string $attribute

```

```

    * @param mixed $value
    * @return bool
    */
    public function __invoke($attribute, $value, $fail)
    {
        $regex='/^[A-Z]{1}[A-Za-z0-9]{2,}(\s[A-Z]{1}[A-Za-z0-9]{2,})*$/';

        if(!preg_match($regex,$value)) {
            $fail("Product name must start with uppercase letter");
        }
    }

    /**
     * Get the validation error message.
     *
     * @return string
     */
    public function message()
    {
        return 'The validation error message.';
    }
}

```

ProductNameUnique.php

```

<?php

namespace App\Rules;

use Illuminate\Contracts\Validation\InvokableRule;
use Illuminate\Contracts\Validation\Rule;
use Illuminate\Support\Facades\DB;

class ProductNameUnique implements InvokableRule
{
    /**
     * Create a new rule instance.
     *
     * @return void
     */
    private $name;
    public function __construct($name)
    {
        $this->name=$name;
    }
}

```

```

/**
 * Determine if the validation rule passes.
 *
 * @param string $attribute
 * @param mixed $value
 * @return bool
 */
public function __invoke($attribute, $value, $fail)
{
    $count = DB::table("products")->where("name", '=', $value);

    if($count) {
        $fail("Product name is already taken");
    }
}

/**
 * Get the validation error message.
 *
 * @return string
 */
public function message()
{
    return 'The validation error message.';
}
}

```

UserFullName.php

```

<?php

namespace App\Rules;

use Illuminate\Contracts\Validation\InvokableRule;
use Illuminate\Contracts\Validation\Rule;

class UserFullName implements InvokableRule
{
    /**
     * Create a new rule instance.
     *
     * @return void
     */
    private $name;

    public function __construct($name)
    {
    }
}

```



```

{
    $this->name=$name;
}

/**
 * Determine if the validation rule passes.
 *
 * @param string $attribute
 * @param mixed $value
 * @return bool
 */
public function __invoke($attribute, $value, $fail)
{
    $regName="/^[A-ZČĎŽŠ]{1}[a-zčďžš]{2,15}(\s[A-ZČĎŽŠ]{1}[a-zčďžš]{2,15})*$/";

    if(!preg_match($regName,$value)) {
        $fail("User name has to start with one uppercase letter and
length has to be at least 3 characters");
    }
}

/**
 * Get the validation error message.
 *
 * @return string
 */
public function message()
{
    return 'The validation error message.';
}
}

```

Requests

AddToCartRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class AddToCartRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            "productId" => "required|numeric"
        ];
    }
}
```

MessageAdminRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class MessageAdminRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
}
```

```

    */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            "message"=>'required|string|min:3|max:300',
            "admin"=>'required|exists:users,id'
        ];
    }
}

```

OrderFormRequest.php

```

<?php

namespace App\Http\Requests;

use App\Rules\Address;
use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Validation\Rule;

class OrderFormRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *

```

```

        * @return array<string, mixed>
        */
    public function rules()
    {
        return [
            "address"=>[
                'required','string', new Address($this->get("address"))
            ],
            "payment"=>['required','string', Rule::in(['card', 'cash'])],
            "delivery"=>'required|string',
        ];
    }
}

```

ProductInsertRequest.php

```

<?php

namespace App\Http\Requests;

use App\Rules\ProductName;
use App\Rules\ProductNameUnique;
use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Validation\Rule;

class ProductInsertRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            "name"=>[

```

```

        'required', 'string', 'min:3', 'max:20',
        new ProductName($this->get("name")),
        'unique:products,name'
    ],
    "price"=>'required|numeric|min:1',
    "color"=>'required|exists:colors,id',
    "category"=>'required|exists:categories,id',
    "material"=>'required|exists:materials,id',
    "image"=>'required|image|mimes:jpg,png|max:2080',
    "discountFilter"=>[
        Rule::in(['0', '1', '2', '3']),
    ],
    "discountPrice"=>['bail', 'nullable', 'numeric', 'min:1',
    'required_unless:discountFilter,0'],
    ];
}
}

```

ProductUpdateReuquest.php

```

<?php

namespace App\Http\Requests;

use App\Rules\ProductName;
use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Support\Facades\Validator;
use Illuminate\Validation\Rule;

class ProductUpdateRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
}

```

```

    public function rules()
    {
        return [
            "name"=>[
                'required','string','min:3','max:20',
                new ProductName($this->get("name"))
            ],
            "color"=>'required|exists:colors,id',
            "category"=>'required|exists:categories,id',
            "material"=>'required|exists:materials,id',
            "price"=>'required|numeric|min:1',
            "status"=>[
                'required',
                'exists:products,status'
            ],
            "discountFilter"=>[
                Rule::in(['0','1','2','3']),
            ],
            "discountPrice"=>['bail','nullable','numeric','min:1',
            'required_unless:discountFilter,0'],
            "pImage"=>'image|mimes:jpg,png|max:2080'
        ];
    }
}

```

RegisterUserRequest.php

```

<?php

namespace App\Http\Requests;

use App\Rules\EmailUnique;
use App\Rules>Password;
use App\Rules\UserFullName;
use Illuminate\Foundation\Http\FormRequest;

class RegisterUserRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
}

```

```

    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [

            'firstName'=>[
                'required', 'string',
                new UserFullName($this->get('firstName'))
            ],
            'lastName'=>[
                'bail',
                'required',
                'string',
                new UserFullName($this->get('lastName'))
            ],

            'email'=>['required', new EmailUnique($this->get('email')), 'email', ],
            'password'=>['required', 'string',
                new Password($this->get('password'))]
        ];
    }
}

```

UserRequest.php

```

<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Validation\Rule;

class UserRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     */
}

```

```

    *
    * @return bool
    */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, mixed>
     */
    public function rules()
    {
        return [
            "role"=>'required|exists:roles,id',
            "status"=>["required", Rule::in(['0', '1']),]
        ];
    }
}

```

Helpers

ActivityLogger.php

```

<?php

namespace App\Helpers;

use Carbon\Carbon;
use Illuminate\Support\Facades\DB;

class ActivityLogger
{
    public static function LogActivity($name,$data) {

        DB::table("activities")->insert([
            "name" => $name,
            "date" => \Carbon\Carbon::now()->toDateTimeString(),
            "user" => session()->has("user") ? session()->get("user")->email : request()->ip(),
            "request_data" => $data
        ]);
    }
}

```



```

    }

    public static function LogActivityReq($name) {

        $requestData = json_encode(request()->all());

        DB::table("activities")->insert([
            "name" => $name,
            "date" => \Carbon\Carbon::now()->toDateTimeString(),
            "user" => session()->has("user") ? session()->get("user")-
>email : request()->ip(),
            "request_data" => $requestData
        ]);
    }
}

```

Controllers

AdminController.php

```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Http\Requests\UserRequest;
use App\Models\ActivitiesModel;
use App\Models\Category;
use App\Models\Discount;
use App\Models\Message;
use App\Models\MessageModel;
use App\Models\OrdersModel;
use App\Models\Product;
use App\Models\ProductModel;
use App\Models\Role;
use App\Models\UserModel;
use App\Models\Users as Users;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;
use PHPUnit\Exception;
use Illuminate\Pagination\LengthAwarePaginator;
use Illuminate\Pagination\Paginator;
use Illuminate\Pagination\CursorPaginator;

```

```

class AdminController extends MainController
{

    public function index(Request $request){

        $model=new ActivitiesModel();
        $activitieNames=DB::table('activities')->distinct()->select('name
as name')->get();
        $activitieUsers=DB::table('activities')->select('user')-
>distinct()->get();

        $this->data['users']=DB::table('users')->where('id_role', '2')-
>where('active', '1')->count('id');
        $this->data['orders']=DB::table('orders')->count('id');
        $this->data['inStock']=DB::table('products')->where('status',
'1')->whereNull('old')->count('id');
        $this->data['outOfStock']=DB::table('products')->where('status',
'0')->whereNull('old')->count('id');
        $this->data['acNames']=$activitieNames;
        $this->data['acUsers']=$activitieUsers;
        $request->session()->forget('nameAc');
        $request->session()->forget('userAc');
        return view('pages.admin.home', ['data'=>$this->data,
"activities"=>$model->searchActivities($request)]);
    }

    public function messages(Request $request){
        $model=new MessageModel();
        $users=DB::table('messages')->distinct()->select('user as user')-
>get();
        $request->session()->forget('emailMsg');
        return view('pages.admin.messages.index', ['messages'=>$model-
>searchMessages($request), "users"=>$users]);
    }

    public function deleteMsg(Request $request) {

        $msgId=$request->msgId;
        try{
            DB::table('messages')->where('id', '=', $msgId)->delete();
            ActivityLogger::LogActivity("Message deleted ",
"id=".$msgId);
        }catch(\Exception $e){
            ActivityLogger::LogActivity("Error while deleting
message", "id=".$msgId);
        }
    }
}

```

```

        Log::error($e->getMessage(). "\n". $e->getTraceAsString());
        return redirect()->back()->with('error-msg', 'An error
occurred while deleting message');
    }

}

public function orders(Request $request){

    $users=Users::all();
    $model=new OrdersModel();
    $usersEmail=DB::table('users')->join('orders', 'users.id', '=',
'orders.id_user')->distinct()->select('email', 'id_user')->get();
    $this->data['emails']=$usersEmail;
    $this->data['users']=$users;
    $request->session()->forget('userO');
    $request->session()->forget('deliveryU');
    $request->session()->forget('paymentU');
    return view('pages.admin.orders.index', ['model'=>$model-
>searchOrders($request), 'data'=>$this->data]);
}

public function deleteOrder(Request $request) {

    $orderId=$request->orderId;

    try{

        DB::table('orders')->where('id', '=', $orderId)->delete();

        ActivityLogger::LogActivity("Order deleted", "id=".$orderId);

    }catch(\Exception $e){
        ActivityLogger::LogActivity("Error while deleting
order", "id=".$orderId);
        Log::error($e->getMessage(). "\n". $e->getTraceAsString());
        return redirect()->back()->with('error-msg', 'An error
occurred while deleting order');
    }

}

public function showOrderItems(Request $request){
    $id=$request->orderItemId;
    $products=Product::all();
    $ordersItems=DB::table('order_items')->where("id_order", '=',
$id)->get();

```

```

        return response()->json(["data"=>$ordersItems,
"products"=>$products]);
    }

    public function users(Request $request){
        $model=new UserModel();
        $this->data['emails']= Users::all();
        $this->data['roles']=Role::all();
        $request->session()->forget('emailU');
        $request->session()->forget('roleU');
        $request->session()->forget('statusU');
        return view('pages.admin.users.index', ["model"=>$model-
>searchUsers($request), 'data'=>$this->data]);
    }

    public function showUserParam(Request $request){
        $id=$request->userId;
        $roles=Role::all();
        $user=DB::table('users')->where('id', $id)->get();
        return response()->json(['data'=>$user, 'roles'=>$roles]);
    }

    public function deleteUser(Request $request){
        $id=$request->userId;

        try{

            DB::table('orders')->where('id_user', $id)->delete();
            DB::table('users')->where('id', $id)->delete();
            ActivityLogger::LogActivity('User deleted','id'.$id);

        }catch(\Exception $e){
            ActivityLogger::LogActivity('Error while deleting user ',
'id'.$id);
            Log::error($e->getMessage(). "\n". $e->getTraceAsString());
            return redirect()->back()->with('error-msg', 'An error
occurred while deleting user');
        }

    }

    public function editUser(UserRequest $request){

        $status=$request->get('status');
        $role=$request->get('role');
        $id=$request->get('userId');
        $param="{Id=". $id. "} {id_role=". $role. "} {active=".$status."}";
    }

```

```

        try{
            $user= Users::find($id);
            $user->id_role=(int)$role;
            $user->active=(int)$status;
            $user->save();
            ActivityLogger::LogActivity("User edited ", $param);
            return redirect()->back()->with('success', 'User edited
successfully');
        }catch(\Exception $e){
            ActivityLogger::LogActivity("Error while editing user ",
$param);

            Log::error($e->getMessage(). "\n". $e->getTraceAsString());
            return redirect()->back()->with('error-msg', 'An error
occurred while editing user');
        }
    }

    public function products(Request $request){

        $model=new ProductModel();
        $this->data['discounts']=Discount::all();
        $this->data['categories']=Category::all();
        $request->session()->forget('statusP');
        $request->session()->forget('discountP');
        $request->session()->forget('categoryP');
        $request->session()->forget('nameP');
        return view('pages.admin.products.index', ['model'=>$model-
>searchProducts($request), 'data'=>$this->data]);
    }

}

```

AuthorController.php

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class AuthorController extends MainController
{
    public function index() {
        return view('pages.main.author');
    }
}

```

CartController.php

```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Http\Requests\AddToCartRequest;

use App\Models\Order;
use App\Models\OrdersModel;
use App\Models\Product;
use App\Models\ProductModel;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class CartController extends MainController
{

    public function index(Request $request){

        if($request->session()->has("cart")) {
            $productIds = array_keys($request->session()->get("cart"));
            $model = new ProductModel();
            $products = $model->getProductsById($productIds);
            return view("pages.cart.index", [
                "cartItems" => $products
            ]);
        }
    }
}

```

```

    } else {
        return view("pages.cart.index", ['cartItems'=>[]]);
    }
}

public function update(Request $request) {
    $id = $request->productId;
    $qty = $request->quantity;
    $param="{id=".$id."}{quantity=".$qty."}";
    if(session()->has("cart")) {
        $cart = session()->get("cart");

        if(isset($cart[$id])) {
            $cart[$id] = $qty;
            session()->put("cart", $cart);
        }
    }
    ActivityLogger::LogActivity("Product added to cart",$param) ;
}

public function add(AddToCartRequest $request){
    if($request->session()->has("cart")) {
        $cart = $request->session()->get("cart");

        if(isset($cart[$request->productId])) {
            $cart[$request->productId] = $cart[$request->productId]+1;
        } else {
            $cart[$request->productId] = 1;
        }
        ActivityLogger::LogActivityReq("Product added to cart");
        $request->session()->put("cart", $cart);
    } else {
        $cart = [];
        $productId = $request->productId;
        $key = strval($productId);
        $cart[$key] = 1;
        ActivityLogger::LogActivityReq("Product added to cart");
        $request->session()->put("cart", $cart);
    }
}

public function remove(Request $request) {
    $cart = session()->get("cart");
    if(isset($cart[$request->productId])) {

```

```

        unset($cart[$request->productId]);
        session()->put("cart", $cart);
        if(count(session()->get("cart"))==0){
            ActivityLogger::LogActivityReq("Product removed from
cart");
            $request->session()->forget('cart');
        }
    } else {
        return response()->setStatusCode(404);
    }
}

public function removeAll(Request $request) {
    ActivityLogger::LogActivityReq("Products removed from cart");
    $request->session()->forget('cart');
    return redirect()->back();
}
}

```

ContactController.php

```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Http\Requests\MessageAdminRequest;
use App\Models\Message;
use App\Models\Product;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class ContactController extends MainController
{
    public function index(){
        $admins=DB::table('users')->where('id_role', '=', 1)->get();
        return view('pages.main.contact', ["admins"=>$admins]);
    }

    public function message(MessageAdminRequest $request){
        try{

```



```

        $message=new Message();
        $message->user=session()->get('user')->email;
        $message->message=$request->get('message');
        $message->id_admin=$request->get('admin');
        $message->save();
        ActivityLogger::LogActivity("Message sent",
"user=".session()->get('user')->email);
        return redirect()->back()->with("success", "Message sent ");
    }catch(\Exception $e){
        ActivityLogger::LogActivity("Error while sending message ",
"user=".session()->get('user')->email);
        Log::error( $e->getMessage(). " " . $e->getTraceAsString());
        return redirect()->back()->with("error", "An error has
occurred while sending your message");
    }
}
}
}

```

HomeController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Category;
use Illuminate\Http\Request;

class HomeController extends MainController
{
    public function index(){

        $this->data['rooms']=
        [
            "src"=>"room1.jpg",
            "alt"=>"Room 1"
        ],
        [
            "src"=>"room2.jpg",
            "alt"=>"Room 2"
        ],
        [
            "src"=>"room5.jpg",
            "alt"=>"Room 5"
        ],
    ],

```

```

        [
            "src"=>"room4.jpg",
            "alt"=>"Room 4"
        ]
    ];

    $this->data['categoryId']=Category::all();
    return view('pages.main.home', ["data"=> $this->data]);
}
}

```

LoginController.php

```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Facades\Log;

class LoginController extends MainController
{
    public function index(){
        return view('pages.main.login');
    }

    public function login(Request $request){
        try {
            $email = $request->email;
            $password = $request->password;

            $user = User::where('email', $email)->first();
            if (!$user) {
                ActivityLogger::LogActivity("User not
found", "user=".$email);
                return redirect()->back()->with('error', 'No user
found!');
            }
            if ($user->active == 0) {
                ActivityLogger::LogActivity("User blocked",

```

```

"user=".$email);
        return redirect()->back()->with('error', 'Your account is
blocked');
    }
    $passwordMatches = $user->password == md5($password);
    if($passwordMatches){

        $request->session()->put("user", $user);
        ActivityLogger::LogActivity("Login", "user=".$email );

        if(session()->get('user')->id_role==2){
            return redirect()->route('home-user');
        }else{
            return redirect()->route('home-admin');
        }

    }
    else{
        return redirect()->back()->with('error', 'Wrong
password');
    }

    }catch (\Exception $e){
        ActivityLogger::LogActivity("Login error", "user=".$email);
        Log::error($e->getMessage(). "\n". $e->getTraceAsString());
        return redirect()->back()->with('error', 'An error occurred
while login');
    }

}

    public function logout(Request $request) {
        ActivityLogger::LogActivity("Logout", "user=".$request-
>session()->get('user')->email);
        $request->session()->flush();
        return redirect()->route("login-form");
    }

}

```

MainController.php

```

<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class MainController extends Controller
{
    public $data;
}

```

OrdersController.php

```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Http\Requests\OrderFormRequest;
use App\Models\Order;
use App\Models\OrdersModel;
use App\Models\Product;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;
use PHPUnit\Exception;

class OrdersController extends MainController
{
    public function index(Request $request){

        $this->data['orders']=$this->paginate($request);
        return view('pages.orders.index',['data'=>$this->data]);
    }

    public function orderForm(Request $request){
        if($request->session()->has('cart')){
            return view('pages.orders.orderForm');
        }else{
            return back()->with('error', 'Your cart is empty');
        }
    }
}

```

```

    }
    public function pagginate(Request $request){
        $all=DB::table('orders')->select('id');

        $query =DB::table('orders')->where('id_user', '=', session()-
>get('user')->id)->whereExists(function ($query) {
            $query->select(DB::raw(1))
            ->from('order_items')
            ->whereColumn('order_items.id_order', 'orders.id');
        });

        $perPage = 4;
        $query = $query->orderBy("id", "DESC");

        $query = $query->select("id", "address", "quantity", "total",
"payment_type", "delivery_method", "created_at");

        return $query->paginate($perPage)->withQueryString();
    }

    public function orderFormSubmit(OrderFormRequest $request){

        if($request->session()->has('cart')){

            $products=DB::table("products")->join('price',
'products.id', '=', 'price.id_product')->leftJoin('discount_price',
'price.id', '=', 'discount_price.id_price')->whereNull('price.old')-
>whereNull('discount_price.old')->select("products.id as idProd","name",
"img_src","img_alt","price", "price.id as id price", "discount")->get();
            $cart=$request->session()->get('cart');
            $productsCount=count($cart);
            $user=$request->session()->get('user');

            try{
                $order=new Order();
                $order->id_user=$user->id;
                $order->address=$request->address;
                $order->quantity=$productsCount;

                $order->payment_type=$request->payment;
                $order->delivery_method=$request->delivery;
                $total=0;

                foreach($cart as $id=>$quantity){
                    foreach ($products as $prod){
                        if($prod->idProd == $id){

                            if($prod->discount){

```

```

        $total+=(int)$quantity*$prod->discount;
    }
    else{
        $total+=(int)$quantity*$prod->price;
    }
    }
}

$order->total=$total;
$order->save();

$orderId=$order->id;

$params="{email=".$user->email."}{order
id=".$orderId."}";
foreach($cart as $id=>$quantity){
    foreach ($products as $prod){
        if($prod->idProd == $id){

            if($prod->discount){
                $price=(int)$quantity*$prod->discount;
            }
            else{
                $price=(int)$quantity*$prod->price;
            }

            DB::table('order_items')->insert([
                "id_order"=>$orderId,
                "id_product"=>$prod->idProd,
                "quantity"=>$quantity,
                "price"=>$price
            ]);
        }
    }
}

$request->session()->forget('cart');
ActivityLogger::LogActivity("Order made ", $params);
return redirect()->route('orders');

} catch (\Exception $e){
    ActivityLogger::LogActivity("Error while making order",
$params);
    Log::error($e->getMessage(). "\n". $e-
>getTraceAsString());
    return redirect()->back()->with('error-msg', 'An error
occurred while checkout');
}

```

```

    }
    else{
        return response()->setStatusCode(404);
    }
}

public function deleteOrder(Request $request) {
    $orderId=$request->orderId;

    try{
        DB::table('orders')->where('id', '=', $orderId)->delete();

        ActivityLogger::LogActivity("Order deleted id= ", $orderId );

    }catch(\Exception $e){
        ActivityLogger::LogActivity("Error while deleting
order", "id=".$orderId);
        Log::error($e->getMessage(). "\n". $e->getTraceAsString());
        return redirect()->back()->with('error-msg', 'An error
occurred while deleting order');
    }
}

public function showOrderItems(Request $request){
    $id=$request->orderItemId;
    $products=Product::all();
    $ordersItems=DB::table('order_items')->where("id_order", '=',
$id)->get();

    return response()->json(["data"=>$ordersItems,
"products"=>$products]);
}
}

```

ProductsController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Category;
use App\Models\Color;
use App\Models\Discount;
use App\Models\Product;
use App\Models\ProductModel;
use Illuminate\Http\Request;

class ProductsController extends MainController
{
    public function index(Request $request){

        $model=new ProductModel();

        $this->data['categoryId']=Category::all();
        $this->data['colors']=Color::all();
        $this->data['discounts']=Discount::all();

        $request->session()->forget('color');
        $request->session()->forget('discount');
        $request->session()->forget('status');
        $request->session()->forget('keyword');
        $request->session()->forget('category');
        $request->session()->forget('color');
        $request->session()->forget('priceSort');
        //dd($model->search($request));

        return view('pages.products.index', ["data"=> $this->data,
"model"=> $model->search($request)]);
    }
}

```

ProductsInsertController.php


```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Http\Requests\ProductInsertRequest;
use App\Models\Category;
use App\Models\Color;
use App\Models\Discount;
use App\Models\Material;
use App\Models\Price;
use App\Models\Product;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\File;
use Illuminate\Support\Facades\Log;

class ProductsInsertController extends MainController
{
    public function show(){
        $this->data['colors']=Color::all();
        $this->data['categories']=Category::all();
        $this->data['materials']=Material::all();
        $this->data['discounts']=Discount::all();
        return view ('pages.admin.products.insert', ["data"=>$this->data]);
    }

    public function insert(ProductInsertRequest $request){

        $imageName = time() . '.' . $request->image->extension();

        try {
            DB::beginTransaction();

            $newProduct = Product::create(
                ["name"=> $request->name,
                 "img_src" => $imageName,
                 "status"=>0,
                 "img_alt"=> $request->name,
                 "id_category"=>$request->category,
                 "id_color"=>$request->color,
                 "id_material"=>$request->material]
            );

            $prodId=$newProduct->id;
            $param="{id:".$prodId."}{name:".$request->name."}{img_src:".$imageName."}{img_alt:".$request->name."}{id_category:".$request->category."}{id_color:".$request->color."}{id_material:".$request->material."}";

```

```

        $newPrice=Price::create(
            ["id_product"=> $prodId, "price" => $request->price]
        );
        if($request->get('discountFilter')!=0){
            DB::table('discount_price')->insert([
                "id_price"=>$newPrice->id,
                "id_discount"=>(int)$request-
>get('discountFilter'),
                "discount"=>(float)$request->get('discountPrice')
            ]);
        }

        DB::commit();
        ActivityLogger::LogActivity("Product inserted", $param);
        $request->image->move(public_path('assets/img/'),
$imageName);
        return redirect()->route('products-admin');
    } catch (\Exception $e){
        DB::rollBack();
        ActivityLogger::LogActivity("Error while inserting product",
$param);
        Log::error($e->getMessage().'\n'. $e->getTraceAsString());
        if(File::exists(public_path('/assets/img/' . $imageName))){
            File::delete(public_path('/assets/img/' . $imageName));
        }
        return redirect()->back()->with('error', 'An error occurred
while inserting product');
    }
}
}
}

```

ProductsUpdateController.php

```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Http\Requests\ProductUpdateRequest;
use App\Models\Category;
use App\Models\Color;
use App\Models\Discount;

```

```

use App\Models\Material;
use App\Models\Price;
use App\Models\Product;
use Illuminate\Http\Request;

use Illuminate\Http\Response;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\File;
use Illuminate\Support\Facades\Log;

class ProductUpdateController extends MainController
{
    private $productPriceNew;
    private $productDiscount;
    public function show($id){
        $product = Product::find($id);
        $productPrice=DB::table('price')->select('price', 'id')->
>where('id_product', '=', $id)->whereNull('old')->first();
        $productDiscount=DB::table('discount_price')->
>select('discount','id_discount')->where('id_price', '=', $productPrice->
>id)->whereNull('old')->first();
        $this->data['discounts']=Discount::all();
        $this->data['colors']=Color::all();
        $this->data['categories']=Category::all();
        $this->data['materials']=Material::all();
        return view('pages.admin.products.update',
["product"=>$product,"productPrice"=>$productPrice,
"productDiscount"=>$productDiscount ,"data"=>$this->data]);
    }

    public function update(ProductUpdateRequest $request, $id){
        try {
            DB::beginTransaction();
            $product = Product::find($id);
            $param="{Id=".$product->id."}";
            if(!$product) {
                return redirect()->back()->with("error", "There is no
product in the database with this id");
            }
            else{
                if($product->name!=$request->get('name')){
                    $product->name = $request->get("name");
                    $param.=" {name=".$request->get('name')." }";
                }
            }
        }
    }
}

```

```

        if($request->file('pImage')){
            if(File::exists(public_path('/assets/img/' .
$product->img_src))){
                File::delete(public_path('/assets/img/' .
$product->img_src));
            }
            $file=$request->file('pImage');
            $fileName=time()." ".$file-
>getClientOriginalExtension();

            $file->move(public_path('assets/img'), $fileName);

            $product->img_src=$fileName;
            $product->img_alt=$product->name;

            $param="{image=".$fileName."}";
        }

        if($product->status!=$request->get('status')){
            $product->status = (int)$request->get("status");
            $param="{status=".$request->get('status')." }";
        }

        if($product->id_category!=$request->get('category')){
            $product->id_category = $request->get("category");
            $param="{id_category=".$request-
>get('category')." }";
        }

        if($product->id_color!=$request->get('color')){
            $product->id_color = $request->get("color");
            $param="{id_color=".$request->get('color')." }";
        }

        if($product->id_material!=$request->get('material')){
            $product->id_material = $request->get("material");
            $param="{id_material=".$request-
>get('material')." }";
        }
        $product->save();
    }

    $productPrice = DB::table('price')->select('id', 'price',
'id_product')->where('id_product', '=', $id)->orderByDesc('id')->first();

    if($productPrice){
        if($productPrice->price != (float)$request-
>get('price')){

```

```

        DB::table('price')->where('id','',$productPrice->id)->update(['old'=>1]);
        $price= new Price();
        $price->id_product=$id;
        $price->price=(float)$request->get('price');
        $this->productPriceNew=$price->id;
        $price->save();
        $param.="{price=".$request->get('price')."}";
    }
}
else{
    $price= new Price();
    $price->id_product=$id;
    $price->price=(float)$request->get('price');
    $this->productPriceNew=$price->id;
    $price->save();
    $param.="{price=".$request->get('price')."}";
}

if(empty($this->productPriceNew)){
    $this->productDiscount =DB::table('discount_price')->select('id','id_discount', 'id_price', 'discount')->where('id_price','',$productPrice->id)->orderByDesc('id')->first();
}
else{
    $this->productDiscount =DB::table('discount_price')->select('id','id_discount', 'id_price', 'discount')->where('id_price','',$this->productPriceNew->id)->orderByDesc('id')->first();
}

if($this->productDiscount){
    if($request->get('discountFilter')==="0"){
        DB::table('discount_price')->where('id_price','',$this->productDiscount->id_price)->delete();
    }
    elseif($request->get('discountFilter')===$this->productDiscount->id_discount && $request->get('discountPrice')!=$this->productDiscount->discount){
        DB::table('discount_price')->where('id_price','',$this->productDiscount->id_price)->update(['old'=>1]);
        DB::table('discount_price')->insert([
            "id_price"=>$this->productDiscount->id_price,
            "id_discount"=>(int)$request->get('discountFilter'),
            "discount"=>(float)$request->get('discountPrice')
        ]);
        $param.="{discount_filter=".$request->get('discountFilter')."}";
    }
}

```

```

        $param.="{"discount_price=".$request->
>get('discountFilter')."}";
    }
    elseif($request->get('discountFilter')!="0" &&
!empty($request->get('discountPrice'))){
        if($this->productDiscount->id_discount!=$request->
>get('discountFilter')){
            DB::table('discount_price')->where('id_price',
'=', $this->productDiscount->id_price)->update(['old'=>1]);

            DB::table('discount_price')->insert([
                "id_price"=>$this->productDiscount->id_price,
                "id_discount"=>(int) $request->
>get('discountFilter'),
                "discount"=>(float) $request->
>get('discountPrice')
            ]);
            $param.="{"discount_filter=".$request->
>get('discountFilter')."}";
            $param.="{"discount_price=".$request->
>get('discountFilter')."}";
        }
    }
    elseif($request->get('discountFilter')!="0" &&
!empty($request->get('discountPrice'))){
        DB::table('discount_price')->insert([
            "id_price"=>$productPrice->id,
            "id_discount"=>(int) $request->get('discountFilter'),
            "discount"=>(float) $request->get('discountPrice')
        ]);
        $param.="{"discount_filter=".$request->
>get('discountFilter')."}";
        $param.="{"discount_price=".$request->
>get('discountFilter')."}";
    }

    ActivityLogger::LogActivity("Product updated", $param);
    DB::commit();
    return redirect()->route("products-admin");

} catch (\Exception $e) {
    ActivityLogger::LogActivity("Error while updating
product", "id=".$product->id);

    echo $e->getMessage(). " " . $e->getMessage();
    Log::error( $e->getMessage(). " " . $e->getTraceAsString());
    return redirect()->back()->with("error", "An error has

```

```

occurred, while editing product");
    }

    }

    public function delete(Request $request,$id){
        try{
            $product = Product::find($id);

            if(!$product) {
                return redirect()->back()->with("error", "There is no
product in the database with this id");
            }
            DB::table('products')->where('id', '=', $id)->delete();
            if(File::exists(public_path('/assets/img/products/' .
$product->img_src))){
                File::delete(public_path('/assets/img/products/' .
$product->img_src));
            }
            ActivityLogger::LogActivity("Product deleted ",
"id=".$product->id);
            return redirect()->route("products-admin");
        }catch(\Exception $e){
            ActivityLogger::LogActivity("Error while deleting
product","id=".$product->id);
            Log::error( $e->getMessage(). " " . $e->getTraceAsString());
            return redirect()->back()->with("error", "An error has
occurred, while deleting product");
        }
    }
}

```

RegisterController.php

```

<?php

namespace App\Http\Controllers;

use App\Helpers\ActivityLogger;
use App\Http\Requests\RegisterUserRequest;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Log;

class RegisterController extends MainController
{

```

```

public function register(){
    return view('pages.main.register');
}

public function post(RegisterUserRequest $request){
    try{
        $passwordMd5=md5($request->get('password'));

        $user=new User();
        $user->first_name=$request->get('firstName');
        $user->last_name=$request->get('lastName');
        $user->email=$request->get('email');
        $user->password=$passwordMd5;
        $user->id_role=2;
        $user->active=1;
        $user->save();

        ActivityLogger::LogActivity("User registered",
"email=".$user->email);
        return redirect()->route('login')->with('success',
'Successful registration');
    }catch(\Exception $e){
        ActivityLogger::LogActivity("Error while
registering","email=".$user->email);
        Log::error($e->getMessage(). "\n". $e->getTraceAsString());
        return redirect()->back()->with('error-msg', 'An error
occurred while registering');
    }
}
}
}

```

Assets


```
@import
url('https://fonts.googleapis.com/css2?family=EB+Garamond:ital@1&display=
swap');
@import
url('https://fonts.googleapis.com/css2?family=EB+Garamond&display=swap');
*{
    margin:0px;
    padding:0px;
    font-family: 'EB Garamond', serif;
}
header{
    font-family: 'EB Garamond', serif;
    background-color: #fff;
    padding:0;
}
ul{
    list-style-type: none;
}
ul li{
    display: inline;
}
ul li a{
    font-size:25px;
    color:#7D4F50 !important;
}
ul li a:hover{
    border-bottom: #839791 2px solid;
    text-decoration: none;
}
.colorRottenCherry{
    color:#7D4F50;
}
.colorMint{
    color:#839791;
}
.colorPink{
    color:#CC8B86;
}
.colorWhite{
    color:#fff!important;
```

```

}
#filterP{
    position: sticky;
    top: 8rem;
}

#find{
    width: 140px;
}
.btnFilter{
    background-color: #839791;
    color: #7D4F50;
    font-weight: bold;
}
.font26{
    font-size: 26px;
}
.font18{
    font-size: 18px;
}
#navigation i{
    display: none;
}

#banner{
    background-image: url("../img/living-room-g1b3b990f6_1280.jpg");
    background-size: cover;
    width: 100%;
    height: 680px;
    border-radius: 5px;
    margin-top: 5%;
}
.marginTop{
    margin-top: 7%;
}
.marginTop3{
    margin-top: 3%;
    margin-bottom: 3%;
}
.marginTop5{
    margin-top: 5%;
    margin-bottom: 5%;
}
#messageAdmin{
    height: 150px;
}
.borderBottom{
    border-bottom: 2px solid #7D4F50;
}

```

```

}
.backgroundNav{
    background-color:#839791;
}
#motto{
    width: 30%;
    margin-top: 17%;
    margin-bottom: 3%;
    border: 2px solid #7D4F50;
    border-radius: 5px;
    background-color: #ffff;
    padding: 30px 10px;
}
.tableBg{
    background-color: white;
}
#buttons-Links{
    margin:1px auto;
}
.marginTB{
    margin-top:10%;
    margin-bottom:10%;
}
.marginTB2{
    margin-top:6%;
    margin-bottom:8%;
}
.dugme{
    border: 1px solid #7D4F50;
    background-color: #ffff;
    font-weight: bold;
    font-size: 20px;
}
.dugme:hover{
    color:#7D4F50;
    box-shadow: 3px 4px #839791;
}
.btnCart{
    border: 1px solid #7D4F50;
    background-color: #ffff;
    font-size: 15px;
}
.btnCart:hover{
    color:#7D4F50;
    box-shadow: 3px 4px #839791;
}
.btnProduct{
    border: 1px solid #7D4F50;

```

```

    background-color: #ffff;
    font-size: 15px;
}
.btnProduct:hover{
    color:#7D4F50;
    box-shadow: 3px 4px #839791;
}

.btnSubmit{
    border: 2px solid #7D4F50;
    background-color: #ffff;
    font-size: 18px;
}
.btnSubmit:hover{
    color:#7D4F50;
    box-shadow: 3px 4px #839791;
}
.description{
    padding:2%;
    height: inherit;
}
.centering{
    margin:0 auto;
}
.top-margin{
    margin-top:10%;
}

#footer{
    border-top:2px solid #839791;
    border-radius: 5px;
    padding: 2% 0;
}

#cart span{
    font-size: 26px;
    border:1px solid #7D4F50;
    padding:3px 15px;
    border-radius: 5px 10px;
}
#cart i{
    font-size: 26px;
}
#cart i:hover{
    font-size: 30px;
}
.borderCards{
    border:2px solid #839791;
    border-radius: 20px 5px;
}

```

```

border-style: outset;
padding: 4% 2%;
}

.borderLi{
border-color: #839791;
border-style: inset;
}

.week{
background-color: #839791;
color:#fff;
border-radius:5px 10px;
}

.spring{
background-color:#CC8B86;
color:#fff;
border-radius:5px 10px;
}

.holiday{
background-color:#7D4F50;
color:#fff;
border-radius:5px 10px;
}

.filterC{
background-color:#AA998F;
color:#fff;
border-radius: 5px 10px;
}

.pointer {
cursor: pointer;
}

input[type=search]{
border: none;
border-bottom:2px solid #7D4F50;
padding: 5px;
}

.fontIS{
font-size: 22px;
}

.inStock{
color:green;
font-size: 17px;
}

.outStock{
color:#ae2012;
font-size: 17px;
}

.fontSize{

```

```

    font-size: 19px;
}
.footerCol{
    background-color:#839791;
    border-radius: 5px 10px;
    color:#fff;
    font-size: 18px;
}
.fontSI{
    font-size:25px
}
#socialN a:hover{
    color:#839791;
}
#cart{
    width:30%;
}
#cart img{
    width: 70%;
}
.bcGreen{
    background-color:#839791
}

.widthNum{
    width:60%;
}
.removeButton{
    border: 1px solid #7D4F50;
    border-radius: 5px 10px;
    background-color: #ffff;
    font-weight: bold;
    font-size: 17px;
}
#loginForm{
    border-radius: 5px 10px;
    border:3px solid #839791;
    box-shadow: 10px 10px #7D4F50;
}
.margin-top50{
    margin-top:7%;
}
#authorImg img{
    border-radius: 10px 30px;
}
#authorText{
    border-radius: 10px 30px;
    border:3px solid #7D4F50;
}

```

```

.register:hover{
    text-decoration: none;
    color:#7D4F50;
}
.rowItem{
    margin-top:5%;
}
.imgWidth{
    width:70px;
}

.mAuto{
    margin:0 auto;
}
.bd-placeholder-img {
    font-size: 1.125rem;
    text-anchor: middle;
    -webkit-user-select: none;
    -moz-user-select: none;
    -ms-user-select: none;
    user-select: none;
}

.fa-inbox{
    font-size:19px;
}
.stat{
    font-size:24px;
    color:#7D4F50;
    margin-right: 5px;
}
.colorBlue{
    color:#2d3748;
}
.navbar-brand2 {
    padding-top: .75rem;
    padding-bottom: .75rem;
    font-size: 1rem;
}
@media screen and (max-width:1440px){
    .btnProduct{
        font-size:12px;
    }
}

```

```

@media screen and (max-width:1025px){
    .btnProduct{
        font-size:14px;
    }
}
@media screen and (max-width:769px){
    ul li{
        display: block !important;
    }
    #navigation i{
        display: block !important;
    }
    #motto{
        margin-top: 35%;
        margin-bottom: 3%;
    }
    #motto h2{
        font-size: 18px;
    }
    .marginTop{
        margin-top: 15%;
    }
    .btnProduct{
        font-size:13px;
    }
    .rowItem{
        margin-top:0%;
    }
    .marginTB2{
        margin-top: 8%;
        margin-bottom: 3%;
    }
    .bd-placeholder-img-lg {
        font-size: 3.5rem;
    }
}
@media screen and (max-width:426px){
    .centering{
        font-size:20px;
    }
    #banner{
        height: 300px;
        margin-top: 17%;
    }

    #motto h2{
        font-size: 10px;
    }
}

```



```

        padding:0px;
    }
    .dugme{
        font-size:14px;
    }
    .marginTop{
        margin-top: 30%;
    }
    .btnProduct{
        font-size:12px;
    }
    .marginTB2{
        margin-top: 15%;
        margin-bottom: 3%;
    }

    #filterP{
        position: initial;
    }
}
@media screen and (max-width:376px){
    .btnProduct{
        font-size:11px;
    }
    .marginTB2{
        margin-top: 19%;
        margin-bottom: 3%;
    }
}

```

js/main.js

```

$(document).ready(function(){

    $('#filterP ul > li ul')
    .click(function(e){
        e.stopPropagation();
    })
    .filter(':not(:first)')
    .hide();

    $('#filterP ul > li').click(function(){
        var selfClick = $(this).find('ul:first').is(':visible');
        if(!selfClick) {
            $(this)

```

```

        .parent()
        .find('> li ul:visible')
        .slideToggle();
    }

    $(this)
        .find('ul:first')
        .stop(true, true)
        .slideToggle();
    });

    $('.paginationP').click(function(e) {
        e.preventDefault();
        let limit = $(this).data('limit');
        let token = $(this).data('token');
        let url= $(this).data('url');
        let parent=$(this).parent().parent();

        if(url==="order-pag"){
            $("#pagination0").children(".active").removeClass('active');
        }

        $(".li.active").removeClass('active');
        $(this).parent().addClass('active');

        $.ajax({
            url: url,
            method: 'post',
            data: {
                limit:limit,
                _token: token
            },
            success: function(result){

                if(url==="order-pag"){
                    displayOrder(result);
                }
            },
            error: function(xhr) {
                console.log(xhr)
            }
        });
    });
});

$.ajaxSetup({
    headers: {
        'X-CSRF-TOKEN': $('meta[name="csrf-token"]').attr('content')
    }
});

```

```

});

const displayOrderItemsAdmin = (data) => {

  const products=data['products'];
  document.getElementById('orderItems').innerHTML = data['data'].map(el
=> {

    if (data['data']) {
      for(const prod of products){
        if(prod.id == el.id_product){
          return `
            <tr id="orderItemId_${el.id}">
              <td class="col-3 text-center"></td>
              <td class="col-2 text-center" >${prod.name}</td>
              <td class="col-2 text-center">${el.quantity}</td>
              <td class="col-3 text-center">${el.price} $</td>

            </tr>`
          ;
        }
      }
    } else {
      return `<div class="col-12">
        <p class="alert-danger my-5 text-center py-2 font-weight-
bold">No orders</p>
        </div>`;
    }

  }).join('');
}

const displayOrderItems = (data) => {

  const products=data['products'];
  document.getElementById('orderItems').innerHTML = data['data'].map(el
=> {

    if (data['data']) {
      for(const prod of products){
        if(prod.id == el.id_product){
          return `
            <tr id="orderItemId_${el.id}">
              <td class="col-3 text-center"></td>

```

```

        <td class="col-2 text-center" >${prod.name}</td>
        <td class="col-2 text-center">${el.quantity}</td>
        <td class="col-3 text-center">${el.price} $</td>
      </tr>`
    ;
  }
}
} else {
  return `<div class="col-12">
    <p class="alert-danger my-5 text-center py-2 font-weight-
bold">No orders</p>
    </div>`;
}

}).join('');
}

const displayUserParam= (data)=>{
  const roles=data['roles'];
  document.getElementById('user').innerHTML=data['data'].map(el=>{
    let html="";

    html=`<div class='col-12'>

      <p class="font-weight-bold colorRottenCherry
font18">User: ${el.email}</p>

      </div>
      <div class='col-12'>
        <label class="font-weight-bold colorRottenCherry
font18">Account status</label>
        <select name="status" class="form-control">`;

        if(el.active===0){
          html+=`<option value="0" selected>Inactive</option>
            <option value="1" >Active</option>`;
        }

        else if(el.active===1){
          html+=`<option value="0" >Inactive</option>
            <option value="1" selected>Active</option>`;
        }

        html+=`</select>
      </div>
      <div class='col-12'>
        <label class="font-weight-bold colorRottenCherry
font18">Role</label>

```

```

        <select name="role" class="form-control">`;

        for(const r of roles){

            if(el.id_role===r.id){
                html+=`<option value="${r.id}" selected
>${r.role}</option>`;
            }
            else {
                html += `<option value="${r.id}"
>${r.role}</option>`;
            }

        }

        html+=`</select>
</div>
<div class="col-12 mt-2">
    <input type="hidden" value="${el.id}" name="userId">
    <button type="submit" name="btnUser" class="btn btnSubmit
colorMint font-weight-bold font18"> Edit</button>
</div>`;
        return html;
    }).join('');
}

function addToCart(id) {

    $.ajax({
        url : "add-to-cart",
        beforeSend: function(request) {
            request.setRequestHeader("X-CSRF-TOKEN", token);
        },
        method: "POST",
        data: {
            productId:id
        },
        success: function(data) {
            toastr.success('Product added to cart!');
        },
        error:function(xhr) {
            console.log(xhr);
        }
    })
}

function removeFromCart(id) {

    $.ajax({

```

```

        method: "DELETE",
        beforeSend: function(request) {
            request.setRequestHeader("X-CSRF-TOKEN", token);
        },
        url: baseUrl+"/remove-item",
        data:{
            productId:id
        },
        success: function(data) {
            let trToRemove = $("#cartItem_" + id);
            trToRemove.remove();
            location.reload();
        },
        error: function(xhr) {
            console.log(xhr)
        }
    })
}

function changeQuantity(productId, price, count, element) {
    $.ajax({
        url: "/cart",
        method: "PATCH",
        data: {
            productId : productId,
            quantity: element.value
        },
        success: function() {
            $("#price_" + productId).html(element.value * price + "$")
        },
        error: function (xhr) {
            console.log(xhr);
        }
    })
}

function deleteMsg(id, token) {
    $.ajax({
        method: "DELETE",
        beforeSend: function(request) {
            request.setRequestHeader("X-CSRF-TOKEN", token);
        },
        url: baseUrl+"/delete-msg",
        data:{
            msgId:id,
        },
        success: function(data) {
            let trToRemove = $("#msgId_" + id);

```

```

        trToRemove.remove();
        location.reload();
    },
    error: function(xhr) {
        console.log(xhr)
    }
})
}

function deleteOrder(id) {
    $.ajax({
        method: "DELETE",
        beforeSend: function(request) {
            request.setRequestHeader("X-CSRF-TOKEN", token);
        },
        url: baseUrl+"/delete-order",
        data:{
            "orderId":id
        },
        success: function(data) {
            let trToRemove = $("#orderId_" + id);
            trToRemove.remove();

        },
        error: function(xhr) {
            console.log(xhr)
        }
    })
}

function deleteOrderAdmin(id) {
    $.ajax({
        method: "DELETE",
        beforeSend: function(request) {
            request.setRequestHeader("X-CSRF-TOKEN", token);
        },
        url: baseUrl+"/delete-order-admin",
        data:{
            "orderId":id
        },
        success: function(data) {
            let trToRemove = $("#orderId_" + id);
            trToRemove.remove();

        },
        error: function(xhr) {
            console.log(xhr)
        }
    })
}

```

```

}

function deleteUser(id) {
    $.ajax({
        method: "DELETE",
        beforeSend: function(request) {
            request.setRequestHeader("X-CSRF-TOKEN", token);
        },
        url: baseUrl+"/delete-user",
        data:{
            "userId":id
        },
        success: function(data) {
            let trToRemove = $("#userId_" + id);
            trToRemove.remove();
            toastr.success('User deleted!');
        },
        error: function(xhr) {
            console.log(xhr)
        }
    })
}

$('.btnShowOrderItems').on('click', function() {

    let id = $(this).data('id');

    $.ajax({
        method: "POST",
        beforeSend: function(request) {
            request.setRequestHeader("X-CSRF-TOKEN", token);
        },
        url: baseUrl+"/show-order-items",
        data:{
            "orderId":id
        },
        success: function(data) {
            console.log(id);
            displayOrderItems(data);
        },
        error: function(xhr) {
            console.log(xhr)
        }
    })
});

$('.btnShowUserParam').on('click', function(){
    let id=$(this).data('id');

```



```

$.ajax({
  method: 'POST',
  beforeSend: function (request) {
    request.setRequestHeader("X-CSRF-TOKEN", token);
  },
  url: baseUrl + "/show-user-param",
  data: {
    "userId": id
  },
  success: function (data) {
    console.log(id);
    displayUserParam(data);
  }
})
});

$('.btnShowOrderItemsAdmin').on('click', function() {

  let id = $(this).data('id');

  $.ajax({
    method: "POST",
    beforeSend: function (request) {
      request.setRequestHeader("X-CSRF-TOKEN", token);
    },
    url: baseUrl + "/show-order-items-admin",
    data: {
      "orderId": id
    },
    success: function (data) {
      console.log(id);
      displayOrderItemsAdmin(data);
    },
    error: function (xhr) {
      console.log(xhr)
    }
  })
});

```

Database

