

# What's New In Java

...

Streams, lambdas, method references, LVTI, JPMS, ...

# Contact Info

Ken Kousen

Kousen IT, Inc.





[ken.kousen@kousenit.com](mailto:ken.kousen@kousenit.com)

<http://www.kousenit.com>

<http://kousenit.org> (blog)

[@kenkousen](https://twitter.com/kenkousen) (twitter)

<https://kenkousen.substack.com> (newsletter)



# Videos (available on the O'Reilly Learning Platform)

O'Reilly video courses: See <http://shop.oreilly.com> for details

[Groovy Programming Fundamentals](#)

[Practical Groovy Programming](#)

[Mastering Groovy Programming](#)

[Learning Android](#)

[Practical Android](#)

[Gradle Fundamentals](#)

[Gradle for Android](#)

[Spring Framework Essentials](#)

[Advanced Java Development](#)

# GitHub Repository

Java Latest

[https://github.com/kousen/java\\_latest](https://github.com/kousen/java_latest)

# Documentation pages

<https://docs.oracle.com/en/java/javase/11/>

- [Tools Reference](#)
- [JShell User Guide](#)
- [Javadoc Guide](#)

Note: Actual API Javadocs are at:

<https://docs.oracle.com/en/java/javase/11/docs/api/index.html>

# Java Licensing Is a Mess, But...

## Java is Still Free 2.0.3 - Java Champions

### Java 8

End of life without commercial support (ended Jan 2019)

Open JDK (and others) still provide updates

### Java 11

Oracle JDK requires license for production use

Open JDK (and others) are free

# Features You Need To Know

# Java Functional Features

Streams, lambdas, method references



# Lambda Expressions

Java lambda expressions

Assigned to **S**ingle **A**bstract **M**ethod interfaces

Parameter types inferred from context

# Functional Interface

Interface with a **Single Abstract Method**

Lambdas can only be assigned to  
functional interfaces

# Functional Interface

See `java.util.function` package

`@FunctionalInterface`

Not required, but used in library

# Functional Interfaces

**Consumer** → single arg, no result

```
void accept(T t)
```

**Predicate** → returns boolean

```
boolean test(T t)
```

**Supplier** → no arg, returns single result

```
T get()
```

**Function** → single arg, returns result

```
R apply(T t)
```

# Functional Interfaces

Primitive variations

Consumer

IntConsumer, LongConsumer,

DoubleConsumer,

BiConsumer<T,U>

# Functional Interfaces

**BiFunction**  $\rightarrow$  binary function from T and U to R

R apply(T, U)

**UnaryOperator** extends Function (T and R same type)

**BinaryOperator** extends BiFunction (T, U, and R same type)

# Method References

Method references use :: notation

`System.out::println`

`x → System.out.println(x)`

`Math::max`

`(x,y) → Math.max(x,y)`

`String::length`

`x → x.length()`

`String::compareToIgnoreCase`

`(x,y) → x.compareToIgnoreCase(y)`

# Streams

A sequence of elements

Does not store the elements

Does not change the source

Operations are lazy when possible

Closed when terminal expression reached



# Streams

A stream carries values

from a source

through a pipeline

# Pipelines

Okay, so what's a pipeline?

A source

Zero or more **intermediate** operations

A **terminal** operation

# Reduction Operations

Reduction operations

Terminal operations that produce  
one value from a stream

`average, sum, max, min, count, ...`

# Creating Streams

Creating streams

```
Collection.stream()
```

```
Stream.of(T... values)
```

```
Stream.generate(Supplier<T> s)
```

```
Stream.iterate(T seed, UnaryOperator<T> f)
```

```
Stream.empty()
```

# Transforming Streams

Process data from one stream into another

```
filter(Predicate<T> p)
```

```
map(Function<T,R> mapper)
```

# Transforming Streams

There's also flatMap:

```
Stream<R> flatMap(Function<T, Stream<R>> mapper)
```

Map from single element to multiple elements

Remove internal structure

# Using Collectors

`Stream.of( ... )`

`.collect( Collectors.toList() )` → creates an `ArrayList`

`.collect( Collectors.toSet() )` → creates a `HashSet`

`.collect( Collectors.toCollection( Supplier ) )`

→ creates the supplier (`LinkedList::new`, `TreeSet::new`, etc)

`.collect( Collectors.toMap( Function, Function ) )`

→ creates a map; first function is keys, second is values

# Static And Default Methods in Interfaces



# Default methods

Default methods in interfaces

Use keyword **default**

# Default methods

What if there is a conflict?

Class vs Interface → **Class always wins**

Interface vs Interface →

Child overrides parent

Otherwise compiler error

# Static methods in interfaces

Can add static methods to interfaces

See `Comparator.comparing`

# Optional Type

# Optional

Alternative to returning object or null

`Optional<T>` value

`isPresent()` → boolean

`get()` → return the value

Goal is to return a default if value is null

# Optional

`ifPresent()` accepts a consumer

```
optional.ifPresent( ... do something ...)
```

`orElse()` provides an alternative

```
optional.orElse(... default ...)
```

```
optional.orElseGet(Supplier<? extends T> other)
```

```
optional.orElseThrow(Supplier<? extends X> exSupplier)
```

# The java.time Package

LocalDate, LocalTime, ZonedDateTime, and more

# LocalDate

A date without time zone info

contains year, month, day of month

```
LocalDate.of(2017, Month.FEBRUARY, 2)
```

months actually count from 1 now



# Date and Time API

`java.util.Date` is a disaster

`java.util.Calendar` isn't much better

Now we have `java.time`

# LocalTime

`LocalTime` is just `LocalDate` for times

hh:mm:ss

`LocalDateTime` is both, but then you

might need time zones

# ZonedDateTime

Database of timezones from IANA

<https://www.iana.org/time-zones>

```
Set<String> ZoneId.getAvailableZoneIds()
```

```
ZoneId.of("... tz name ...")
```


# ZonedDateTime

LocalDateTime → ZonedDateTime

```
local.atZone(zoneId)
```

Instant → ZonedDateTime

```
instant.atZone(ZoneId.of("UTC"))
```



# Dates and Times

Java 8 Date-Time: `java.time` package

`AntarcticaTimeZones.java`

# Collection Factory Methods

List.of, Set.of, Map.of, Map.ofEntries

# Collection Factory Methods

```
List.of(a, b, b, c, ...)
```

```
Set.of(a, b, b, c, ...)
```

```
Map.of(k1, v1, k2, v2, k3, v3, ...)
```

```
Map.ofEntries(  
    Map.entry(k1, v1),  
    Map.entry(k2, v2),  
    Map.entry(k3, v3), ...)
```



# Local Variable Type Inference

The var reserved type name

# var Data Type

Local variables only

- No fields
- No method parameters
- No method return types

`var` is a "reserved type name", not a keyword (can still have variable called "var")

Can also use on

- for loops
- try-with-resources blocks

# var Data Type

Stuart Marks: Style Guidelines for Local Variable Type Inference in Java

<http://openjdk.java.net/projects/amber/LVTIstyle.html>

Local variables only

# Features You Should Probably Know

# HTTP Client

Built-in synch and asynch networking

# HTTP 2 Client

New HTTP Client API

Supports HTTP/2 and websockets

Replaces HTTPURLConnection

Both synchronous and asynchronous modes

# JShell

The Java REPL

# JShell

Java interpreter

<https://docs.oracle.com/en/java/javase/11/jshell/introduction-jshell.html>

> `jshell` (or add `-v` for verbose)

`jshell>`

`/exit` to leave

No semicolons needed



# Enhanced Switch Statement

Makes switch useable

# Enhanced Switch

- Expressions → return a value
- Arrow rather than colon → no fall through
- Multiple case labels
- Statement blocks → yield
- Exhaustive

# Text Blocks

Multiline Strings

# Text Blocks

- Use "triple double" quotes (""") *and a newline*
- Indentation based on closing """
- `stripIndent`, `indent`, `translateEscapes`

# Records

Preview feature of Java 14

# Records

- Like a data class → intended to hold data
- Add attributes using constructor syntax
- generates getter methods
- final
- extends `java.lang.Record`
- generates `toString`, `equals`, and `hashCode`
- can add static fields

# Pattern Matching

Preview feature of Java 14

# Pattern matching

- Enhances the `instanceof` operator
- `if (shape instanceof Square s) → use square methods on s`
- Like a "smart cast"



# Miscellaneous Features

# Private Methods in Interfaces

Both `default` and `static` methods in interfaces  
can call `private` methods

# Try-With-Resources

Always had to declare variable inside the **try** block parentheses

Can now declare try-block variable outside

```
public void loadDataFromDB() throws SQLException {  
    Connection dbCon = DriverManager.getConnection(url, user, password);  
    try (dbCon; ResultSet rs = dbCon.createStatement().executeQuery("select * from emp")) {
```

dbCon variable will **automatically be closed** (no **finally** needed)

# Deprecated Annotation

`@Deprecated` now has fields:

- `forRemoval`
- `since`

Tool `jdeprscan` to scan a jar file for deprecated uses

# SafeVarargs

Until Java 8, `@SafeVarargs` could only be applied to:

- static methods
- final methods
- constructors

In Java 9, can add `@SafeVarargs` to private methods

# Features You Can Probably Skip

# The Module System

The Good and Bad of JPMS

# JPMS

Module descriptors

`module-info.java`

exports, requires, opens, ...

Quick start guide:

<http://openjdk.java.net/projects/jigsaw/quick-start>

State of the Module System

<http://openjdk.java.net/projects/jigsaw/spec/sotms/>



# JPMS

module name → use "reverse dns" (like packages)

**requires** → add a module to the "module path"

**java.base** added automatically

**transitive** → any package using this module can read the arg

**exports** → list of packages exported by a module

can export to selected modules

# JPMS

Changes the nature of public and private

Reflection only works on opened packages

Use "**opens**" to expose a package to reflection

requires **static** → make available at compile time but not runtime (optional)

# Summary

- Need to know functional features
  - Streams with map / filter / reduce
  - Lambda expressions
  - Method references
  - Concurrent, parallel streams
- Need to use Optional
- Helpful to know preview features
  - Enhanced switch
  - Text blocks
  - Records
  - Pattern matching
- Can probably ignore modules (unless you're a library developer)