



IKONPAY CCSSv9 LEVEL-2 READINESS ASSESSMENT REPORT

CCSSA: Aniruddha Dhumal (AW7bDUoMwW3)

Organization: Plusnineone Security

Assessment Period: 15/02/2026 - 10/03/2026

Report Version: v1.0 FINAL

Report Date: 16/03/2026

TABLE OF CONTENTS

OVERVIEW	3
AUDIT SCOPE	3
TECHNICAL COMPONENTS	4
PHYSICAL LOCATIONS	5
PERSONNEL	5
READINESS ASSESSMENT MATRIX	6
GAPS AND REMEDIATION	12
APPENDIX A – EVIDENCE REGISTER	14
POLICIES & PROCEDURES	14
HOT WALLET KEY GENERATION	14
WARM WALLET KEY GENERATION	15
COLD WALLET KEY GENERATION	16
COORDINATOR & RELAY MACHINE	16
PERSONNEL	17

OVERVIEW

This report is meant to assess gaps between IkonPay's existing custody solution and the CCSSv9 Level 2 standard. It also aims to provide relevant remediation suggestions to bridge the non-conformities. The assessment only focuses on Aspect 1.01 (Key Material Generation) and Aspect 1.02 (Wallet Generation). The assessment activities, including inspections, documentation reviews, personnel interviews, and procedural observations, were conducted between 15/02/2026 and 10/03/2026. All findings and compliance verdicts in this report reflect the state of IkonPay's custody system as observed during this period.

The Entity under assessment is a hypothetical fintech company offering merchant crypto settlement for e-commerce platforms across India and Southeast Asia. The firm temporarily holds digital assets on behalf of merchants and performs daily settlements across a custody subsystem supporting both Bitcoin and EVM chains. The architecture consists of: a hot wallet backed by a cloud HSM for automated payouts, a warm wallet running a 2-of-3 multisig for treasury operations, and a cold wallet running a 2-of-3 multisig for longer-term reserves.

Of the 10 requirements assessed in the scope, 6 were found to be compliant, 3 non-compliant and 1 not applicable. IkonPay's custody architecture is broadly well-designed and demonstrates several strong foundational controls across hot, warm, and cold wallet operations. However, readiness for CCSSv9 Level 2 for the aspects in scope is constrained by a few material gaps: inconsistent pre-execution verification of the key-generation mechanism (including the hot-wallet container supply chain and independent validation for hardware-wallet firmware), lack of geographic separation for multi-signer key storage, and corresponding omissions in the documented policies. Addressing these issues through enforced verification controls, key location distribution, and policy updates would improve the compliance posture.

Though IkonPay's architecture was curated to grasp the essence of a real world custody system, IkonPay is not a real custody solution and the detailed scenario was generated using AI for the purpose of a mock audit. Any similarities are purely coincidental.

AUDIT SCOPE

The audit scope (Trusted Environment) for this assessment primarily covers the hot, warm and cold wallets of IkonPay Custody which manage client funds. Machines and network elements used to build, sign and relay transactions have also been included in the scope. The audit scope also extends to:

1. The surrounding components which may have a direct impact on the key management security.
2. Personnel directly or indirectly involved in key management.
3. Physical locations relevant to key management.

TECHNICAL COMPONENTS	
Component	Description
Hot Wallets: Cloud HSM	IkonPay uses AWS CloudHSM as the cryptographic boundary for all hot wallet key material. Private keys for BTC and EVM hot wallets are generated and stored within the HSM cluster and are not permitted to leave the HSM boundary in plaintext. All signing operations are performed inside the HSM. External services interact with it solely through API calls via the HSM client library.
Hot Wallet Automated Signer System	The Signer System is a containerised software service running in IkonPay's production AWS environment. It is the sole authorised client permitted to request signing operations from the Cloud HSM. When a merchant payout is approved, the Signer Service receives the transaction from the Tx Builder, authenticates to the Cloud HSM, and retrieves a signature. The private key does not leave the HSM during this process. The signing service system boundary includes: Settlement API, Policy/Limit Engine, Tx Builder, Signer Service, Cloud HSM, and the Broadcast Gateway.
Warm Wallets: Hardware	Warm wallets are used for treasury refills of the hot wallet and for large settlements that exceed the automated hot wallet daily limit. Key material is held on dedicated Ledger NanoX hardware wallet devices, one per signer, across three warm wallet signers: Treasury Operator A, Treasury Operator B, and the Security Officer. The warm wallet implements a 2-of-3 multisig scheme.
Cold Wallets: Hardware	Cold wallets are used for longer-term reserves. Key material is held on dedicated Ledger NanoX hardware wallet devices, held by IkonPay's three co-founders. The cold wallet implements a 2-of-3 multisig scheme.
Multisig Coordinator Machine	The Multisig Coordinator Machine is a dedicated laptop used as the offline assembly point for both warm and cold multisig signing workflows. By policy, this machine is not used for any general corporate purpose and is intended to remain offline during all operations. Its role is to receive partially signed transaction data from the hardware wallet devices, constructing or completing the multisig transaction, before the fully signed transaction is transferred to the Transaction Relay Machine for broadcast.
Transaction Relay Machine	The Transaction Relay Machine is an online laptop that sits at the boundary between the offline signing environment and the public blockchain network. Its role is to receive the fully signed transaction from the Multisig Coordinator Machine and broadcast it to the relevant blockchain network, either BTC or EVM. It does not hold any key material and does not participate in the signing process.

USB Transfer Medium	The USB transfer medium is the sole sanctioned physical data transfer mechanism used to move fully signed transaction data across the air gap between the Multisig Coordinator Machine and the Transaction Relay Machine. It carries no key material at any point; its contents are limited to fully constructed, signed transaction data ready for broadcast.
---------------------	--

PHYSICAL LOCATIONS

Location	Description
XYZ Bank Locker	The intended off-site storage location for the third cold wallet signer's hardware wallet device between ceremonies.
IkonPay HQ - Pune	The primary physical location for IkonPay's custody operations. It is the operational base for all warm and cold signing personnel, housing the Multisig Coordinator Machine, the Transaction Relay Machine, and the hardware wallet devices of Treasury Operators A and B, the Security Officer, and currently all three cold wallet signers.

PERSONNEL

Name	Position	Role
John	Co-Founder	Cold wallet signer (1/3)
Doe	Co-Founder	Cold wallet signer (2/3)
Alice	Co-Founder	Cold wallet signer (3/3)
Bob	Treasury Operator	Warm wallet signer (1/3)
Ken	Treasury Operator	Warm wallet signer (2/3)
Carol	Security Officer	Warm wallet signer (3/3)
Dave	CISO	Owner of the security architecture and the policies governing it.
Eve	Sr. Platform Engineer	Owner of the hot wallet signing service.

READINESS ASSESSMENT MATRIX

The CCSSA conducted a thorough assessment on the Entity's key management system, specifically for CCSS aspects 1.01 (Key Material Generation) and 1.02 (Wallet Generation). The following table presents the findings for each requirement in a tabular format with the CCSSA's verdict on compliance.

06

Compliant

03

Non-Compliant

01

Not Applicable

Requirement	Compliance	Findings
1.01.1.1 Key material is generated by the actor who will be using it.	Compliant	For the hot wallet, the Signer Service is the actor that generates and uses the key material. Key material is generated by the Signer Service within the AWS CloudHSM boundary, and the same Signer Service is the sole authorized entity that uses the key material for transaction signing. The place of generation and the place of use are the same component, satisfying the requirement. For cold wallets, each of the three co-founders generated their own key material independently on their individually assigned Ledger Nano X hardware wallet devices during a scheduled key generation ceremony. Each co-founder is the actor who will be using the key material they generated, satisfying the requirement. For warm wallets, Treasury Operator A and Treasury Operator B each generated their own key material on their individually assigned hardware wallet devices during the warm wallet ceremony, satisfying the requirement for those two keys. A non-conformity was identified for the Security Officer's key, which was generated on Treasury Operator A's personal machine at the time of the original ceremony. The Entity identified this gap and performed a key rotation, with the Security Officer subsequently generating a replacement key on a newly procured Ledger Nano X device assigned to them. The current state is considered compliant following the completed remediation.

		Evidence: <i>IP-POL-01, IP-INV-05, HOT-HSM-KEY-01, HOT-JIRA-01, HOT-NET-01, HOT-IAM-01, HOT-CKLS-01, HOT-DEMO-01, WARM-JIRA-01, WARM-HW-PHOTO-01, WARM-CKLS-01, COLD-HW-PHOTO-01, COLD-CKLS-01, INT-CISO-01, INT-PLAT-ENG-01, INT-SEC-OFF-01, INT-TREAS-B-01, INT-TREAS-A-01</i>
1.01.1.3 A digital signature for the key material generation mechanism is generated, published, and validated prior to each execution.	Non-Comp...	For the hot wallet, digital signature verification of the key generation mechanism is not consistent as the container image for the software is not signed at deployment to be verified during generation events. Though SHA256 checksum verification of the binary is mentioned in the pipeline, it comes with two issues. Firstly, the validation is not consistent as discussed in the interviews. Secondly, the validation happens at deployment and not before the key generation event (execution). For warm and cold wallets, the firmware of the hardware wallets is checked prior to each execution. The keyholders perform a Ledger Genuine Check on the hardware wallet which confirms the authenticity of the wallet with Ledger's servers. However, this check relies on Ledger's attestation infrastructure and does not constitute an independent verification of the key generation mechanism by the Entity itself. An independent validation, performed and recorded by the Entity, is required to satisfy this requirement. Evidence: <i>HOT-AWS-ECS-01, HOT-DEMO-01, WARM-DEMO-01, COLD-DEMO-01, WARM-LEDGER-LOG-01, COLD-LEDGER-LOG-01, WARM-CKLS-01, COLD-CKLS-01, INT-PLAT-ENG-01, INT-FOUND-A-01, INT-FOUND-B-01, INT-FOUND-C-01</i>

1.01.1.2 Where an automated signing agent will use key material, and the place of generation of key material is different from the place of use. The following criteria are addressed: 1. The key material is generated within a secure Key Management System that meets applicable CCSS requirements. 2. The key material is transferred securely to the automated signing agent from the place of generation that meets applicable CCSS requirements. 3. The key material is securely removed from the place of generation that meets applicable CCSS requirements.	Compliant	Hot wallet keys are generated and used within the CloudHSM boundary contained in a VPC and no transfer of key material takes place. Cold and warm wallets are generated manually by keyholders on hardware wallets making this requirement not applicable for the hardware wallets. Evidence: <i>IP-STD-02, IP-POL-01, HOT-CKLS-01, HOT-ARCH-01, HOT-AWS-VPC-01, HOT-AWS-HSM-01, HOT-AWS-ECS-01, HOT-AWS-NAT-01, HOT-AWS-MTLS-01, INT-PLAT-ENG-01, HOT-DEMO-01</i>
1.01.2.1 The methodology for generating key material is validated prior to use. Software does not include features that restrict which values can be used. Software does not include features that store or transmit data to another actor, unless that feature enhances security.	Compliant	AWS CloudHSM used for the hot wallet key generation and signing, is configured as a FIPS cluster which makes it FIPS-140-2 Level 3 certified. For warm and cold wallets, Ledger NanoX hardware wallets are used which are considered to be industry standard. Prior to operational use, the Security Officer and the CISO conducted an assessment on these hardware wallets to validate that the key generation mechanism uses the full entropy space of the secure element TRNG, with no known restrictions on the range of values that can be generated. This assessment was formally documented and signed off by the two assessors. Evidence: <i>HOT-AWS-HSM-01, IP-STD-02, IP-KMTA-08, WARM-RCPT-01,</i>

		<i>COLD-RCPT-01, WARM-CKLS-01, COLD-CKLS-01, COLD-DEMO-01, WARM-DEMO-01, INT-CISO-01</i>
1.01.2.2 In cases where key material is generated without the use of software, the generation methodology is validated to ensure determinism is not present.	Not Applic...	This requirement is not applicable since no key material used is generated using mechanical means and relies on software for key generation.
1.01.4.1 Key material is generated on a Key Management System with sufficient entropy to ensure key material is not generated with any bias towards a reduced range of values, or other deterministic properties.	Compliant	For the hot wallet, the requirement is satisfied. AWS CloudHSM uses a FIPS 140-2 Level 3 validated hardware TRNG compliant with NIST SP 800-90B as the entropy source for all key material generation operations, providing formal assurance that key material is not generated with bias toward a reduced range of values or other deterministic properties. For warm and cold wallets, the Ledger Nano X is built on the ST33 series secure element, which contains a hardware TRNG operating at the chip level, independent of software processes. The secure element holds Common Criteria certification. The authenticity and integrity of each device was confirmed through the Ledger Genuine Check performed before each key generation ceremony, and all devices were procured from legitimate Ledger-affiliated stores. The requirement is considered satisfied for both warm and cold wallets on the basis of the device certification and the pre-ceremony integrity verification controls in place.
		Evidence: <i>HOT-AWS-HSM-01, COLD-DEMO-01, WARM-DEMO-01, WARM-LEDGER-LOG-01, HOT-CKLS-01, WARM-CKLS-01, COLD-CKLS-01, COLD-LEDGER-LOG-01, WARM-RCPT-01, COLD-RCPT-01, WARM-HW-PHOTO-01, COLD-HW-PHOTO-01, INT-CISO-01, INT-FOUND-A-01, INT-FOUND-B-01, INT-FOUND-C-01</i>

1.02.1.1 When considering the application of a single-signer mechanism to a wallet, the following criteria are addressed: 1. The criticality of the wallet to the CCSS Trusted Environment. 2. The impact of loss of customer funds controlled by the wallet. 3. The risk of a wallet compromise is included in the threat model defined in requirement 2.03.2.1. 4. The effectiveness of the security controls implemented to protect the wallet.	Compliant ✓	The Entity uses a single signer configuration for their hot wallet. A maximum of 5% of the entire reserves are held in the hot wallet at a time with replenishments from the warm wallets as and when needed. The Entity has conducted threat modeling and risk assessments taking into consideration single-signer risks, impact of loss, threat scenarios and has chosen appropriate controls in the risk treatment plan in accordance to their risk appetite. This requirement is not applicable for warm and cold wallets as they implement a multi-signer configuration. Evidence: <i>IP-STD-04, IP-STD-02, IP-THRM-06, IP-RISK-07, IP-POL-01, INT-CISO-01</i>
1.02.2.1 A wallet that has implemented a multi-signer mechanism has at least one redundant key for recovery purposes.	Compliant ✓	The Entity uses a 2-of-3 multisig configuration for their warm and cold wallets. In addition to video demonstrations, the existence of all hardware wallets was confirmed using photographic evidence, policy review and inspection of Safe Wallet configurations. This requirement is not applicable for the hot wallet as it implements a single-signer configuration. Evidence: <i>IP-POL-01, WARM-HW-PHOTO-01, IP-STD-02, COLD-HW-PHOTO-01, WARM-EVM-SAFE-01, COLD-EVM-SAFE-01, RECOV-BTC-WARM-01, RECOV-EVM-WARM-01, RECOV-BTC-COLD-01, RECOV-EVM-COLD-01</i>

1.02.3.1 Key materials for a wallet that implements a multi-signer mechanism are stored in different locations.	Non-Comp...	For warm wallets, two of the three signer devices are held by Treasury Operator A and Treasury Operator B, both located at the Pune office. The Security Officer, the third signer, also stores their device at the Pune office in a desk drawer. All three warm wallet keys are therefore stored at the same physical location, which does not satisfy the requirement for key materials to be stored in different locations. For cold wallets, the intended design requires the third co-founder's device to be stored at a bank locker, which would provide geographic separation from the two devices held at the Pune office. However, as confirmed during interviews with the Compliance Manager, this arrangement has not been implemented. All three cold wallet devices are currently stored locally in the Pune office. The requirement is not satisfied in the current state for cold wallets either. This requirement is not applicable for the hot wallet as it implements a single-signer configuration. Evidence: <i>INT-SEC-OFF-01, INT-COMPL-01</i>
1.02.5.1 The entity has a documented policy in place which details the company's internal policies and procedures and covers the relevant areas of wallet generation.	Non-Comp...	The Entity documents their wallet generation process in the Custody Wallet Policy (<i>IP-POL-01 v1.4</i>). The policy covers all types of wallets, the signer service and peripheral devices like the coordinator and relay machines. Though it covers a substantial part, it omits the digital signature verification of the key generation mechanism step and the geographic distribution of keys for warm and cold wallets resulting in all the hardware wallets being stored at the same office. Evidence: <i>IP-POL-01, INT-COMPL-01</i>

GAPS AND REMEDIATION

1.01.1.3 Digital Signature Verification of Key Generation Mechanism

Gap:

As per the wallet policy, warm and cold wallet generation follows a key ceremony checklist which mandates Ledger's Genuine Check prior to each use. Though this is a good start, the digital signature verification is conducted on Ledger's side and is not an independent verification done by the Entity.

For the hot wallet, digital signature validation of the key generation mechanism is not consistent without a verifiable proof of application.

Recommendation:

To remediate, update the wallet policy and add a manual check to the warm and cold wallet setup process. The manual check step would entail downloading the firmware binary independently from GitHub, computing the hash and comparing it with what the device reports. This comparison needs to be recorded in the key ceremony checklist for that session. A redo for the warm and cold wallets setup is needed.

It is recommended that IkonPay digitally sign the container image for the hot wallet key generation software using a recognized signing framework and enforce signature verification immediately prior to each key generation event. The SHA256 checksum verification must be standardized through a formal procedure that mandates its execution before every key generation event without exception, not solely at deployment. The outcome of each verification must be logged as part of the key generation ceremony record, with responsibility assigned to a named role.

Post-Remediation Evidence:

- Updated Wallet Management Policy
- Updated Key Ceremony Checklist
- Logs of the manual firmware validation performed

1.02.3.1 Geographic Distribution of Multi-Signer Key Material

Gap:

All three warm wallet signer devices are co-located at the Pune office, with the Security Officer's device stored in a desk drawer, resulting in no geographic separation. The cold wallet arrangement has the same issue. While the intended design requires the third co-founder's device to be held at a bank locker, this has not been implemented. In both cases, the concentration of all signer devices at a single location does not satisfy the requirement for key material to be stored in geographically separated locations.

Recommendation:

It is recommended that IkonPay distribute all three warm wallet signer devices across separate, access controlled physical locations, such that no two devices are co-located at the same premises. The same should be done for the cold wallets as well. The key storage

locations should be updated in the Key Inventory, specifying the designated storage location for each device and the responsible custodian. Periodic verification that devices remain stored at their designated locations should be incorporated into IkonPay's operational review cycle, with findings recorded and escalated to the CISO where deviations are identified.

Post-Remediation Evidence:

- Geotagged and timestamped photographic evidence of each device at its respective storage location
- Updated Wallet Management Policy
- Updated Key Inventory
- JIRA ticket escalations documenting the relocation as a controlled change

1.02.5.1 Custody Wallet Policy Omissions

Gap:

IkonPay's Custody Wallet Policy (IP-POL-01 v1.4) has two material omissions. First, the policy does not include the step requiring digital signature verification of the key generation mechanism. Second, the policy does not address the requirement for geographic distribution of key material for multi-signer wallets, which has directly contributed to all warm and cold wallet devices being stored at the same Pune office location.

Recommendation:

IP-POL-01 must be revised to include an explicit procedural step requiring digital signature verification of the key generation mechanism prior to each key generation event, with a clear requirement that the outcome be recorded in the ceremony log. The policy must also be updated to mandate that all signer devices for multi-signer wallets are stored at geographically separate locations, naming the designated location for each device and the responsible custodian. The revised policy must be reviewed, approved, and signed off by the CISO before being reissued under a new version number. Following policy reissuance, the physical relocation of devices must be executed in accordance with the updated policy.

Post-Remediation Evidence:

- Revised IP-POL-01 at an incremented version number, showing the two additions, with CISO sign-off
- JIRA ticket documenting the policy update as a controlled change

APPENDIX A – EVIDENCE REGISTER

POLICIES & PROCEDURES	
Reference ID	Document Title
IP-POL-01 v1.4	Custody Wallet Policy
IP-STD-02 v0.9	Key Generation Standard
IP-ARCH-03 v2.2	Signer Service Architecture
IP-STD-04 v1.0	Hot Wallet Single-Signer Risk Acceptance
IP-INV-05 v3.0	Key and Wallet Inventory
IP-THRM-06 v1.0	Threat Model Documentation
IP-RISK-07 v2.0	Risk Assessment and Treatment Plans
IP-KMTA-08 v1.0	Key Management Technology Acceptance Review

HOT WALLET KEY GENERATION	
Evidence ID	Description
HOT-ARCH-01	Signed-off Architectural Diagram of Automated Signing Agent
HOT-JIRA-01	JIRA Tickets Showing Design Phase (Settlement API to Broadcast Gateway)
HOT-AWS-VPC-01	Screenshot: AWS VPC Route Tables (PROD-CUSTODY VPC)
HOT-AWS-ECS-01	Screenshot: ECS Task Definition for Signer Service Container
HOT-AWS-HSM-01	Screenshot: AWS CloudHSM Policy Reflecting FIPS 140-2 Level 3 Configuration
HOT-AWS-MTLS-01	Screenshot: mTLS Certificate Configuration for Signer Service to CloudHSM Connection
HOT-AWS-NAT-01	Screenshot: NAT Gateway Rules Implementing Outbound-Only Connection

HOT-HSM-KEY-01	Screenshot: HSM Console Showing Key <code>hot_evm_signing_prod_01</code> Created by Service Principal <code>svc-signer-prod</code>
HOT-CKLS-01	Key Ceremony Checklist/Runbook for Hot Wallet Key Generation (indexed, dated, mapped to IP-INV-05)
HOT-DEMO-01	Recorded Screen/Video Demonstration: Signer Service Calling HSM API in Staging/Dev Environment
HOT-NET-01	Network Diagram: CCSS Trusted Environment Components (VPC, ECS, CloudHSM, NAT Gateway, Coordinator Laptop, Relay Laptop)
HOT-IAM-01	AWS IAM Policy: Permissions for CloudHSM Access

WARM WALLET KEY GENERATION	
Evidence ID	Description
WARM-JIRA-01	JIRA Ticket/Meeting Minutes: Security Officer Key Rotation (vulnerable key replaced with new hardware wallet key)
WARM-HW-PHOT O-01	Photographs: Hardware Wallets with Serial Numbers Visible (Treasury Operator A, Treasury Operator B, Security Officer)
WARM-RCPT-01	Purchase Receipts: Ledger Hardware Wallets Procured from Legitimate Ledger-Affiliated Stores
WARM-CKLS-01	Key Ceremony Checklist/Runbook for Warm Wallet Key Generation (indexed, dated, mapped to IP-INV-05)
WARM-DEMO-01	Recorded Video: Non-Production Key Rehearsal/Dry-Run on Similar Hardware Wallet Following Production Checklist
WARM-LEDGER-L OG-01	Ledger Live Log File: Genuine Check and Firmware Verification Sessions (parsed through Ledger log viewer)
WARM-BTC-XPUB -01	Documented xpub Derivation Paths for BTC Warm Wallet with Access Controls
WARM-EVM-SAF E-01	Smart Contract Address/Safe Application Excerpt: EVM Warm Wallet 2-of-3 Multisig Configuration
RECOV-BTC-WAR M-01	Recorded Screen/Video Demonstration: BTC Warm Wallet Recovery Dry-Run (confirming redundant key can complete signing quorum)

RECOV-EVM-WA RM-01	Recorded Screen/Video Demonstration: EVM Warm Wallet Recovery Dry-Run (confirming redundant key can complete signing quorum)
-----------------------	--

COLD WALLET KEY GENERATION	
Evidence ID	Description
COLD-HW-PHOT O-01	Photographs: Hardware Wallets with Serial Numbers Visible (Co-Founder 1, Co-Founder 2, Co-Founder 3)
COLD-RCPT-01	Purchase Receipts: Ledger Hardware Wallets Procured from Legitimate Ledger-Affiliated Stores
COLD-CKLS-01	Key Ceremony Checklist/Runbook for Cold Wallet Key Generation (indexed, dated, mapped to IP-INV-05)
COLD-DEMO-01	Recorded Video: Non-Production Key Rehearsal/Dry-Run on Similar Hardware Wallet Following Production Checklist
COLD-LEDGER-L OG-01	Ledger Live Log File: Genuine Check and Firmware Verification Sessions (parsed through Ledger log viewer)
COLD-BTC-XPUB -01	Documented xpub Derivation Paths for BTC Cold Wallet with Access Controls
COLD-EVM-SAFE -01	Smart Contract Address/Safe Application Excerpt: EVM Cold Wallet 2-of-3 Multisig Configuration
RECOV-BTC-COL D-01	Recorded Screen/Video Demonstration: BTC Cold Wallet Recovery Dry-Run (confirming redundant key can complete signing quorum)
RECOV-EVM-COL D-01	Recorded Screen/Video Demonstration: EVM Cold Wallet Recovery Dry-Run (confirming redundant key can complete signing quorum)

COORDINATOR & RELAY MACHINE	
Evidence ID	Description
COORD-STORAG E-01	Photographic Evidence: Multisig Coordinator Laptop Stored in Locked Cabinet/Safe/Restricted-Access Room
COORD-ASSET-0 1	Asset Register: Multisig Coordinator Laptop Registered as Dedicated Custody Device (not assigned to any employee)

COORD-BIOS-01	Screenshot: BIOS Configuration Showing Wi-Fi and Network Adapters Permanently Disabled at Firmware Level
COORD-USB-SCAN-01	USB Drive Malware Scan Log: Pre-Use Scan Results
COORD-USB-WIPE-01	USB Drive Wipe Log: Evidence of Drive Being Wiped Between Uses (as per wallet policy)

PERSONNEL	
Evidence ID	Description
INT-CISO-01	Interview Transcript: CISO (covering hot wallet architecture, single-signer rationale, compensating controls)
INT-PLAT-ENG-01	Interview Transcript: Platform Engineer (covering HSM API, Signer Service, CI pipeline, container image signing gap)
INT-TREAS-A-01	Interview Transcript: Treasury Operator A (covering warm wallet ceremony, Security Officer key generation on laptop)
INT-TREAS-B-01	Interview Transcript: Treasury Operator B (covering warm wallet key generation)
INT-FOUND-A-01	Interview Transcript: Co-Founder A (covering warm wallet key generation)
INT-FOUND-B-01	Interview Transcript: Co-Founder B (covering warm wallet key generation)
INT-FOUND-C-01	Interview Transcript: Co-Founder C (covering warm wallet key generation)
INT-SEC-OFF-01	Interview Transcript: Security Officer (covering late multisig join, config file import, device storage in desk drawer)
INT-COMPL-01	Interview Transcript: Compliance Manager (covering policy review cadence, geographic distribution gap)