


# The Metalysis-FFC process for the efficient extraction of oxygen on the lunar surface

B. Lomax\*, M. Conti, N. Khan, A. Ganin & M. Symes

[b.lomax.1@research.gla.ac.uk](mailto:b.lomax.1@research.gla.ac.uk)



- Regolith is a widely available source of oxygen
- All major elements in lunar regolith can be reduced - removes constraints on location
- Simultaneous production of metals highly beneficial

Figure 1: schematic showing the FFC-Cambridge process operating at ~900 °C

# Results: Oxygen extraction




Figure 3: oxygen recovery (% of total oxygen) from JSC-2A simulant vs. time ( $\text{CaCl}_2$ , 950 °C, 4A, inert anode)

- Oxygen detected in gas stream lower due to reactor corrosion (terrestrial cells designed for  $\text{CO}/\text{CO}_2$ )
- Oxygen remaining in product a more accurate indication of process success

Table 1: comparison to other oxygen extraction processes

	Hydrogen reduction	Carbothermal reduction	Molten regolith electrolysis	Metalysis-FFC
Temp.	~900 °C	>1600 °C	>1600 °C	~900 °C
Oxygen yield*	1-2% <sup>1</sup>	10-20% <sup>1</sup>	20-30% <sup>1</sup>	40-45%

1. Sanders, G.B. and Larson, W.E., 2012, *Journal of Aerospace Engineering*, 26(1), pp.5-17.

\*Yield (%) = kg oxygen/kg regolith

# Results: Metal/alloy production




Figure 4: SEM/EDX image of a fully reduced metallised JSC-2A grain




Figure 5: SEM/EDX image of a partially reduced JSC-2A grain




Figure 6: metal powder produced by the reduction of powdered JSC-2A lunar regolith simulant

- Mixed alloy from bulk lunar regolith – potentially useful?
  - Possibility of metal/alloy separation based on electrolysis parameters
- 
- Terrestrial technology is focused on pure metal and alloy production from various oxides
  - Off-Earth technology development for lunar oxygen can feed into Mars metal production capabilities





University  
of Glasgow

### Future directions

- Optimise process parameters
- Identify the sweet spot between oxygen yield vs. processing time/energy input
- Understand the reduction behaviour of individual minerals, how this relates to different regolith deposits and regions, and how this could potentially lead to metal/alloy separation

*Thanks to my supervisors and to ESA, Metalysis and the University of Glasgow for funding this research.*

Beth Lomax – University of Glasgow  
b.lomax.1@research.gla.ac.uk




Figure x: elements produced and scaled up by Metalysis as of 2018