Title: SLH-DSA Hash-based Signatures: Toward Quantum-resistant TLS Deployment in Satellite Quantum Links

Year: 2016

Authors: Y. Chen, F. Haddad, D. Silva (Department of Computer Science, Northbridge University)

Keywords: Shor's algorithm, post-quantum cryptography, hash-based signatures, lattice cryptography, quantum-safe

Abstract:

Quantum-resistant TLS deployment remains a critical challenge for the NIST standardization process, particularly in satellite quantum links. This paper proposes a framework built on SLH-DSA hash-based signatures that explicitly accounts for post-quantum certificate chain size. We evaluate the framework on resource-estimation tables for 2048-bit moduli and compare it against 6 baseline methods. Experimental results show that the proposed approach improves logical qubit count by 4.8% while keeping signature size within acceptable bounds. We further analyse its limitations and discuss implications for practical deployment.

1. Introduction

The rapid maturation of the NIST standardization process has changed how researchers and practitioners approach quantum-resistant TLS deployment, yet practical deployment is still limited by scalability, cost, and reproducibility concerns. Over the past decade, SLH-DSA hash-based signatures have attracted sustained attention as a promising route toward solving quantum-resistant TLS deployment in realistic settings such as satellite quantum links. A central difficulty is that improvements in secret key rate frequently come at the expense of decapsulation time, forcing designers to accept trade-offs that are poorly understood. This paper addresses these gaps by studying how SLH-DSA hash-based signatures interact with Grover search attacks when applied to quantum-resistant TLS deployment.

Our work is motivated by the growing demand for satellite quantum links, where reliability and transparency requirements are especially strict. We make three contributions: a unified formulation of quantum-resistant TLS deployment, a practical design built on SLH-DSA hash-based signatures, and an empirical evaluation on resource-estimation tables for 2048-bit moduli. Understanding post-quantum certificate chain size is equally important, because it shapes both the theoretical limits and the operational cost of any proposed approach. The remainder of this paper reviews related work, describes the proposed methodology, and concludes with a discussion of limitations and directions for future research.

2. Related Work

Novak et al. (2013) introduced an early framework based on SLH-DSA hash-based signatures, reporting a 36.4% improvement in signature size over previous baselines. Subsequent work by Novak et al. (2014) extended this line of research to satellite quantum links, although the evaluation was restricted to small-scale settings. A survey by Larsen et al. (2012) categorised existing approaches to quantum-resistant TLS deployment into three families and highlighted the lack of standard benchmarks. Researchers working on the NIST standardization process have explored Grover search attacks as an alternative, with Bianchi et al. (2009) noting that the approach scales poorly beyond 64 components. Okafor et al. (2009) analysed post-quantum certificate chain size and showed that purely heuristic solutions cannot guarantee consistent logical qubit count.

More recently, Takahashi et al. (2009) combined SLH-DSA hash-based signatures with Grover search attacks, achieving a 18.6% reduction in overhead on resource-estimation tables for 2048-bit moduli. Several studies have criticised the reliance on synthetic workloads, arguing that results on resource-estimation tables for 2048-bit moduli may not generalise to satellite quantum links. In contrast to these efforts, our work treats

quantum-resistant TLS deployment and post-quantum certificate chain size jointly rather than as independent concerns. Despite this body of literature, no prior study has systematically compared SLH-DSA hash-based signatures and Grover search attacks under identical experimental conditions.

3. Methodology

We formalise quantum-resistant TLS deployment as a constrained optimisation task in which the objective is to maximise logical qubit count while keeping logical qubit count within a prescribed budget. The proposed architecture consists of four stages: data acquisition, preprocessing, core processing based on SLH-DSA hash-based signatures, and a validation layer that incorporates Grover search attacks. All experiments were conducted on resource-estimation tables for 2048-bit moduli, which provides 1200 labelled instances or configurations covering a broad range of operating conditions. To ensure reproducibility, every experiment was repeated 10 times with independent random seeds, and we report mean values together with 95% confidence intervals.

Hyperparameters were selected through grid search over a validation split, and the final configuration was fixed before any evaluation on held-out data. The core routine applies SLH-DSA hash-based signatures to reduce the effect of post-quantum certificate chain size, followed by a calibration step that stabilises logical qubit count. Our implementation is written in Python and C++, and was executed on a workstation with 64 GB of memory and a single mid-range accelerator. We compare against 6 baseline methods, including a conventional approach built on Grover search attacks and two recent variants reported in the literature.

The proposed design improves logical qubit count by 4.8% relative to the strongest baseline and reduces signature size by 27.3%, a statistically significant difference ($p < 0.05$). Ablation experiments show that removing the Grover search attacks component reduces logical qubit count by approximately 9.2%, confirming its contribution. A sensitivity analysis over 8 parameter settings shows that performance remains stable, with variation in decapsulation time below 13.7%.

4. Conclusion

This paper investigated quantum-resistant TLS deployment through the lens of SLH-DSA hash-based signatures, and demonstrated that a carefully designed pipeline can improve logical qubit count by 4.8% on resource-estimation tables for 2048-bit moduli. The findings suggest that the NIST standardization process will continue to benefit from closer integration of SLH-DSA hash-based signatures and Grover search attacks, particularly in satellite quantum links. Several limitations remain, including the restricted scale of our evaluation and the simplified treatment of post-quantum certificate chain size. Future work will extend the framework to larger deployments, explore tighter theoretical guarantees, and release an open benchmark to facilitate fair comparison. We hope the evidence presented here encourages the community to adopt more rigorous and transparent evaluation practices for quantum-resistant TLS deployment.