Title: Smart-contract Vulnerability Detection in Consensus Mechanisms: Lessons from Proof-of-stake Consensus

Year: 2023

Authors: L. Zhang, A. Müller, C. Petrov, E. Takahashi (National Laboratory for Applied Computation)

Keywords: distributed ledger, decentralized identity, zero-knowledge rollups, Ethereum, Byzantine fault tolerance

Abstract:

Smart-contract vulnerability detection remains a critical challenge for consensus mechanisms, particularly in supply-chain traceability. This paper proposes a framework built on proof-of-stake consensus that explicitly accounts for miner extractable value mitigation. We evaluate the framework on the Ethereum mainnet transaction history and compare it against 7 baseline methods. Experimental results show that the proposed approach improves transactions per second by 30.6% while keeping fork rate within acceptable bounds. We further analyse its limitations and discuss implications for practical deployment.

1. Introduction

The rapid maturation of consensus mechanisms has changed how researchers and practitioners approach smart-contract vulnerability detection, yet practical deployment is still limited by scalability, cost, and reproducibility concerns. Despite considerable progress, existing solutions for smart-contract vulnerability detection tend to degrade when moving from controlled laboratory conditions to production workloads, which motivates a more systematic investigation. A central difficulty is that improvements in finality time frequently come at the expense of fork rate, forcing designers to accept trade-offs that are poorly understood. This paper addresses these gaps by studying how proof-of-stake consensus interact with zk-rollup constructions when applied to smart-contract vulnerability detection.

Our work is motivated by the growing demand for supply-chain traceability, where reliability and transparency requirements are especially strict. We make three contributions: a unified formulation of smart-contract vulnerability detection, a practical design built on proof-of-stake consensus, and an empirical evaluation on the Ethereum mainnet transaction history. Understanding miner extractable value mitigation is equally important, because it shapes both the theoretical limits and the operational cost of any proposed approach. The remainder of this paper reviews related work, describes the proposed methodology, and concludes with a discussion of limitations and directions for future research.

2. Related Work

Zhang et al. (2019) introduced an early framework based on proof-of-stake consensus, reporting a 6.3% improvement in fork rate over previous baselines. Subsequent work by Takahashi et al. (2016) extended this line of research to supply-chain traceability, although the evaluation was restricted to small-scale settings. A survey by Kowalski et al. (2020) categorised existing approaches to smart-contract vulnerability detection into three families and highlighted the lack of standard benchmarks. Researchers working on consensus mechanisms have explored zk-rollup constructions as an alternative, with Kowalski et al. (2020) noting that the approach scales poorly beyond 500 components. Rossi et al. (2011) analysed miner extractable value mitigation and showed that purely heuristic solutions cannot guarantee consistent gas cost.

More recently, Silva et al. (2008) combined proof-of-stake consensus with zk-rollup constructions, achieving a 29.1% reduction in overhead on the Ethereum mainnet transaction history. Several studies have criticised the reliance on synthetic workloads, arguing that results on the Ethereum mainnet transaction history may not generalise to supply-chain traceability. Industry reports corroborate these academic findings, pointing to

smart-contract vulnerability detection as a persistent obstacle for supply-chain traceability. Despite this body of literature, no prior study has systematically compared proof-of-stake consensus and zk-rollup constructions under identical experimental conditions.

3. Methodology

We formalise smart-contract vulnerability detection as a constrained optimisation task in which the objective is to maximise transactions per second while keeping gas cost within a prescribed budget. The proposed architecture consists of four stages: data acquisition, preprocessing, core processing based on proof-of-stake consensus, and a validation layer that incorporates zk-rollup constructions. All experiments were conducted on the Ethereum mainnet transaction history, which provides 5000 labelled instances or configurations covering a broad range of operating conditions. To ensure reproducibility, every experiment was repeated 10 times with independent random seeds, and we report mean values together with 95% confidence intervals.

Hyperparameters were selected through grid search over a validation split, and the final configuration was fixed before any evaluation on held-out data. Our implementation is written in Python and C++, and was executed on a workstation with 64 GB of memory and a single mid-range accelerator. We compare against 7 baseline methods, including a conventional approach built on zk-rollup constructions and two recent variants reported in the literature. The proposed design improves transactions per second by 30.6% relative to the strongest baseline and reduces fork rate by 27.6%, a statistically significant difference ($p < 0.05$).

Ablation experiments show that removing the zk-rollup constructions component reduces transactions per second by approximately 14.4%, confirming its contribution. A sensitivity analysis over 128 parameter settings shows that performance remains stable, with variation in finality time below 14.1%. Threats to validity include the limited diversity of the Ethereum mainnet transaction history and the possibility that deployment in supply-chain traceability introduces conditions not captured in our setup.

4. Conclusion

This paper investigated smart-contract vulnerability detection through the lens of proof-of-stake consensus, and demonstrated that a carefully designed pipeline can improve transactions per second by 30.6% on the Ethereum mainnet transaction history. The findings suggest that consensus mechanisms will continue to benefit from closer integration of proof-of-stake consensus and zk-rollup constructions, particularly in supply-chain traceability. Several limitations remain, including the restricted scale of our evaluation and the simplified treatment of miner extractable value mitigation. Future work will extend the framework to larger deployments, explore tighter theoretical guarantees, and release an open benchmark to facilitate fair comparison. We hope the evidence presented here encourages the community to adopt more rigorous and transparent evaluation practices for smart-contract vulnerability detection.