Title: Post-quantum Certificate Chain Size in Information-theoretic Security: Lessons from HQC Code-based Key Encapsulation

Year: 2026

Authors: T. Nakamura, Z. Novak, F. Sharma, H. Haddad (Faculty of Engineering, Meridian Polytechnic)

Keywords: post-quantum cryptography, cryptanalysis, quantum-safe, hash-based signatures, cryptographic agility

Abstract:

Post-quantum certificate chain size remains a critical challenge for information-theoretic security, particularly in long-term archival encryption. This paper proposes a framework built on HQC code-based key encapsulation that explicitly accounts for quantum-resistant TLS deployment. We evaluate the framework on the NIST PQC round-three submissions and compare it against 3 baseline methods. Experimental results show that the proposed approach improves logical qubit count by 32.0% while keeping decapsulation time within acceptable bounds. We further analyse its limitations and discuss implications for practical deployment.

1. Introduction

The rapid maturation of information-theoretic security has changed how researchers and practitioners approach post-quantum certificate chain size, yet practical deployment is still limited by scalability, cost, and reproducibility concerns. Over the past decade, HQC code-based key encapsulation have attracted sustained attention as a promising route toward solving post-quantum certificate chain size in realistic settings such as long-term archival encryption. Despite considerable progress, existing solutions for post-quantum certificate chain size tend to degrade when moving from controlled laboratory conditions to production workloads, which motivates a more systematic investigation. A central difficulty is that improvements in decapsulation time frequently come at the expense of logical qubit count, forcing designers to accept trade-offs that are poorly understood.

This paper addresses these gaps by studying how HQC code-based key encapsulation interact with code-based encryption when applied to post-quantum certificate chain size. Our work is motivated by the growing demand for long-term archival encryption, where reliability and transparency requirements are especially strict. We make three contributions: a unified formulation of post-quantum certificate chain size, a practical design built on HQC code-based key encapsulation, and an empirical evaluation on the NIST PQC round-three submissions. The remainder of this paper reviews related work, describes the proposed methodology, and concludes with a discussion of limitations and directions for future research.

2. Related Work

Chen et al. (2010) introduced an early framework based on HQC code-based key encapsulation, reporting a 23.9% improvement in secret key rate over previous baselines. Subsequent work by Petrov et al. (2010) extended this line of research to long-term archival encryption, although the evaluation was restricted to small-scale settings. A survey by Nakamura et al. (2025) categorised existing approaches to post-quantum certificate chain size into three families and highlighted the lack of standard benchmarks. Researchers working on information-theoretic security have explored code-based encryption as an alternative, with Sharma et al. (2019) noting that the approach scales poorly beyond 1200 components. More recently, Singh et al. (2014) combined HQC code-based key encapsulation with code-based encryption, achieving a 25.5% reduction in overhead on the NIST PQC round-three submissions.

Several studies have criticised the reliance on synthetic workloads, arguing that results on the NIST PQC round-three submissions may not generalise to long-term archival encryption. In contrast to these efforts, our

work treats post-quantum certificate chain size and quantum-resistant TLS deployment jointly rather than as independent concerns. Industry reports corroborate these academic findings, pointing to post-quantum certificate chain size as a persistent obstacle for long-term archival encryption. Despite this body of literature, no prior study has systematically compared HQC code-based key encapsulation and code-based encryption under identical experimental conditions.

3. Methodology

We formalise post-quantum certificate chain size as a constrained optimisation task in which the objective is to maximise logical qubit count while keeping logical qubit count within a prescribed budget. The proposed architecture consists of four stages: data acquisition, preprocessing, core processing based on HQC code-based key encapsulation, and a validation layer that incorporates code-based encryption. All experiments were conducted on the NIST PQC round-three submissions, which provides 64 labelled instances or configurations covering a broad range of operating conditions. Hyperparameters were selected through grid search over a validation split, and the final configuration was fixed before any evaluation on held-out data.

The core routine applies HQC code-based key encapsulation to reduce the effect of quantum-resistant TLS deployment, followed by a calibration step that stabilises signature size. Our implementation is written in Python and C++, and was executed on a workstation with 64 GB of memory and a single mid-range accelerator. We compare against 3 baseline methods, including a conventional approach built on code-based encryption and two recent variants reported in the literature. The proposed design improves logical qubit count by 32.0% relative to the strongest baseline and reduces decapsulation time by 13.9%, a statistically significant difference ($p < 0.05$).

Ablation experiments show that removing the code-based encryption component reduces logical qubit count by approximately 5.7%, confirming its contribution. A sensitivity analysis over 1200 parameter settings shows that performance remains stable, with variation in signature size below 12.1%. Threats to validity include the limited diversity of the NIST PQC round-three submissions and the possibility that deployment in long-term archival encryption introduces conditions not captured in our setup.

4. Conclusion

This paper investigated post-quantum certificate chain size through the lens of HQC code-based key encapsulation, and demonstrated that a carefully designed pipeline can improve logical qubit count by 32.0% on the NIST PQC round-three submissions. The findings suggest that information-theoretic security will continue to benefit from closer integration of HQC code-based key encapsulation and code-based encryption, particularly in long-term archival encryption. Several limitations remain, including the restricted scale of our evaluation and the simplified treatment of quantum-resistant TLS deployment. Future work will extend the framework to larger deployments, explore tighter theoretical guarantees, and release an open benchmark to facilitate fair comparison. We hope the evidence presented here encourages the community to adopt more rigorous and transparent evaluation practices for post-quantum certificate chain size.