Title: Rethinking Protocol Formal Verification: A ML-DSA Lattice Signatures Perspective

Year: 2026

Authors: Y. Haddad, Z. Larsen (School of Information Sciences, Lakeshore University)

Keywords: secure computation, side-channel attacks, authentication, cryptography, provable security

Abstract:

Protocol formal verification remains a critical challenge for provable security, particularly in digital identity management. This paper proposes a framework built on ML-DSA lattice signatures that explicitly accounts for privacy-preserving data sharing. We evaluate the framework on the eBACS benchmarking results and compare it against 4 baseline methods. Experimental results show that the proposed approach improves key generation latency by 31.0% while keeping ciphertext overhead within acceptable bounds. We further analyse its limitations and discuss implications for practical deployment.

1. Introduction

The rapid maturation of provable security has changed how researchers and practitioners approach protocol formal verification, yet practical deployment is still limited by scalability, cost, and reproducibility concerns. Over the past decade, ML-DSA lattice signatures have attracted sustained attention as a promising route toward solving protocol formal verification in realistic settings such as digital identity management. Despite considerable progress, existing solutions for protocol formal verification tend to degrade when moving from controlled laboratory conditions to production workloads, which motivates a more systematic investigation. A central difficulty is that improvements in encryption throughput frequently come at the expense of ciphertext overhead, forcing designers to accept trade-offs that are poorly understood.

Our work is motivated by the growing demand for digital identity management, where reliability and transparency requirements are especially strict. We make three contributions: a unified formulation of protocol formal verification, a practical design built on ML-DSA lattice signatures, and an empirical evaluation on the eBACS benchmarking results. Understanding privacy-preserving data sharing is equally important, because it shapes both the theoretical limits and the operational cost of any proposed approach. The remainder of this paper reviews related work, describes the proposed methodology, and concludes with a discussion of limitations and directions for future research.

2. Related Work

Subsequent work by Dubois et al. (2024) extended this line of research to digital identity management, although the evaluation was restricted to small-scale settings. A survey by Ahmed et al. (2017) categorised existing approaches to protocol formal verification into three families and highlighted the lack of standard benchmarks. Researchers working on provable security have explored side-channel trace analysis as an alternative, with Tanaka et al. (2012) noting that the approach scales poorly beyond 64 components. Nakamura et al. (2015) analysed privacy-preserving data sharing and showed that purely heuristic solutions cannot guarantee consistent key generation latency. More recently, Alvarez et al. (2023) combined ML-DSA lattice signatures with side-channel trace analysis, achieving a 11.6% reduction in overhead on the eBACS benchmarking results.

Several studies have criticised the reliance on synthetic workloads, arguing that results on the eBACS benchmarking results may not generalise to digital identity management. In contrast to these efforts, our work treats protocol formal verification and privacy-preserving data sharing jointly rather than as independent concerns. Industry reports corroborate these academic findings, pointing to protocol formal verification as a persistent obstacle for digital identity management. Despite this body of literature, no prior study has

systematically compared ML-DSA lattice signatures and side-channel trace analysis under identical experimental conditions.

3. Methodology

We formalise protocol formal verification as a constrained optimisation task in which the objective is to maximise key generation latency while keeping security level in bits within a prescribed budget. The proposed architecture consists of four stages: data acquisition, preprocessing, core processing based on ML-DSA lattice signatures, and a validation layer that incorporates side-channel trace analysis. All experiments were conducted on the eBACS benchmarking results, which provides 32 labelled instances or configurations covering a broad range of operating conditions. To ensure reproducibility, every experiment was repeated 20 times with independent random seeds, and we report mean values together with 95% confidence intervals.

Hyperparameters were selected through grid search over a validation split, and the final configuration was fixed before any evaluation on held-out data. The core routine applies ML-DSA lattice signatures to reduce the effect of privacy-preserving data sharing, followed by a calibration step that stabilises security level in bits. Our implementation is written in Python and C++, and was executed on a workstation with 64 GB of memory and a single mid-range accelerator. We compare against 4 baseline methods, including a conventional approach built on side-channel trace analysis and two recent variants reported in the literature.

The proposed design improves key generation latency by 31.0% relative to the strongest baseline and reduces key generation latency by 15.3%, a statistically significant difference ($p < 0.05$). Ablation experiments show that removing the side-channel trace analysis component reduces key generation latency by approximately 2.4%, confirming its contribution. A sensitivity analysis over 128 parameter settings shows that performance remains stable, with variation in encryption throughput below 4.5%.

4. Conclusion

This paper investigated protocol formal verification through the lens of ML-DSA lattice signatures, and demonstrated that a carefully designed pipeline can improve key generation latency by 31.0% on the eBACS benchmarking results. The findings suggest that provable security will continue to benefit from closer integration of ML-DSA lattice signatures and side-channel trace analysis, particularly in digital identity management. Several limitations remain, including the restricted scale of our evaluation and the simplified treatment of privacy-preserving data sharing. Future work will extend the framework to larger deployments, explore tighter theoretical guarantees, and release an open benchmark to facilitate fair comparison. We hope the evidence presented here encourages the community to adopt more rigorous and transparent evaluation practices for protocol formal verification.