# Title: A Comparative Study of Energy-harvesting Sensor Nodes for Smart Grid Monitoring

**Year:** 2021

**Authors:** Y. Iyer, J. Rossi (Institute of Data and Intelligent Systems, Summit College)

**Keywords:** digital twins, LoRaWAN, cyber-physical systems, low-power networks, TinyML

## Abstract:

Battery lifetime extension remains a critical challenge for wireless sensor networks, particularly in smart grid monitoring. This paper proposes a framework built on energy-harvesting sensor nodes that explicitly accounts for sensor data aggregation. We evaluate the framework on the Intel Berkeley Research Lab sensor data and compare it against 6 baseline methods. Experimental results show that the proposed approach improves detection rate by 13.3% while keeping packet delivery ratio within acceptable bounds. We further analyse its limitations and discuss implications for practical deployment.

## 1. Introduction

The rapid maturation of wireless sensor networks has changed how researchers and practitioners approach battery lifetime extension, yet practical deployment is still limited by scalability, cost, and reproducibility concerns. Despite considerable progress, existing solutions for battery lifetime extension tend to degrade when moving from controlled laboratory conditions to production workloads, which motivates a more systematic investigation. A central difficulty is that improvements in detection rate frequently come at the expense of end-to-end delay, forcing designers to accept trade-offs that are poorly understood. This paper addresses these gaps by studying how energy-harvesting sensor nodes interact with edge computing nodes when applied to battery lifetime extension.

Our work is motivated by the growing demand for smart grid monitoring, where reliability and transparency requirements are especially strict. We make three contributions: a unified formulation of battery lifetime extension, a practical design built on energy-harvesting sensor nodes, and an empirical evaluation on the Intel Berkeley Research Lab sensor data. Understanding sensor data aggregation is equally important, because it shapes both the theoretical limits and the operational cost of any proposed approach. The remainder of this paper reviews related work, describes the proposed methodology, and concludes with a discussion of limitations and directions for future research.

## 2. Related Work

Nakamura et al. (2015) introduced an early framework based on energy-harvesting sensor nodes, reporting a 40.4% improvement in detection rate over previous baselines. Subsequent work by Nakamura et al. (2009) extended this line of research to smart grid monitoring, although the evaluation was restricted to small-scale settings. A survey by Mukherjee et al. (2008) categorised existing approaches to battery lifetime extension into three families and highlighted the lack of standard benchmarks. Müller et al. (2014) analysed sensor data aggregation and showed that purely heuristic solutions cannot guarantee consistent detection rate. More recently, Fernandez et al. (2009) combined energy-harvesting sensor nodes with edge computing nodes, achieving a 13.3% reduction in overhead on the Intel Berkeley Research Lab sensor data.

Several studies have criticised the reliance on synthetic workloads, arguing that results on the Intel Berkeley Research Lab sensor data may not generalise to smart grid monitoring. In contrast to these efforts, our work treats battery lifetime extension and sensor data aggregation jointly rather than as independent concerns. Industry reports corroborate these academic findings, pointing to battery lifetime extension as a persistent obstacle for smart grid monitoring. Despite this body of literature, no prior study has systematically compared

energy-harvesting sensor nodes and edge computing nodes under identical experimental conditions.

## 3. Methodology

We formalise battery lifetime extension as a constrained optimisation task in which the objective is to maximise detection rate while keeping energy per transmitted bit within a prescribed budget. All experiments were conducted on the Intel Berkeley Research Lab sensor data, which provides 16 labelled instances or configurations covering a broad range of operating conditions. To ensure reproducibility, every experiment was repeated 10 times with independent random seeds, and we report mean values together with 95% confidence intervals. Hyperparameters were selected through grid search over a validation split, and the final configuration was fixed before any evaluation on held-out data.

The core routine applies energy-harvesting sensor nodes to reduce the effect of sensor data aggregation, followed by a calibration step that stabilises detection rate. Our implementation is written in Python and C++, and was executed on a workstation with 64 GB of memory and a single mid-range accelerator. We compare against 6 baseline methods, including a conventional approach built on edge computing nodes and two recent variants reported in the literature. The proposed design improves detection rate by 13.3% relative to the strongest baseline and reduces detection rate by 33.8%, a statistically significant difference ($p < 0.05$).

Ablation experiments show that removing the edge computing nodes component reduces detection rate by approximately 13.0%, confirming its contribution. A sensitivity analysis over 128 parameter settings shows that performance remains stable, with variation in energy per transmitted bit below 11.0%. Threats to validity include the limited diversity of the Intel Berkeley Research Lab sensor data and the possibility that deployment in smart grid monitoring introduces conditions not captured in our setup.

## 4. Conclusion

This paper investigated battery lifetime extension through the lens of energy-harvesting sensor nodes, and demonstrated that a carefully designed pipeline can improve detection rate by 13.3% on the Intel Berkeley Research Lab sensor data. The findings suggest that wireless sensor networks will continue to benefit from closer integration of energy-harvesting sensor nodes and edge computing nodes, particularly in smart grid monitoring. Several limitations remain, including the restricted scale of our evaluation and the simplified treatment of sensor data aggregation. Future work will extend the framework to larger deployments, explore tighter theoretical guarantees, and release an open benchmark to facilitate fair comparison. We hope the evidence presented here encourages the community to adopt more rigorous and transparent evaluation practices for battery lifetime extension.