



# UNIX SYSTEM PROGRAMMING

## File I/O

---

**Chandravva Hebbi**  
**Department of Computer Science and Engineering**  
**[chandravvahebbs@pes.edu](mailto:chandravvahebbs@pes.edu)**

# UNIX SYSTEM PROGRAMMING



## File I/O

---

**Chandravva Hebbi**

Department of Computer Science and Engineering

# UNIX SYSTEM PROGRAMMING

## Topics to be Covered

---

❖ System calls

❖ Kernel Data structures




# UNIX SYSTEM PROGRAMMING

## Library and System calls



- The functions which are a part of standard C library are known as **Library functions**.
- The functions which change the execution mode of the program from user mode to kernel mode are known as **system calls**.
- The system calls are required when the user programs need services from the OS.



# UNIX SYSTEM PROGRAMMING

system calls

---



## Why System Calls

- System calls acts as entry point to OS kernel.
- There are certain tasks that can only be done if a process is running in kernel mode.
- Examples of these tasks can be interacting with hardware etc.

## Types of Library Functions.

- Functions which do not call any system call.
- Functions that make a system call

# UNIX SYSTEM PROGRAMMING

## System Calls

---



There are 5 basic system calls that Unix provides for file I/O.

1. `int open(char *path, int flags [ , int mode ] );`
2. `int close(int fd);`
3. `int read(int fd, char *buf, int size);`
4. `int write(int fd, char *buf, int size);`
5. `off_t lseek(int fd, off_t offset, int whence);`

# UNIX SYSTEM PROGRAMMING

## Open Calls

---



```
int open(char *path, int flags [ , int mode ] );
```

Open makes a request to the operating system to use a file.

- ❖ 'path' argument specifies what file you would like to use
- ❖ 'flags' and 'mode' arguments specify how you would like to use the file.
- ❖ Return: File descriptor, -1.

# UNIX SYSTEM PROGRAMMING

## Open Call

---



`open(filename, flags, mode)`

Returns lowest numbered available file descriptor

Filename

Flags for mode of access

`O_RDONLY`

`O_WRONLY`

`O_RDWR`

### **Other flags**

`O_CREAT` - Mode to be specified if file is to be created

`O_APPEND`

`O_TRUNC`

`O_EXCL`

`O_NONBLOCK, O_DSYNC, O_RSYNC, O_SYNC`



# UNIX SYSTEM PROGRAMMING

## The creat() system call

---



### **creat(pathname,mode)**

Returns the file descriptor opened for write-only

Returns -1 on error

Equivalent to :-

**open(pathname,O\_WRONLY|O\_CREAT|O\_TRUNC,mode)**

File is opened only for writing

Before new version of open, to write and read,  
had to call creat, then open.

Better way :-

**open(pathname,O\_RDWR|O\_CREAT|O\_TRUNC,mode)**

# UNIX SYSTEM PROGRAMMING

The close() system call

---

## **close(filedes)**

Returns 0 if OK, -1 on error

Closing releases any record locks that process may have on the file

When process terminates, all of its open files are closed automatically by the kernel.



# UNIX SYSTEM PROGRAMMING

The read() and Write system calls

---

Different from fread() and fwrite()

Uses fd returned from open() call

Take three arguments, fd, Buffer to be read into or written from  
Count.



# UNIX SYSTEM PROGRAMMING

## lseek() system call

---

Used to position the file pointer randomly  
Next I/O proceeds from that point onwards  
lseek(fd, offset, origin)  
Origin  
0 - beginning of file  
1 – current position  
2 – end of file  
SEEK\_SET, SEEK\_CUR, SEEK\_END



**THANK YOU**

---

**Chandravva Hebbi**

Department of Computer Science and Engineering