OPERATING SYSTEM

Inter-Process Communication

Dr Rahul Nagpal
Computer Science

OPERATING SYSTEM

Inter-Process Communication

Dr. Rahul Nagpal
Computer Science

- Processes within a system may be ***independent*** or ***cooperating***
- Cooperating process can affect or be affected by other processes, including sharing data
- Reasons for cooperating processes:
  - Information sharing
  - Computation speedup
  - Modularity
  - Convenience
- Cooperating processes need **inter-process communication** (**IPC**)
- Two models of IPC
  - **Shared memory**
  - **Message passing**

OPERATING SYSTEMS - IPC

Communications Models

(a) Message passing. (b) shared memory.



Cooperating Processes

- Processes within a system may be ***independent*** or ***cooperating***
- Cooperating process can affect or be affected by other processes, including sharing data
- Reasons for cooperating processes:
    - Information sharing
    - Computation speedup
    - Modularity
    - Convenience

Producer-Consumer Problem

- Paradigm for cooperating processes, *producer* process produces information that is consumed by a *consumer* process
  - **unbounded-buffer** places no practical limit on the size of the buffer
  - **bounded-buffer** assumes that there is a fixed buffer size

Bounded-Buffer – Shared-Memory Solution

- Shared data

```
#define BUFFER_SIZE 10
typedef struct {
  . . .
} item;

item buffer[BUFFER_SIZE];
int in = 0;
int out = 0;
```

- Solution is correct, but can only use BUFFER_SIZE-1 elements

Bounded-Buffer – Producer & Consumer

```
item next_produced;
while (true) {
      /* produce an item in next produced */
      while (((in + 1) % BUFFER_SIZE) == out)
            ; /* do nothing */
      buffer[in] = next_produced;
      in = (in + 1) % BUFFER_SIZE;
}

item next_consumed;
while (true) {
      while (in == out)
            ; /* do nothing */
      next_consumed = buffer[out];
      out = (out + 1) % BUFFER_SIZE;

      /* consume the item in next consumed */
}
```

- An area of memory shared among the processes that wish to communicate
- The communication is under the control of the users processes not the operating system.
- Major issues is to provide mechanism that will allow the user processes to synchronize their actions when they access shared memory.
- Synchronization is discussed in great details in Chapter 5

Inter-process Communication – Message Passing

- Mechanism for processes to communicate and to synchronize their actions

- Message system – processes communicate with each other without resorting to shared variables

- IPC facility provides two operations:
  - **`send`**(*message*)
  - **`receive`**(*message*)

- The *message* size is either fixed or variable

Message Passing (Cont.)

If processes *P* and *Q* wish to communicate, they need to:

- Establish a ***communication link*** between them
- Exchange messages via send/receive

Implementation issues:

- How are links established?
- Can a link be associated with more than two processes?
- How many links can there be between every pair of communicating processes?
- What is the capacity of a link?
- Is the size of a message that the link can accommodate fixed or variable?
- Is a link unidirectional or bi-directional?

Message Passing (Cont.)

- Implementation of communication link
  - Physical:
    - Shared memory
    - Hardware bus
    - Network
  - Logical:
    - Direct or indirect
    - Synchronous or asynchronous
    - Automatic or explicit buffering

Direct Communication

- Processes must name each other explicitly:
  - **`send`** (*P, message*) – send a message to process P
  - **`receive`**(*Q, message*) – receive a message from process Q

- Properties of communication link
  - Links are established automatically
  - A link is associated with exactly one pair of communicating processes
  - Between each pair there exists exactly one link
  - The link may be unidirectional, but is usually bi-directional

Indirect Communication

- Messages are directed and received from mailboxes (also referred to as ports)
  - Each mailbox has a unique id
  - Processes can communicate only if they share a mailbox

- Properties of communication link
  - Link established only if processes share a common mailbox
  - A link may be associated with many processes
  - Each pair of processes may share several communication links
  - Link may be unidirectional or bi-directional

Indirect Communication

- Messages are directed and received from mailboxes (also referred to as ports)
  - Each mailbox has a unique id
  - Processes can communicate only if they share a mailbox

- Properties of communication link
  - Link established only if processes share a common mailbox
  - A link may be associated with many processes
  - Each pair of processes may share several communication links
  - Link may be unidirectional or bi-directional

Indirect Communication

- Operations
  - create a new mailbox (port)
  - send and receive messages through mailbox
  - destroy a mailbox

- Primitives are defined as:

  `send`(*A, message*) – send a message to mailbox A

  `receive`(*A, message*) – receive a message from mailbox A

Indirect Communication

- Mailbox sharing
  - P_1, P_2, and P_3 share mailbox A
  - P_1, sends; P_2 and P_3 receive
  - Who gets the message?

- Solutions
  - Allow a link to be associated with at most two processes
  - Allow only one process at a time to execute a receive operation
  - Allow the system to select arbitrarily the receiver. Sender is notified who the receiver was

- Message passing may be either blocking or non-blocking
- **Blocking** is considered **synchronous**
  - **Blocking send** -- the sender is blocked until the message is received
  - **Blocking receive** -- the receiver is blocked until a message is available
- **Non-blocking** is considered **asynchronous**
  - **Non-blocking send** -- the sender sends the message and continue
  - **Non-blocking receive** -- the receiver receives:
    - A valid message, or Null message
  - Different combinations possible
  - If both send and receive are blocking, we have a **rendezvous**

Producer-consumer becomes trivial

```
 message next_produced;
        while (true) {
            /* produce an item in next
produced */
        send(next_produced);
        }
```

```
message next_consumed;
while (true) {
   receive(next_consumed);

   /* consume the item in next consumed */
}
```

Buffering

- Queue of messages attached to the link.

- implemented in one of three ways
  - Zero capacity – no messages are queued on a link.
    Sender must wait for receiver (rendezvous)
  - Bounded capacity – finite length of *n* messages
    Sender must wait if link full
  - Unbounded capacity – infinite length
    Sender never waits

Pipes

- Acts as a conduit allowing two processes to communicate
- Issues:
  - Is communication unidirectional or bidirectional?
  - In the case of two-way communication, is it half or full-duplex?
  - Must there exist a relationship (i.e., ***parent-child***) between the communicating processes?
  - Can the pipes be used over a network?
- Ordinary pipes – cannot be accessed from outside the process that created it. Typically, a parent process creates a pipe and uses it to communicate with a child process that it created.
- Named pipes – can be accessed without a parent-child relationship

Ordinary Pipes

- Ordinary Pipes allow communication in standard producer-consumer style
- Producer writes to one end (the **write-end** of the pipe)
- Consumer reads from the other end (the **read-end** of the pipe)
- Ordinary pipes are therefore unidirectional
- Require parent-child relationship between communicating processes



- Windows calls these **anonymous pipes**
- See Unix and Windows code samples in textbook

Named Pipes

- Named Pipes are more powerful than ordinary pipes
- Communication is bidirectional
- No parent-child relationship is necessary between the communicating processes
- Several processes can use the named pipe for communication
- Provided on both UNIX and Windows systems

THANK YOU

Dr Rahul Nagpal

Computer Science

rahulnagpal@pes.edu