



MACHINE INTELLIGENCE

Dr. N MEHALA

Department of Computer Science and Engineering

MACHINE INTELLIGENCE

Module 4 [Unsupervised Learning]

Dr. N MEHALA

Department of Computer Science and Engineering


MACHINE INTELLIGENCE

Supervised Vs Unsupervised Learning




MACHINE INTELLIGENCE

Supervised Learning



We train our model using the independent variables in the supervision of the target variable and hence the name supervised learning.



Independent
Variables




Dependent
Variable


- There might be situations when we do not have any target variable to predict.
- Such problems, without any explicit target variable, are known as unsupervised learning problems.
- We only have the independent variables and no target/dependent variable in these problems.

MACHINE INTELLIGENCE

UnSupervised Learning



- Divide the entire data (X) into a set of groups. These groups are known as clusters and the process of making these clusters is known as **clustering**.



Why Supervised Learning?


- Supervised learning allows you to collect data or produce a data output from the previous experience.
- Helps you to optimize performance criteria using experience
- Supervised machine learning helps you to solve various types of real-world computation problems.

MACHINE INTELLIGENCE

Supervised Vs Unsupervised Learning



Finding groups of objects such that the objects in a group will be similar (or related) to one another and different from (or unrelated to) the objects in other groups






MACHINE INTELLIGENCE

Clustering: Example Applications





- Marketing
- Insurance
- City-planning
- Earth-quake studies






Original Points



A Partitional Clustering


MACHINE INTELLIGENCE

Hierarchical Clustering




MACHINE INTELLIGENCE


Hierarchical Clustering




Traditional Hierarchical Clustering



Traditional Dendrogram





Non-traditional Hierarchical Clustering




Non-traditional Dendrogram

- Produces a set of nested clusters organized as a hierarchical tree
- Can be visualized as a dendrogram
 - A tree like diagram that records the sequences of merges or splits




- Do not have to assume any particular number of clusters
 - Any desired number of clusters can be obtained by 'cutting' the dendrogram at the proper level



- Popular hierarchical clustering technique
- Basic algorithm is straightforward
 1. Compute the proximity matrix
 2. Let each data point be a cluster
 3. **Repeat**
 4. Merge the two closest clusters
 5. Update the proximity matrix
 6. **Until** only a single cluster remains
- Key operation is the computation of the proximity of two clusters
 - Different approaches to defining the distance between clusters distinguish the different algorithms

- Start with clusters of individual points and a proximity matrix




	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						
.						
.						

Proximity Matrix




- After some merging steps, we have some clusters



	C1	C2	C3	C4	C5
C1					
C2					
C3					
C4					
C5					


Proximity Matrix




- We want to merge the two closest clusters (C2 and C5) and update the proximity matrix.


	C1	C2	C3	C4	C5
C1					
C2					
C3					
C4					
C5					

Proximity Matrix



- The question is “How do we update the proximity matrix?”






- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error

	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						


. Proximity Matrix

.




. Proximity Matrix .

- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error



- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error

. Proximity Matrix .




	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						

Proximity Matrix

$$\text{proximity}(\text{Cluster}_i, \text{Cluster}_j) = \frac{\sum_{\substack{p_i \in \text{Cluster}_i \\ p_j \in \text{Cluster}_j}} \text{proximity}(p_i, p_j)}{|\text{Cluster}_i| * |\text{Cluster}_j|}$$

- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function
 - Ward's Method uses squared error



- MIN
- MAX
- Group Average
- Distance Between Centroids
- Other methods driven by an objective function

	p1	p2	p3	p4	p5	...
p1						
p2						
p3						
p4						
p5						
.						

. Proximity Matrix

.

assume that there are two clusters: $C_1: \{a, b\}$ and $C_2: \{c, d, e\}$.

	a	b	c	d	e
Feature	1	2	4	5	6

1. Calculate the distance matrix . 2. Calculate three cluster distances between C_1 and C_2 .

Single link

$$\begin{aligned} \text{dist}(C_1, C_2) &= \min\{d(a, c), d(a, d), d(a, e), d(b, c), d(b, d), d(b, e)\} \\ &= \min\{3, 4, 5, 2, 3, 4\} = 2 \end{aligned}$$

Complete link

$$\begin{aligned} \text{dist}(C_1, C_2) &= \max\{d(a, c), d(a, d), d(a, e), d(b, c), d(b, d), d(b, e)\} \\ &= \max\{3, 4, 5, 2, 3, 4\} = 5 \end{aligned}$$

Average

$$\begin{aligned} \text{dist}(C_1, C_2) &= \frac{d(a, c) + d(a, d) + d(a, e) + d(b, c) + d(b, d) + d(b, e)}{6} \\ &= \frac{3 + 4 + 5 + 2 + 3 + 4}{6} = \frac{21}{6} = 3.5 \end{aligned}$$

	a	b	c	d	e
a	0	1	3	4	5
b	1	0	2	3	4
c	3	2	0	1	2
d	4	3	1	0	1
e	5	4	2	1	0



MACHINE INTELLIGENCE

Dr. N MEHALA

Department of Computer Science and Engineering

MACHINE INTELLIGENCE

Module 4 [Unsupervised Learning]

Dr. N MEHALA


Department of Computer Science and Engineering

MACHINE INTELLIGENCE

Example1: Hierarchical Clustering



- Problem: clustering analysis with agglomerative algorithm



data matrix

	X1	X2
A	1	1
B	1.5	1.5
C	5	5
D	3	4
E	4	4
F	3	3.5

distance matrix

Dist	A	B	C	D	E	F
A	0.00	0.71	5.66	3.61	4.24	3.20
B	0.71	0.00	4.95	2.92	3.54	2.50
C	5.66	4.95	0.00	2.24	1.41	2.50
D	3.61	2.92	2.24	0.00	1.00	0.50
E	4.24	3.54	1.41	1.00	0.00	1.12
F	3.20	2.50	2.50	0.50	1.12	0.00

$$d_{AB} = \left((1-1.5)^2 + (1-1.5)^2 \right)^{\frac{1}{2}} = \sqrt{\frac{1}{2}} = 0.7071$$


$$d_{DF} = \left((3-3)^2 + (4-3.5)^2 \right)^{\frac{1}{2}} = 0.5$$

Euclidean distance

MACHINE INTELLIGENCE

Example1: Hierarchical Clustering

- Merge two closest clusters (iteration 1)



Dist	A	B	C	D	E	F
A	0.00	0.71	5.66	3.61	4.24	3.20
B	0.71	0.00	4.95	2.92	3.54	2.50
C	5.66	4.95	0.00	2.24	1.41	2.50
D	3.61	2.92	2.24	0.00	1.00	0.50
E	4.24	3.54	1.41	1.00	0.00	1.12
F	3.20	2.50	2.50	0.50	1.12	0.00

Dist	A	B	C	D, F	E
A	0.00	0.71	5.66	?	4.24
B	0.71	0.00	4.95	4.95	3.54
C	5.66	4.95	0.00	?	1.41
D, F	?	?	?	0.00	?
E	4.24	3.54	1.41	?	0.00

- Update distance matrix (iteration 1)

Dist	A	B	C	D	E	F
A	0.00	0.71	5.66	3.61	4.24	3.20
B	0.71	0.00	4.95	2.92	3.54	2.50
C	5.66	4.95	0.00	2.24	1.41	2.50
D	3.61	2.92	2.24	0.00	1.00	0.50
E	4.24	3.54	1.41	1.00	0.00	1.12
F	3.20	2.50	2.50	0.50	1.12	0.00

$$d_{(D,F) \rightarrow A} = \min(d_{DA}, d_{FA}) = \min(3.61, 3.20) = 3.20$$

$$d_{(D,F) \rightarrow B} = \min(d_{DB}, d_{FB}) = \min(2.92, 2.50) = 2.50$$

$$d_{(D,F) \rightarrow C} = \min(d_{DC}, d_{FC}) = \min(2.24, 2.50) = 2.24$$

$$d_{E \rightarrow (D,F)} = \min(d_{ED}, d_{EF}) = \min(1.00, 1.12) = 1.00$$

Dist	A	B	C	D, F	E
A	0.00	0.71	5.66	?	4.24
B	0.71	0.00	4.95	?	3.54
C	5.66	4.95	0.00	?	1.41
D, F	?	?	?	0.00	?
E	4.24	3.54	1.41	?	0.00


Min Distance (Single Linkage)



Dist	A	B	C	D, F	E
A	0.00	0.71	5.66	3.20	4.24
B	0.71	0.00	4.95	2.50	3.54
C	5.66	4.95	0.00	2.24	1.41
D, F	3.20	2.50	2.24	0.00	1.00
E	4.24	3.54	1.41	1.00	0.00

- Merge two closest clusters (iteration 2)

Min Distance (Single Linkage)



Dist	A	B	C	D, F	E
A	0.00	0.71	5.66	3.20	4.24
B	0.71	0.00	4.95	2.50	3.54
C	5.66	4.95	0.00	2.24	1.41
D, F	3.20	2.50	2.24	0.00	1.00
E	4.24	3.54	1.41	1.00	0.00

Dist	A,B	C	(D, F)	E
A,B	0	?	?	?
C	?	0	2.24	1.41
(D, F)	?	2.24	0	1.00
E	?	1.41	1.00	0

Example1: Hierarchical Clustering

- Update distance matrix (iteration 2)

Min Distance (Single Linkage)

Dist	A	B	C	D, F	E
A	0.00	0.71	5.66	3.20	4.24
B	0.71	0.00	4.95	2.50	3.54
C	5.66	4.95	0.00	2.24	1.41
D, F	3.20	2.50	2.24	0.00	1.00
E	4.24	3.54	1.41	1.00	0.00

$d_{C \rightarrow \{A,B\}} = \min(d_{CA}, d_{CB}) = \min(5.66, 4.95) = 4.95$
 $d_{\{D,F\} \rightarrow \{A,B\}} = \min(d_{DA}, d_{DB}, d_{FA}, d_{FB})$
 $= \min(3.61, 2.92, 3.20, 2.50) = 2.50$
 $d_{E \rightarrow \{A,B\}} = \min(d_{EA}, d_{EB}) = \min(4.24, 3.54) = 3.54$


Dist	A,B	C	(D, F)	E
A,B	0	?	?	?
C	?	0	2.24	1.41
(D, F)	?	2.24	0	1.00
E	?	1.41	1.00	0

→

Dist	A,B	C	(D, F)	E
A,B	0	4.95	2.50	3.54
C	4.95	0	2.24	1.41
(D, F)	2.50	2.24	0	1.00
E	3.54	1.41	1.00	0

Example1: Hierarchical Clustering

- Merge two closest clusters/update distance matrix (iteration 3)



Min Distance (Single Linkage)


Dist	A,B	C	(D, F)	E
A,B	0	4.95	2.50	3.54
C	4.95	0	2.24	1.41
(D, F)	2.50	2.24	0	1.00
E	3.54	1.41	1.00	0

Min Distance (Single Linkage)

Dist	(A,B)	C	(D, F), E
(A,B)	0.00	4.95	2.50
C	4.95	0.00	1.41
(D, F), E	2.50	1.41	0.00

Example1: Hierarchical Clustering

- Merge two closest clusters/update distance matrix (iteration 4)



Min Distance (Single Linkage)

Dist	(A,B)	C	(D, F), E
(A,B)	0.00	4.95	2.50
C	4.95	0.00	1.41
(D, F), E	2.50	1.41	0.00


Min Distance (Single Linkage)

Dist	(A,B)	((D, F), E),C
(A,B)	0.00	2.50
((D, F), E),C	2.50	0.00

MACHINE INTELLIGENCE

Example1: Hierarchical Clustering

- Final result (meeting termination condition)



- $O(N^2)$ space since it uses the proximity matrix.
 - N is the number of points.
- $O(N^3)$ time in many cases
 - There are N steps and at each step the size, N^2 , proximity matrix must be updated and searched
 - Complexity can be reduced to $O(N^2 \log(N))$ time for some approaches

- Once a decision is made to combine two clusters, it cannot be undone
- Different schemes have problems with one or more of the following:
 - Sensitivity to noise and outliers
 - Difficulty handling different sized clusters and convex shapes
 - Breaking large clusters

- Supervised Vs Unsupervised Learning
- Clustering
- Clustering Types
- Partitional Vs Hierarchical Clustering
- Agglomerative Vs Divisive Clustering
- Agglomerative Hierarchical Clustering: Variants
- Example: Agglomerative Hierarchical Clustering Variants

MACHINE INTELLIGENCE

Resources

- [http://www2.ift.ulaval.ca/~chaib/IFT-4102-7025/public_html/Fichiers/Machine Learning in Action.pdf](http://www2.ift.ulaval.ca/~chaib/IFT-4102-7025/public_html/Fichiers/Machine_Learning_in_Action.pdf)
- <http://wwwusers.cs.umn.edu/~kumar/dmbook/>.
- <ftp://ftp.aw.com/cseng/authors/tan>
- <http://web.ccsu.edu/datamining/resources.html>



THANK YOU

Dr. N MEHALA

Department of Computer Science and Engineering

mehala@pes.edu