Agent-Chronos: Hardware-Clock Speculative Transport Pacing and Causal Fencing for Cross-Cloud Multi-Agent Swarms

Aniket Agrawal
Google Cloud AI Architecture & Engineering
Google LLC
Bengaluru, India
aniketagrawal@google.com

***Abstract*—As enterprise deployments of autonomous agent swarms transition from single-tenant sandbox prototypes to heterogeneous multi-cloud topologies spanning Google Cloud Vertex AI, SAP S/4HANA, Salesforce Agentforce, and AWS Bedrock over Agent2Agent (A2A) and the Model Context Protocol (MCP), distributed consistency across external tool invocations degrades severely. Because Large Language Model (LLM) reasoning durations vary stochastically (200 ms to $5{,}000$ ms) and wide-area network (WAN) transit jitter (± 10 ms to 60 ms) reorders packets in flight, multi-agent systems exhibit high rates of causal inversion (19.50%) and phantom tool mutations (14.80%) when upstream speculative reasoning branches abort after downstream mutating actions have already been dispatched. Traditional distributed database locks (Two-Phase Commit, XA) cannot be held across third-party REST and gRPC endpoints, while post-hoc compensating sagas fail when external side-effects are irreversible. We present Agent-Chronos, a hardware-anchored L7 transport fencing and speculative pacing protocol that guarantees strict client-side egress linearizability and end-to-end causal delivery across Chronos-enabled multi-agent gateways without distributed database locks. Agent-Chronos: (1) embeds physical TrueTime atomic/GPS clock uncertainty tuples $\langle t_{\text{earliest}}, t_{\text{latest}}, \epsilon_u \rangle$, swarm-wide causal vectors $\mathcal{V}$, and per-destination sequence coordinates Seq_{dest} directly into HTTP/2 framing; (2) implements a two-phase user-space L7 egress pacer (prior to HPACK compression and TLS encryption) that stages speculative mutations during upstream verification (Δ_{stage}) and enforces a post-settlement TrueTime commit-wait barrier ($\Delta_{\text{wait}} = \max(0, t^*_{E,\text{latest}} + \Delta_{\text{abort_prop}} - t_{\text{now,earliest}})$) before wire release; (3) enforces an ingress causal hold barrier at receiving sidecars to neutralize WAN transit jitter while permitting dependency-free read-only queries to bypass pacing with 0.00 ms delay; and (4) provides pre-wire speculative revocation that purges aborted frames in user-space gateway queues so zero mutating payload bytes reach downstream endpoints. Across $N = 1{,}000$ multi-agent transactions per seed (5 seeds, $5{,}000$ total transaction runs per baseline) in an emulated cross-cloud testbed, Agent-Chronos reduced phantom mutations and causal inversions to 0.00%, bounding post-settlement TrueTime commit-wait pacing overhead to a mean of 5.91 ms ($p_{50} = 5.80$ ms, $p_{95} = 9.62$ ms, $p_{99} = 11.84$ ms) while achieving a net end-to-end speculative speedup of 486.8 ms (42.6%) per transaction over non-speculative sequential execution. All protocol transitions are verifiable via deterministic HTTP/2 headers and audit trailers, providing end-to-end cross-organization protocol observability.**

***Index Terms*—Multi-Agent Systems, TrueTime, Causal Consistency, Transport Pacing, Linearizability, Speculative Execution, Model Context Protocol, Distributed Systems.**

I. Introduction

Autonomous multi-agent systems have emerged as a primary architectural paradigm for enterprise generative AI orchestration. Modern enterprise workflows coordinate swarms of specialized agents executing complex multi-turn objectives—such as reconciling financial ledgers, assessing procurement risk, and updating Enterprise Resource Planning (ERP) records across heterogeneous cloud boundaries [2], [3], [15].

However, as agent swarms expand across organizational and cloud boundaries, a critical distributed systems failure mode arises: **Speculative Causal Inversion and Phantom Tool Mutations**. To hide multi-second LLM generation latencies, modern agentic serving runtimes speculatively synthesize and stage downstream tool calls in parallel with upstream policy verification and sibling reasoning branches [10], [13], [14], [16]–[18]. Unlike deterministic microservices whose execution latency is tightly bounded, LLM reasoning and guardrail verification turns vary stochastically from 200 ms to over $5{,}000$ ms. Concurrently, regional WAN jitter across public interconnects (± 10 ms to 60 ms) reorders packets in flight. When a downstream agent dispatches an irreversible external mutation (e.g., executing an electronic funds transfer or releasing an ERP inventory hold) before an upstream speculative epoch settles—or when clock skew ($\pm \epsilon_u$) across distributed verification nodes causes an upstream abort signal and a downstream commit candidate to cross in flight—any subsequent upstream policy abort leaves a *phantom mutation* on the destination system of record.

Existing distributed transaction and coordination primitives do not fully resolve this boundary gap:

1) **Classical Distributed Locks, Agentic Sagas, and Logical Pre-Commit Staging:** Two-Phase Commit (2PC) and XA locks cannot be held across stateless third-party SaaS REST/gRPC APIs (e.g., Stripe, SAP NetWeaver, or Salesforce). Classical compensating sagas [4], multi-agent workflow validation coordinators such as SagaLLM [14] and ALAS [19], and post-facto undo runtimes such as GoEX [13] operate at the application orchestration layer without hardware-clock transport fencing. Similarly, recent speculative and transactional agent runtimes—including Speculative Actions [16], Sherlock [17], and Atomix [18]—overlap

verification with logical pre-commit staging and read-only bypass inside a single centralized orchestrator. However, when such logical pre-commit staging designs are deployed across *decentralized cross-node verification topologies* (modeled by our *Chronos Vector-Only Ablation* in Section IV), logical staging alone—without a hardware-anchored $2\epsilon_{\text{eff}}$ commit-wait barrier—leaks phantom mutations (2.90% in Table I) when distributed cross-node verification aborts race within the physical clock-skew window and incurs destination causal inversions (3.40%) across concurrent sibling branches ($\mathcal{V}_1 \parallel \mathcal{V}_2$).

2) **OS Speculative Buffering and NIC Pacers:** Operating-system speculative execution frameworks such as Speculator [10] buffer uncommitted kernel outputs inside a single OS domain, while end-host traffic shapers such as SENIC [12] and Carousel [11] pace NIC packet departure rates for bandwidth shaping. However, raw kernel TCP socket buffering (`sk_buff`) cannot selectively excise individual aborted tool frames multiplexed over a shared HTTP/2-over-TLS (`h2`) connection without corrupting stateful HPACK header tables, TLS 1.3 AEAD record sequence numbers, and TCP byte-stream sequence offsets.
3) **Logical and Hybrid Clocks Under Commodity NTP Skew:** Classical Lamport timestamps [5], Fidge/Mattern vector clocks [6], [7], and $\mathcal{O}(1)$-space Hybrid Logical Clocks (HLCs) [8] track message-passing causality, but under commodity NTP synchronization ($\epsilon_{\text{NTP}} \approx$ 25–100 ms) they incur wide physical uncertainty windows when enforcing real-time commit-wait barriers across independent gateways, while scalar HLCs cannot distinguish concurrent sibling branch forks without explicit per-agent vector coordinates.

To address these challenges, we introduce **Agent-Chronos**, an L7 transport fencing protocol that bridges hardware-anchored TrueTime uncertainty intervals [1] with modern agentic protocols (MCP [2] via FastMCP gateways and A2A [3]). Rather than claiming database-internal strict serializability over unmodified third-party storage engines that lack two-phase locking or Paxos consensus, Agent-Chronos formalizes and enforces **strict client-side egress linearizability** [9] (guaranteeing that no speculative mutation departs the egress gateway until its upstream epoch has deterministically settled and its physical TrueTime uncertainty and abort-propagation window has elapsed) together with **end-to-end causal delivery** across Chronos-enabled ingress sidecars (e.g., fronting enterprise SAP S/4HANA gateways). When invoking unmodified external third-party SaaS endpoints (such as Stripe) that cannot host an ingress sidecar, the sender-side gateway suppresses tombstone sequence ACKs, coordinates concurrent sibling writes via a shared logical egress gateway, and falls back to sequential per-resource in-flight pipelining ($+42.0$ ms mean per-transaction overhead) paired with compensating sagas for post-transmission HTTP 5xx faults.

II. System Architecture and Formal Invariants

Agent-Chronos operates as a user-space L7 HTTP/2 frame-staging filter embedded at the egress and ingress boundaries of agent runtimes—specifically Google Agent Development Kit (ADK) workers, FastMCP gateways, and Envoy sidecar proxies—prior to stateful HTTP/2 HPACK compression, TLS 1.3 record encryption, and kernel TCP `sendmsg()` socket calls.

A. TrueTime Uncertainty Representation and Multi-Cloud Clock Model

Let $t_{\text{real}} \in \mathbb{N}$ denote absolute physical coordinate time expressed in discrete integer nanoseconds since the Unix epoch. On any node u, a hardware-anchored TrueTime provider [1] backed by GPS receivers and rubidium atomic clocks exposes a closed physical time uncertainty interval:

$$T_{\text{now},u} = [t_{\text{now},u,\text{earliest}},\ t_{\text{now},u,\text{latest}}], \quad t_{\text{now},u,\text{latest}} - t_{\text{now},u,\text{earliest}} = 2\epsilon_u \tag{1}$$

where $\epsilon_u \in \mathbb{N}$ represents node u's instantaneous local clock drift bound ($\epsilon_u \in [1, 7]$ ms in production Google Cloud data centers). For wire serialization of a single node's raw clock sample $T_{\text{now},u}$, Agent-Chronos encodes the 3-tuple $\mathcal{W}(T_{\text{now},u}) = \langle t_{\text{now},u,\text{earliest}}, t_{\text{now},u,\text{latest}}, \epsilon_u \rangle$, where receivers verify the exact single-node framing identity $t_{\text{now},u,\text{latest}} - t_{\text{now},u,\text{earliest}} = 2\epsilon_u$ and use ϵ_u to compose heterogeneous cross-node uncertainty bounds $\epsilon_{\text{eff}} = \lceil (\epsilon_{\text{verifier}} + \epsilon_{\text{gateway}})/2 \rceil \in \mathbb{N}$ (ceiling-rounded to preserve conservative integer nanosecond header encoding when $\epsilon_{\text{verifier}}$ and $\epsilon_{\text{gateway}}$ have opposite parity, while the Phase 2 barrier in Eq. (5) evaluates the exact integer sum $2\epsilon_{\text{eff}}^{\text{exact}} = \epsilon_{\text{verifier}} + \epsilon_{\text{gateway}} \in \mathbb{N}$; for the composite settlement header `X-Agent-TrueTime-Window` $\langle t_{E,\text{earliest}}, t_{F,\text{latest}}, \epsilon_{\text{eff}} \rangle$, where $t_{F,\text{latest}} = \max(t_{E,\text{latest}}, t_{\text{max},F})$ may be advanced by the causal floor $t_{\text{max},F}$, receivers verify the generalized framing invariant $t_{F,\text{latest}} - t_{E,\text{earliest}} > 0$, or $t_{F,\text{latest}} - t_{E,\text{earliest}} \geq 2\epsilon_{\text{verifier}}$ when $\epsilon_{\text{verifier}}$ is advertised). The fundamental TrueTime invariant guarantees that at the instant of query on node u:

$$t_{\text{now},u,\text{earliest}} \leq t_{\text{real}} \leq t_{\text{now},u,\text{latest}} \tag{2}$$

Cross-Cloud Clock Synchronization Topology: In heterogeneous deployments spanning Google Cloud Vertex AI and external cloud environments (e.g., AWS Bedrock, Salesforce Agentforce, or SAP S/4HANA), Agent-Chronos supports two deployment modes: (i) *Federated Egress Gateway Mode*, where external agent runtimes route both upstream epoch settlement signals and outbound MCP/A2A tool calls through a regional Google Cloud Apigee / Envoy Chronos gateway so that epoch commit timestamps T_E and egress commit-wait checks $T_{\text{now,gateway}}$ are anchored by the regional TrueTime cluster ($\epsilon_u \in [1, 7]$ ms). To prevent differential WAN transit jitter on the pre-gateway path from inverting external commit/abort signals prior to gateway arrival, external verifiers either attach origin-signed PTP/NTP bounds $\mathcal{W}(T_{\text{origin}})$ (in which case $\epsilon_{\text{eff}} = \lceil (\epsilon_{\text{origin}} + \epsilon_{\text{gateway}})/2 \rceil$ inherits the origin clock's uncertainty bound, expanding Δ_{wait} toward the NTP baseline if commodity NTP is used) or the federated gateway requires a synchronous quorum ACK from all participating verifiers of epoch E plus a conservative pre-gateway jitter margin $\Delta_{\text{wan_pre}}$ before minting T_E at its local TrueTime clock (specifically, when all abort-capable verifiers participate in a unanimous monotonic quorum where no verifier can emit an abort after a positive ACK, unanimous ACK arrival alone precludes a racing abort with $\Delta_{\text{wan_pre}} = 0$ ms; when a

subset quorum is configured or an asynchronous out-of-band guardrail can emit aborts independently of the quorum ACK channel, the gateway waits $\Delta_{\text{wan_pre}}$ before minting T_E and assigns a monotonic quorum-epoch fence token so any pathologically delayed pre-gateway abort arriving past $\Delta_{\text{wan_pre}}$ either revokes F if still in Phase 2 `PACED_HELD` or triggers deterministic compensation if F has already released); and (ii) *Hardware PTP Sidecar Mode*, where non-Google cloud participants query local GPS/atomic Precision Time Protocol hardware clocks (e.g., AWS Time Sync Service `/dev/ptp0` with hardware-reported error bound $\epsilon_{\text{PTP},u} \in [1, 10]$ ms) at both verification and egress nodes and advertise $\epsilon_{\text{PTP},u}$ in $\mathcal{W}(T_{\text{now},u})$ (noting that when invoking unmodified third-party SaaS endpoints lacking an ingress sidecar across concurrent writers, distributed PTP sidecars still route through a single logical egress serialization gateway for that SaaS target).

B. Decoupled Swarm Causal Vectors and Per-Destination Sequence Coordinates

While $\mathcal{O}(1)$-space Hybrid Logical Clocks (HLCs) [8] track a single scalar logical-physical frontier, multi-agent swarms dynamically fork parallel sibling subagents whose speculative branches must be tested for strict causal precedence ($\mathcal{V}_1 \prec_{\mathcal{V}} \mathcal{V}_2$) versus concurrent incomparability ($\mathcal{V}_1 \parallel \mathcal{V}_2$). At the same time, using a single swarm-wide vector clock simultaneously as a per-destination CBCAST sequence counter would stall downstream ingress sidecars whenever an agent executes internal reasoning turns, dispatches `IMMEDIATE` reads, or routes unicast tool calls to distinct endpoints $d_1 \neq d_2$. Agent-Chronos therefore strictly decouples two transport structures:

- **Swarm-Wide Composite Causal Vector ($\mathcal{V}_i = \langle \mathbf{C}_i, t_{\mathbf{max},i} \rangle$):** Maintained by each agent $a_i \in$ AgentID, where $\mathbf{C}_i$: AgentID $\to \mathbb{N}$ is a Fidge/Mattern vector clock [6], [7] over active swarm agent IDs (with $\text{dom}(\mathbf{C}_i)$ denoting the finite non-zero support and missing keys defaulting to 0) and $t_{\text{max},i} \in \mathbb{N}$ (equivalently written $\mathcal{V}_i.t_{\text{max}} \equiv t_{\text{max},i}$) is the maximum TrueTime upper bound (t_{latest}) observed across a_i's causal history. Evaluated strictly over the logical vector component $\mathbf{C}$ (with $t_{\text{max},i}$ serving as a commit-wait floor and physical tie-breaker for concurrent writes), strict causal precedence over $D = \text{dom}(\mathbf{C}_1) \cup \text{dom}(\mathbf{C}_2)$ is defined as $\mathcal{V}_1 \prec_{\mathcal{V}} \mathcal{V}_2 \iff (\forall k \in D,\, \mathbf{C}_1[k] \leq \mathbf{C}_2[k]) \wedge (\exists k \in D,\, \mathbf{C}_1[k] < \mathbf{C}_2[k])$, and concurrency as $\mathcal{V}_1 \parallel \mathcal{V}_2 \iff \neg(\mathcal{V}_1 \prec_{\mathcal{V}} \mathcal{V}_2) \wedge \neg(\mathcal{V}_2 \prec_{\mathcal{V}} \mathcal{V}_1)$.
- **Per-Destination Transport Sequence Coordinate ($\mathbf{Seq}_{\mathbf{dest}}[d, a_i]$):** For each destination endpoint d, the egress gateway maintains a dedicated gap-free monotonic counter $\text{Seq}_{\text{dest}}[d, a_i] \in \mathbb{N}$ and a compact destination dependency map $\text{Dep}_{d,i}$: AgentID $\to \mathbb{N}$ recording the highest destination-d sequence numbers causally preceding the current frame.

1) **Two-Stage Pre-Staging vs. Post-Phase-2 Sequence Assignment:** When agent $a_i \in$ AgentID initiates a reasoning/delegation turn or stages a candidate mutating tool frame F to destination d at local TrueTime interval $T_{\text{now},i} = [t_{\text{now},i,\text{earliest}}, t_{\text{now},i,\text{latest}}]$, it constructs an isolated branch-local tentative pre-staging vector $\mathcal{V}_F = \langle \mathbf{C}_F, t_{\text{max},F} \rangle$ from its committed state $\langle \mathbf{C}_i, t_{\text{max},i} \rangle$ using an atomic per-agent tentative ticket counter $c_{\text{tent},i} \leftarrow c_{\text{tent},i} + 1$ (used to test causal ordering in Rule 1 and to establish the pre-staging causal floor $t_{\text{max},F}$ in Rule 2; if F is revoked in Rule 4, $\mathcal{V}_F$ is simply discarded without mutating a_i's shared committed state $\langle \mathbf{C}_i, t_{\text{max},i} \rangle$, preventing rollback interference across concurrent multiplexed streams or intervening inbound merges):

$$\mathbf{C}_F \leftarrow \mathbf{C}_i[a_i \mapsto c_{\text{tent},i}], \quad t_{\text{max},F} \leftarrow \max(t_{\text{max},i},\, t_{\text{now},i,\text{latest}}). \tag{3}$$

Crucially, the per-destination sequence counter $\text{Seq}_{\text{dest},F}[d, a_i] \leftarrow \text{Seq}_{\text{dest}}[d, a_i] + 1$ is assigned and incremented **strictly upon Phase 2 commit-wait release** of a mutating frame addressed to d, at which point a_i's shared committed causal frontier atomically joins $\mathbf{C}_i \leftarrow \mathbf{C}_i \sqcup \mathbf{C}_F$ and $t_{\text{max},i} \leftarrow \max(t_{\text{max},i}, t_{F,\text{latest}})$ (serialized in `X-Agent-Causal-Fence-Vector`) and records $\text{Seq}_{\text{dest},F}[d, a_i]$ in $\text{Dep}_{d,i}[a_i]$. Because Phase 2 waits until $t_{\text{real}} \geq t_{F,\text{latest}}$ and unpaced local/A2A turns in Eqs. (3)–(4) take the pointwise maximum of existing $t_{\text{now},u,\text{latest}} \leq t_{\text{real}} + \epsilon_u$ bounds rather than summing ϵ_u across hops, the physical lead of $t_{\text{max},i}$ is strictly non-accumulating ($t_{\text{max},i} - t_{\text{real}} \leq \max_u \epsilon_u$) across deep multi-agent delegation chains and cannot inflate downstream Δ_{floor}. To ensure transitive causal ordering across A2A delegations, any outbound A2A task delegation from a_i to subagent a_j that depends on an uncommitted write F_1 in epoch E either awaits Phase 2 release of F_1 so $\text{Dep}_{d,i}$ carries the committed $\text{Seq}_{\text{dest},F_1}[d, a_i]$, or propagates a tentative epoch dependency handle (E, F_1) so a_j's downstream calls inherit E's Phase 1/Phase 2 barrier. Because frames revoked pre-wire during Phase 1 or Phase 2 are purged before $\text{Seq}_{\text{dest}}[d, a_i]$ is incremented, pre-wire revocations never create sequence gaps and never transmit traffic toward downstream targets; payload-free tombstone sequence ACKs are emitted only if a post-release transport stream resets mid-flight on a sidecar-fronted link (and are suppressed for unmodified SaaS endpoints).

2) **Causal Merge Rule:** When agent a_j receives an A2A or tool response frame carrying $\mathcal{V}_i = \langle \mathbf{C}_i, t_{\text{max},i} \rangle$ and per-destination watermarks $\text{Dep}_{d,i}$, it merges $\mathcal{V}_i$ via the pointwise join operator ($\sqcup$) across $\text{dom}(\mathbf{C}_j) \cup \text{dom}(\mathbf{C}_i)$:

$$\mathcal{V}_j.\text{merge}(\mathcal{V}_i) = \langle \mathbf{C}_j \sqcup \mathbf{C}_i,\, \max(t_{\text{max},j},\, t_{\text{max},i}) \rangle\,, \tag{4}$$

where $(\mathbf{C}_j \sqcup \mathbf{C}_i)[k] \triangleq \max(\mathbf{C}_j[k], \mathbf{C}_i[k])$, and merges $\text{Dep}_{d,j}[k] \leftarrow \max(\text{Dep}_{d,j}[k], \text{Dep}_{d,i}[k])$. Mapping active swarm agent IDs ($|\text{AgentID}| \leq 16$) to a 16-element positional integer array in compact JSON `{"c":[c_0,...,c_15],"t":t_max,"b":bitmap}` (with per-session counters $c_k < 10^4$, a 19-digit nanosecond integer `t`, and a 16-bit integer bitmap `b` ≤ 65535) requires 69–121 bytes of unformatted raw JSON (117–121 bytes at 4-digit counters, or up to 142–184 bytes when including optional whitespace/epoch metadata, remaining $\leq$ 190 bytes) and ≤ 256 bytes ($4\lceil 190/3 \rceil$) when Base64-encoded in HTTP/2 headers.

C. Two-Phase L7 Speculative Staging and TrueTime Commit-Wait Pacing

Because MCP `tools/call` and A2A task dispatches use HTTP `POST` for both queries and state mutations, the L7 gateway inspects the registered MCP tool annotation (`readOnlyHint: true|false`) or OpenAPI operation metadata to set `F.is_mutation` $\in$ {true, false}, extracts the composite target resource key-set $\mathcal{K}(F) \subseteq \mathcal{K}$ via registered per-tool JSONPath selectors over MCP `params.arguments`, A2A task/artifact payloads, or OpenAPI path/query/body parameters (e.g., {`$.ledger_id`}, multi-key {`$.debit_id`, `$.credit_id`} for atomic transfers, or default wildcard $\{\star\}$ for unmapped or range/aggregate queries that fall back to full causal vector precedence), and reads the upstream speculative epoch identifier E and causal vector $\mathcal{V}_F$ from the request context. Operating in user-space L7 frame queues prior to HPACK/TLS encoding prevents head-of-line blocking across multiplexed HTTP/2 streams and coordinates four deterministic rules:

1) **Conditional Safe Read-Only Bypass:** If `F.is_mutation` = false and neither (a) a causally preceding write F_{prior} ($\mathcal{V}_{F_{\text{prior}}} \prec_{\mathcal{V}} \mathcal{V}_F$) across Phase 1 (`STAGE_HELD`) or Phase 2 (`PACED_HELD`) nor (b) a concurrent sibling write F_{sib} currently in Phase 2 (`PACED_HELD`) with an earlier or overlapping commit interval $t_{E_{\text{sib}},\text{earliest}} \leq t_{\text{now},F,\text{latest}}$ shares an overlapping resource key ($\mathcal{K}(F_{\text{prior/sib}}) \cap \mathcal{K}(F) \neq \emptyset$), pacing status is set to `IMMEDIATE` and the frame is dispatched with 0.00 ms pacing delay (unsettled speculative sibling writes in Phase 1 `STAGE_HELD` lack a settlement timestamp and are linearized after concurrent exploratory `IMMEDIATE` reads to avoid stalling reads for 200–5,000 ms, while Phase 2 visibility is evaluated over the egress gateway's locally observed settlement state, replicated across distributed PTP sidecars via intra-cluster settlement tokens). Otherwise, F is chained behind the pending write (`SAFE_READ_WAIT`) at the egress gateway (and aborted with HTTP 409 if that write is revoked via Rule 4); furthermore, on sidecar-fronted links, the egress gateway merges the sequence coordinate $\text{Seq}_{\text{dest},F_{\text{sib}}}[d, a_{\text{sib}}]$ of any overlapping chained or recently released sibling write (within $\Delta_{\text{jitter_hold}}$) into $\text{Dep}_{d,F}$, and any read F with non-empty $\text{Dep}_{d,F}$ attaches $\langle \text{Seq}_{\text{dest},F} = 0, \text{Dep}_{d,F} \rangle$ in `X-Agent-Dest-Seq` so the ingress sidecar holds F until $\forall a_k \in \text{dom}(\text{Dep}_{d,F})$, $\text{Seq}_{\text{loc},d}[a_k] \geq \text{Dep}_{d,F}[a_k]$, preventing WAN jitter from reordering a post-release read ahead of an in-flight released write.
2) **Phase 1 — Speculative Epoch Staging (Δ_{stage}):** If `F.is_mutation` = true and F depends on an active upstream speculative reasoning or policy-verification branch E (duration 200–5,000 ms), the L7 filter holds F in user-space staging memory (`STAGE_HELD`) while upstream generation and parallel policy verification execute concurrently. Once upstream epoch E completes verification and commits its decision at verifier TrueTime interval $T_E = [t_{E,\text{earliest}}, t_{E,\text{latest}}]$ (with verifier uncertainty $\epsilon_{\text{verifier}}$), the epoch broadcasts a settlement token containing $t^*_{E,\text{latest}} = \max(t_{E,\text{latest}}, t_{\max,F})$, which defines the frame's commit upper bound $t_{F,\text{latest}} \equiv t^*_{E,\text{latest}}$.
3) **Phase 2 — TrueTime Commit-Wait Serialization (Δ_{wait}):** Upon receiving the settlement token for epoch E, the L7 egress pacer transitions F to `PACED_HELD` and halts wire transmission until its local TrueTime lower bound $t_{\text{now,earliest}} = t_{\text{now,gateway}} - \epsilon_{\text{gateway}}$ strictly surpasses $t^*_{E,\text{latest}} + \Delta_{\text{abort_prop}}$, where $\Delta_{\text{abort_prop}}$ is the upper bound on intra-cluster control-plane abort propagation delay from any sibling verification node ($\Delta_{\text{abort_prop}} \leq 0.5$ ms over intra-cluster gRPC, or 0 ms under co-located quorum settlement):
$$\Delta_{\text{wait}} = \max\big(0,\, t^*_{E,\text{latest}} + \Delta_{\text{abort_prop}} - t_{\text{now,earliest}}\big)\,,$$
$$\mathbb{E}[\Delta_{\text{wait}}] \approx \max(0,\, 2\epsilon_{\text{eff}} + \Delta_{\text{abort_prop}} - \Delta t_{\text{ipc}}) \tag{5}$$
where the first line is the **normative runtime barrier** evaluated by polling local TrueTime hardware (since under signed local clock offsets $\delta_u \in [-\epsilon_u, +\epsilon_u]$, physical IPC transit $\Delta_{\text{real_ipc}} \triangleq t_{\text{real,now}} - t_{\text{real},E}$, and causal floor $\Delta_{\text{floor}} = t^*_{E,\text{latest}} - t_{E,\text{latest}} \geq 0$, the instantaneous wait equals $\max(0, \Delta_{\text{floor}} + 2\epsilon_{\text{eff}} + (\delta_{\text{verifier}} - \delta_{\text{gateway}}) + \Delta_{\text{abort_prop}} - \Delta_{\text{real_ipc}})$), and the second line gives the tight Jensen's inequality approximation ($\mathbb{E}[\max(0, X)] \approx \max(0, \mathbb{E}[X])$, exact to $< 0.4\%$ zero-clamping) under zero-mean clock offsets ($\mathbb{E}[\delta_{\text{verifier}} - \delta_{\text{gateway}}] = 0$) and $\Delta_{\text{floor}} = 0$, where $\Delta t_{\text{ipc}} \triangleq \mathbb{E}[\Delta_{\text{real_ipc}}] = \mathbb{E}[t_{\text{now,gateway}} - t^*_E]$ denotes expected IPC transit relative to the floor-adjusted midpoint $t^*_E \triangleq t^*_{E,\text{latest}} - \epsilon_{\text{verifier}}$. A conflicting causal abort emitted by a sibling verifier at TrueTime interval $T_{\text{abort}} = [t_{\text{abort,earliest}}, t_{\text{abort,latest}}]$ preempts epoch E if $t_{\text{abort,latest}} \leq t^*_{E,\text{latest}}$ (or for any abort physically emitted at $t_{\text{real,abort}} \leq t^*_{E,\text{latest}}$): waiting until $t_{\text{now,earliest}} \geq t^*_{E,\text{latest}} + \Delta_{\text{abort_prop}}$ guarantees by Eq. (2) that $t_{\text{real}} \geq t^*_{E,\text{latest}} + \Delta_{\text{abort_prop}} \geq t_{\text{real,abort}} + \Delta_{\text{abort_prop}}$, ensuring that any such abort has both been emitted and physically arrived at the egress pacer before F is released.
4) **Pre-Wire In-Flight Revocation:** If epoch E aborts during Phase 1 (Δ_{stage}) or if a cross-node policy abort stamped within the $2\epsilon_{\text{eff}}$ uncertainty window arrives during Phase 2 (Δ_{wait}), the unencoded frame F is immediately purged from the user-space L7 queue before any bytes enter the HPACK encoder, TLS record layer, or kernel TCP socket buffer. The gateway returns a deterministic HTTP 409 Conflict response to the calling agent, ensuring **zero mutating payload bytes** reach the downstream SaaS endpoint.

D. Ingress Causal Re-Sequencing Barrier Against WAN Jitter

While sender-side commit-wait pacing orders departure timestamps in t_{real}, public WAN transit jitter (± 10 ms to 60 ms) can reorder packets in flight. For endpoints fronted by an Agent-Chronos ingress sidecar or enterprise API gateway (e.g., fronting SAP S/4HANA OData/RFC connectors), the ingress filter maintains per-destination applied sequence watermarks $\text{Seq}_{\text{loc},d}$ and buffers any arriving mutating frame F from sender a_s until $\text{Seq}_{\text{loc},d}[a_s] = \text{Seq}_{\text{dest},F}[d, a_s] - 1$ and $\forall a_k \in \text{dom}(\text{Dep}_{d,F})$, $\text{Seq}_{\text{loc},d}[a_k] \geq \text{Dep}_{d,F}[a_k]$ (and similarly holds any dependent read carrying $\text{Dep}_{d,F}$ until $\forall a_k \in \text{dom}(\text{Dep}_{d,F})$, $\text{Seq}_{\text{loc},d}[a_k] \geq \text{Dep}_{d,F}[a_k]$). For concurrent

sibling writes ($\mathcal{V}_1 \parallel \mathcal{V}_2$), the egress gateway finalizes the active sibling fork bitmap in `X-Agent-Causal-Fence-Vector` upon Phase 2 release of F_1, setting bits *only* for concurrent sibling branches that have already settled Phase 1 with overlapping resource keys ($\mathcal{K}(F_1) \cap \mathcal{K}(F_2) \neq \emptyset$) targeting the same destination d while advancing a monotonic per-key settlement floor $t_{\text{key_floor}}[d,k] \leftarrow \max(t_{\text{key_floor}}[d,k], t_{F_1,\text{latest}} + 1\text{ ns})$ so any sibling settling Phase 1 after F_1 cannot receive an earlier commit bound $t_{F_2,\text{latest}} < t_{F_1,\text{latest}}$ (and emitting a lightweight control-plane sibling-clear signal if a flagged sibling is revoked during Phase 2, so aborted, read-only, or disjoint-key sibling branches never stall F_1). Upon ingress arrival of F_1 once $t_{\text{now,earliest}} \geq t_{F_1,\text{latest}}$, the ingress sidecar starts a countdown for bounded WAN jitter window $\Delta_{\text{jitter_hold}}$ (absorbing one-way WAN jitter spread after any earlier-bound sibling F_2 with $t_{F_2,\text{latest}} < t_{F_1,\text{latest}}$ has completed its Phase 2 wait) and applies conflicting writes in deterministic ($t_{F,\text{latest}}$, AgentID) lexicographical order once $t_{\text{now,earliest}} \geq t_{F,\text{latest}}$ (rejecting any pathologically delayed sibling write F_2 that arrives after $\Delta_{\text{jitter_hold}}$ expires with $t_{F_2,\text{latest}} < t_{F_1,\text{latest}}$ via deterministic HTTP 409 Stale Sibling Timestamp while advancing $\text{Seq}_{\text{loc},d}[a_{s2}]$ to $\text{Seq}_{\text{dest},F_2}[d,a_{s2}]$ as a tombstoned coordinate so subsequent frames from a_{s2} never stall, and cascading HTTP 409 aborts to any unapplied frames dependent on that tombstoned coordinate). For unmodified external third-party SaaS APIs without an ingress sidecar, the sender-side gateway acquires per-resource pipeline locks in $\mathcal{K}(F)$ atomically in canonical lexicographical key order (preventing multi-key deadlocks), holds any dependent write or read F_2 ($\mathcal{K}(F_1) \cap \mathcal{K}(F_2) \neq \emptyset$) until the HTTP 2xx acknowledgement of F_1 returns (or a bounded lock-lease timeout on gateway crash/timeout triggers idempotency-key status reconciliation and compensating saga recovery), and pairs post-transmission HTTP 5xx faults with compensating sagas [4].

III. Wire Protocol and Observability Invariants

Internal pre-wire gateway queue states (`STAGE_HELD`, `PACED_HELD`) resolve to four terminal wire dispositions ({`IMMEDIATE`, `SAFE_READ_WAIT`, `RELEASED`, `REVOKED`}) prior to wire emission. Each speculative unary or client-streaming gRPC/MCP mutation either opens a dedicated multiplexed HTTP/2 stream whose initial `HEADERS` and request `DATA` frames are held in user-space until Phase 2 completes, or—on long-lived bidirectional MCP/A2A streams—holds individual JSON-RPC request `DATA` frames in user-space `STAGE_HELD`/`PACED_HELD` queues prior to wire emission (carrying per-call `X-Agent-*` settlement fields inside the L7 JSON-RPC `_meta` envelope upon Phase 2 release, while session-closing HTTP/2 `END_STREAM` trailers emit a cumulative session audit digest), strictly preserving the zero-byte wire invariant upon revocation without prematurely half-closing active bidirectional streams. Agent-Chronos injects four core settlement/pacing HTTP/2 headers (plus `X-Agent-Dest-Seq` carrying $\langle \text{Seq}_{\text{dest},F}[d,a_s], \text{Dep}_{d,F} \rangle$ on mutating calls and dependent reads, totaling five `X-Agent-*` headers):

- `X-Agent-TrueTime-Window`: Serialized settlement 3-tuple $\langle t_{E,\text{earliest}}, t_{F,\text{latest}}, \epsilon_{\text{eff}} \rangle$ in integer nanoseconds (where $t_{F,\text{latest}} \equiv t^*_{E,\text{latest}}$ and $t_{F,\text{latest}} - t_{E,\text{earliest}} > 0$).
- `X-Agent-Causal-Fence-Vector`: Compact base64/JSON serialization ($\leq$ 256 B) of committed $\mathcal{V}_F = \langle \mathbf{C}_F, t_{\text{max},F} \rangle$ and active sibling fork bitmap.
- `X-Agent-Pacing-Status`: Terminal disposition in {`IMMEDIATE`, `SAFE_READ_WAIT`, `RELEASED`, `REVOKED`}.
- `X-Agent-Pacing-Delay-Ms`: Post-settlement gateway hold duration in milliseconds (Δ_{wait} for `RELEASED` mutations, chained wait for `SAFE_READ_WAIT` reads, and elapsed Phase 2 hold prior to abort for `REVOKED` frames; Phase 1 Δ_{stage} is exported in OpenTelemetry attribute `chronos.stage_delay_ms`).

Dual-Plane Observability of Revoked Frames: When a frame is purged via Pre-Wire In-Flight Revocation, zero mutating bytes are transmitted to the external SaaS target. Instead, `X-Agent-Pacing-Status: REVOKED` and `X-Agent-Pacing-Delay-Ms` are emitted on (i) the synchronous HTTP 409 response wire back to the upstream orchestrator and (ii) a payload-free signed telemetry trailer exported to the cross-organization OpenTelemetry audit sink, ensuring 100% protocol auditability without leaking aborted payloads to third-party APIs.

IV. Empirical Evaluation

A. Experimental Testbed and Workload Methodology

We evaluated Agent-Chronos on an emulated cross-cloud HTTP/2 Envoy + FastMCP testbed modelling multi-agent financial ledger and procurement workflows (adapted from τ-bench [15] tool-invocation schemas) between Google Cloud Vertex AI and an SAP S/4HANA ERP gateway across $N = 1{,}000$ multi-agent transactions per seed (4,200 total tool frames per run: 2,520 [60%] mutating frames and 1,680 [40%] read-only queries over a $|\mathcal{K}| = 64$ resource key-space under Zipf($s = 1.15$) contention, evaluated across 5 independent random seeds [5,000 total transactions per baseline] with fixed fault-injection schedules and stochastic network/clock draws). The 6-agent hierarchical DAG topology comprises 1 root orchestrator, 2 tier-1 domain planners, and 3 tier-2 execution subagents (depth 3, max branching factor 2, baseline 650.0 ms mean tool/agent execution path), where each transaction dispatches 1 to 2 exploratory read queries and 2 to 3 mutating tool calls (mean 4.20 frames/-transaction, with 46.6% of transactions containing dependent same-key multi-write chains and 5.8% [97.4/1,680] of reads issuing post-settlement verification queries during an active Phase 2 `PACED_HELD` window on the same key), with speculative verification guarding the terminal mutating commit frame of each transaction. Network links were configured with Linux `tc netem` around a 90 ms base RTT (45 ms one-way base delay with $\pm$30 ms independent uniform per-direction jitter, yielding Triangular(-60 ms, 0 ms, $+60$ ms) RTT jitter, strictly positive one-way transit $\in [15, 75]$ ms, and ingress sibling hold bound $\Delta_{\text{jitter_hold}} = 60$ ms matching the $75 - 15 = 60$ ms max one-way spread; co-located regional verifiers use $\Delta_{\text{wan_pre}} = 0$ ms), independent verifier and egress gateway TrueTime drift bounds $\epsilon_{\text{verifier}}, \epsilon_{\text{gateway}}$ i.i.d. $\sim$ Uniform(1.0 ms, 7.0 ms) (whose sum $2\epsilon_{\text{eff}} = \epsilon_{\text{verifier}} + \epsilon_{\text{gateway}} \sim$ Triangular(2.0 ms, 8.0 ms, 14.0 ms) has mean 8.00 ms and theoretical SD 2.45 ms), upstream speculative

verification durations Δ_{stage} clamped to $[200, 5{,}000]$ ms from LogNormal($\mu = 6.2, \sigma = 0.55$) (median 492.7 ms), and a 14.80% ($148.0 \pm 0.0/1{,}000$) transaction-level speculative branch abort rate where sibling verifier completion offsets follow $\Delta t_{\text{sib}} \sim \text{Normal}(0, 22^2\ \text{ms}^2)$ around T_E—yielding a stochastic clock/network boundary split of 119.0 ± 1.1 (80.41%, 5-seed mean $\pm$ SD) aborting during Phase 1 concurrent verification and 29.0 ± 1.1 (19.59%) arriving within the $2\epsilon_{\text{eff}}$ cross-node clock-skew window during Phase 2. Because net intra-cluster settlement token transit minus abort margin ($\Delta t_{\text{ipc}} - \Delta_{\text{abort_prop}} \sim \text{LogNormal}(\mu = 0.72, \sigma = 0.18)$ ms, mean 2.09 ± 0.38 ms with load correlation $\rho = 0.42$ and $< 0.4\%$ zero-clamping) elapses before $t_{\text{now,earliest}}$ is queried, the residual Phase 2 wait Δ_{wait} (pooled over non-aborted committed mutations) averages 5.91 ± 2.14 ms ($p_{50} = 5.80$ ms, $p_{95} = 9.62$ ms, $p_{99} = 11.84$ ms). Transaction-level causal inversions are counted out of $N = 1{,}000$ transactions when any mutating or dependent frame arrives at the destination ERP ingress boundary ahead of a causally preceding frame ($\mathcal{V}_1 \prec_{\mathcal{V}} \mathcal{V}_2$) or out of physical commit order across concurrent conflicting writes.

B. Comparative Results and Component Ablations

Table I compares Agent-Chronos against four baselines: (1) an **Unmitigated Baseline Swarm**, (2) **Application-Layer Compensating Sagas / Post-Facto Undo** [4], [13], [14] (where 28.38% [$42.0/148.0$] of aborted writes hit non-reversible external settlement locks and reversible rollbacks incur LogNormal($\mu = 4.90, \sigma = 0.35$) ms compensation latency), (3) a software-only **NTP Hybrid Logical Clock (HLC) Barrier** [8] enforcing dynamic $\Delta_{\text{wait,NTP}} = \max(0, 2\hat{\epsilon}_{\text{NTP}} + \Delta_{\text{abort_prop}} - \Delta t_{\text{ipc}})$ over local NTP daemon error estimates $\hat{\epsilon}_{\text{NTP}} \sim \text{Normal}(35\ \text{ms}, 8^2\ \text{ms}^2)$ plus a 5% Bernoulli spike mixture Uniform$(40, 85)$ ms (where half of spikes are reflected in $\hat{\epsilon}_{\text{NTP}}$—raising wait SD to 19.20 ms and preventing abort leaks—and half are uncompensated physical offset spikes on sibling branches that exceed the 25 ms scalar HLC ingress watermark hold window, causing 21.0 ± 1.9 [2.10%] sibling causal inversions and 1.2% stale dependent reads), and (4) a **Chronos Vector-Only Ablation** (removing Phase 2 TrueTime commit-wait pacing while retaining Phase 1 staging, logical vector clocks, and per-destination sequence fencing—serving as an architectural proxy for logical pre-commit staging runtimes such as Atomix [18], Sherlock [17], Speculative Actions [16], and ALAS [19] when deployed across *decentralized cross-node verification topologies*).

In the Unmitigated Baseline, the 195.0 ± 4.2 (19.50%) destination causal inversions decompose into 148.0 ± 0.0 transactions where an unrevoked speculative mutation arrived ahead of its subsequent abort/recovery branch plus 47.0 ± 4.2 pure WAN packet-reordering inversions across valid multi-frame transactions. Ablating TrueTime commit-wait (**Chronos Vector-Only Ablation**) intercepts the 119.0 ± 1.1 (80.41%) Phase 1 aborts before wire release, but leaks the 29.0 ± 1.1 (2.90%) cross-node race aborts arriving within the $2\epsilon_{\text{eff}}$ physical clock-skew window; because each leaked mutation executes ahead of the orchestrator's subsequent recovery write on the same resource key—and because ablating TrueTime physical bounds forces the ingress sidecar to fall back to arrival-order tie-breaking on vector-concurrent colliding sibling writes ($\mathcal{V}_1 \parallel \mathcal{V}_2$, 5.0 ± 0.9 collisions/run under Zipf(1.15)), Vector-Only incurs $29.0 + 5.0 = 34.0 \pm 1.5$ (3.40%) destination inversions. Note that ingress jitter re-sequencing hold latency (8.42 ± 4.90 ms, which includes $+0.03$ ms amortized from sibling-fork holds across the $5.0/2{,}520$ colliding frames) matches between Vector-Only and Full Agent-Chronos on the 90 ms WAN link because minimum one-way transit (15 ms) already exceeds $2\epsilon_{\text{eff}} \leq 14$ ms upon arrival ($t_{\text{now,earliest}} \geq t_{F,\text{latest}}$); by contrast, in an auxiliary low-latency intra-region metro interconnect experiment (4 ms base RTT, one-way transit $[1, 3]$ ms $< 2\epsilon_{\text{eff}}$), the ingress physical-time barrier ($t_{\text{now,earliest}} \geq t_{F,\text{latest}}$) actively holds arriving frames for 3.92 ± 1.85 ms to preserve 0.00% inversions.

Full **Agent-Chronos** intercepts 100.00% ($148.0/148.0$) of aborted mutations pre-wire and eliminates 100.00% ($195.0/195.0$) of causal inversions, with a mean Phase 2 commit-wait of 5.91 ± 2.14 ms ($p_{95} = 9.62$ ms, $p_{99} = 11.84$ ms; when remote cross-cloud quorum verifiers require $\Delta_{\text{wan_pre}} = 20$ ms, pre-minting quorum wait adds $+18.5 \pm 4.2$ ms) and 0.00 ms delay on independent read-only queries (94.2% bypass immediately; the 5.8% post-settlement dependent reads wait 5.40 ± 1.98 ms via `SAFE_READ_WAIT`). End-to-end, compared to non-speculative sequential execution ($1{,}142.5 \pm 318.0$ ms mean completion, summing the 650.0 ms execution path and 492.5 ms mean verification), Agent-Chronos overlaps tool synthesis and staging with verification while adding 5.91 ms commit-wait (plus retry overhead on the 14.8% aborted branches), reducing mean completion latency to 655.7 ± 184.2 ms (a net speculative speedup of 486.8 ms, or 42.6%). When invoking unmodified third-party SaaS APIs without an ingress sidecar via sequential per-resource in-flight pipelining (0% injected HTTP 5xx faults, incurring one 90 ms WAN RTT per dependent same-key write across 46.6% of transactions), mean transaction latency increases by $+42.0 \pm 19.4$ ms (697.7 ms total) with 0.00% phantom mutations and 0.00% inversions. Evaluating Hardware PTP Sidecar Mode ($\epsilon_{\text{PTP},u}$ i.i.d. $\sim$ Uniform$(1.0\ \text{ms}, 10.0\ \text{ms})$, $2\epsilon_{\text{eff}} \sim$ Triangular$(2.0\ \text{ms}, 11.0\ \text{ms}, 20.0\ \text{ms})$) similarly achieved 0.00% phantom mutations and 0.00% inversions at a mean commit-wait of 8.84 ± 3.12 ms and ingress hold of 8.76 ± 5.04 ms (reflecting the 15–20 ms upper tail of $2\epsilon_{\text{eff}}$), while user-space L7 staging required only 1.8 MB peak memory across 100 concurrent staged frames and < 0.12 ms CPU overhead per frame. Finally, an auxiliary stress suite confirmed 0.00% phantom mutations and 0.00% inversions under: (i) heavy-tailed Pareto$(\alpha = 2.5)$ WAN jitter spikes up to 180 ms (where conflicting sibling writes arriving past $\Delta_{\text{jitter_hold}} = 60$ ms are safely rejected with HTTP 409 Stale Sibling Timestamp), (ii) temporally autocorrelated sawtooth GPS holdover (ϵ_u ramping to 12 ms, raising p_{99} commit-wait to 19.40 ms), (iii) 2% injected mid-flight HTTP/2 `RST_STREAM` resets (resolved via tombstone sequence ACKs with zero ingress stalls), and (iv) 16-agent swarm fan-out (121 B unformatted positional / 184 B with optional metadata max raw JSON vector).

V. Conclusion and Operational Scope

Agent-Chronos establishes a hardware-anchored L7 transport fencing and speculative pacing protocol for cross-cloud

TABLE I
EMPIRICAL BENCHMARK AND ABLATION COMPARISON ACROSS $N = 1{,}000$ CROSS-CLOUD MULTI-AGENT TRANSACTIONS PER SEED (5 SEEDS)[A]

Metric (Basis / Granularity)	Unmitigated Baseline	Compensating Sagas [4], [13], [14]	NTP Software HLC [8]	Chronos Vector-Only (Ablation)	Agent-Chronos (Full)
Transactions Evaluated (Per Seed, $n = 5$ Seeds)	1,000	1,000	1,000	1,000	**1,000**
Phantom Tool Mutations (Tx Count, % of 1,000 Tx)[a]	148.0 ± 0.0 (14.80%)	42.0 ± 1.6 (4.20% uncomp.)	0.0 ± 0.0 (0.00%)	29.0 ± 1.1 (2.90% skew leak)	$\mathbf{0.0 \pm 0.0}$ (**0.00%**)
Causal Inversion Rate (Tx Count, % of 1,000 Tx)[a]	195.0 ± 4.2 (19.50%)	195.0 ± 4.2 (19.50%)	21.0 ± 1.9 (2.10%)	34.0 ± 1.5 (3.40%)	$\mathbf{0.0 \pm 0.0}$ (**0.00%**)
Pre-Wire Aborted Revocations (% of 148 Aborted Tx)[a]	0.0 ± 0.0 (0.00%)	0.0 ± 0.0 (0.00%)	148.0 ± 0.0 (100.00%)	119.0 ± 1.1 (80.41%)	$\mathbf{148.0 \pm 0.0}$ (**100.00%**)
Mean Commit-Wait Pacing (Δ_{wait}, Per-Frame SD)[a,b]	0.00 ms	0.00 ms ($+142.50 \pm 18.40$ ms undo)[b]	68.40 ± 19.20 ms	0.00 ms	$\mathbf{5.91 \pm 2.14}$ ms
Commit-Wait Tail Latency ($p_{50}/p_{95}/p_{99}$)[b]	0.00/0.00/0.00 ms	0.00/310.40/485.00 ms (undo)[b]	67.10/98.40/112.60 ms	0.00/0.00/0.00 ms	$\mathbf{5.80/9.62/11.84}$ ms
Ingress Jitter Re-Sequencing Hold (Per-Frame SD)[a]	0.00 ms	0.00 ms	11.20 ± 6.40 ms	8.42 ± 4.90 ms	$\mathbf{8.42 \pm 4.90}$ ms
Independent Read-Only Bypass (94.2% of 1,680 Reads)	0.00 ms	0.00 ms	0.00 ms	0.00 ms	**0.00** ms
Dependent Read-Only Wait (`SAFE_READ_WAIT`, 5.8% of Reads)[c]	0.00 ms (stale read)	0.00 ms (stale read)	61.20 ± 17.50 ms	0.00 ms (stale read in $2\epsilon_{\text{eff}}$)[c]	$\mathbf{5.40 \pm 1.98}$ ms
Protocol Auditability	None	Application Logs Only	Partial (Scalar HLC)	Logical Vector Only	**100.00% (Dual-Plane)**

[a]Event-count rows report 5-seed mean $\pm$ across-seed SD ($n = 5$ seeds); continuous latency rows report 5-seed mean $\pm$ pooled per-frame within-run SD across non-aborted committed frames.
[b]For Compensating Sagas, $+142.50 \pm 18.40$ ms is the conditional rollback latency (LogNormal($\mu = 4.90, \sigma = 0.35$) ms) over 148 aborted Tx ($+21.09$ ms unconditional mean across 1,000 Tx), while 0.00/310.40/485.00 ms (undo) reports unconditional rollback percentiles across all 1,000 transactions (85.2% non-aborted at 0.00 ms; conditional $p_{50}/p_{95}/p_{99} = 138.2/392.0/512.4$ ms).
[c]Of the 5.8% (97.4/1,680) post-settlement dependent reads, 100% observe uncommitted/stale state under Unmitigated/Saga, 19.6% under Vector-Only ($\Delta_{\text{wait}} = 0$), 1.2% under NTP HLC, and 0.0% under Chronos.

multi-agent swarms. By combining two-phase user-space speculative staging, TrueTime commit-wait serialization ($\Delta_{\text{wait}} = \max(0, t^*_{E,\text{latest}} + \Delta_{\text{abort_prop}} - t_{\text{now,earliest}})$), decoupled swarm-wide causal vectors and per-destination sequence coordinates, and ingress jitter re-sequencing, Agent-Chronos eliminates phantom tool mutations and causal inversions across Chronos-enabled sidecar gateways while delivering a 486.8 ms (42.6%) net speculative latency reduction per transaction without holding distributed database locks. Functionally, Agent-Chronos guarantees strict client-side egress linearizability and end-to-end causal delivery across sidecar-fronted endpoints rather than internal database strict serializability; when invoking unmodified third-party SaaS APIs that lack an ingress sidecar, the gateway suppresses tombstone sequence ACKs, routes concurrent sibling writes ($\mathcal{V}_1 \parallel \mathcal{V}_2$) through a shared logical egress gateway, and falls back to sequential per-resource in-flight pipelining ($+42.0$ ms mean per-transaction overhead) paired with compensating sagas for post-transmission HTTP 5xx faults. Operational deployment assumes access to TrueTime, local `/dev/ptp0` hardware clocks, or a federated Chronos egress gateway, alongside bounded active swarm fan-out ($|\text{AgentID}| \leq 16$). Future work will extend Agent-Chronos to dynamic hierarchical vector compression for massive ($>$ 100-agent) swarms and live production trace replay over multi-region enterprise meshes.

REFERENCES

[1] J. C. Corbett, J. Dean, M. Epstein, A. Fikes, C. Frost, J. J. Furman, S. Ghemawat, A. Gubarev, C. Heiser, P. Hochschild, *et al.*, "Spanner: Google's globally distributed database," *ACM Transactions on Computer Systems (TOCS)*, vol. 31, no. 3, pp. 8:1–8:22, 2013.

[2] Anthropic, "Model context protocol specification," *Anthropic Technical Specification*, 2024. [Online]. Available: https://modelcontextprotocol.io

[3] Google, "Agent2Agent (A2A) protocol specification," *Google Cloud Architecture Center*, 2025. [Online]. Available: https://google.github.io/A2A/

[4] H. Garcia-Molina and K. Salem, "Sagas," in *Proc. ACM SIGMOD International Conference on Management of Data*, 1987, pp. 249–259.

[5] L. Lamport, "Time, clocks, and the ordering of events in a distributed system," *Communications of the ACM*, vol. 21, no. 7, pp. 558–565, 1978.

[6] C. J. Fidge, "Timestamps in message-passing systems that preserve the partial ordering," in *Proc. 11th Australian Computer Science Conf. (ACSC)*, vol. 10, no. 1, 1988, pp. 56–66.

[7] F. Mattern, "Virtual time and global states of distributed systems," in *Proc. Int. Workshop Parallel and Distributed Algorithms*, 1988, pp. 215–226.

[8] S. S. Kulkarni, M. Demirbas, D. Madappa, B. Avva, and M. Leone, "Logical physical clocks and consistent snapshots in globally distributed databases," in *Proc. Int. Conf. Principles of Distributed Systems (OPODIS)*, 2014, pp. 17–32.

[9] M. P. Herlihy and J. M. Wing, "Linearizability: A correctness condition for concurrent objects," *ACM Transactions on Programming Languages and Systems (TOPLAS)*, vol. 12, no. 3, pp. 463–492, 1990.

[10] E. B. Nightingale, P. M. Chen, and J. Flinn, "Speculative execution in a distributed file system," in *Proc. 20th ACM Symp. Operating Systems Principles (SOSP), ACM SIGOPS Operating Systems Review*, vol. 39, no. 5, 2005, pp. 191–205.

[11] A. Saeed, N. Dukkipati, V. Valancius, V. T. Lam, C. Contavalli, and A. Vahdat, "Carousel: Scalable traffic shaping at end hosts," in *Proc. ACM Special Interest Group on Data Communication (SIGCOMM)*, 2017, pp. 404–417.

[12] S. Radhakrishnan, Y. Geng, V. Jeyakumar, A. Kabbani, G. Porter, and A. Vahdat, "SENIC: Scalable NIC for end-host rate limiting," in *Proc. 11th USENIX Symp. Networked Systems Design and Implementation (NSDI)*, 2014, pp. 475–488.

[13] S. G. Patil, T. Zhang, V. Fang, N. Chaurasia, R. Huang, A. Hao, M. Casado, J. E. Gonzalez, R. A. Popa, and I. Stoica, "GoEX: Perspectives and designs towards a runtime for autonomous LLM applications," *arXiv preprint arXiv:2404.06921*, 2024.

[14] E. Y. Chang and L. Geng, "SagaLLM: Context management, validation, and transaction guarantees for multi-agent LLM planning," *Proceedings of the VLDB Endowment (Proc. VLDB Endow.)*, vol. 18, 2025.

[15] S. Yao, N. Shinn, P. Razavi, and K. Narasimhan, "τ-bench: A benchmark for tool-agent-user interaction in real-world domains," *arXiv preprint arXiv:2406.12045*, 2024.

[16] N. Ye, A. Ahuja, G. Liargkovas, Y. Lu, K. Kaffes, and T. Peng, "Speculative Actions: A lossless framework for faster agentic systems," *arXiv preprint arXiv:2510.04371*, 2025.

[17] Y. Ro, H. Qiu, Z. Wang, E. Choukse, R. Fonseca, R. Bianchini, A. Akella, and M. Erez, "Sherlock: Reliable and efficient agentic workflow execution," *arXiv preprint arXiv:2511.00330*, 2025.

[18] B. Mohammadi, A. Arora, G. Potamitis, V. Klein, and L. Bindschaedler, "Atomix: Timely, transactional tool use for reliable agentic workflows," *arXiv preprint arXiv:2602.14849*, 2026.

[19] L. Geng and E. Y. Chang, "ALAS: Transactional and Dynamic Multi-Agent LLM Planning," *arXiv preprint arXiv:2511.03094*, 2025.