

# Feedback — Interview Questions: Priority Queues

You submitted this homework on **Sun 24 Mar 2013 2:27 PM PDT -0700**. You will be able to view your score after the deadline passes.

These interview questions are for your own enrichment and are not assessed. If you click the *Submit Answers* button, you will get a hint.

## Question 1

**Dynamic median.** Design a data type that supports insert in logarithmic time, find-the-median in constant time, and remove-the-median in logarithmic time.

Your Answer	Score	Explanation
Total	0.00 / 0.00	

### Question Explanation

*Hint:* maintain *two* binary heaps, one that is max-oriented and one that is min-oriented.

## Question 2

**Randomized priority queue.** Describe how to add the methods `sample()` and `delRandom()` to our binary heap implementation. The two methods return a key that is chosen uniformly at random among the remaining keys, with the latter method also removing that key. The `sample()` method should take constant time; the `delRandom()` method should take logarithmic time. Do not worry about resizing the underlying array.

Your Answer	Score	Explanation
Total	0.00 / 0.00	

## Question 3

**Taxicab numbers.** A *taxicab* number is an integer that can be expressed as the sum of two cubes of integers in two different ways:  $a^3 + b^3 = c^3 + d^3$ . For example,  $1729 = 9^3 + 10^3 = 1^3 + 12^3$ . Design an algorithm to find all taxicab numbers with  $a$ ,  $b$ ,  $c$ , and  $d$  less than  $N$ .

- *Version 1:* Use time proportional to  $N^2 \log N$  and space proportional to  $N^2$ .
- *Version 2:* Use time proportional to  $N^2 \log N$  and space proportional to  $N$ .

Your Answer	Score	Explanation
Total	0.00 / 0.00	

### Question Explanation

*Hints:*

- *Version 1:* Form the sums  $a^3 + b^3$  and sort.

- *Version 2:* Use a min-oriented priority queue with  $N$  items.
-