

[CENG 315 All Sections] Algorithms

[Dashboard](#) / [My courses](#) / [571 - Computer Engineering](#) / [CENG 315 All Sections](#) / [November 14 - November 20](#) / [THE4](#)

Description

Submission

Edit

Submission view

THE4

Available from: Friday, November 18, 2022, 11:59 AM **Due date:** Saturday, November 19, 2022, 11:59 PM **Requested files:** the4.cpp, test.cpp ([Download](#))**Type of work:** Individual workProblem:

In this exam, you are given two 2D boxes consisting of full and empty cells. The goal is to convert the first box into the second with the minimum cost of operations (the operations are defined below). The boxes are represented as 2D char arrays. In the arguments, both boxes will be defined to include the same number of rows, yet the number of their columns may be different. For instance, Box-1 can be an array of the size of 10x12 whereas Box-2 can be an array of the size of 10x15. In order to represent empty cells, '-' character is used and for the full cells a letter is used. In the figure below, a few input box illustrations are given:

<div>(a)</div> <div><div>BOX-1</div><div><div>M</div><div>R</div><div>V</div><div>-</div></div><div>A box defined as an array of 4x1</div></div>	<div><div>BOX-2</div><div><div><div>-</div><div>M</div><div>V</div></div><div><div>M</div><div>-</div><div>M</div></div><div><div>R</div><div>-</div><div>R</div></div><div><div>V</div><div>R</div><div>-</div></div></div><div>A box defined as an array of 4x3</div></div>	<div><div>Resulting mem</div><div><div><div>0</div><div>3</div><div>5</div><div>8</div></div><div><div>3</div><div>4</div><div>6</div><div>8</div></div></div></div>
<div><div>(b)</div><div><div>BOX-1</div><div><div><div>-</div><div>B</div><div>C</div></div><div><div>B</div><div>-</div><div>C</div></div></div><div>A box defined as an array of 2x3</div></div></div>	<div><div><div>BOX-2</div><div><div><div>A</div><div>-</div><div>C</div><div>A</div><div>B</div></div><div><div>-</div><div>C</div><div>C</div><div>A</div><div>-</div></div></div><div>A box defined as an array of 2x5</div></div></div>	<div><div><div>Resulting mem</div><div><div><div>0</div><div>1</div><div>2</div><div>4</div><div>6</div><div>7</div></div><div><div>1</div><div>2</div><div>2</div><div>4</div><div>6</div><div>7</div></div><div><div>2</div><div>2</div><div>3</div><div>5</div><div>7</div><div>6</div></div><div><div>4</div><div>4</div><div>4</div><div>3</div><div>5</div><div>6</div></div></div></div></div>
<div><div><div>(c)</div><div><div>BOX-1</div><div><div><div>A</div><div>A</div><div>C</div><div>B</div><div>-</div></div><div><div>B</div><div>C</div><div>-</div><div>-</div><div>A</div></div><div><div>A</div><div>C</div><div>-</div><div>A</div><div>-</div></div><div><div>-</div><div>C</div><div>-</div><div>-</div><div>C</div></div></div><div>A box defined as an array of 4x5</div></div></div></div>	<div><div><div>BOX-2</div><div><div><div>A</div><div>C</div><div>B</div><div>-</div><div>A</div><div>B</div><div>A</div></div><div><div>B</div><div>A</div><div>B</div><div>-</div><div>C</div><div>-</div><div>C</div></div><div><div>B</div><div>-</div><div>-</div><div>A</div><div>C</div><div>A</div><div>B</div></div><div><div>C</div><div>-</div><div>B</div><div>-</div><div>B</div><div>A</div><div>B</div></div></div><div>A box defined as an array of 4x7</div></div></div>	<div><div><div>Resulting mem</div><div><div><div>0</div><div>4</div><div>6</div><div>9</div><div>10</div><div>14</div><div>17</div><div>21</div></div><div><div>3</div><div>3</div><div>5</div><div>8</div><div>9</div><div>13</div><div>16</div><div>20</div></div><div><div>7</div><div>5</div><div>7</div><div>10</div><div>11</div><div>10</div><div>13</div><div>17</div></div><div><div>8</div><div>6</div><div>7</div><div>10</div><div>11</div><div>11</div><div>14</div><div>18</div></div><div><div>10</div><div>8</div><div>9</div><div>12</div><div>12</div><div>13</div><div>13</div><div>17</div></div><div><div>12</div><div>10</div><div>10</div><div>13</div><div>14</div><div>15</div><div>15</div><div>19</div></div></div></div></div>

(d)	<div>BOX-1</div> <table><tr><td>-</td><td>Y</td><td>W</td><td>Y</td><td>-</td><td>-</td></tr><tr><td>-</td><td>Z</td><td>Y</td><td>Y</td><td>-</td><td>W</td></tr><tr><td>W</td><td>Y</td><td>Z</td><td>Y</td><td>-</td><td>-</td></tr><tr><td>W</td><td>W</td><td>-</td><td>Y</td><td>-</td><td>Y</td></tr><tr><td>-</td><td>Z</td><td>-</td><td>-</td><td>Z</td><td>Z</td></tr></table> <div>A box defined as an array of 5x6</div>	-	Y	W	Y	-	-	-	Z	Y	Y	-	W	W	Y	Z	Y	-	-	W	W	-	Y	-	Y	-	Z	-	-	Z	Z	<div>BOX-2</div> <table><tr><td>Z</td><td>W</td><td>-</td></tr><tr><td>W</td><td>Y</td><td>-</td></tr><tr><td>Y</td><td>Z</td><td>Y</td></tr><tr><td>-</td><td>Z</td><td>-</td></tr><tr><td>-</td><td>-</td><td>-</td></tr></table> <div>A box defined as an array of 5x3</div>	Z	W	-	W	Y	-	Y	Z	Y	-	Z	-	-	-	-	<div>Resulting mem</div> <table><tr><td>0</td><td>3</td><td>7</td><td>8</td></tr><tr><td>2</td><td>5</td><td>9</td><td>10</td></tr><tr><td>7</td><td>8</td><td>11</td><td>12</td></tr><tr><td>10</td><td>10</td><td>10</td><td>11</td></tr><tr><td>14</td><td>14</td><td>13</td><td>14</td></tr><tr><td>15</td><td>15</td><td>14</td><td>15</td></tr><tr><td>18</td><td>18</td><td>17</td><td>18</td></tr></table>	0	3	7	8	2	5	9	10	7	8	11	12	10	10	10	11	14	14	13	14	15	15	14	15	18	18	17	18
	-	Y	W	Y	-	-																																																																						
	-	Z	Y	Y	-	W																																																																						
W	Y	Z	Y	-	-																																																																							
W	W	-	Y	-	Y																																																																							
-	Z	-	-	Z	Z																																																																							
Z	W	-																																																																										
W	Y	-																																																																										
Y	Z	Y																																																																										
-	Z	-																																																																										
-	-	-																																																																										
0	3	7	8																																																																									
2	5	9	10																																																																									
7	8	11	12																																																																									
10	10	10	11																																																																									
14	14	13	14																																																																									
15	15	14	15																																																																									
18	18	17	18																																																																									
(e)	<div>BOX-1</div> <table><tr><td>A</td><td>B</td><td>C</td><td>A</td><td>B</td><td>C</td></tr><tr><td>B</td><td>C</td><td>C</td><td>A</td><td>-</td><td>A</td></tr></table> <div>A box defined as an array of 2x6</div>	A	B	C	A	B	C	B	C	C	A	-	A	<div>BOX-2</div> <table><tr><td>A</td><td>B</td><td>B</td><td>A</td></tr><tr><td>B</td><td>A</td><td>-</td><td>C</td></tr></table> <div>A box defined as an array of 2x4</div>	A	B	B	A	B	A	-	C	<div>Resulting mem</div> <table><tr><td>0</td><td>2</td><td>4</td><td>5</td><td>7</td></tr><tr><td>2</td><td>0</td><td>2</td><td>3</td><td>5</td></tr><tr><td>4</td><td>2</td><td>1</td><td>2</td><td>4</td></tr><tr><td>6</td><td>4</td><td>3</td><td>4</td><td>3</td></tr><tr><td>8</td><td>6</td><td>5</td><td>6</td><td>5</td></tr><tr><td>9</td><td>7</td><td>6</td><td>5</td><td>6</td></tr><tr><td>11</td><td>9</td><td>8</td><td>7</td><td>7</td></tr></table>	0	2	4	5	7	2	0	2	3	5	4	2	1	2	4	6	4	3	4	3	8	6	5	6	5	9	7	6	5	6	11	9	8	7	7																		
	A	B	C	A	B	C																																																																						
	B	C	C	A	-	A																																																																						
A	B	B	A																																																																									
B	A	-	C																																																																									
0	2	4	5	7																																																																								
2	0	2	3	5																																																																								
4	2	1	2	4																																																																								
6	4	3	4	3																																																																								
8	6	5	6	5																																																																								
9	7	6	5	6																																																																								
11	9	8	7	7																																																																								
(f)	<div>BOX-1</div> <table><tr><td>-</td><td>M</td><td>V</td><td>R</td></tr><tr><td>M</td><td>-</td><td>R</td><td>-</td></tr><tr><td>R</td><td>M</td><td>M</td><td>-</td></tr><tr><td>V</td><td>M</td><td>-</td><td>R</td></tr></table> <div>A box defined as an array of 4x4</div>	-	M	V	R	M	-	R	-	R	M	M	-	V	M	-	R	<div>BOX-2</div> <table><tr><td>M</td><td>-</td><td>-</td><td>V</td></tr><tr><td>V</td><td>R</td><td>R</td><td>M</td></tr><tr><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-</td><td>M</td><td>-</td><td>R</td></tr></table> <div>A box defined as an array of 4x4</div>	M	-	-	V	V	R	R	M	-	-	-	-	-	M	-	R	<div>Resulting mem</div> <table><tr><td>0</td><td>2</td><td>4</td><td>5</td><td>8</td></tr><tr><td>3</td><td>5</td><td>6</td><td>7</td><td>8</td></tr><tr><td>6</td><td>8</td><td>9</td><td>10</td><td>11</td></tr><tr><td>9</td><td>10</td><td>12</td><td>13</td><td>13</td></tr><tr><td>11</td><td>12</td><td>14</td><td>15</td><td>15</td></tr></table>	0	2	4	5	8	3	5	6	7	8	6	8	9	10	11	9	10	12	13	13	11	12	14	15	15																
	-	M	V	R																																																																								
	M	-	R	-																																																																								
R	M	M	-																																																																									
V	M	-	R																																																																									
M	-	-	V																																																																									
V	R	R	M																																																																									
-	-	-	-																																																																									
-	M	-	R																																																																									
0	2	4	5	8																																																																								
3	5	6	7	8																																																																								
6	8	9	10	11																																																																								
9	10	12	13	13																																																																								
11	12	14	15	15																																																																								

Your task is to convert the first box into the second box by using some operations resulting in the minimum cost. The conversion rules and operations are defined as follows:

- You should compare the boxes column by column. Each conversion operation is column-wise.
- A column could be deleted completely. The **deletion operation** costs as much as the number of full cells in the column. For instance; if the column consists of 5 cells where 3 of them full and 2 of them are empty, then deleting that column costs 3 units.
- For a column of Box-2, a new corresponding column could be inserted into Box-1 at any location (between two columns or as the initial column or as the final column). The **insertion operation** costs as much as the number of full cells inside the new column. For instance; if the newly inserted column consists of 5 cells where 3 of them full and 2 of them are empty, then inserting that column costs 3 units.
- A column could be converted into a new column by reordering its cells. For instance, if a column consists of 5 cells including ['X', 'A', '-', 'B', '-'], it can be reordered as ['A', '-', '-', 'B', 'X']. The **reordering operation** costs as much as the number of cells whose locations are changed. For the example given, since the locations of the cells including 'A', 'X' and '-' changed only, it costs 3 units.
- A column could be converted into a new column by replacing its cells with some other cells. For the **replacement operation**, if a full cell is replaced with some other full cell, then it costs 1 unit. However, if an empty cell is replaced with a full cell, or vice versa, then it costs 2 units. For instance, if a column consists of 5 cells including ['X', 'A', '-', 'B', '-'], its cells can be replaced as ['X', 'C', 'D', '-', '-'], it costs <change from 'A' to 'C'> + <change from '-' to 'D'> + <change from 'B' to '-'> = 1 + 2 + 2 = 5 units.
- Each operation is independent from each other. At each transition, apply only one of them.
- HINT:** You should implement the dynamic programming column-wise. That is, for each column of Box-2, consider a corresponding column inside Box-1 which has been obtained by the operations above. The way of how to apply memoization is explained in the following parts.

Example IO:

1) Given boxes in (a) of the above Figure:

- return value (i.e. min cost) is 8.
- Since this is the first example, let's explain all the cells of mem array:

mem[0][0] : Conversion of no columns of box1 to no columns of box2
No operation
=> costs 0

mem[0][1] : Conversion of no columns of box1 to first column of box2
Apply insertion operation to obtain the first column of box2
=> costs 3

mem[0][2] : Conversion of no columns of box1 to first 2 columns of box2
Apply insertion operation for both of the first two columns of box2
=> costs $3 + 2 = 5$

mem[0][3] : Conversion of no columns of box1 to first 3 columns of box2
Apply insertion operation for each of the 3 columns of box2
=> costs $3 + 2 + 3 = 8$

mem[1][0] : Conversion of first column of box1 to no columns of box2
Apply deletion operation on the initial column of box1
=> costs 3

mem[1][1] : Conversion of first column of box1 to first column of box2
Apply reordering operation to change the first column of box1 to the first column of box2
=> costs 4

mem[1][2] : Conversion of first column of box1 to first 2 columns of box2
Apply reordering operation to change the first column of box1 to the first column of box2 and
Apply insertion operation to obtain the second column of box2
=> costs $4 + 2 = 6$

mem[1][3] : Conversion of first column of box1 to first 3 columns of box2
Apply insertion operation to obtain the first column of box2 and
Apply insertion operation to obtain the second column of box2 and
Apply reordering operation to change the first column of box1 to the third column of box2
=> costs $3 + 2 + 3 = 8$

2) Given boxes in (b) of the above Figure:

- return value (i.e. min cost) is 6.
- at dynamic programming, final mem array is given its right side.

3) Given boxes in (c) of the above Figure:

- return value (i.e. min cost) is 19.
- at dynamic programming, final mem array is given its right side.

4) Given boxes in (d) of the above Figure:

- return value (i.e. min cost) is 18.
- at dynamic programming, final mem array is given its right side.

5) Given boxes in (e) of the above Figure:

- return value (i.e. min cost) is 7.
- at dynamic programming, final mem array is given its right side.

6) Given boxes in (f) of the above Figure:

- return value (i.e. min cost) is 15.
- at dynamic programming, final mem array is given its right side.

Implementation:

You will implement only one function for solution of that problem:

- Dynamic programming in **dp_sln()**

The function is expected to **return** the answer to the given problem which is **the minimum cost of operations**. Return **only** the min cost value and nothing more.

The **`char**& box1`** and **`char**& box2`** variables are the parameters which pass the input 2D array of boxes to your functions. **Do not modify those arrays!** The format of boxes will be as stated in the problem definition above.

The **`int nrow`**, **`int ncol1`** and **`int ncol2`** variables are the parameters which passes the number of rows of both boxes, number of columns of **`box1`** and number of columns of **`box2`**, respectively, to your function.

You should use **`int**& mem`** variable (i.e. array), which is the last parameter at definition of the function, as **the array of memoized values**. For **`dp_sln()`** function, final values in the **`mem`** variable will be considered for grading. Note that it is a 2D array. It is defined as **the size of $(ncol1+1) \times (ncol2+1)$** such that its rows correspond to columns of **`box1`** and its columns correspond to columns of **`box2`**. **That is, the `mem[i][j]` will be used to indicate the TOTAL COST of matching of THE FIRST i columns of `box1` with THE FIRST j columns of `box2`.** Thus **`mem[0][0]`** indicates there is no matching columns in **`box1`** and **`box2`**! While testing and grading, all the cells of **`mem`** array will be initialized to -1's. So, while implementing your function, **you can assume that `mem` is an array of array of -1's. Do not return that variable/array.**

The **`dp_sln()`** function should be implemented with bottom-up (iterative) approach.

Implement the function in most efficient way.

Constraints:

- Maximum number of rows and columns of boxes will be **100**.

Evaluation:

- After your exam, black box evaluation will be carried out. You will get full points if
 - your functions return the correct min cost
 - and you fill the **`mem`** array correctly, as stated.
 - you did not change the input arrays (the array of boxes).

Specifications:

- There is **1 task** to be solved in **12 hours** in this take home exam.
- You will implement your solution in **`the4.cpp`** file.
- Do **not** change the first line of **`the4.cpp`**, which is **`#include "the4.h"`**
- `<iostream>`**, **`<climits>`**, **`<cmath>`**, **`<stdlib>`** are included in "the4.h" for your convenience.
- Do **not** change the arguments and return **type** of the function **`dp_sln()`** in the file **`the4.cpp`**. (You should change return **value**, on the other hand.)
- Do **not** include any other library or write include anywhere in your **`the4.cpp`** file (not even in comments).
- Do **not** write any helper method.

Compilation:

- You are given **`test.cpp`** file to **test** your work on **ODTÜClass** or your **locale**. You can and you are encouraged to modify this file to add different test cases.
- If you want to **test** your work and see your outputs you can **compile and run** your work on your locale as:

```
>g++ test.cpp the4.cpp -Wall -std=c++11 -o test
> ./test
```

- You can test your **`the4.cpp`** on virtual lab environment. If you click **run**, your function will be compiled and executed with **`test.cpp`**. If you click **evaluate**, you will get a feedback for your current work and your work will be **temporarily** graded for **limited** number of inputs.
- The grade you see in lab is **not** your final grade, your code will be re-evaluated with **completely different** inputs after the exam.

The system has the following limits:

- a maximum execution time of 32 seconds
- a 192 MB maximum memory limit
- an execution file size of 1M.
- Solutions with longer running times will not be graded.
- If you are sure that your solution works in the expected complexity constraints but your evaluation fails due to limits in the lab environment, the constant factors may be the problem.

```
int dp_sln(char**& arr1, char**& arr2, int nrow, int ncol1, int ncol2, int**& mem);
```

Requested files

the4.cpp

```
1  #include "the4.h"
2
3
4  int dp_sln(char**& arr1, char**& arr2, int nrow, int ncol1, int ncol2, int**& mem){ //dynamic programming
5
6      //your code here
7
8      return 0; // this is a dummy return value. YOU SHOULD CHANGE THIS!
9  }
10
11
```

test.cpp

```

1  // this file is for you for testing purposes, it won't be included in evaluation.
2
3  #include <iostream>
4  #include <random>
5  #include <ctime>
6  #include <cstdlib>
7  #include <algorithm>
8  #include <vector>
9  #include "the4.h"
10
11 char getRandomChar(){
12     char r = rand() % 5 + 65;
13     return r;
14 }
15
16
17 void randomArray(char**& box1, char**& box2, int nrow, int ncol1, int ncol2)
18 {
19     box1 = new char* [nrow];
20     box2 = new char* [nrow];
21     std::vector<char> column;
22
23     for (int i = 0; i < nrow; i++) {
24         box1[i] = new char [ncol1];
25         box2[i] = new char [ncol2];
26     }
27
28     for (int i = 0; i < ncol1; i++)
29     {
30         int nfull = rand() % nrow + 1;
31         for (int j = 0; j < nfull; j++) {
32             char r = getRandomChar();
33             column.push_back(r);
34         }
35         for (int j = nfull; j < nrow; j++) {
36             column.push_back('-');
37         }
38         std::random_shuffle(column.begin(), column.end());
39         for (int j = 0; j < nrow; j++)
40             box1[j][i] = column[j];
41         column.clear();
42     }
43
44     for (int i = 0; i < ncol2; i++)
45     {
46         int nfull = rand() % nrow + 1;
47         for (int j = 0; j < nfull; j++) {
48             char r = getRandomChar();
49             column.push_back(r);
50         }
51         for (int j = nfull; j < nrow; j++) {
52             column.push_back('-');
53         }
54         std::random_shuffle(column.begin(), column.end());
55         for (int j = 0; j < nrow; j++)
56             box2[j][i] = column[j];
57     }
58 }
59
60
61 void printArrayInLine(char** arr, int nrow, int ncol){
62     std::cout << "[ ";
63     for(int i = 0; i < nrow; i++){
64         std::cout << "[";
65         for (int j = 0; j < ncol; j++) {
66             std::cout << arr[i][j];
67             if (j == ncol - 1)
68                 std::cout << "]";
69             else
70                 std::cout << ", ";
71         }
72         if (i == nrow - 1)
73             std::cout << " ]" << std::endl;
74         else
75             std::cout << ",\n";
76     }
77 }
78
79
80 void printMemInLine(int** arr, int nrow, int ncol){
81     std::cout << "[ ";
82     for(int i = 0; i < nrow; i++){
83         std::cout << "[";
84         for (int j = 0; j < ncol; j++) {
85             std::cout << arr[i][j];
86             if (j == ncol - 1)
87                 std::cout << "]";
88             else
89                 std::cout << ", ";
90         }
91         if (i == nrow - 1)
92             std::cout << " ]" << std::endl;
93         else
94             std::cout << ",\n";
95     }
96 }
97
98
99 void fillArray(char**& box1, char**& box2, int nrow, int ncol1, int ncol2)
100 {
101
102     box1 = new char* [nrow];
103     box2 = new char* [nrow];
104
105

```

```

104
105     for (int i = 0; i < nrow; i++) {
106         box1[i] = new char [ncol1];
107         box2[i] = new char [ncol2];
108     }
109
110     // "DO NOT FORGET TO CHANGE THE nrow, ncol1, ncol2 VALUES AT THE BEGINNING OF test() METHOD!!!!!!"
111     // EXAMPLE (a)
112
113     box1[0][0] = 'M';
114     box1[1][0] = 'R';
115     box1[2][0] = 'V';
116     box1[3][0] = '-';
117
118     box2[0][0] = '-'; box2[0][1] = 'M'; box2[0][2] = 'V';
119     box2[1][0] = 'M'; box2[1][1] = '-'; box2[1][2] = 'M';
120     box2[2][0] = 'R'; box2[2][1] = '-'; box2[2][2] = 'R';
121     box2[3][0] = 'V'; box2[3][1] = 'R'; box2[3][2] = '-';
122
123
124     // "DO NOT FORGET TO CHANGE THE nrow, ncol1, ncol2 VALUES AT THE BEGINNING OF test() METHOD!!!!!!"
125     // EXAMPLE (b)
126     /*
127     box1[0][0] = '-'; box1[0][1] = 'B'; box1[0][2] = 'C';
128     box1[1][0] = 'B'; box1[1][1] = '-'; box1[1][2] = 'C';
129
130     box2[0][0] = 'A'; box2[0][1] = '-'; box2[0][2] = 'C'; box2[0][3] = 'A'; box2[0][4] = 'B';
131     box2[1][0] = '-'; box2[1][1] = 'C'; box2[1][2] = 'C'; box2[1][3] = 'A'; box2[1][4] = '-';
132     */
133
134     // "DO NOT FORGET TO CHANGE THE nrow, ncol1, ncol2 VALUES AT THE BEGINNING OF test() METHOD!!!!!!"
135     // EXAMPLE (c)
136     /*
137     box1[0][0] = 'A'; box1[0][1] = 'A'; box1[0][2] = 'C'; box1[0][3] = 'B'; box1[0][4] = '-';
138     box1[1][0] = 'B'; box1[1][1] = 'C'; box1[1][2] = '-'; box1[1][3] = '-'; box1[1][4] = 'A';
139     box1[2][0] = 'A'; box1[2][1] = 'C'; box1[2][2] = '-'; box1[2][3] = 'A'; box1[2][4] = '-';
140     box1[3][0] = '-'; box1[3][1] = 'C'; box1[3][2] = '-'; box1[3][3] = '-'; box1[3][4] = 'C';
141
142     box2[0][0] = 'A'; box2[0][1] = 'C'; box2[0][2] = 'B'; box2[0][3] = '-'; box2[0][4] = 'A'; box2[0][5] = 'B'; box2[0][6] = 'A';
143     box2[1][0] = 'B'; box2[1][1] = 'A'; box2[1][2] = 'B'; box2[1][3] = '-'; box2[1][4] = 'C'; box2[1][5] = '-'; box2[1][6] = 'C';
144     box2[2][0] = 'B'; box2[2][1] = '-'; box2[2][2] = '-'; box2[2][3] = 'A'; box2[2][4] = 'C'; box2[2][5] = 'A'; box2[2][6] = 'B';
145     box2[3][0] = 'C'; box2[3][1] = '-'; box2[3][2] = 'B'; box2[3][3] = '-'; box2[3][4] = 'B'; box2[3][5] = 'A'; box2[3][6] = 'B';
146     */
147
148     // "DO NOT FORGET TO CHANGE THE nrow, ncol1, ncol2 VALUES AT THE BEGINNING OF test() METHOD!!!!!!"
149     // EXAMPLE (d)
150     /*
151     box1[0][0] = '-'; box1[0][1] = 'Y'; box1[0][2] = 'W'; box1[0][3] = 'Y'; box1[0][4] = '-'; box1[0][5] = '-';
152     box1[1][0] = '-'; box1[1][1] = 'Z'; box1[1][2] = 'Y'; box1[1][3] = 'Y'; box1[1][4] = '-'; box1[1][5] = 'W';
153     box1[2][0] = 'W'; box1[2][1] = 'Y'; box1[2][2] = 'Z'; box1[2][3] = 'Y'; box1[2][4] = '-'; box1[2][5] = '-';
154     box1[3][0] = 'W'; box1[3][1] = 'W'; box1[3][2] = '-'; box1[3][3] = 'Y'; box1[3][4] = '-'; box1[3][5] = 'Y';
155     box1[4][0] = '-'; box1[4][1] = 'Z'; box1[4][2] = '-'; box1[4][3] = '-'; box1[4][4] = 'Z'; box1[4][5] = 'Z';
156
157     box2[0][0] = 'Z'; box2[0][1] = 'W'; box2[0][2] = '-';
158     box2[1][0] = 'W'; box2[1][1] = 'Y'; box2[1][2] = '-';
159     box2[2][0] = 'Y'; box2[2][1] = 'Z'; box2[2][2] = 'Y';
160     box2[3][0] = '-'; box2[3][1] = 'Z'; box2[3][2] = '-';
161     box2[4][0] = '-'; box2[4][1] = '-'; box2[4][2] = '-';
162     */
163
164     // "DO NOT FORGET TO CHANGE THE nrow, ncol1, ncol2 VALUES AT THE BEGINNING OF test() METHOD!!!!!!"
165     // EXAMPLE (e)
166     /*
167     box1[0][0] = 'A'; box1[0][1] = 'B'; box1[0][2] = 'C'; box1[0][3] = 'A'; box1[0][4] = 'B'; box1[0][5] = 'C';
168     box1[1][0] = 'B'; box1[1][1] = 'C'; box1[1][2] = 'C'; box1[1][3] = 'A'; box1[1][4] = '-'; box1[1][5] = 'A';
169
170     box2[0][0] = 'A'; box2[0][1] = 'B'; box2[0][2] = 'B'; box2[0][3] = 'A';
171     box2[1][0] = 'B'; box2[1][1] = 'A'; box2[1][2] = '-'; box2[1][3] = 'C';
172     */
173
174     // "DO NOT FORGET TO CHANGE THE nrow, ncol1, ncol2 VALUES AT THE BEGINNING OF test() METHOD!!!!!!"
175     // EXAMPLE (f)
176     /*
177     box1[0][0] = '-'; box1[0][1] = 'M'; box1[0][2] = 'V'; box1[0][3] = 'R';
178     box1[1][0] = 'M'; box1[1][1] = '-'; box1[1][2] = 'R'; box1[1][3] = '-';
179     box1[2][0] = 'R'; box1[2][1] = 'M'; box1[2][2] = 'M'; box1[2][3] = '-';
180     box1[3][0] = 'V'; box1[3][1] = 'M'; box1[3][2] = '-'; box1[3][3] = 'R';
181
182     box2[0][0] = 'M'; box2[0][1] = '-'; box2[0][2] = '-'; box2[0][3] = 'V';
183     box2[1][0] = 'V'; box2[1][1] = 'R'; box2[1][2] = 'R'; box2[1][3] = 'M';
184     box2[2][0] = '-'; box2[2][1] = '-'; box2[2][2] = '-'; box2[2][3] = '-';
185     box2[3][0] = '-'; box2[3][1] = 'M'; box2[3][2] = '-'; box2[3][3] = 'R';
186     */
187
188 }
189
190
191 void test(){
192     clock_t begin, end;
193     double duration;
194     int min_cost_dp;
195
196
197     int nrow = 4;        // max 100
198     int ncol1 = 1;       // max 100
199     int ncol2 = 3;       // max 100
200     char** box1, ** box2;
201     //randomArray(box1, box2, nrow, ncol1, ncol2);
202     fillArray(box1, box2, nrow, ncol1, ncol2);
203     std::cout << "BOX-1:" << std::endl;
204     printArrayInLine(box1, nrow, ncol1);
205     std::cout << "\nBOX-2:" << std::endl;
206     printArrayInLine(box2, nrow, ncol2);
207     std::cout << "\n\n";

```

```

207     cout << "VPL" << endl;
208
209     int** mem = new int*[ncol1+1];
210
211     for(int i = 0; i <= ncol1; i++){
212         mem[i] = new int [ncol2+1];
213         for (int j = 0; j <= ncol2; j++)
214             mem[i][j] = -1;
215     }
216
217
218
219     std::cout << " _____ DYNAMIC PROGRAMMING: _____ " << std::endl;
220
221     for(int i = 0; i <= ncol1; i++){
222         for (int j = 0; j <= ncol2; j++)
223             mem[i][j] = -1;
224     }
225
226
227     if ((begin = clock() ) == -1)
228         std::cerr << "clock error" << std::endl;
229
230     min_cost_dp = dp_sln(box1, box2, nrow, ncol1, ncol2, mem);
231
232     if ((end = clock() ) == -1)
233         std::cerr << "clock error" << std::endl;
234
235     duration = ((double) end - begin) / CLOCKS_PER_SEC;
236     std::cout << "Duration: " << duration << " seconds." << std::endl;
237
238     std::cout << "Min cost: " << min_cost_dp << std::endl;
239     std::cout << "Final mem: " << std::endl;
240     printMemInline(mem, ncol1+1, ncol2+1);
241
242     std::cout << "-----";
243     std::cout << "\n" << std::endl;
244
245 }
246
247 int main()
248 {
249     srand(time(0));
250     test();
251     return 0;
252 }
253

```

[VPL](#)

You are logged in as anil eren gocer (Log out)

CENG 315 All Sections

ODTÜClass Archive

2021-2022 Summer

2021-2022 Spring

2021-2022 Fall

2020-2021 Summer

2020-2021 Spring

2020-2021 Fall

2019-2020 Summer

2019-2020 Spring

2019-2020 Fall

Class Archive

ODTÜClass 2021-2022 Summer School

Get the mobile app

