

Audio Transmission And Reception over RF

Final MTP Phase-II
Electronics System

Anil Kumar Garg (173074018)

under the guidance of
Prof. Shalabh Gupta



Department of Electrical Engineering
Indian Institute of Technology, Bombay.

Jun30 ,2020

Introduction

- ① Access for gradually tapered spaces like ground tunnels and enemy occupied buildings is very difficult.
- ② For solving this problem, a camera and audio receiver is mounted on trained animal.
- ③ Camera captures the images and sends back to the control center.
- ④ Control center sends the audio command to the animal via transmitter to receiver.
- ⑤ Trained animal performs the action as per command



Motivation

Problem??

- ① ADC Resolution: 12bits (Need 2 bytes to store the sampled value)
- ② Considering ADC sampling rate 8000 samples/sec
- ③ For 100 samples, capturing time is : 12.5 msec ($100 \times 125 \mu \text{ sec}$)
- ④ Considering RF data Transmitting bit Rate (symbol rate): 50 kbps
- ⑤ If consider 14 bytes RF frame overheads then time required to transmit one RF packet : 34.2 msec [$\frac{214 \times 8}{50000}$]
- ⑥ **Transmitting time > Sampled capturing time**

Real time data transmission is not possible

Motivation

Solution??

- ① ADC Resolution: 12bits (Need 2 bytes to store the sampled value)
- ② Considering ADC sampling rate 8000 samples/sec
- ③ For 100 samples, capturing time is : 12.5 msec ($100 \times 125 \mu \text{ sec}$)
- ④ Considering RF data Transmitting bit Rate (symbol rate): 50 kbps
- ⑤ Apply compression technique and convert 16 bits data into 4 bits encoded signal.
- ⑥ If consider 14 bytes RF frame overheads then time required to transmit one RF packet : 10.56 msec [$\frac{66 \times 8}{50000}$]
- ⑦ **Transmitting time < Sampled capturing time**

Real time data transmission is now possible

Motivation

Proposal

- ① For one to one data transfer from transmitter to receiver, symbol rate is required 200 kbps at 8000 sampling rate.
- ② Using the technique of **ADPCM**, same data can be transferred with symbol rate 50 kbps.
- ③ 75% reduction in communication data bit-rate for same performance.
- ④ Effective task handling and processor utilization is required during implementation.
- ⑤ Fast ADPCM encoder- decoder algorithm for ARM controller at lower operating speed.
- ⑥ Synchronization between transmitter and receiver.


MTP Phase-2 Activities

Completed


- ① ADPCM technique implementation and testing
- ② Implementation and testing at higher sampling rate (8kSPS)
- ③ Synchronization between transmitter and receiver
- ④ DAC interface with higher sampling
- ⑤ MIC interface and signal conditioning
- ⑥ Speaker interface with audio amplifier
- ⑦ Simulation and Prototype development
- ⑧ Design calculation and costing
- ⑨ Schematic design and BOM creation
- ⑩ Schematic design with automatic gain controller.
- ⑪ Testing and troubleshooting
- ⑫ Reporting, documentation and version control

System Block Diagram

Transmitter - Receiver



(a) Audio on RF Transmission



(b) Audio on RF Reception

Hardware Block Diagram

Transmitter




Figure: Audio on RF Transmission

Hardware Block Diagram

Receiver





Figure: Audio on RF Reception

Software Architecture

Transmitter and Receiver

- ① For Radio interface **RF Simplelink proprietary TI library** is used.
- ② **ADPCM** technique is used for data compression and expansion.
- ③ **noRTOS** for avoiding extra processor overheads.
- ④ **DMA ping pong** mechanism for peripheral data transmission for better processor utilization.
- ⑤ **SmartRF studio** for RF command configuration.
- ⑥ Simultaneous processing of RF , main and sensor core.

Software Architecture



RF Frame

EasyLink API reference and Frame Structure

RF Frame Transmission

- ① EasyLink layer is initialized by calling `EasyLink_init()`.
- ② TX is enabled by calling `EasyLink_transmitAsync()`
- ③ Entering TX can be immediate or scheduled
- ④ An Async operation can be cancelled with `EasyLink_abort()`

RF Frame Reception


- ① EasyLink layer is initialized by calling `EasyLink_init()`.
- ② RX is enabled by calling `EasyLink_receiveAsync()`
- ③ Entering RX can be immediate or scheduled
- ④ An Async operation can be cancelled with `EasyLink_abort()`

| Preamble | Syncword | Length | Address | Seq no | Code | Index | CRC |
|----------|----------|--------|---------|--------|------|-------|-----|
| 4B | 4B | 1B | 1B | 2B | 50B | 2B | 2B |


Analog Signal Conditioning

Schematic

- ① Input coupling capacitor for DC blocking and passing signal above freq 40 Hz
- ② A low pass filter of cutoff frequency 3 Khz in feedback circuit.
- ③ A 2V DC shift for uni-polar analog signal detection



(a) Mic Interfacing




(b) Frequency Response


Audio Amplifier and LC Filter

Schematic

- ① 12 bits resolution DAC with fast settling time $4.5 \mu\text{ sec}$
- ② TPA2005D1 Class D audio amplifier as audio driver with unity gain.
- ③ Audio amplifier and LC filter for pass-band frequency range 75 Hz to 4 kHz



(a) MCP4921 Interface




(b) Audio amplifier and LC filter

Adaptive Differential Pulse Code Modulation Technique


Code Generation and Decoding

- ① Inbuilt decoder in encoder logic
- ② Index and size of quantization is fixed in a table during the initialization.
- ③ Synchronization between encoder and decoder.




Data Flow Diagram

Transmitter



Data Flow Diagram

Receiver



Firmware Memory Utilization

Transmitter and Receiver

| Name | Origin | Length | Used | Unused | % Utilization |
|-------|----------|----------|----------|----------|---------------|
| FLASH | 00000000 | 00020000 | 0000ae4a | 000151b6 | 34% |
| SRAM | 20000000 | 00005000 | 000019b0 | 00003650 | 32% |

Table: Transmitter :CC1310 Memory utilization


| Name | Origin | Length | Used | Unused | % Utilization |
|-------|----------|----------|----------|----------|---------------|
| FLASH | 00000000 | 00020000 | 0000b02e | 00014fd2 | 34% |
| SRAM | 20000000 | 00005000 | 00001a50 | 000035b0 | 33% |

Table: Receiver :CC1310 Memory utilization

RF Range Test

Tested In Phase-1

- ① Testing is done on uncompressed signal (Without ADPCM)
- ② Able to detect signal up to -84.4 dbm as received signal strength indicator
- ③ Radio configuration and data testing has been done via **SmartRF studio** on fixed data stream.



Frequency: 868Mhz
Symbol rate: 50kbps
Deviation: 25 KHz
Rx filter BW: 96 kHz
Tx power : 14 dBm

Radio operation commands:

1. CMD_FS
2. CMD_PROP_RX
3. CMD_PROP_RADIO_DEV_SETUP

Average RSSI: -84.4 dBm
Received OK: 100
Received not OK: 0
Packet error rate: 0.0%
Bit error rate: 0.00%

RF Range Test

Tested In Phase-1



- ① Range has been checked **H7 Canteen and convocation hall** inside IITB campus.
- ② Testing has been done via **SmartRF studio** on fixed data stream.
- ③ Google map and GPS error is excluded in range value




Test Setup

Analog Input vs ADC output


- ① 12 bits ADC resolution with internal ref voltage 4.3V.
- ② Fast ADC conversion time : $5 \mu\text{seconds}$



(a) ADC with DC



(b) ADC with AC





Prototype Testing

Transmitter Analog Input vs Receiver DAC output

- ① Data captured at ADC sampling frequency 4kHz without delta modulation.
 - ② ADC Input frequency: 1kHz @ $2V_{PP}$
 - ③ DAC output frequency:
1.004kHz @ $1.52V_{PP}$



 - ① ADC Input frequency: 50Hz @ $2V_{PP}$
 - ② DAC output frequency: 50.2Hz @ $1.64V_{PP}$



Prototype Testing

Transmitter Analog Input vs Receiver DAC output


- ① Data captured at ADC sampling frequency 4kHz without delta modulation.
- ② ADC Input frequency: 500Hz @ $2V_{PP}$
- ③ DAC output frequency: .502kHz @ $1.64V_{PP}$
- ④ Input to output delay is 46 msec @4kSPS sampling rate.
- ⑤ Measured delay is improved up-to 30 msec in Phase 2 by increasing sampling rate @8kSPS.



Hardware Prototype

Transmitter


- ① Final prototype with audio input and delta modulation encoder.
- ② LED is indicating the healthiness of communication
- ③ Power supply is given by USB power bank.



Hardware Prototype

Receiver

- ① Final prototype with audio output and delta modulation decoder.
- ② LED is indicating the healthiness of communication
- ③ Power supply is given by USB power bank.




Modular Testing

Transmitter: signal before encoder vs Receiver : signal after decoder


- ① ADC and DAC sampling rate is 8KSPS.
- ② Delta modulation is implemented during testing
- ③ Results are captured on CCS IDE developed by TI.



Input Injection from PC 3.5mm jack



Receive Samples after
ADPCM decoding



Transmitter ADC Samples
before ADPCM encoding

BOM and Costing

Transmitter

- ① Total cost of electronics is coming approximately **10.38\$**.
- ② Cost is calculated as reference of DigiKey price from quantity 500 to 4K as per applicable.
- ③ Mechanical, PCB , Antenna , battery cost is excluded

| Quantity | Parts | Cost (\$) |
|----------|------------------------|-----------|
| 1 | LS L296-P2Q2-1 RLED | 0.11821 |
| 1 | LS LPL296-J2L2-25 GLED | 0.11821 |
| 1 | BLM18HE152SN1 Inductor | 0.06619 |
| 1 | LF356 Opamp | 0.297 |
| 1 | CC1310F128RGZT | 4.8564 |
| 1 | TPS79601DR | 2.3403 |
| 1 | LM4040N | 0.5292 |
| 1 | 32.768kHz Xtal | 0.77 |
| 1 | 24MHz Xtal | 0.77 |
| 27 | capacitors | 0.04131 |
| 11 | Resistors | 0.01474 |
| 6 | Indicators | 0.4662 |

BOM and Costing

Receiver

- ① Total cost of electronics is coming approximately **12.04\$**.
- ② Cost is calculated as reference of DigiKey price from quantity 500 to 4K as per applicable.
- ③ Mechanical, PCB , Antenna , battery cost is excluded

| Quantity | Parts | Cost (\$) |
|----------|----------------------------|-----------|
| 1 | LS L296-P2Q2-1 RLED | 0.11821 |
| 1 | LS LPL296-J2L2-25 GLED | 0.11821 |
| 1 | BLM18HE152SN1 Inductor | 0.06619 |
| 1 | TPA2005D1 | 0.35 |
| 1 | CC1310F128RGZT | 4.8564 |
| 1 | TPS79601DR | 2.3403 |
| 1 | MCP4921EP | 1.49 |
| 1 | 32.768kHz Xtal | 0.77 |
| 1 | 24MHz Xtal | 0.77 |
| 1 | 3.5mm audio jack connector | 0.4832 |
| 31 | capacitors | 0.0474 |
| 9 | Resistors | 0.0121 |
| 8 | Indicators | 0.6216 |

Conclusion

- A prototype proof of concept is developed for audio transmission and reception.
- Delta modulation technique is implemented for utilizing same channel bandwidth (Symbol rate 50 kbps) with higher sampling rate (8kSPS).
- Hardware filter implementation for noise suppression.
- Prototype is tested up-to 750 meters line of sight at 14dbm power transmission via mono-pole PCB antenna
- Proprietary protocol to synchronize the transmitter and receiver during delta modulation
- Smart processor handling for effective utilization

Future Work

- Interfacing with automatics gain controller (companding circuit) and testing
- Can be replaced the DAC MCP4921 and driver circuit with **codec circuit** for better voice quality and noise suppression.
- High power and high efficient antenna designing to communicate between transmitter and receiver.
- Forward error correction (FEC) mechanism for frame auto correction for long range communication.
- PCB layout and product development testing with new hardware.

Thank You!!!