☰   Documentation Settings   ▼

ℹ️   This documentation is not published yet, this is only a preview. Changes to the publishing set…

Bulls and Cows

POST CreateGame

/backend/CreateGame

BODY raw

```
{
    "user":{"name": "anil"}
}
```

Example Request   CreateGame

```
curl --location --request POST '/backend/CreateGame' \
--data-raw '{
    "user":{"name": "anil"}
}'
```

Example Response

Body   Headers (0)

```
{
  "move": {
    "id": 2,
    "session": {
      "id": 2,
      "date": "now",
      "start": 0,
      "end": 0,
      "winner": 0
    },
```

View More

POST JoinGame

/backend/JoinGame

BODY raw

```
{
    "user": {
        "name": "anil"
    },
    "session": {
        "id": 1
    }
}
```

Example Request   JoinGame

```
curl --location --request POST '/backend/JoinGame' \
--data-raw '{
    "user": {
        "name": "anil"
    },
    "session": {
        "id": 1
    }
}'
```

POST StartGame

/backend/StartGame

BODY raw

```
{
        "id": 1
}
```

☰　　　　　　　　　　　　　　　Documentation Settings　▼

Example Request　　　　　　　　　　　　　　　StartGame

```
curl --location --request POST '/backend/StartGame' \
--data-raw '{
        "id": 1
}'
```

POST GetReady

```
/backend/GetReady
```

BODY raw

```
{
        "user": {"id": 1},
        "session": {"id": 1}

}
```

Example Request　　　　　　　　　　　　　　　GetReady

```
curl --location --request POST '/backend/GetReady' \
--data-raw '{
        "user": {"id": 1},
        "session": {"id": 1}

}'
```

POST MakePrediction

```
/backend/MakePrediction
```

BODY raw

☰   Documentation Settings ▼

```json
{
    "user": {
        "name": "anil"
    },
    "session": {
        "id": 1
    },
    "prediction": 1234
}
```

Example Request   MakePrediction

```bash
curl --location --request POST '/backend/MakePrediction' \
--data-raw '{
    "user": {
        "name": "anil"
    },
    "session": {
        "id": 1
    },
    "prediction": 1234
}'
```

POST Connect

/backend/Connect

BODY raw

```json
{
    "user": {
        "name": "anil"
    },
    "session": {
        "id": 1
    }
}
```

Example Request   Connect

```
curl --location --request POST '/backend/Connect' \
--data-raw '{
    "user": {
        "name": "anil"
    },
    "session": {
        "id": 1
    }
}'
```