

TUTORIAL

How To Add Login Authentication to React Applications

Development JavaScript React

By [Joe Morgan](#)

Published on December 2, 2020 70.3k

The author selected [Creative Commons](#) to receive a donation as part of the [Write for DOnations](#) program.

Introduction

Many web applications are a mix of public and private pages. Public pages are available to anyone, while a private page requires a user login. You can use *authentication* to manage which users have access to which pages. Your [React](#) application will need ' [SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

In this tutorial, you'll create a React application using a token-based authentication system. You'll create a mock API that will return a user token, build a login page that will fetch the token, and check for authentication without rerouting a user. If a user is not authenticated, you'll provide an opportunity for them to log in and then allow them to continue without navigating to a dedicated login page. As you build the application, you'll explore different methods for storing tokens and will learn the security and experience trade-offs for each approach. This tutorial will focus on storing tokens in `localStorage` and `sessionStorage`.

By the end of this tutorial, you'll be able to add authentication to a React application and integrate the login and token storage strategies into a complete user workflow.

Prerequisites

- You will need a development environment running `Node.js`; this tutorial was tested on Node.js version 10.22.0 and npm version 6.14.6. To install this on macOS or Ubuntu 18.04, follow the steps in [How to Install Node.js and Create a Local Development Environment on macOS](#) or the **Installing Using a PPA** section of [How To Install Node.js on Ubuntu 18.04](#).
- A React development environment set up with [Create React App](#), with the non-essential boilerplate removed. To set this up, follow **Step 1 — Creating an Empty Project** of the [How To Manage State on React Class Components](#) tutorial. This tutorial will use `auth-tutorial` as the project name.
- You will be fetching data from APIs using React. You can learn about working with APIs in [How To Call Web APIs with the `useEffect` Hook in React](#).
- You will also need a basic knowledge of JavaScript, HTML, and CSS, which you can find in our [How To Build a Website With HTML](#) series, [How To Style HTML with CSS](#), and in [How To Code in JavaScript](#).

Step 1 — Building a Login Page

In this step, you'll create a login page for your application. You'll start by installing [React Router](#) and creating components to represent a full application. Then you'll render the login page on any route so that your users can login to the application without being redirected to a new page.

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

To begin, install react router with `npm`. There are two different versions: a web version and a native version for use with React Native. Install the web version:

```
$ npm install react-router-dom
```

The package will install and you'll receive a message when the installation is complete. Your message may vary slightly:

Output

```
...  
+ react-router-dom@5.2.0  
added 11 packages from 6 contributors, removed 10 packages and audited 1945 packages in 12.794  
...
```

Next, create two components called `Dashboard` and `Preferences` to act as private pages. These will represent components that a user should not see until they have successfully logged into the application.

First, create the directories:

```
$ mkdir src/components/Dashboard  
$ mkdir src/components/Preferences
```

Then open `Dashboard.js` in a text editor. This tutorial will use nano:

```
$ nano src/components/Dashboard/Dashboard.js
```

Inside of `Dashboard.js`, add an `<h2>` tag with the content of `Dashboard`:

```
auth-tutorial/src/components/Dashboard/Dashboard.js
```

```
import React from 'react';
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
);  
}
```

Save and close the file.

Repeat the same steps for `Preferences`. Open the component:

```
$ nano src/components/Preferences/Preferences.js
```

Add the content:

auth-tutorial/src/components/Preferences/Preferences.js

```
import React from 'react';  
  
export default function Preferences() {  
  return(  
    <h2>Preferences</h2>  
  );  
}
```

Save and close the file.

Now that you have some components, you need to import the components and create routes inside of `App.js`. Check out the tutorial [How To Handle Routing in React Apps with React Router](#) for a full introduction to routing in React applications.

To begin, open `App.js`:

```
$ nano src/components/App/App.js
```

Then import `Dashboard` and `Preferences` by adding the following highlighted code:

auth-tutorial/src/components/App/App.js

```
import React from 'react';  
import './App.css';
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
function App() {  
  return (  
    <></>  
  );  
}  
  
export default App;
```

Next, import `BrowserRouter`, `Switch`, and `Route` from `react-router-dom`:

auth-tutorial/src/components/App/App.js

```
import React from 'react';  
import './App.css';  
import { BrowserRouter, Route, Switch } from 'react-router-dom';  
import Dashboard from '../Dashboard/Dashboard';  
import Preferences from '../Preferences/Preferences';  
  
function App() {  
  return (  
    <></>  
  );  
}  
  
export default App;
```

Add a surrounding `<div>` with a `className` of `wrapper` and an `<h1>` tag to serve as a template for the application. Be sure that you are importing `App.css` so that you can apply the styles.

Next, create routes for the `Dashboard` and `Preferences` components. Add `BrowserRouter`, then add a `Switch` component as a child. Inside of the `Switch`, add a `Route` with a path for each component:

tutorial/src/components/App/App.js

```
import React from 'react';  
import './App.css';  
import { BrowserRouter, Route, Switch } from 'react-router-dom';  
import Dashboard from '../Dashboard/Dashboard';  
import Preferences from '../Preferences/Preferences';
```

[Copy](#)[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

```
<div className="wrapper">
  <h1>Application</h1>
  <BrowserRouter>
    <Switch>
      <Route path="/dashboard">
        <Dashboard />
      </Route>
      <Route path="/preferences">
        <Preferences />
      </Route>
    </Switch>
  </BrowserRouter>
</div>
);
}

export default App;
```

Save and close the file.

The final step is to add some padding to the main `<div>` so your component is not directly at the edge of the browser. To do this, you will change the CSS.

Open `App.css` :

```
$ nano src/components/App/App.css
```

Replace the contents with a class of `.wrapper` with padding of 20px :

auth-tutorial/src/components/App/App.css

```
.wrapper {
  padding: 20px;
}
```

Save and close the file. When you do, the browser will reload and you'll find your basic components:

[SCROLL TO TOP](#)

[How To Code in React.js](#)[How To Add Login Authentication...](#) ☐

Application

Check each of the routes. If you visit <http://localhost:3000/dashboard>, you'll find the dashboard page:

[SCROLL TO TOP](#)

[How To Code in React.js](#)[How To Add Login Authentication...](#) ☐

Application

Dashboard

Your routes are working as expected, but there is a slight problem. The route `/dashboard` should be a protected page and should not be viewable by an unauthenticated user. There are different ways to handle a private page. For example, you can create a new route for a login page and use [React Router to redirect if the user is not logged in](#). This is a fine approach, but the user would lose their route and have to navigate back to the page they originally wanted to view.

A less intrusive option is to generate the login page regardless of the route. With this approach, you'll render a login page if there is not a stored user token and when the user logs in, they'll be on the same route that they initially visited. That means if a user visits `/dashboard`, they will still be on the `/dashboard` route after login.

To begin, make a new directory for the `Login` component:

```
$ mkdir src/components/Login
```

Next, open `Login.js` in a text editor:

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

Create a basic form with a submit `<button>` and an `<input>` for the username and the password. Be sure to set the input type for the password to `password`:

auth-tutorial/src/components/Login/Login.js

```
import React from 'react';

export default function Login() {
  return(
    <form>
      <label>
        <p>Username</p>
        <input type="text" />
      </label>
      <label>
        <p>Password</p>
        <input type="password" />
      </label>
      <div>
        <button type="submit">Submit</button>
      </div>
    </form>
  )
}
```

For more on forms in React, check out the tutorial [How To Build Forms in React](#).

Next, add an `<h1>` tag asking the user to log in. Wrap the `<form>` and the `<h1>` in a `<div>` with a `className` of `login-wrapper`. Finally, import `Login.css`:

auth-tutorial/src/components/Login/Login.js

```
import React from 'react';
import './Login.css';

export default function Login() {
  return(
    <div className="login-wrapper">
      <h1>Please Log In</h1>
      <form>
        <label>
          <p>Username</p>
          <input type="text" />
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
        <input type="password" />
      </label>
      <div>
        <button type="submit">Submit</button>
      </div>
    </form>
  </div>
)
}
```

Save and close the file.

Now that you have a basic `Login` component, you'll need to add some styling. Open `Login.css`:

```
$ nano src/components/Login/Login.css
```

Center the component on the page by adding a `display` of `flex`, then setting the `flex-direction` to `column` to align the elements vertically and adding `align-items` to `center` to make the component centered in the browser:

```
auth-tutorial/src/components/Login/Login.css
```

```
.login-wrapper {
  display: flex;
  flex-direction: column;
  align-items: center;
}
```

For more information on using Flexbox, see our [CSS Flexbox Cheatsheet](#)

Save and close the file.

Finally, you'll need to render it inside of `App.js` if there is no user token. Open `App.js`:

```
$ nano src/components/App/App.js
```

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

Import `useState` from `react`, then call `useState` and set return values to `token` and `setToken`:

auth-tutorial/src/components/App/App.js

```
import React, { useState } from 'react';
import { BrowserRouter, Route, Switch } from 'react-router-dom';
import './App.css';
import Dashboard from '../Dashboard/Dashboard';
import Preferences from '../Preferences/Preferences';

function App() {
  const [token, setToken] = useState();
  return (
    <div className="wrapper">
      <h1>Application</h1>
      <BrowserRouter>
        <Switch>
          <Route path="/dashboard">
            <Dashboard />
          </Route>
          <Route path="/preferences">
            <Preferences />
          </Route>
        </Switch>
      </BrowserRouter>
    </div>
  );
}

export default App;
```

Import the `Login` component. Add a conditional statement to display `Login` if the `token` is falsy.

Pass the `setToken` function to the `Login` component:

auth-tutorial/src/components/App/App.js

```
import React, { useState } from 'react';
import { BrowserRouter, Route, Switch } from 'react-router-dom';
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
import Preferences from '../Preferences/Preferences';

function App() {
  const [token, setToken] = useState();

  if(!token) {
    return <Login setToken={setToken} />
  }

  return (
    <div className="wrapper">
      <h1>Application</h1>
      <BrowserRouter>
        <Switch>
          <Route path="/dashboard">
            <Dashboard />
          </Route>
          <Route path="/preferences">
            <Preferences />
          </Route>
        </Switch>
      </BrowserRouter>
    </div>
  );
}

export default App;
```

For now, there is no token; in the next step, you'll call an API and set the token with the return value.

Save and close the file. When you do, the browser will reload and you'll see the login page. Notice that if you visit <http://localhost:3000/dashboard>, you'll still find the login page since the token has not yet been set:

[SCROLL TO TOP](#)

[How To Code in React.js](#)[How To Add Login Authentication...](#) ☐

Application

Dashboard

In this step, you created an application with private components and a login component that will display until you set a token. You also configured routes to display the pages and added a check to display the `Login` component on every route if the user is not yet logged into the application.

In the next step, you'll create a local API that will return a user token. You'll call the API from the `Login` component and save the token to memory on success.

Step 2 — Creating a Token API

In this step, you'll create a local API to fetch a user token. You'll build a mock API using [Node.js](#) that will return a user token. You'll then call that API from your login page and render the component after you successfully retrieve the token. By the end of this step, you'll have an application with a working login page and protected pages that will only be accessible after login.

You are going to need a server to act as a backend that will return the token. You can create a server quickly using Node.js and the [Express web framework](#). For a detailed introduction to creating an Express server, see the tutorial [Basic Express Server in Node](#).

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

You'll also need to install `cors`. This library will enable cross origin resource sharing for all routes.

Warning: Do not enable CORS for all routes in a production application. This can lead to security vulnerabilities.

```
$ npm install --save-dev express cors
```

When the installation is complete, you'll receive a success message:

Output

```
...  
+ cors@2.8.5  
+ express@4.17.1  
removed 10 packages, updated 2 packages and audited 2059 packages in 12.597s  
...
```

Next, open a new file called `server.js` in the root of your application. Do not add this file to the `/src` directory since you do not want it to be part of the final build.

```
$ nano server.js
```

Import `express`, then initialize a new app by calling `express()` and saving the result to a variable called `app`:

auth-tutorial/server.js

```
const express = require('express');  
const app = express();
```

After creating the `app`, add `cors` as a middleware. First, import `cors`, then add it to the application by calling the `use` method on `app`:

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

```
const express = require('express');
const cors = require('cors');
const app = express();

app.use(cors());
```

Next, listen to a specific route with `app.use`. The first argument is the path the application will listen to and the second argument is a callback function that will run when the application serves the path. The callback takes a `req` argument, which contains the request data and a `res` argument that handles the result.

Add in a handler for the `/login` path. Call `res.send` with a JavaScript object containing a token:

auth-tutorial/server.js

```
const express = require('express');
const cors = require('cors')
const app = express();

app.use(cors());

app.use('/login', (req, res) => {
  res.send({
    token: 'test123'
  });
});
```

Finally, run the server on port 8080 using `app.listen`:

auth-tutorial/server.js

```
const express = require('express');
const cors = require('cors')
const app = express();

app.use(cors());

app.use('/login', (req, res) => {
  res.send({
    token: 'test123'
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
app.listen(8080, () => console.log('API is running on http://localhost:8080/login'));
```

Save and close the file. In a new terminal window or tab, start the server:

```
$ node server.js
```

You will receive a response indicating that the server is starting:

Output

```
API is running on http://localhost:8080/login
```

Visit <http://localhost:8080/login> and you'll find your JSON object.

```
{"token": "test123"}
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

up your route with `app.use`, Express will handle all requests the same. In a production application, you should be more specific and only allow certain request methods for each route.

Now that you have a running API server, you need to make a request from your login page. Open `Login.js`:

```
$ nano src/components/Login/Login.js
```

In the previous step, you passed a new prop called `setToken` to the `Login` component. Add in the `PropType` from the new prop and destructure the props object to pull out the `setToken` prop.

auth-tutorial/src/components/Login/Login.js

```
import React from 'react';
import PropTypes from 'prop-types';

import './Login.css';

export default function Login({ setToken }) {
  return(
    <div className="login-wrapper">
      <h1>Please Log In</h1>
      <form>
        <label>
          <p>Username</p>
          <input type="text" />
        </label>
        <label>
          <p>Password</p>
          <input type="password" />
        </label>
        <div>
          <button type="submit">Submit</button>
        </div>
      </form>
    </div>
  )
}
```

```
Login.propTypes = {
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

Next, create a local state to capture the `Username` and `Password`. Since you do not need to manually set data, make the `<inputs>` uncontrolled components. You can find detailed information about uncontrolled components in [How To Build Forms in React](#).

auth-tutorial/src/components/Login/Login.js

```
import React, { useState } from 'react';
import PropTypes from 'prop-types';

import './Login.css';

export default function Login({ setToken }) {
  const [username, setUsername] = useState();
  const [password, setPassword] = useState();
  return(
    <div className="login-wrapper">
      <h1>Please Log In</h1>
      <form>
        <label>
          <p>Username</p>
          <input type="text" onChange={e => setUsername(e.target.value)} />
        </label>
        <label>
          <p>Password</p>
          <input type="password" onChange={e => setPassword(e.target.value)} />
        </label>
        <div>
          <button type="submit">Submit</button>
        </div>
      </form>
    </div>
  )
}

Login.propTypes = {
  setToken: PropTypes.func.isRequired
};
```

Next, create a function to make a `POST` request to the server. In a large application, you would add these to a separate directory. In this example, you'll add the service directly to the component. Check out the tutorial [How To Call Web APIs with the useEffect Hook in React](#) for a detailed look at calling APIs in React components.

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

auth-tutorial/src/components/Login/Login.js

```
import React, { useState } from 'react';
import PropTypes from 'prop-types';
import './Login.css';

async function loginUser(credentials) {
  return fetch('http://localhost:8080/login', {
    method: 'POST',
    headers: {
      'Content-Type': 'application/json'
    },
    body: JSON.stringify(credentials)
  })
  .then(data => data.json())
}

export default function Login({ setToken }) {
  ...
}
```

Finally, create a form submit handler called `handleSubmit` that will call `loginUser` with the username and password. Call `setToken` with a successful result. Call `handleSubmit` using the `onSubmit` event handler on the `<form>`:

auth-tutorial/src/components/Login/Login.js

```
import React, { useState } from 'react';
import PropTypes from 'prop-types';
import './Login.css';

async function loginUser(credentials) {
  return fetch('http://localhost:8080/login', {
    method: 'POST',
    headers: {
      'Content-Type': 'application/json'
    },
    body: JSON.stringify(credentials)
  })
  .then(data => data.json())
}

export default function Login({ setToken }) {
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
const handleSubmit = async e => {
  e.preventDefault();
  const token = await loginUser({
    username,
    password
  });
  setToken(token);
}

return(
  <div className="login-wrapper">
    <h1>Please Log In</h1>
    <form onSubmit={handleSubmit}>
      <label>
        <p>Username</p>
        <input type="text" onChange={e => setUsername(e.target.value)} />
      </label>
      <label>
        <p>Password</p>
        <input type="password" onChange={e => setPassword(e.target.value)} />
      </label>
      <div>
        <button type="submit">Submit</button>
      </div>
    </form>
  </div>
)
}

Login.propTypes = {
  setToken: PropTypes.func.isRequired
};
```

Note: In a full application, you'll need to handle situations where the component unmounts before a Promise resolves. Check out the tutorial How To Call Web APIs with the `useEffect` Hook in React for more information.

Save and close the file. Make sure that your local API is still running, then open a browser to <http://localhost:3000/dashboard>.

You will see the login page instead of the dashboard. Fill out and submit the form. You will receive a web token then redirect to the page for the dashboard.

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

Please Login

Username

Password

Submit

You now have a working local API and an application that requests a token using a username and password. But there is still a problem. The token is currently stored using a local state, which means that it is stored in JavaScript memory. If you open a new window, tab, or even just refresh the page, you will lose the token and the user will need to login again. This will be addressed in the next step.

In this step you created a local API and a login page for your application. You learned how to create a Node server to send a token and how to call the server and store the token from a login component. In the next step, you'll learn how to store the user token so that a session will persist across page refreshes or tabs.

Step 3 — Storing a User Token with `sessionStorage` and `localStorage`

In this step, you'll store the user token. You'll implement different token storage options and learn the security implications of each approach. Finally, you'll learn how different approaches will change the user experience as the user opens new tabs or closes a session.

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

There are several options for storing tokens. Every option has costs and benefits. In brief the options are: storing in JavaScript memory, storing in `sessionStorage`, storing in `localStorage`, and storing in a `cookie`. The primary trade-off is security. Any information that is stored outside of the memory of the current application is vulnerable to Cross-Site Scripting (XSS) attacks. The danger is that if a malicious user is able to load code into your application, it can access `localStorage`, `sessionStorage`, and any cookie that is also accessible to your application. The benefit of the non-memory storage methods is that you can reduce the number of times a user will need to log in to create a better user experience.

This tutorial will cover `sessionStorage` and `localStorage`, since these are more modern than using cookies.

Session Storage

To test the benefits of storing outside of memory, convert the in-memory storage to `sessionStorage`. Open `App.js`:

```
$ nano src/components/App/App.js
```

Remove the call to `useState` and create two new functions called `setToken` and `getToken`. Then call `getToken` and assign the results to a variable called `token`:

auth-tutorial/src/components/App/App.js

```
import React from 'react';
import { BrowserRouter, Route, Switch } from 'react-router-dom';

import './App.css';
import Dashboard from '../Dashboard/Dashboard';
import Login from '../Login/Login';
import Preferences from '../Preferences/Preferences';

function setToken(userToken) {
}

function getToken() {
}
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```

    if(!token) {
      return <Login setToken={setToken} />
    }

    return (
      <div className="wrapper">
        ...
      </div>
    );
  }

  export default App;

```

Since you are using the same function and variable names, you will not need to change any code in the `Login` component or the rest of the `App` component.

Inside of `setToken`, save the `userToken` argument to `sessionStorage` using the `setItem` method. This method takes a key as a first argument and a string as the second argument. That means you'll need to convert the `userToken` from an object to a string using the `JSON.stringify` function. Call `setItem` with a key of `token` and the converted object.

auth-tutorial/src/components/App/App.js

```

import React from 'react';
import { BrowserRouter, Route, Switch } from 'react-router-dom';

import './App.css';
import Dashboard from '../Dashboard/Dashboard';
import Login from '../Login/Login';
import Preferences from '../Preferences/Preferences';

function setToken(userToken) {
  sessionStorage.setItem('token', JSON.stringify(userToken));
}

function getToken() {
}

function App() {
  const token = getToken();

  if(!token) {
    return <Login setToken={setToken} />
  }

```


SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
...  
</div>  
);  
}  
  
export default App;
```

Save the file. When you do the browser will reload. If you type in a username and password and submit, the browser will still render the login page, but if you look inside your browser console tools, you'll find the token is stored in `sessionStorage`. This image is from Firefox, but you'll find the same results in Chrome or other modern browsers.



Now you need to retrieve the token to render the correct page. Inside the `getToken` function, call `sessionStorage.getItem`. This method takes a `key` as an argument and returns the string value. Convert the string to an object using `JSON.parse`, then return the value of `token`:

auth-tutorial/src/components/App/App.js

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
import './App.css';
import Dashboard from '../Dashboard/Dashboard';
import Login from '../Login/Login';
import Preferences from '../Preferences/Preferences';

function setToken(userToken) {
  sessionStorage.setItem('token', JSON.stringify(userToken));
}

function getToken() {
  const tokenString = sessionStorage.getItem('token');
  const userToken = JSON.parse(tokenString);
  return userToken?.token
}

function App() {
  const token = getToken();

  if(!token) {
    return <Login setToken={setToken} />
  }

  return (
    <div className="wrapper">
      ...
    </div>
  );
}

export default App;
```

You need to use the optional chaining operator—?.—when accessing the `token` property because when you first access the application, the value of `sessionStorage.getItem('token')` will be `undefined`. If you try to access a property, you will generate an error.

Save and close the file. In this case, you already have a token stored, so when the browser refreshes, you will navigate to the private pages:

[SCROLL TO TOP](#)

[How To Code in React.js](#)[How To Add Login Authentication...](#) ☐

Application

Dashboard


Clear out the token by either deleting the token in the **Storage** tab in your developer tools or by typing `sessionStorage.clear()` in your developer console.

There's a little problem now. When you log in, the browser saves the token, but you still see the login page.

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐



The problem is your code never alerts React that the token retrieval was successful. You'll still need to set some state that will trigger a re-render when the data changes. Like most problems in React, there are multiple ways to solve it. One of the most elegant and reusable is to create a custom Hook.

Creating a Custom Token Hook

A custom Hook is a function that wraps custom logic. A custom Hook usually wraps one or more built-in React Hooks along with custom implementations. The primary advantage of a custom Hook is that you can remove the implementation logic from the component and you can reuse it across multiple components.

By convention, custom Hooks start with the keyword `use*`.

Open a new file in the `App` directory called `useToken.js`:

```
$ nano src/components/App/useToken.js
```

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

start to reuse this Hook across multiple components, you might also want to move it to a separate directory.

Inside `useToken.js`, import `useState` from `react`. Notice that you do not need to import `React` since you will have no `JSX` in the file. Create and export a function called `useToken`. Inside this function, use the `useState` Hook to create a `token` state and a `setToken` function:

auth-tutorial/src/components/App/useToken.js

```
import { useState } from 'react';

export default function useToken() {
  const [token, setToken] = useState();
}
```

Next, copy the `getToken` function to `useHook` and convert it to an arrow function, since you placed it inside `useToken`. You could leave the function as a standard, named function, but it can be easier to read when top-level functions are standard and internal functions are arrow functions. However, each team will be different. Choose one style and stick with it.

Place `getToken` before the state declaration, then initialize `useState` with `getToken`. This will fetch the token and set it as the initial state:

auth-tutorial/src/components/App/useToken.js

```
import { useState } from 'react';

export default function useToken() {
  const getToken = () => {
    const tokenString = sessionStorage.getItem('token');
    const userToken = JSON.parse(tokenString);
    return userToken?.token;
  };
  const [token, setToken] = useState(getToken());
}
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

to state by calling `setToken`:

auth-tutorial/src/components/App/useToken.js

```
import { useState } from 'react';

export default function useToken() {
  const getToken = () => {
    const tokenString = sessionStorage.getItem('token');
    const userToken = JSON.parse(tokenString);
    return userToken?.token
  };

  const [token, setToken] = useState(getToken());

  const saveToken = userToken => {
    sessionStorage.setItem('token', JSON.stringify(userToken));
    setToken(userToken.token);
  };
}
```

Finally, return an object that contains the `token` and `saveToken` set to the `setToken` property name. This will give the component the same interface. You can also return the values as an array, but an object will give users a chance to destructure only the values they want if you reuse this in another component.

auth-tutorial/src/components/App/useToken.js

```
import { useState } from 'react';

export default function useToken() {
  const getToken = () => {
    const tokenString = sessionStorage.getItem('token');
    const userToken = JSON.parse(tokenString);
    return userToken?.token
  };

  const [token, setToken] = useState(getToken());

  const saveToken = userToken => {
    sessionStorage.setItem('token', JSON.stringify(userToken));
    setToken(userToken.token);
  };
}
```

SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
    token
  }
}
```

Save and close the file.

Next, open `App.js`:

```
$ nano src/components/App/App.js
```

Remove the `getToken` and `setToken` functions. Then import `useToken` and call the function destructuring the `setToken` and `token` values. You can also remove the import of `useState` since you are no longer using the Hook:

auth-tutorial/src/components/App/App.js

```
import React from 'react';
import { BrowserRouter, Route, Switch } from 'react-router-dom';
import './App.css';
import Dashboard from '../Dashboard/Dashboard';
import Login from '../Login/Login';
import Preferences from '../Preferences/Preferences';
import useToken from './useToken';

function App() {

  const { token, setToken } = useToken();

  if(!token) {
    return <Login setToken={setToken} />
  }

  return (
    <div className="wrapper">
      <h1>Application</h1>
      <BrowserRouter>
        <Switch>
          <Route path="/dashboard">
            <Dashboard />
          </Route>
          <Route path="/preferences">
            <Preferences />

```


SCROLL TO TOP

How To Code in React.js

How To Add Login Authentication... ☐

```
</div>  
);  
}  
  
export default App;
```

Save and close the file. When you do, the browser will refresh, and when you log in, you will immediately go to the page. This is happening because you are calling `useState` in your custom Hook, which will trigger a component re-render:



Please Log In

Username

Password

You now have a custom Hook to store your token in `sessionStorage`. Now you can refresh your page and the user will remain logged in. But if you try to open the application in another tab, the user will be logged out. `sessionStorage` belongs only to the specific window session. Any data will not be available in a new tab and will be lost when the active tab is closed. If you want to save the token across tabs, you'll need to convert to `localStorage`.

Using `localStorage` to Save Data Across Windows

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

but it does have some security problems. If the user shares their computer, they will remain logged in to the application even though they close the browser. It will be the user's responsibility to explicitly log out. The next user would have immediate access to the application without a login. It's a risk, but the convenience may be worth it for some applications.

To convert to `localStorage`, open `useToken.js`:

```
$ nano src/components/App/useToken.js
```

Then change every reference of `sessionStorage` to `localStorage`. The methods you call will be the same:

auth-tutorial/src/components/App/useToken.js

```
import { useState } from 'react';

export default function useToken() {
  const getToken = () => {
    const tokenString = localStorage.getItem('token');
    const userToken = JSON.parse(tokenString);
    return userToken?.token
  };

  const [token, setToken] = useState(getToken());

  const saveToken = userToken => {
    localStorage.setItem('token', JSON.stringify(userToken));
    setToken(userToken.token);
  };

  return {
    setToken: saveToken,
    token
  }
}
```

Save the file. When you do, the browser will refresh. You will need to log in again since there is no token yet in `localStorage`, but after you do, you will remain logged in new tab.

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

Please Log In

Username

Password

Submit

In this step, you saved tokens with `sessionStorage` and `localStorage`. You also created a custom Hook to trigger a component re-render and to move component logic to a separate function. You also learned about how `sessionStorage` and `localStorage` affect the user's ability to start new sessions without login.

Conclusion

Authentication is a crucial requirement of many applications. The mixture of security concerns and user experience can be intimidating, but if you focus on validating data and rendering components at the correct time, it can become a lightweight process.

Each storage solution offers distinct advantages and disadvantages. Your choice may change as your application evolves. By moving your component logic into an abstract custom Hook, you give yourself the ability to refactor without disrupting existing components.

If you would like to read more React tutorials, check out our [React Topic page](#), or return to the [How To Code in React.js series page](#).

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

Was this helpful?

Yes

No



[Report an issue](#)

About the authors



Joe Morgan

Author of Simplifying JavaScript. Writing featured in Slate, FreeCodeCamp, and here! I like to break things and put them back together. ✂



Timothy Nolan

Editor

Tutorial Series

How To Code in React.js

React is a popular JavaScript framework for creating front-end applications, such as user interfaces that allow users to interact with programs. Originally created by Facebook, it has gained popularity by allowing developers to create fast applications using an intuitive programming paradigm that ties JavaScript with an HTML-like syntax known as JSX.

In this series, you will build out examples of React projects to gain an understanding of this framework, giving you the knowledge you need to pursue front-end web development or start out on your way to full stack development.

[Next in series: How To Avoid Performance Pitfalls in React with memo, useMemo, and useCallback →](#)

[SCROLL TO TOP](#)

[How To Code in React.js](#)[How To Add Login Authentication...](#) ☐

Still looking for an answer?

[Ask a question](#)[Search for more help](#)

RELATED

Join the DigitalOcean Community



Join 1M+ other developers and:

- Get help and share knowledge in Q&A
- Subscribe to topics of interest
- Get courses & tools that help you grow as a developer or small business owner

[Join Now](#)[Coding for Beginners: Tutorials to Help New Developers](#)[Tutorial](#)[How To Apply Background Styles to HTML Elements with CSS](#)[Tutorial](#)

Comments

45 Comments

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

Sign In to Comment

 **gakis41** December 7, 2020

0 Gr8 stuff in here!!!1 thanks a lot really helpful article! I still have to go through docs for some parts!!!Happy to stumble upon this guide!

[Reply](#) [Report](#)

 **JoeMorgan** December 8, 2020

0 Great. Glad it helps!

[Reply](#) [Report](#)

 **nickisyourfan** December 8, 2020

0 Awesome little tutorial. Why is express a Dev-dependency? Wouldn't we need the server if the app was launched on heroku or something similar?

Do ya'll plan on extending the tutorial to the backend logic? I'd love to see how to set unique tokens per user and authenticate the validity of the tokens after the user logs in. Right now it seems as long as the user's token is set, they can access the restricted content... so any user can just set any value through the local or the session storage and get instant access.

Is this where you would use something like PassportJS to authenticate the validity of the token?

Thanks for the great work! I look forward to reading more!

[Reply](#) [Report](#)

 **JoeMorgan** December 8, 2020

1 These are great questions. As you noted express is a dev dependency because this assumes that there is a backend service somewhere that is handling the token generation and validation. I don't know if there are any plans to create that tutorial. [SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

request. Since all of the data would need to come from API (since it's a single page application), if there was an invalid token, the user would not receive the data.

You could add in a standard function or a wrapper or an axios interceptor to logout the user if an API returns unauthorized.

[Reply](#) [Report](#)

 [karatesoon](#) December 28, 2020

0 Pretty easy to understand, thanks!

[Reply](#) [Report](#)

 [ckwagaba](#) December 31, 2020

0 Awesome 🙏

[Reply](#) [Report](#)

 [ahmadfadlydziljalal](#) January 3, 2021

0 You do a great job.

Please continue to logout Authentication.

God Bless You.

[Reply](#) [Report](#)

 [liamgsmith](#) January 16, 2021

0 Thanks Joe.

Is there some error handling missing for the async function loginUser in Login.js?

I already had a jwt token being generated from a backend server and I'm getting an invalid credential error from the backend (expected - I'm deliberately entering the wrong data) but this system still logs me in anyway due to what I'm assuming is the assigning of setToken(token) in the Login function.

[Reply](#) [Report](#)

 [JoeMorgan](#) January 18, 2021

1 Hi,

To keep things short, I did need to simplify things a bit. It's correct that if you return any result, then the `setToken` function will set data and the application would log you in.

Similarly, you could manually set a token and bypass the log in which we [SCROLL TO TOP](#) security flaw.

How To Code in React.js

How To Add Login Authentication... ☐

data by checking the response status.

In a real application, you would need to validate the authorization code along with any request and logout the user if the code is bad.

[Reply](#) [Report](#)


 [toihihalim](#) January 21, 2021

 0 Awesome !!! really got me to understand much more about react

thank you !


[Reply](#) [Report](#)

 [illyayushchenko](#) January 23, 2021

 1 If user will manually write anything as "token" to localStorage he will get access to website, if I understand correctly?

[Reply](#) [Report](#)

 [illyayushchenko](#) January 23, 2021

 0 and another thing, setting state is asynchronous, does it mean that on refresh first route will be rendered for some milliseconds as (!token) will be true while setState is in process?

[Reply](#) [Report](#)

 [JoeMorgan](#) January 25, 2021

 1 Hi,

Due to space constraints, I had to leave a little out. In this case, you are correct a user can set anything and bypass the login.

In a full application, you'll need to verify that the token is correct before loading the application. You can do this in the root application as part of the initialization. You can also possibly handle it in the `useToken` custom Hook.

Regardless, your API should *always* validate the token when the user hits the API. If the token is invalid, return an **unauthorized** response code (401). Then handle that in your application by deleting the locally stored token. You can either handle this in the service or if you use a 3rd party library such as axios, you can add a global script to handle a 401 code.


[Reply](#) [Report](#)

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐


[Reply](#) [Report](#)

 [robertbracco1](#) February 8, 2021
0

"Due to space constraints, I had to leave a little out. In this case, you are correct a user can set anything and bypass the login."

Great tutorial but I think this is a HUGE gap. You're writing an auth tutorial for auth novices that if they follow step by step will allow an unauthorized user to access data on their app. In my (very novice opinion) this is way more important than how to use SessionStorage.

[Reply](#) [Report](#)

 [lewandowskiset](#) January 24, 2021
0

Hey Joe,

I'm trying to decide on how to store a jwt token for a user. I've read that using http only cookies are better than local or session storage. But you mention:

"


This tutorial will cover sessionStorage and localStorage, since these are more modern than using cookies.

"

How do you advise developers to choose where to store their users JWT tokens (LS, SS, Cookie). At this point, I'm not interesting in any kind of Server side session based auth, so really just struggling to find any kind of consistent advice on best practice for storing tokens on the client side.

The reason I ask is because many sites have mentioned that Local Storage is a big 'no no' when it comes to having a production ready secure web app. But every other website I read says something different.

[Reply](#) [Report](#)

 [JoeMorgan](#) January 25, 2021
0

Hi, Token storage is a tough one. Http Only cookies are the most secure because they are not vulnerable to a cross site scripting attack (XSS). The problem is the reason they are not vulnerable is because they are not accessible to JavaScript at all. That means your own code wouldn't be able to access it.

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐


sessionStorage in situations where you cannot use an http only cookie.

OWASP is an industry leader in web security so I always go for them when I'm in doubt. The worst thing about localStorage is that it stores it after you leave, so it will persist for long after the user stops using the page. However, if you want your user to be able to open a new tab, it's the easiest method.

Again, it comes down to your personal need and your code reality.


[Reply](#) [Report](#)

 [LakmalPremaratne](#) January 26, 2021

 0 My application runs in a restrictive environment so that I can ask the User to stick to a particular browser. I managed to copy the session information from one window/tab to the other using BroadcastChannel so that I was able to use sessionStorage instead of localStorage. I do not have to keep the session when the user closes the window. So I do not have to persist the token.


[Reply](#) [Report](#)

 [LakmalPremaratne](#) January 26, 2021

 0 Nicely laid out and very descriptive. You have put all the links to be referred for further information and I found it is beneficial. I learned a lot. Thank you once again!!!


[Reply](#) [Report](#)

 [muqriafif14](#) February 2, 2021

 0 i have a question, where can i know the password of login


[Reply](#) [Report](#)

 [rubensantana](#) February 7, 2021

 0 Hi Joe, it's 4 am around here. 4th tutorial I read from you in a row. Very well written. I look forward to a continuation of this topic.

[Reply](#) [Report](#)

 [kripakova4](#) February 17, 2021

 0 I don't understand how the PropTypes property works? Why wasn't the code from 'prop-types' shown?

[Reply](#) [Report](#)

[JoeMorgan](#) February 22, 2021

[SCROLL TO TOP](#)


How To Code in React.js

How To Add Login Authentication... ☐

 **c0d3henry** February 20, 2021

0 This comment has been marked as resolved by **c0d3henry**.

[SHOW COMMENT](#)

 **Miky** February 23, 2021

0 Hi Joe:

Thanks for this thorough tutorial. I am following along this but I am getting an error.

“Unhandled Rejection (TypeError): setToken is not a function”

This is in Login.js where you have setToken(token)

Do you know why?

[Reply](#) [Report](#)

 **JoeMorgan** February 24, 2021


0 It's hard to debug without seeing where you are at.

My best guess is you forgot to export `setToken` from the `useToken` function like this:

```
return {  
  setToken: saveToken,  
  token  
}
```

It's also possible that you did not import it from the Hook correctly. What section of the tutorial were you on when you encountered the problem?

[Reply](#) [Report](#)

 **Miky** February 24, 2021

0 I have a few extra components and the construction of my proj is not the same.

I replaced `({setToken})` with `(props)` in `...function Login(props)` and then using `props.setToken(token)` in `Login.js` I eliminated the error regarding `setToken` not being a function. Not sure about the cons of doing so down the road.

Thank you for the insights.

[Reply](#) [Report](#)

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

approach.. replacing setToken with props and changing setToken to props.setToken.. i was facing the same issue, which is "setToken is not a function" in Login.js.. any lead on this is highly appreciable.

[Reply](#) [Report](#)



MaLoH123 August 11, 2021

Hi! Having the same issue. Have you been able to get this resolved?

[Reply](#) [Report](#)



inhemant February 26, 2021

Thanks for such an informative article. I am trying to use both public and protected routes in my SPA. Can you give a little hint on how I can get around that?

[Reply](#) [Report](#)



c0d3henry March 2, 2021

I have a quick question - any chance you can write a post about handling refresh tokens? or if you have one can you post a link here? Thank you!

[Reply](#) [Report](#)



prattd March 5, 2021

In Step two there seems to be a contradiction with components/App/App.js. In one step you show adding a Login function to App.js and using this as the default export. But in the next step you have the function App() as the default export. Since they both can't be the default export which one is correct?

[Reply](#) [Report](#)



andrejgajdos March 28, 2021

It's strange this tutorial doesn't mention authenticated routes.

[Reply](#) [Report](#)



rohitsingh4137 April 2, 2021

Thanks for the great tutorial. I was following the steps upto step 2 and then I got this error: Error: Element type is invalid: expected a string (for built-in components) or a class/function (for composite components) but got: object. You likely forgot to export your component from the file it's defined in, or you might have mixed up default and named imports.

Check the render method of App .

► 22 stack frames were collapsed.

[SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication...



```
26 | username,  
27 | password  
28 | });  
  
29 | setToken(token);  
   | ^ 30 | }  
31 |  
32 | return(
```

can you please help me resolve this error?

[Reply](#) [Report](#)

 [JoeMorgan](#) April 2, 2021


0 That's hard because it's a pretty generic error. Assuming you are exporting your component, there could be a syntax error. Or an unclosed object. It's really hard to say without seeing the full source.

[Reply](#) [Report](#)

Load More Comments



This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License.




[SCROLL TO TOP](#)

How To Code in React.js


How To Add Login Authentication... ☐

Newsletter.



HOLLIE'S HUB FOR GOOD

Working on improving health and education, reducing inequality, and spurring economic growth? We'd like to help.



BECOME A CONTRIBUTOR

You get paid; we donate to tech nonprofits.

Featured on [Community](#) [Kubernetes Course](#) [Learn Python 3](#) [Machine Learning in Python](#)
[Getting started with Go](#) [Intro to Kubernetes](#)

DigitalOcean Products [Virtual Machines](#) [Managed Databases](#) [Managed Kubernetes](#) [Object Storage](#) [Marketplace](#) [VPC](#) [Load Balancers](#) [SCROLL TO TOP](#)

How To Code in React.js

How To Add Login Authentication... ☐

Welcome to the developer cloud

DigitalOcean makes it simple to launch in the cloud and scale up as you grow – whether you're running one virtual machine or ten thousand.

[Learn More](#)



© 2021 DigitalOcean, LLC. All rights reserved.

Company

[About](#)

[Leadership](#)

[Blog](#)

[Careers](#)

[Partners](#)

[Referral Program](#)

[Press](#)

[Legal](#)

[Security & Trust Center](#)

Products

[Pricing](#)

[Products Overview](#)

[Droplets](#)

Community

[Tutorials](#)

[Q&A](#)

[Tools and Integrations](#)

Contact

[Get Support](#)

[Trouble Signin](#) [SCROLL TO TOP](#)

[Sales](#)

How To Code in React.js

How To Add Login Authentication... ☐

Spaces	Write for DigitalOcean
Marketplace	Presentation Grants
Load Balancers	Hatch Startup Program
Block Storage	Shop Swag
API Documentation	Research Program
Documentation	Open Source
Release Notes	Code of Conduct

SCROLL TO TOP