

Machine Learning for Document Layout Analysis

Animesh Prasad

June 2018

Hervé Déjean

Jean-Luc Meunier



The Problem: Information Extraction from Marriage Records

dilluns a. 13. rebere de Antoni Duran pages del Regne de França

dilluns	a	13	reberé	de	Antoni	Duran	pages	del	Regne	de	fransa
other	other	other	other	other	name	surname	occupation	other	location	location	location
none	none	none	none	none	husband	husband	husband	none	husband	husband	husband

habitat en Barç^a ab Elisabeth Juana donfella filla de Bernat Prats

habitat	en	Bara	ab	Elisabeth	Juana	donsella	filla	de	Bernat	Prats
other	other	location	other	name	name	state	other	other	name	surname
none	none	husband	none	wife	wife	wife	none	none	wife's father	wife's father

forner de Barç^a y de Juana

forner	de	Bara	y	de	Juana
occupation	other	location	other	other	name
wife's father	none	wife's father	none	none	wife's mother

A Record

Dataset: Esposalles

- Marriage license book conserved at the Archives of the Cathedral of Barcelona, written in old Catalan by only one writer in the 17th century

*husband> fille de <husband's father> y <husband's mother> ab
<wife> fille de <wife's father> y <wife's mother>*

*<husband> fille de <husband's father> y <husband's mother> ab
<wife> viusa <wife's former husband>*

The Problem: Information Extraction from Marriage Records

dilluns	a	13	reberé	de	Antoni	Duran	pages	del	Regne	de	fransa
other	other	other	other	other	name	surname	occupation	other	location	location	location
none	none	none	none	none	husband	husband	husband	none	husband	husband	husband

habitat	en	Bara	ab	Elisabeth	Juana	donsella	filla	de	Bernat	Prats
other	other	location	other	name	name	state	other	other	name	surname
none	none	husband	none	wife	wife	wife	none	none	wife's father	wife's father

forner	de	Bara	y	de	Juana
occupation	other	location	other	other	name
wife's father	none	wife's father	none	none	wife's mother



Track 1: Basic: CSV file

Antoni, **name**
Duran, **surname**
pages, **occupation**
Regne, **location**
de, **location**
fransa, **location**
Bara, **location**
Elisabeth, **name**
Juana, **name**
donsella, **state**
Bernat, **name**
Prats, **surname**
forner, **occupation**
Bara, **location**
Juana, **name**

Track 2: Complete: CSV file

Antoni, **name**, **husband**
Duran, **surname**, **husband**
pages, **occupation**, **husband**
Regne, **location**, **husband**
de, **location**, **husband**
fransa, **location**, **husband**
Bara, **location**, **husband**
Elisabeth, **name**, **wife**
Juana, **name**, **wife**
donsella, **state**, **wife**
Bernat, **name**, **wifes_father**
Prats, **surname**, **wifes_father**
forner, **occupation**, **wifes_father**
Bara, **location**, **wifes_father**
Juana, **name**, **wifes_mother**



Dataset: Esposalles

- Gold: 774 Records with Handwritten Transcriptions (~1K unique Tokens)
- Input: HTR performed by CITLab with fairly high accuracy (~5%CER)
- Output: CSV with transcription and predetermined classes
 - CAT: name, surname, occupation, etc
 - PER: husband, wife, wife's father, etc
- Evaluation:
 - Basic (Task1 only)
 - Complete (Task1 and Task2)

Approach: Modeling

Graph-based approach

- One Record : one graph
- Features: n-gram [2-4] (~3K)/ CE (Dim 10)
- Nodes: tokens
- Edges: positional encoding
- Machine learning algorithms
 - (((Node Type)? Edge-Feature)? Graph?) Conditional Random Fields
 - ((CE?)CRF?)LSTM

Graph Conditional Random Field

A CRF is an (undirected) graph:

- The x_i are the nodes

- The y_i are the node labels

- An edge between two nodes indicates that their labels have a dependency

$$\sum_{i \in V} W_{y_i}^T \cdot \text{node_feature}(x_i) + \sum_{(i,j) \in E} W_{y_i, y_j}^T \cdot \text{edge_feature}(x_i, x_j)$$

Graph Conditional Random Field

A CRF is an (undirected) graph:

The x_i are the nodes

The y_i are the node labels

An edge between two nodes indicates that their labels have a dependency

$$\sum_{i \in V} W_{y_i}^T \cdot \text{node_feature}(x_i) + \sum_{(i,j) \in E} W_{y_i, y_j}^T \cdot \text{edge_feature}(x_i, x_j)$$

Graph Conditional Random Field

A CRF is an (undirected) graph:

The x_i are the nodes

The y_i are the node labels

An edge between two nodes indicates that their labels have a dependency

$$\sum_{i \in V} W_{y_i}^T \cdot \text{node_feature}(x_i) + \sum_{(i,j) \in E} W_{y_i, y_j}^T \cdot \text{edge_feature}(x_i, x_j)$$

- No Feature (always 1)
- Positional one-hot

Dev-Results (10Fold-CV)

Train/Test	Task 1							Task 2								
Class	Name	Surname	State	Location	Occupation	Other#	F_1	Husband	Husband's Father	Husband's Mother	Other Person	Wife	Wife's Father	Wife's Mother	Other#	F_1
CCRF																
True/True	0.9831	0.9534	0.9668	0.9546	0.9826	0.9851	0.9844	0.8089	0.5733	0.2959	0.6704	0.1992	0.6621	0.1119	0.9569	0.7333
True/Noisy	0.9921	0.9742	0.9794	0.9703	0.9854	0.9887	0.9759	0.8367	0.653	0.4575	0.7234	0.2942	0.7014	0.3533	0.9581	0.7797
GCRF																
True/True	0.9384	0.8523	0.8979	0.835	0.9721	0.9534	0.9218	0.8759	0.8668	0.912	0.9244	0.7586	0.8739	0.6793	0.9536	0.9072
True/Noisy	0.9554	0.895	0.9174	0.8536	0.9816	0.9568	0.9345	0.9116	0.8894	0.9363	0.9479	0.8289	0.92	0.815	0.9557	0.9260
EFGCRF																
True/True	0.9876	0.9611	0.9699	0.9638	0.9844	0.9868	0.9798	0.9334	0.922	0.9403	0.9607	0.9032	0.945	0.9008	0.9595	0.9430
True/Noisy	0.9937	0.9758	0.982	0.9731	0.9864	0.9896	0.9859	0.9469	0.9341	0.9521	0.981	0.9352	0.957	0.9562	0.9623	0.9529
BLSTM																
True/True	0.9914	0.9667	0.9795	0.9757	0.987	0.9893	0.9848	0.9714	0.9864	0.9841	0.9874	0.9857	0.9832	0.9672	0.9873	0.9849
True/Noisy	0.9984	0.9935	0.996	0.9905	0.9916	0.9964	0.9954	0.9912	0.9951	0.9958	0.9966	0.9944	0.994	0.9957	0.9959	0.9952

TABLE I

CLASS-WISE F_1 SCORES FOR BOTH SEMANTIC CATEGORIES (ONLY BEST PERFORMING MODELS OR MODELS WITH INTERESTING OBSERVATIONS ARE SHOWN, # CLASSES ARE NOT CONSIDERED FOR IHHER EVALUATION)

Dev-Results: Reading Between the Lines



CRF, GCRF, EFGCRF



LSTM



NTEFGCRF



Multitasking (in general on all model types)



CRF-LSTM



CE-(LSTM/CNN)-(CRF?)-LSTM

PRIVATE method: Naver Labs 2018-06-25

Authors: Naver Labs

⚠ expires on 2018-07-25

edit

delete

method: CITlab ARGUS (with OOV)
2017-07-09

Authors: Tobias Strauß, Max Weidemann, Johannes Michael, Gundram Leifert, Tobias Grüning, Roger Labahn

Description: The training data is divided into a training set (2790 line images) and a validation set (280 line images). Several normalization methods such as contrast, size, slant and skew normalization are applied. These preprocessed line images serve as input for the optical model, a recurrent neural network (layer from input to output: conv, conv, lstm (256 cells), conv, lstm (512 cells)) trained by CTC (150 epochs of 5000 noisy line images each). To enlarge input variety, the line images we use data argumentation on line images.

The output of the optical model are probabilities for each character at each position in the image collected in a matrix. The various output matrices for one record (which represent the lines) are glued together to one single matrix. We define regular expressions to extract the required information from this matrix. This is done in two steps: First, we segment the matrix into regions of interest: regions containing information about the husband, the husbands parents, the wife or the wife's parents. These regions are matched against a valid combination of dictionary items in a second step. For the name fields additional OOV words are allowed if the dictionary items do not fit.

method: CITlab ARGUS (with OOV, net2)
2017-07-10

Authors: Tobias Strauß, Max Weidemann, Johannes Michael, Gundram Leifert, Tobias Grüning, Roger Labahn

Description: The training data is divided into a training set (2790 line images) and a validation set (280 line images). Several normalization methods such as contrast, size, slant and skew normalization are applied. These preprocessed line images serve as input for the optical model, a recurrent neural network (layer from input to output: conv, conv, blstm (512), conv, blstm (512 cells), blstm (512 cells)) trained by CTC (150 epochs of 5000 noisy line images each). To enlarge input variety, the line images we use data argumentation on line images.

The output of the optical model are probabilities for each character at each position in the image collected in a matrix. The various output matrices for one record (which represent the lines) are glued together to one single matrix. We define regular expressions to extract the required information from this matrix. This is done in two steps: First, we segment the matrix into regions of interest: regions containing information about the husband, the husbands parents, the wife or the wife's parents. These regions are matched against a valid combination of dictionary items in a second step. For the name fields additional OOV words are allowed if the dictionary items do not fit.

Blind Test Results

Ranking Table ⓘ

☐ Description ☐ Paper ☐ Source Code




Date	Method	Basic Score	Complete Score	Name	Surname	Location	Occupation	State
2018-06-25	Naver Labs	95.46%	95.03%	97.01%	92.73%	95.03%	96.43%	96.41%
2017-07-09 ⓘ	CITlab ARGUS (with OOV)	91.94%	91.58%	95.14%	85.78%	88.43%	93.08%	97.54%
2017-07-10 ⓘ	CITlab ARGUS (with OOV, net2)	91.63%	91.19%	95.09%	85.84%	87.32%	92.96%	97.19%
2017-07-09 ⓘ	CITlab ARGUS (without OOV)	89.54%	89.17%	94.37%	76.54%	87.65%	92.66%	97.43%
2017-07-01 ⓘ	Baseline HMM	80.28%	63.11%	81.06%	60.15%	78.90%	90.23%	93.79%

Takeaways

- Fine grain semantic class is difficult to classify for graphical models. Increasing the model complexity in graphical models while keeping the surface features from the tokens same increases the performance
- Due to small CER on the HTR system the models trained with the noisy data as well perform near the gold data standards.
- Structured surface level strings with anchors are easy to parse using ML models as compared to RegEx match and end-to-end models as well. (Near perfect Result 95% given 5% CER; ~3% gain)




Moving On....

The Problem: BAR "Bundesratsprotokolle"






Some Pages

The Problem: BAR "Bundesratsprotokolle"



Some Pages

The Problem: BAR "Bundesratsprotokolle"




Some Pages

The Problem: BAR “Bundesratsprotokolle”

Heading and Resolution number, marginalia, paragraphs

(page 1 of doc 13685 in collection 4583)



Why a problem?



For a collection of Documents like BAR

- Horizontal line is not strictly the delimiter (unlike ABP - Table Understanding)

It requires a knowledge of what is a Segment

- Model the problem as learning that knowledge
- Can utilise the semantic tags here

Input: Line Dual Graph



Edge Conv Nets (ECN)

DAS 2018 Idea: learn graph convolutions which depends on edge features

A convolution computes a scalar for each edge

i.e a parametrized adjacency matrix: E_{ij}

$$h_i^{l+1} = \sigma \left(\left[\sum_{j \in N_i} E_{ij}^l W^l h_j, \quad W^l h_i \right] \right)$$



Stack/Adding them

several convolutions per layer

Similar Idea in Graph Attention Network, ICLR'18

Modeling: Retrieving Segments as Clusters

- Score [0,1] Use score to form cluster
 - Many pure/heuristic approaches
 - Threshold Based selection ($T > 0.5$)



Results

Edge Classification (with textual features, positional features, relative positional and other geographical features)

Feature	Model	Accuracy (3Fold-CV)	
TestUnit		TextRegion	TextLine
F	CRF*(==1)	0.89	0.91
	ECN(>0.5)	0.88	0.90
	SVM(==1)	0.70	0.73
	LR(>0.5)	0.81	0.82
F+S	CRF(==1)	0.92	0.92
	ECN(>0.5)	0.90	0.91
	SVM(==1)	0.72	0.74
	LR(>0.5)	0.82	0.83

Results

Segmentation @ F1 (CRF)

Seg Type/F1	0.6	0.7	0.8	0.9	1.0
with 'IGNORE'					
TextUnit (Micro)	0.82	0.74	0.65	0.58	0.47
Resolution(Macro)	0.83	0.75	0.67	0.58	0.49
without 'IGNORE'					
TextUnit (Micro)	0.79	0.72	0.65	0.56	0.45
Resolution(Macro)	0.76	0.69	0.63	0.52	0.44

*Comparison with other EC models reflect direct correlation with edge classification

**Comparison with complete different approach (1/0 segmentation ~59% Micro F1)

Devotatensieg vom 29. Januar 1855.

ine vom 8. Januar 2. 7. N. J. erledigt, nach Vorverlung

Aaa-gewiesen.

h.

der Devotatensieg über macht unterm 25. 1. ein

vom Pedellen der Btrenommandungen ihm zugewiesenes Aus-

Kurfürstehoren der HH. Dek und oldo2s betreffend einen

and laids in Anweille und gibt zugleich edie gewünschte Aus-

Kunst indem ir heinehus, auf die Ainstatthaftigkeit

anfreersam macht, daß Schweizer sich mit solchen Begehren-

an die Landesbehörde wenden, währendt in Konsulat zur

Wahenung ihrer Interessen auf dem Pflaze bestehe

n Annat.

An den Konsul Mittheilung der Beilage

3.) Zuschrift vom 11. 25. 1. erstattet des Konsul in

Diga Bericht über dors Ergebnis der nach Auftrag vom 30. 5.

s75f. pvAd, eingezogenen Eptundigeungen betreffend die

Nachlaßverhältnisse des in Anitan verstorbenen Rndolf Frsse-

von Ikon-Dyukan, im Wesentlichen dahin gehend, daß

das erhaantene Detizthum Banum zur Letung der darauf

haftenten Schalden genigen Türfte

A. nane

Di Regierung von Shnyzersucht unterm No. 3.

um Einziehung von Erfändigungen über einen Peit 1855

Verschollenen C. Micsnes-Henyon rtte, der sich noch

im Juni 1855 zu Weiten in eheimpreussischen Freis

Masegbanden aufgehalten habe

Andie Gesandtschaftan Salin z. 6

frer Bezunnahme auf die Eisladung vom

Madolte Lonct

Dang etiacnd

Aassmift

N

Riga Nrenl

Rndolf Lontor

Nicolaßratältnuß

E

koog-

c. Militior Anna-

Mumudigung

§29.

Bo Wri

Ingeho. Motinan

0

Devotärsieg vom 29. Januar 1855.

ine vom 8. Januar 2. 7. N. J. erledigt, nach Vormerlung

Aaaa gewiesen.

h.

der Deuin candell über macht unterm 25. 1. ein

vom Pedellen der Btrnommungen ihm zugewiesenes Aus-

Kurfürstehren der HH. Dek und oldo's betrifft einen

and laids in Anweille und gibt zugleich edie gewünschte Aus-

Kunst indem ir heinehus, auf die Ainstatthaftigkeit

anfreuersam macht, daß Schweizer sich mit solchen Begehren-

an die Landesbehörde wenden, während in Konsulat zur

Wahenung ihrer Interessen auf dem Pflaze bestehe

n Annat.

13

An den Konsul Mittheilung der Beilage

Madolte Lonct

Dang etjand

Aassmift

N 17

3.) Zuschrift vom 11. 25. 1. erstattet des Konsulin

Diga Bericht über dors Ergebnis der nach Auftrag vom 30. 5.

s. 75 f. pvld, eingezogenen Eptundigeungen betreffend die

Nachlaßverhältnisse des in Ankan verstorbene Rndolf Frsse-

von kon-Dyukan, im Wesentlichen dahin gehed, daß

das erhaatene Detizthum Banum zur Letung der darauf

haftenten Schalden genigen Türfte

25

A. nraue

Riga Nrenl

Rndolf Lontor

Nicolaßratältniß

E 29

Di Regierung von Shny zersucht unterm No. 3.

um Einziehung von Erfändigungen über einen Peit 1855

Verschollenen C. Micsnes-Henyon rtte, der sich noch

im Juni 1855 zu Weiten im eheimpreussischen Freis

Masegbanden aufgehalten habe

35

An die Gesandtschaft an Salin z. 6

kog-

c. Militior Anna-

Mumndigung

\$29

39

40

frer Bezunnahme auf die Eisladung vom

Bo Wri

Ingeho. Motinan

Predicted:

0: [0],

1: [1, 2],

2: [3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17],

3: [18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29],

4: [35, 36, 30, 31],

5: [32, 33, 34, 37, 38, 39],

6: [40, 41, 42, 43, 44, 45, 46]

True:

'bar_576': [1, 2],

'bar_577': [3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17],

'bar_578': [18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29],

'bar_579': [30, 31, 32, 33, 34, 35, 36, 37, 38, 39],

'bar_580': [40, 41, 42, 43, 44, 45, 46],

'bar_IGNORE': [0]

Takeaway

Edge Classification followed by clustering can result into segmentation using document agnostic clustering

Thank you

<https://es.naverlabs.com/animesh-prasad>

© 2017 NAVER LABS. All rights reserved.

LABS