UPnP Technical basics: UPnP Device Architecture (UDA)

July 2014

Universal Plug and Play

This now belongs to Open Connectivity Foundation, OCF

UPnP Functionality

Protocol

What steps are required

E.g. First request list of content transfer protocols then decide which one to use

Control

What does a command do

E.g. setVolume – sets volume between 1 and some device max Play – set a MediaRenderer in PlayState

Description

Which information is exchanged

E.g. List of supported functions grouped in services, function calls, events

Discover

How do devices detect each other

E.g. regular "alive" messages, Bye-bye messages

UPnP Phases (overview)



0 Control points and devices get IP addresses using DHCP (, or AutoIP)

1 Control point finds interesting device

2 Control point learns about device capabilities

3 Control point invokes actions on device

4 Control point listens to state changes of device

5 Control point interacts with a device with sequences of commands and events

UPnP Phases (Discovery)

SSDP:Simple Service Discovery Protocol



1 Find devices: Listen for SSDP Alive messages, or issue search

M-SEARCH * HTTP/1.1
HOST: 239.255.255.250:1900
MAN: "ssdp:discover"
MX: *seconds to delay response*
ST: *search target*

HTTP/1.1 200 OK
CACHE-CONTROL: max-age = *seconds until advertisement expires*
LOCATION: *URL for UPnP description for root device*
ST: *search target*
USN: *advertisement UUID*

SSDP

SSDP - IETF Draft *Simple Service Discovery Protocol*
Based on UDP Multicast

In UDP, we can unicast and multicast

Devices and services post Alive message at regular intervals

- Usually repeated 3 times (because UDP messages might be lost)
- Repeated every few seconds (e.g. 10 secs)
- Determines worst case detection time of a device

Other Messages: Search, Bye-Bye

NOTIFY * HTTP/1.1
HOST: 239.255.255.250:1900
CACHE-CONTROL: max-age = sec
LOCATION: *URL for UPnP descript*
NT: *search target*
NTS: ssdp:alive
USN: *advertisement UUID*

Multicast address

Port usually 1900

DLNA: port 1900 is mandatory

Location of device for further communication

UPnP Phases (Description)



2 Use URL from SSDP message to get device description
Use URL from SSDP message or device description to get service description

Descriptions use XML to describe what
services and functions a device offers
Find out which Optional functions are available
Find out what vendor specific functions are available

Devices

UPnP Device:

- Not a real physical device
- Representation of a logical entity
- A set of functions and state

UPnP Device examples:

- Media Server
- Media Renderer
- Internet Gateway device
- Printer

- No 1 to 1 mapping with real world devices/boxes
- TV: Media Player + Media Renderer
- PC: Media Server + Printer + Scanner
- Wireless Access point: Wireless Access point device + Printer device (proxy)

Device Description – general info

```
<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <URLBase>base URL for all relative URLs</URLBase>
  <device>
    <friendlyName>short user-friendly title</friendlyName>
    <manufacturer>manufacturer name</manufacturer>
    <manufacturerURL>URL to manufacturer site</manufacturerURL>
    <modelDescription>long user-friendly title</modelDescription>
    <modelName>model name</modelName>
    <modelNumber>model number</modelNumber>
    <modelURL>URL to model site</modelURL>
    <serialNumber>manufacturer's serial number</serialNumber>
    <UDN>uuid:UUID</UDN>
    <UPC>Universal Product Code</UPC>
    <deviceType>urn:schemas-upnp-org:device:deviceType:v</deviceType>
    <serviceList>
      <service>
        <serviceType>urn:schemas-upnp-org:service:serviceType:v</serviceType>
        <serviceId>urn:upnp-org:serviceId:serviceID</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      Declarations for other services (if any) go here
    </serviceList>
    <deviceList>Description of embedded devices (if any) go here</deviceList>
    <iconList>
      <icon>
        <mimetype>image/format</mimetype>
        <width>horizontal pixels</width>
        <height>vertical pixels</height>
        <depth>color depth</depth>
        <url>URL to icon</url>
      </icon>
      XML to declare other icons, if any, go here
    </iconList>
    <presentationURL>URL for presentation</presentationURL>
  </device>
  <specVersion>
    <major>1</major><minor>0</minor>
  </specVersion>
</root>
```

Device Description – service information

```
<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <URLBase>base URL for all relative URLs</URLBase>
  <device>
    <friendlyName>short user-friendly title</friendlyName>
    <manufacturer>manufacturer name</manufacturer>
    <manufacturerURL>URL to manufacturer site</manufacturerURL>
    <modelDescription>long user-friendly title</modelDescription>
    <modelName>model name</modelName>
    <modelNumber>model number</modelNumber>
    <modelURL>URL to model site</modelURL>
    <serialNumber>manufacturer's serial number</serialNumber>
    <UDN>uuid:UUID</UDN>
    <UPC>Universal Product Code</UPC>
    <deviceType>urn:schemas-upnp-org:device:deviceType :v</deviceType>
    <serviceList>
      <service>
        <serviceType>urn:schemas-upnp-org:service:serviceType:v</serviceType>
        <serviceId>urn:upnp-org:serviceId:serviceID</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      Declarations for other services (if any) go here
    </serviceList>
    <deviceList>Description of embedded devices (if any) go here</deviceList>
    <iconList>
      <icon>
        <mimetype>image/format</mimetype>
        <width>horizontal pixels</width>
        <height>vertical pixels</height>
        <depth>color depth</depth>
        <url>URL to icon</url>
      </icon>
      XML to declare other icons, if any, go here
    </iconList>
    <presentationURL>URL for presentation</presentationURL>
  </device>
  <specVersion>
    <major>1</major><minor>0</minor>
  </specVersion>
</root>
```

Device Description – display information

```
<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <URLBase>base URL for all relative URLs</URLBase>
  <device>
    <friendlyName>short user-friendly title</friendlyName>
    <manufacturer>manufacturer name</manufacturer>
    <manufacturerURL>URL to manufacturer site</manufacturerURL>
    <modelDescription>long user-friendly title</modelDescription>
    <modelName>model name</modelName>
    <modelNumber>model number</modelNumber>
    <modelURL>URL to model site</modelURL>
    <serialNumber>manufacturer's serial number</serialNumber>
    <UDN>uuid:UUID</UDN>
    <UPC>Universal Product Code</UPC>
    <deviceType>urn:schemas-upnp-org:device:deviceType</deviceType>
    <serviceList>
      <service>
        <serviceType>urn:schemas-upnp-org:service:serviceType:</serviceType>
        <serviceId>urn:upnp-org:serviceId:serviceID</serviceId>
        <SCPDURL>URL to service description</SCPDURL>
        <controlURL>URL for control</controlURL>
        <eventSubURL>URL for eventing</eventSubURL>
      </service>
      Declarations for other services (if any) go here
    </serviceList>
    <deviceList>Description of embedded devices (if any) go here</deviceList>
      <iconList>
        <icon>
          <mimetype>image/format</mimetype>
          <width>horizontal pixels</width>
          <height>vertical pixels</height>
          <depth>color depth</depth>
          <url>URL to icon</url>
        </icon>
        XML to declare other icons, if any, go here
      </iconList>
      <presentationURL>URL for presentation</presentationURL>
    </device>
    <specVersion>
      <major>1</major> <minor>0</minor>
    </specVersion>
</root>
```

Services

Logical grouping of functions and (state) variable definition

Examples:

- Connection Manager service: A set of functions that are used to negotiate which protocol to use for communication
- Content Directory service: set of functions that describe the content available on a server
- Rendering Control (service): set of functions that change settings like volume, brightness, contrast etc.
- Media Renderer: set of functions to control playback (via the network)
- State variables are used 2 two ways
  - Conveying state, like SystemUpdateID of the CDS
  - Type definition of arguments in actions
    - preceded by A_ARG_TYPE_

Service Description - actions

```
<?xml version="1.0"?>
<scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <actionList>
    <action>
      <name>actionName</name>
      <argumentList>
        <argument>
          <name>formalParameterName</name>
          <direction>in xor out</direction>
          <retval />
          <relatedStateVariable>stateVariableName</relatedStateVariable>
        </argument>
       Declarations for other arguments (if any) go here
      </argumentList>
    </action>
    Declarations for other actions (if any) go here
  </actionList>
<serviceStateTable>
  <stateVariable sendEvents="yes" xor "no">
    <name>variableName</name>
    <dataType>variable data type</dataType>
    <defaultValue>default value</defaultValue>
    <allowedValueRange>
      <minimum>minimum value</minimum>
      <maximum>maximum value</maximum>
      <step>increment value</step>
    </allowedValueRange>
  </stateVariable>
  <stateVariable sendEvents="yes" xor "no">
    <name>variableName</name>
    <dataType>variable data type</dataType>
    <defaultValue>default value</defaultValue>
    <allowedValueList>
      <allowedValue>some value</allowedValue>
      <allowedValue>some value</allowedValue>
    </allowedValueList>
  </stateVariable>
  Declarations for other state variables
</serviceStateTable>
<specVersion>
  <major>1</major><minor>0</minor>
</specVersion>
</scpd>
```

Service Description – state variables

```
<?xml version="1.0"?>
<scpd xmlns="urn:schemas-upnp-org:service-1-0">
  <serviceStateTable>
    <stateVariable sendEvents="yes" xor "no">
      <name>variableName</name>
      <dataType>variable datatype</dataType>
      <defaultValue>default value</defaultValue>
      <allowedValueRange>
        <minimum>minimum value</minimum>
        <maximum>maximum value</maximum>
        <step>increment value</step>
      </allowedValueRange>
    </stateVariable>
  </serviceStateTable>
</scpd>
```

UPnP Phases (Control)



3 Send actions to a device using SOAP
Receive responses using SOAP

Remote procedure call mechanism based on SOAP.

Remote Procedure Calls

Based on SOAP (IETF Draft *Simple Object Access Protocol)*
= XML messages using HTTP headers

```
POST path of control URL HTTP/1.1
HOST: host of control URL:port of control URL
CONTENT-TYPE: text/xml; charset="utf-8"
SOAPACTION: "urn:schemas-upnp-org:service:serviceType:v#actionName"

<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/"
   s:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
 <s:Body>
   <u:actionName xmlns:u="urn:schemas-upnp-org:service:serviceType:v">
     <argumentName>in arg value</argumentName>
     other in args and their values (if any) go here
   </u:actionName>
 </s:Body>
</s:Envelope>
```

Remote Procedure Call Response

Response by device:

It's always 200 ok, even if it has an error

```
HTTP/1.1 200 OK
CONTENT-TYPE: text/xml; charset="utf-8"

<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/"
   s:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
  <s:Body>
   <u:actionNameResponse
      xmlns:u="urn:schemas-upnp-org:service:serviceType:v">
    <argumentName>out arg value</argumentName>
    other out args and their values (if any) go here
   </u:actionNameResponse>
  </s:Body>
</s:Envelope>
```

UPnP Phases (Eventing)



4 Control points can subscribe to events from a certain device
Events are send by device to control point when a state variable changes.
E.g. ContainerUpdateID, Volume (LastChange)

GENA - IETF Draft General Event Notification Architecture

Message over HTTP via TCP, but also via UDP multicast

GENA stands for **General Event Notification Architecture**. GENA **Base** defines an HTTP notification architecture that transmits notifications between HTTP resources. An HTTP resource could be any object which might need to send or receive a notification, for example a distribution list, buddy list, print job, etc. It was defined in Internet-Draft *draft-cohen-gena-p-base-01.txt* (now expired).

Alexandre VERDET: Con : it is not very energy effective
girard:it is insecure
Jehad Melad:using SOAP maybe can be a disadvantage
Cédric Gormond: Pro : Upnp is a great architecture for home devices and networks.
dhayananth:SOAP based would be disadvantages. because we implementation would be difficult. also XML is less convenient

GENA - Subscribe

SUBSCRIBE *publisher path* HTTP/1.1
HOST: *publisher host*:*publisher port*
CALLBACK: <*delivery URL*>
NT: **upnp:event**
TIMEOUT: Second-*requested subscription duration*

Control points subscribe per Service and Device.

- Control point is in control for which service it will receive the notifications
- All notifications per service will be received.
- Have to re-subscribe before TIMEOUT elapses

GENA - Notify

NOTIFY *delivery path* HTTP/1.1
HOST: *delivery host*:*delivery port*
CONTENT-TYPE: text/xml
NT: **upnp:event**
NTS: **upnp:propchange**
SID: uuid:*subscription-UUID*
SEQ: *event key*

```
<e:propertyset xmlns:e="urn:schemas-upnp-org:event-1-0">
  <e:property>
    <variableName>new value</variableName>
  </e:property>
  Other variable names and values (if any) go here
</e:propertyset>
```

Device sends same property set to each subscribed control point

- Sequence (SEQ) is tracking initial & following notification
- Initial notification is ALWAYS sent by the device

UPnP Phases (Protocol)

5 List of logical sequences on top of Control and Eventing.

Control point interacts with multiple devices to create an scenario.

Also control points should listen to events, so they know what has changed in the eco system, and should reflect this in their UI.

Protocol example (sequence of actions)

Steps needed to play an item from a Media Server on a Media Renderer

1. Select a Media server
2. Invoke Browse(), to present content for selection for playback
3. Select a Media Server
4. Invoke GetProtocolInfo() on the Media Renderer
5. Match the ProtocolInfo from the content and the MediaRenderer
6. Invoke SetAVTransportURI() with the matched content
7. Invoke Play(), to start the playback of the content

For the interconnected lifestyle