



# Team Contest Reference

**Team: Lühack**

*Lennart Weckeck*

*Thore Tiemann*

*Marcel Wienöbst*

## Contents

<b>1</b>	<b>DP</b>	<b>3</b>
1.1	LongestIncreasingSubsequence . . . . .	3
1.2	LongestIncreasingSubsequence . . . . .	3
<b>2</b>	<b>DataStructures</b>	<b>3</b>
2.1	Fenwick-Tree . . . . .	3
2.2	Range Maximum Query . . . . .	3
2.3	Trie . . . . .	4
2.4	Union-Find . . . . .	4
2.5	Suffix array . . . . .	5
<b>3</b>	<b>Graph</b>	<b>5</b>
3.1	2SAT . . . . .	5
3.2	Breadth First Search . . . . .	5
3.3	BellmanFord . . . . .	6
3.4	Bipartite Graph Check . . . . .	6
3.5	Maximum Bipartite Matching . . . . .	6
3.6	Bitonic TSP . . . . .	7
3.7	Single-source shortest paths in dag . . . . .	7
3.8	Dijkstra . . . . .	7
3.9	EdmondsKarp . . . . .	7
3.10	Reference for Edge classes . . . . .	8
3.11	FloydWarshall . . . . .	8
3.12	Held Karp . . . . .	8
3.13	Iterative DFS . . . . .	9
3.14	Johnsons Algorithm . . . . .	9
3.15	Kruskal . . . . .	9
3.16	Min Cut . . . . .	10
3.17	Prim . . . . .	10
3.18	Recursive Depth First Search . . . . .	10
3.19	Strongly Connected Components . . . . .	11
3.20	Suurballe . . . . .	11
3.21	Kahns Algorithm for TS . . . . .	12
3.22	Topological Sort . . . . .	12
3.23	Tuple . . . . .	12
3.24	Reference for Vertex classes . . . . .	12
3.25	Dijkstra . . . . .	13
3.26	EdmondsKarp . . . . .	13
<b>4</b>	<b>Math</b>	<b>13</b>
4.1	Binomial Coefficient . . . . .	13
4.2	Binomial Matrix . . . . .	14
4.3	Divisability . . . . .	14
4.4	Graham Scan . . . . .	14
4.5	Iterative EEA . . . . .	15
4.6	Polynomial Interpolation . . . . .	15

4.7	Root of permutation . . . . .	16
4.8	Sieve of Eratosthenes . . . . .	17
4.9	Greatest Common Divisor . . . . .	17
4.10	Least Common Multiple . . . . .	17
4.11	GEV . . . . .	17
4.12	Fourier transform . . . . .	19
4.13	Matrix exponentiation . . . . .	19
4.14	phi function calculator . . . . .	20
4.15	prints farey seq . . . . .	20
<b>5</b>	<b>Misc</b>	<b>20</b>
5.1	Binary Search . . . . .	20
5.2	Next number with n bits set . . . . .	20
5.3	Next Permutation . . . . .	20
5.4	Greedy-Scheduling . . . . .	21
5.5	comparator in C++ . . . . .	21
5.6	hashing pair in C++ . . . . .	21
5.7	Mo's algorithm . . . . .	21
<b>6</b>	<b>String</b>	<b>22</b>
6.1	Knuth-Morris-Pratt . . . . .	22
6.2	Levenshtein Distance . . . . .	23
6.3	Longest Common Subsequence . . . . .	23
6.4	Longest common substring . . . . .	23
<b>7</b>	<b>auto</b>	<b>23</b>
<b>8</b>	<b>Math</b>	<b>23</b>
8.1	Tree . . . . .	23
8.2	Divisability Explanation . . . . .	24
8.3	Combinatorics . . . . .	24
8.4	Polynomial Interpolation . . . . .	24
8.4.1	Theory . . . . .	24
8.5	Fibonacci Sequence . . . . .	24
8.5.1	Binet's formula . . . . .	24
8.5.2	Generalization . . . . .	24
8.5.3	Pisano Period . . . . .	24
8.6	Reihen . . . . .	24
8.7	Binomialkoeffizienten . . . . .	24
8.8	Catalanzahlen . . . . .	24
8.9	Geometrie . . . . .	24
8.10	Zahlentheorie . . . . .	24
8.11	Faltung . . . . .	24
<b>9</b>	<b>Java Knowhow</b>	<b>25</b>
9.1	System.out.printf() und String.format() . . . . .	25
9.2	Modulo: Avoiding negative Integers . . . . .	25
9.3	Speed up IO . . . . .	25

$n$	Runtime $100 \cdot 10^6$ in 3s
[10, 11]	$\mathcal{O}(n!)$
$< 22$	$\mathcal{O}(2^n)$
$\leq 100$	$\mathcal{O}(n^4)$
$\leq 400$	$\mathcal{O}(n^3)$
$\leq 2.000$	$\mathcal{O}(n^2 \log n)$
$\leq 10.000$	$\mathcal{O}(n^2)$
$\leq 1.000.000$	$\mathcal{O}(n \log n)$

byte (8 Bit, signed): -128 ... 127

short (16 Bit, signed): -32.768 ... 32.767

integer (32 Bit, signed): -2.147.483.648 ... 2.147.483.647

long (64 Bit, signed):  $-2^{63} \dots 2^{63} - 1$

**MD5:** cat <string>| tr -d [:space:] | md5sum

## 1 DP

### 1.1 LongestIncreasingSubsequence

Computes the length of the longest increasing subsequence and is easy to be adapted.

*Input:* array *arr* containing a sequence of length *N*

*Output:* length of the longest increasing subsequence in *arr*

```

1 // This has not been tested yet
2 // (adapted from tested C++ Murcia Code)
3 public static int LISeasy(int[] arr, int N) {
4     int[] m = new int[N];
5     for (int i = N - 1; i >= 0; i--) {
6         m[i] = 1; //init table
7         for (int j = i + 1; j < N; j++) {
8             // if arr[i] increases the length
9             // of subsequence from array[j]
10            if (arr[j] > arr[i])
11                if (m[i] < m[j] + 1)
12                    // store length of new subseq
13                    m[i] = m[j] + 1;
14        }
15    }
16    // find max in array
17    int longest = 0;
18    for (int i = 0; i < N; i++) {
19        if (m[i] > longest)
20            longest = m[i];
21    }
22    return longest;
23 }
```

**MD5:** 7561f576d50b1dc6262568c0fc6c42dd |  $\mathcal{O}(n^2)$

### 1.2 LongestIncreasingSubsequence

Computes the longest increasing subsequence using binary search.

*Input:* array *arr* containing a sequence and empty array *p* of length *arr.length* for storing indices of the LIS (might be useful to have)

*Output:* array *s* containing the longest increasing subsequence

```

1 public static int[] LISfast(int[] arr, int[] p) {
2     // p[k] stores index of the predecessor of arr[k]
3     // in the LIS ending at arr[k]
4     // m[j] stores index k of smallest value arr[k]
5     // so there is a LIS of length j ending at arr[k]
6     int[] m = new int[arr.length+1];
7     int l = 0;
8     for (int i = 0; i < arr.length; i++) {
9         // bin search for the largest positive j <= l
10        // with arr[m[j]] < arr[i]
11        int lo = 1;
12        int hi = l;
13        while (lo <= hi) {
14            int mid = (int) (((lo + hi) / 2.0) + 0.6);
15            if (arr[m[mid]] <= arr[i])
16                lo = mid+1;
17            else
18                hi = mid-1;
19        }
20    }
```

```

20 // lo is 1 greater than length of the
21 // longest prefix of arr[i]
22 int newL = lo;
23 p[i] = m[newL-1];
24 m[newL] = i;
25 // if LIS found is longer than the ones
26 // found before, then update l
27 if (newL > l)
28     l = newL;
29 }
30 // reconstruct the LIS
31 int[] s = new int[l];
32 int k = m[l];
33 for (int i = l-1; i >= 0; i--) {
34     s[i] = arr[k];
35     k = p[k];
36 }
37 return s;
38 }
```

**MD5:** 1d75905f78041d832632cb76af985b8e |  $\mathcal{O}(n \log n)$

## 2 DataStructures

### 2.1 Fenwick-Tree

Can be used for computing prefix sums.

```

1 //note that 0 can not be used
2 int[] fwktree = new int[m + n + 1];
3 public static int read(int index, int[] fenwickTree) {
4     int sum = 0;
5     while (index > 0) {
6         sum += fenwickTree[index];
7         index -= (index & -index);
8     }
9     return sum;
10 }
11 public static int[] update(int index, int addValue,
12     int[] fenwickTree) {
13     while (index <= fenwickTree.length - 1) {
14         fenwickTree[index] += addValue;
15         index += (index & -index);
16     }
17     return fenwickTree;
18 }
```

**MD5:** 410185d657a3a5140bde465090ff6fb5 |  $\mathcal{O}(\log n)$

### 2.2 Range Maximum Query

*process* processes an array *A* of length *N* in  $\mathcal{O}(N \log N)$  such that *query* can compute the maximum value of *A* in interval  $[i, j]$ . Therefore  $M[a, b]$  stores the maximum value of interval  $[a, a + 2^b - 1]$ .

*Input:* dynamic table *M*, array to search *A*, length *N* of *A*, start index *i* and end index *j*

*Output:* filled dynamic table *M* or the maximum value of *A* in interval  $[i, j]$

```

1 public static void process(int[][] M, int[] A, int N)
2 {
3     for (int i = 0; i < N; i++)
4         M[i][0] = i;
```

```

4 // filling table M
5 // M[i][j] = max(M[i][j-1], M[i+(1<<(j-1))][j-1]),
6 // cause interval of length 2^j can be partitioned
7 // into two intervals of length 2^(j-1)
8 for(int j = 1; 1 << j <= N; j++) {
9     for(int i = 0; i + (1 << j) - 1 < N; i++) {
10         if(A[M[i][j-1]] >= A[M[i+(1 << (j-1))][j-1]])
11             M[i][j] = M[i][j-1];
12         else
13             M[i][j] = M[i + (1 << (j-1))][j-1];
14     }
15 }
16 }
17
18 public static int query(int[][] M, int[] A, int N,
19                         int i, int j) {
20     // k = |_ log_2(j-i+1) _|
21     int k = (int) (Math.log(j - i + 1) / Math.log(2));
22     if(A[M[i][k]] >= A[M[j - (1 << k) + 1][k]])
23         return M[i][k];
24     else
25         return M[j - (1 << k) + 1][k];
26 }

```

MD5: db0999fa40037985ff27dd1a43c53b80 |  $\mathcal{O}(N \log N, 1)$

## 2.3 Trie

```

1 public static boolean insert(TrieNode root, String
   word){
2     char[] s = word.toCharArray();
3     TrieNode node = root;
4
5     for(int i = 0; i < s.length; ++i){
6         int index = charToIndex(s[i]);
7         if(node.children[index] == null){
8             node.children[index] = new TrieNode(node);
9         }
10        node = node.children[index];
11    }
12    node.isEnd = true;
13
14    return true;
15 }
16
17 public static boolean search(TrieNode root, String
   word){
18     char[] s = word.toCharArray();
19     TrieNode node = root;
20
21     for(int i = 0; i < s.length; ++i){
22         int index = charToIndex(s[i]);
23         if(node.children[index] == null){
24             return false;
25         }
26         node = node.children[index];
27     }
28
29     return node.isEnd;
30 }
31
32 public static int charToIndex(char c){
33     return ((int) c - (int) a);
34 }
35
36 static class TrieNode{
37

```

```

38     boolean isEnd;
39     TrieNode[] children;
40
41     public TrieNode(){
42         isEnd = false;
43         children = new TrieNode[26];
44     }
45 }

```

MD5: 95ebde7b285a97b8834aedd9c2bf9ff2 |  $\mathcal{O}(|w|)$

## 2.4 Union-Find

Union-Find is a data structure that keeps track of a set of elements partitioned into a number of disjoint subsets. *UnionFind* creates  $n$  disjoint sets each containing one element. *union* joins the sets  $x$  and  $y$  are contained in. *find* returns the representative of the set  $x$  is contained in.

*Input*: number of elements  $n$ , element  $x$ , element  $y$

*Output*: the representative of element  $x$  or a boolean indicating whether sets got merged.

```

1 class UnionFind {
2     private int[] p = null;
3     private int[] r = null;
4     private int count = 0;
5
6     public int count() {
7         return count;
8     } // number of sets
9
10    public UnionFind(int n) {
11        count = n; // every node is its own set
12        r = new int[n]; // every node is its own tree with
13                       height 0
14        p = new int[n];
15        for (int i = 0; i < n; i++)
16            p[i] = -1; // no parent = -1
17    }
18
19    public int find(int x) {
20        int root = x;
21        while (p[root] >= 0) { // find root
22            root = p[root];
23        }
24        while (p[x] >= 0) { // path compression
25            int tmp = p[x];
26            p[x] = root;
27            x = tmp;
28        }
29        return root;
30    }
31
32    // return true, if sets merged and false, if already
33    // from same set
34    public boolean union(int x, int y) {
35        int px = find(x);
36        int py = find(y);
37        if (px == py)
38            return false; // same set -> reject edge
39        if (r[px] < r[py]) { // swap so that always h[px]
40            >= h[py]
41            int tmp = px;
42            px = py;
43            py = tmp;
44        }
45    }

```

```

42     p[py] = px; // hang flatter tree as child of
        higher tree
43     r[px] = Math.max(r[px], r[py] + 1); // update (
        worst-case) height
44     count--;
45     return true;
46 }
47 }

```

MD5: 5c507168e1ffd9ead25babf7b3769cfd |  $\mathcal{O}(\alpha(n))$

## 2.5 Suffix array

```

1  #include<vector>
2  #include<string>
3  #include<algorithm>
4
5  using namespace std;
6
7  vector<int> sa, pos, tmp, lcp;
8  string s;
9  int N, gap;
10
11 bool sufCmp(int i, int j) {
12     if(pos[i] != pos[j])
13         return pos[i] < pos[j];
14     i += gap;
15     j += gap;
16     return (i < N && j < N) ? pos[i] < pos[j] : i > j;
17 }
18
19 void buildSA()
20 {
21     N = s.size();
22     for(int i = 0; i < N; ++i) {
23         sa.push_back(i);
24         pos.push_back(s[i]);
25     }
26     tmp.resize(N);
27     for(gap = 1; gap * 2 < N; gap *= 2) {
28         sort(sa.begin(), sa.end(), sufCmp);
29         for(int i = 0; i < N - 1; ++i) {
30             tmp[i+1] = tmp[i] + sufCmp(sa[i], sa[i+1]);
31         }
32         for(int i = 0; i < N; ++i) {
33             pos[sa[i]] = tmp[i];
34         }
35         if(tmp[N-1] == N-1) break;
36     }
37 }
38
39 void buildLCP()
40 {
41     lcp.resize(N);
42     for(int i = 0, k = 0; i < N; ++i) {
43         if(pos[i] != N - 1) {
44             for(int j = sa[pos[i] + 1]; s[i + k] == s[j + k]
45                 ;) {
46                 ++k;
47             }
48             lcp[pos[i]] = k;
49             if (k) --k;
50         }
51     }
52 }
53 int main()

```

```

54 {
55     string r, t;
56     cin >> r >> t;
57     s = r + "$" + t;
58     buildSA();
59     buildLCP();
60     for(int i = 0; i < N; ++i) {
61         cout << sa[i] << " " << lcp[i] << endl;
62     }
63     int mx = 0, mxi = -1;
64     for(int i = 0; i+1 < s.size(); ++i) {
65         bool a_in_s = sa[i] < r.size(), b_in_s = sa[i+1] <
66             r.size();
67         if(a_in_s != b_in_s) {
68             int l = lcp[i];
69             if(l > mx) {
70                 mx = l;
71                 mxi = sa[i];
72             }
73         }
74     }
75     cout << mx << endl;
76     cout << s.substr(mxi, mx) << endl;
77 }

```

MD5: 96e0269748dc2834567a075768eb871a |  $\mathcal{O}(?)$

## 3 Graph

### 3.1 2SAT

```

1  //We assume that ind(not a) = ind(a) + N, with N being
        the number of variables
2  //could however be changed easily
3  public static boolean 2SAT(Vertex[] G) {
4      //call SCC
5      double DFS(G);
6      //check for contradiction
7      boolean poss = true;
8      for(int i = 0; i < S+A; i++) {
9          if(G[i].comp == G[i + (S+A)].comp) {
10             poss = false;
11         }
12     }
13     return poss;
14 }

```

MD5: 6c06a2b59fd3a7df3c31b06c58fdaaf5 |  $\mathcal{O}(V + E)$

### 3.2 Breadth First Search

Iterative BFS. Uses ref Vertex class, no Edge class needed. In this version we look for a shortest path from s to t though we could also find the BFS-tree by leaving out t. *Input:* IDs of start and goal vertex and graph as AdjList *Output:* true if there is a connection between s and g, false otherwise

```

1  public static boolean BFS(Vertex[] G, int s, int t) {
2      //make sure that Vertices vis values are false etc
3      Queue<Vertex> q = new LinkedList<Vertex>();
4      G[s].vis = true;
5      G[s].dist = 0;
6      G[s].pre = -1;
7      q.add(G[s]);

```

```

8 //expand frontier between undiscovered and
  discovered vertices
9 while(!q.isEmpty()) {
10     Vertex u = q.poll();
11     //when reaching the goal, return true
12     //if we want to construct a BFS-tree delete this
      line
13     if(u.id == t) return true;
14     //else add adj vertices if not visited
15     for(Vertex v : u.adj) {
16         if(!v.vis) {
17             v.vis = true;
18             v.dist = u.dist + 1;
19             v.pre = u.id;
20             q.add(v);
21         }
22     }
23 }
24 //did not find target
25 return false;
26 }

```

MD5: 71f3fa48b4f1b2abdf3557a27a9a136 |  $\mathcal{O}(|V| + |E|)$

### 3.3 BellmanFord

Finds shortest paths from a single source. Negative edge weights are allowed. Can be used for finding negative cycles.

```

1 public static boolean bellmanFord(Vertex[] G) {
2     //source is 0
3     G[0].dist = 0;
4     //calc distances
5     //the path has max length |V|-1
6     for(int i = 0; i < G.length-1; i++) {
7         //each iteration relax all edges
8         for(int j = 0; j < G.length; j++) {
9             for(Edge e : G[j].adj) {
10                 if(G[j].dist != Integer.MAX_VALUE
11                     && e.t.dist > G[j].dist + e.w) {
12                     e.t.dist = G[j].dist + e.w;
13                 }
14             }
15         }
16     }
17     //check for negative-length cycle
18     for(int i = 0; i < G.length; i++) {
19         for(Edge e : G[i].adj) {
20             if(G[i].dist != Integer.MAX_VALUE
21                 && e.t.dist > G[i].dist + e.w) {
22                 return true;
23             }
24         }
25     }
26     return false;
27 }

```

MD5: d101e6b6915f012b3f0c02dc79e1fc6f |  $\mathcal{O}(|V| \cdot |E|)$

### 3.4 Bipartite Graph Check

Checks a graph represented as adjList for being bipartite. Needs a little adaption, if the graph is not connected.

*Input:* graph as adjList, amount of nodes  $N$  as int

*Output:* true if graph is bipartite, false otherwise

```

1 public static boolean bipartiteGraphCheck(Vertex[] G){
2     // use bfs for coloring each node
3     G[0].color = 1;
4     Queue<Vertex> q = new LinkedList<Vertex>();
5     q.add(G[0]);
6     while(!q.isEmpty()) {
7         Vertex u = q.poll();
8         for(Vertex v : u.adj) {
9             // if node i not yet visited,
10             // give opposite color of parent node u
11             if(v.color == -1) {
12                 v.color = 1-u.color;
13                 q.add(v);
14             } // if node i has same color as parent node u
15             // the graph is not bipartite
16             else if(u.color == v.color)
17                 return false;
18             // if node i has different color
19             // than parent node u keep going
20         }
21     }
22     return true;
23 }

```

MD5: e93d242522e5b4085494c86f0d218dd4 |  $\mathcal{O}(|V| + |E|)$

### 3.5 Maximum Bipartite Matching

Finds the maximum bipartite matching in an unweighted graph using DFS.

*Input:* An unweighted adjacency matrix `boolean[M][N]` with  $M$  nodes being matched to  $N$  nodes.

*Output:* The maximum matching. (For getting the actual matching, little changes have to be made.)

```

1 // A DFS based recursive function that returns true
2 // if a matching for vertex u is possible
3 boolean bpm(boolean bpGraph[][], int u,
4             boolean seen[], int matchR[]) {
5     // Try every job one by one
6     for (int v = 0; v < N; v++) {
7         // If applicant u is interested in job v and v
8         // is not visited
9         if (bpGraph[u][v] && !seen[v]) {
10             seen[v] = true; // Mark v as visited
11
12             // If job v is not assigned to an applicant OR
13             // previously assigned applicant for job v
14             // (which is matchR[v]) has an alternate job
15             // available. Since v is marked as visited in
16             // the above line, matchR[v] in the following
17             // recursive call will not get job v again
18             if (matchR[v] < 0 ||
19                 bpm(bpGraph, matchR[v], seen, matchR)) {
20                 matchR[v] = u;
21                 return true;
22             }
23         }
24     }
25     return false;
26 }
27
28 // Returns maximum number of matching from M to N
29 int maxBPM(boolean bpGraph[][]) {
30     // An array to keep track of the applicants assigned

```

```

31 // to jobs. The value of matchR[i] is the applicant
32 // number assigned to job i, the value -1 indicates
33 // nobody is assigned.
34 int matchR[] = new int[N];
35 // Initially all jobs are available
36 for(int i = 0; i < N; ++i)
37     matchR[i] = -1;
38 // Count of jobs assigned to applicants
39 int result = 0;
40 for (int u = 0; u < M; u++) {
41     // Mark all jobs as not seen for next applicant.
42     boolean seen[] = new boolean[N];
43     for(int i = 0; i < N; ++i)
44         seen[i] = false;
45     // Find if the applicant u can get a job
46     if (bpm(bpGraph, u, seen, matchR))
47         result++;
48 }
49 return result;
50 }

```

MD5: a4cc90bf91c41309ad7aaa0c2514ff06 |  $\mathcal{O}(M \cdot N)$

### 3.6 Bitonic TSP

*Input:* Distance matrix  $d$  with vertices sorted in x-axis direction.

*Output:* Shortest bitonic tour length

```

1 public static double bitonic(double[][] d) {
2     int N = d.length;
3     double[][] B = new double[N][N];
4     for (int j = 0; j < N; j++) {
5         for (int i = 0; i <= j; i++) {
6             if (i < j - 1)
7                 B[i][j] = B[i][j - 1] + d[j - 1][j];
8             else {
9                 double min = 0;
10                for (int k = 0; k < j; k++) {
11                    double r = B[k][i] + d[k][j];
12                    if (min > r || k == 0)
13                        min = r;
14                }
15                B[i][j] = min;
16            }
17        }
18    }
19    return B[N-1][N-1];
20 }

```

MD5: 49fca508fb184da171e4c8e18b6ca4c7 |  $\mathcal{O}(?)$

### 3.7 Single-source shortest paths in dag

Not tested but should be working fine Similar approach can be used for longest paths. Simply go through ts and add 1 to the largest longest path value of the incoming neighbors

```

1 public static void dagSSP(Vertex[] G, int s) {
2     //calls topological sort method
3     LinkedList<Integer> sorting = TS(G);
4     G[s].dist = 0;
5     //go through vertices in ts order
6     for(int u : sorting) {
7         for(Edge e : G[u].adj) {
8             Vertex v = e.t;
9             if(v.dist > u.dist + e.w) {

```

```

10         v.dist = u.dist + e.w;
11         v.pre = u.id;
12     }
13 }
14 }
15 }

```

MD5: 552172db2968f746c4ac0bd322c665f9 |  $\mathcal{O}(|V| + |E|)$

### 3.8 Dijkstra

Finds the shortest paths from one vertex to every other vertex in the graph (SSSP).

For negative weights, add  $|\min|+1$  to each edge, later subtract from result.

To get a different shortest path when edges are ints, add an  $\varepsilon = \frac{1}{k+1}$  on each edge of the shortest path of length  $k$ , run again.

*Input:* A source vertex  $s$  and an adjacency list  $G$ .

*Output:* Modified adj. list with distances from  $s$  and predecessor vertices set.

```

1 public static void dijkstra(Vertex[] G, int s) {
2     G[s].dist = 0;
3     Tuple st = new Tuple(s, 0);
4     PriorityQueue<Tuple> q = new PriorityQueue<Tuple>();
5     q.add(st);
6
7     while(!q.isEmpty()) {
8         Tuple sm = q.poll();
9         Vertex u = G[sm.id];
10        //this checks if the Tuple is still useful, both
11        //checks should be equivalent
12        if(u.vis || sm.dist > u.dist) continue;
13        u.vis = true;
14        for(Edge e : u.adj) {
15            Vertex v = e.t;
16            if(!v.vis && v.dist > u.dist + e.w) {
17                v.pre = u.id;
18                v.dist = u.dist + e.w;
19                Tuple nt = new Tuple(v.id, v.dist);
20                q.add(nt);
21            }
22        }
23    }

```

MD5: e46eb1b919179dab6a42800376f04d7a |  $\mathcal{O}(|E| \log |V|)$

### 3.9 EdmondsKarp

Finds the greatest flow in a graph. Capacities must be positive.

```

1 public static boolean BFS(Vertex[] G, int s, int t) {
2     int N = G.length;
3     for(int i = 0; i < N; i++) {
4         G[i].vis = false;
5     }
6
7     Queue<Vertex> q = new LinkedList<Vertex>();
8     G[s].vis = true;
9     G[s].pre = -1;
10    q.add(G[s]);
11
12    while(!q.isEmpty()) {

```



```

13 Vertex u = q.poll();
14 if(u.id == t) return true;
15 for(int i : u.adj.keySet()) {
16     Edge e = u.adj.get(i);
17     Vertex v = e.t;
18     if(!v.vis && e.rw > 0) {
19         v.vis = true;
20         v.pre = u.id;
21         q.add(v);
22     }
23 }
24 }
25 return (G[t].vis);
26 }
27 //We store the edges in the graph in a hashmap
28 public static int edKarp(Vertex[] G, int s, int t) {
29     int maxflow = 0;
30     while(BFS(G, s, t)) {
31         int pflow = Integer.MAX_VALUE;
32         for(int v = t; v != s; v = G[v].pre) {
33             int u = G[v].pre;
34             pflow = Math.min(pflow, G[u].adj.get(v).rw);
35         }
36         for(int v = t; v != s; v = G[v].pre) {
37             int u = G[v].pre;
38             G[u].adj.get(v).rw -= pflow;
39             G[v].adj.get(u).rw += pflow;
40         }
41         maxflow += pflow;
42     }
43     return maxflow;
44 }

```

MD5: 6067fa877ff237d82294e7511c79d4bc |  $\mathcal{O}(|V|^2 \cdot |E|)$

### 3.10 Reference for Edge classes

Used for example in Dijkstra algorithm, implements edges with weight. Needs testing.

```

1 //for Kruskal we need to sort edges, use: java.lang.
  Comparable
2 class Edge implements Comparable<Edge> {}
3
4 class Edge {
5     //for Kruskal it is helpful to store the start as
6     //well, moreover we might not need the vertex class
7     int s;
8     int t;
9
10    //for EdKarp we also want to store residual weights
11    int rw;
12
13    Vertex t;
14    int w;
15
16    public Edge(Vertex t, int w) {
17        this.t = t;
18        this.w = w;
19        this.rw = w;
20    }
21
22    public Edge(int s, int t, int w) {...}
23
24    public int compareTo(Edge other) {
25        return Integer.compare(this.w, other.w);
26    }

```

```

27 }

```

MD5: aae80ac4bfbfcc0b9ac4c65085f6f123 |  $\mathcal{O}(1)$

### 3.11 FloydWarshall

Finds all shortest paths. Paths in array next, distances in ans.

```

1 public static void floydWarshall(int[][] graph,
2                                 int[][] next, int[][] ans) {
3     for(int i = 0; i < ans.length; i++)
4         for(int j = 0; j < ans.length; j++)
5             ans[i][j] = graph[i][j];
6
7     for (int k = 0; k < ans.length; k++)
8         for (int i = 0; i < ans.length; i++)
9             for (int j = 0; j < ans.length; j++)
10                if (ans[i][k] + ans[k][j] < ans[i][j]
11                    && ans[i][k] < Integer.MAX_VALUE
12                    && ans[k][j] < Integer.MAX_VALUE) {
13                    ans[i][j] = ans[i][k] + ans[k][j];
14                    next[i][j] = next[i][k];
15                }
16 }

```

MD5: a98bbda7e53be8ee0df72dbd8721b306 |  $\mathcal{O}(|V|^3)$

### 3.12 Held Karp

Algorithm for TSP

```

1 public static int[] tsp(int[][] graph) {
2     int n = graph.length;
3     if(n == 1) return new int[]{0};
4     //C stores the shortest distance to node of the
5     //second dimension, first dimension is the
6     //bitstring of included nodes on the way
7     int[][] C = new int[1<<n][n];
8     int[][] p = new int[1<<n][n];
9     //initialize
10    for(int k = 1; k < n; k++) {
11        C[1<<k][k] = graph[0][k];
12    }
13    for(int s = 2; s < n; s++) {
14        for(int S = 1; S < (1<<n); S++) {
15            if(Integer.bitCount(S) != s || (S&1) == 1)
16                continue;
17            for(int k = 1; k < n; k++) {
18                if((S & (1 << k)) == 0) continue;
19
20                //Smk is the set of nodes without k
21                int Smk = S ^ (1<<k);
22
23                int min = Integer.MAX_VALUE;
24                int minprev = 0;
25                for(int m=1; m<n; m++) {
26                    if((Smk & (1<<m)) == 0) continue;
27                    //distance to m with the nodes in Smk +
28                    //connection from m to k
29                    int tmp = C[Smk][m] + graph[m][k];
30                    if(tmp < min) {
31                        min = tmp;
32                        minprev = m;
33                    }
34                }
35                C[S][k] = min;
36            }
37        }
38    }
39    return C[1<<n-1][n-1];
40 }

```



```

32     p[S][k] = minprev;
33 }
34 }
35 }
36
37 //find shortest tour length
38 int min = Integer.MAX_VALUE;
39 int minprev = -1;
40 for(int k = 1; k < n; k++) {
41     //Set of all nodes except for the first + cost
42     //from 0 to k
43     int tmp = C[(1<<n) - 2][k] + graph[0][k];
44     if(tmp < min) {
45         min = tmp;
46         minprev = k;
47     }
48 }
49
50 //Note that the tour has not been tested yet, only
51 //the correctness of the min-tour-value backtrack
52 //tour
53 int[] tour = new int[n+1];
54 tour[n] = 0;
55 tour[n-1] = minprev;
56 int bits = (1<<n)-2;
57 for(int k = n-2; k>0; k--) {
58     tour[k] = p[bits][tour[k+1]];
59     bits = bits ^ (1<<tour[k+1]);
60 }
61 tour[0] = 0;
62 return tour;
63 }

```

MD5: f3e9730287dcbf2695bf7372fc4baf0 |  $\mathcal{O}(2^n n^2)$

### 3.13 Iterative DFS

Simple iterative DFS, the recursive variant is a bit fancier. Not tested.

```

1 //if we want to start the DFS for different connected
2 //components, there is such a method in the
3 //recursive variant of DFS
4 public static boolean ItDFS(Vertex[] G, int s, int t){
5     //take care that all the nodes are not visited at
6     //the beginning
7     Stack<Integer> S = new Stack<Integer>();
8     s.push(s);
9     while(!S.isEmpty()) {
10         int u = S.pop();
11         if(u.id == t) return true;
12         if(!G[u].vis) {
13             G[u].vis = true;
14             for(Vertex v : G[u].adj) {
15                 if(!v.vis)
16                     S.push(v.id);
17             }
18         }
19     }
20     return false;
21 }

```

MD5: 80f28ea9b2a04af19b48277e3c6bce9e |  $\mathcal{O}(|V| + |E|)$

### 3.14 Johnsons Algorithm

```

1 public static int[][] johnson(Vertex[] G) {
2     Vertex[] Gd = new Vertex[G.length+1];
3     int s = G.length;
4     for(int i = 0; i < G.length; i++)
5         Gd[i] = G[i];
6     //init new vertex with zero-weight-edges to each
7     //vertex
8     Vertex S = new Vertex(G.length);
9     for(int i = 0; i < G.length; i++)
10         S.adj.add(new Edge(Gd[i], 0));
11     Gd[G.length] = S;
12
13     //bellman-ford to check for neg-weight-cycles and to
14     //adapt edges to enable running dijkstra
15     if(bellmanFord(Gd, s)) {
16         System.out.println("False");
17         //this should not happen and will cause troubles
18         return null;
19     }
20     //change weights
21     for(int i = 0; i < G.length; i++)
22         for(Edge e : Gd[i].adj)
23             e.w = e.w + Gd[i].dist - e.t.dist;
24     //store distances to invert this step later
25     int[] h = new int[G.length];
26     for(int i = 0; i < G.length; i++)
27         h[i] = G[i].dist;
28
29     //create shortest path matrix
30     int[][] apsp = new int[G.length][G.length];
31
32     //now use original graph G
33     //start a dijkstra for each vertex
34     for(int i = 0; i < G.length; i++) {
35         //reset weights
36         for(int j = 0; j < G.length; j++) {
37             G[j].vis = false;
38             G[j].dist = Integer.MAX_VALUE;
39         }
40         dijkstra(G, i);
41         for(int j = 0; j < G.length; j++)
42             apsp[i][j] = G[j].dist + h[j] - h[i];
43     }
44     return apsp;
45 }

```

MD5: 0a5c741be64b65c5211fe6056ffc1e02 |  $\mathcal{O}(|V|^2 \log V + VE)$

### 3.15 Kruskal

Computes a minimum spanning tree for a weighted undirected graph.

```

1 public static int kruskal(Edge[] edges, int n) {
2     Arrays.sort(edges);
3     //n is the number of vertices
4     UnionFind uf = new UnionFind(n);
5     //we will only compute the sum of the MST, one could
6     //of course also store the edges
7     int sum = 0;
8     int cnt = 0;
9     for(int i = 0; i < edges.length; i++) {
10         if(cnt == n-1) break;
11         if(uf.union(edges[i].s, edges[i].t)) {
12             sum += edges[i].w;
13             cnt++;
14         }
15     }
16 }

```

```

13     }
14 }
15 return sum;
16 }

```

MD5: 91a1657706750a76d384d3130d98e5fb |  $\mathcal{O}(|E| + \log|V|)$

### 3.16 Min Cut

Calculates the min cut using Edmonds Karp algorithm.

```

1 public static void bfs(Vertex[] G, int s) {
2     for(int i = 0; i < G.length; i++) {
3         G[i].vis = false;
4     }
5     Queue<Vertex> q = new LinkedList<Vertex>();
6     q.add(G[s]);
7
8     while(!q.isEmpty()) {
9         Vertex u = q.poll();
10        u.vis = true;
11
12        for(int i : u.adj.keySet()) {
13            Edge e = u.adj.get(i);
14            if(e.rw == 0) continue;
15            Vertex v = e.t;
16            if(v.vis) continue;
17            q.add(v);
18        }
19    }
20 }
21
22 public static int minCut(Vertex[] G, int s, int t) {
23     //get residual graph
24     edmondsKarp(G, s, t);
25     //find all vertices reachable from s
26     bfs(G, s);
27     int sum = 0;
28     for(int i = 0; i < G.length; i++) {
29         for(int j : G[i].adj.keySet()) {
30             Edge e = G[i].adj.get(j);
31             Vertex v = e.t;
32             //if i is reachable and j not this is a cut edge
33             if(G[i].vis && !G[j].vis) {
34                 //System.out.println((i+1) + " " + (j+1));
35                 sum += e.w;
36             }
37         }
38     }
39     return sum;
40 }

```

MD5: 3f081f37a378d8dd750bfe8877e50a87 |  $\mathcal{O}(?)$

### 3.17 Prim

```

1 //s is the startpoint of the algorithm, in general not
  too important; we assume that graph is connected
2 public static int prim(Vertex[] G, int s) {
3     //make sure dists are maxint
4     G[s].dist = 0;
5     Tuple st = new Tuple(s, 0);
6
7     PriorityQueue<Tuple> q = new PriorityQueue<Tuple>();
8     q.add(st);
9     //we will store the sum and each nodes predecessor

```

```

10 int sum = 0;
11
12 while(!q.isEmpty()) {
13     Tuple sm = q.poll();
14     Vertex u = G[sm.id];
15     //u has been visited already
16     if(u.vis) continue;
17     //this is not the latest version of u
18     if(sm.dist > u.dist) continue;
19     u.vis = true;
20     //u is part of the new tree and u.dist the cost of
      adding it
21     sum += u.dist;
22     for(Edge e : u.adj) {
23         Vertex v = e.t;
24         if(!v.vis && v.dist > e.w) {
25             v.pre = u.id;
26             v.dist = e.w;
27             Tuple nt = new Tuple(v.id, e.w);
28             q.add(nt);
29         }
30     }
31 }
32 return sum;
33 }

```

MD5: c82f0bcc19cb735b4ef35dfc7ccfe197 |  $\mathcal{O}(?)$

### 3.18 Recursive Depth First Search

Recursive DFS with different options (storing times, connected/unconnected graph). Needs testing.

*Input:* A source vertex  $s$ , a target vertex  $t$ , and adjlist  $G$  and the time (0 at the start)

*Output:* Indicates if there is connection between  $s$  and  $t$ .

```

1 //if we want to visit the whole graph, even if it is
  not connected we might use this
2 public static void DFS(Vertex[] G) {
3     //make sure all vertices vis value is false etc
4     int time = 0;
5     for(int i = 0; i < G.length; i++) {
6         if(!G[i].vis) {
7             //note that we leave out t so this does not work
              with the below function
8             //adaption will not be too difficult though
9             //time should not always start at zero, change
              if needed
10            recDFS(i, G, 0);
11        }
12    }
13 }
14
15 //first call with time = 0
16 public static boolean recDFS(int s, int t, Vertex[] G,
      int time){
17     //it might be necessary to store the time of
      discovery
18     time = time + 1;
19     G[s].dtime = time;
20
21     G[s].vis = true; //new vertex has been discovered
22     //For cycle check vis should be int and 0 are not
      vis nodes
23     //1 are vis nodes which havent been finished and 2
      are finished nodes

```

```

24 //cycle exists iff edge to node with vis=1
25 //when reaching the target return true
26 //not necessary when calculating the DFS-tree
27 if(s == t) return true;
28 for(Vertex v : G[s].adj) {
29     //exploring a new edge
30     if(!v.vis) {
31         v.pre = u.id;
32         if(recDFS(v.id, t, G)) return true;
33     }
34 }
35 //storing finishing time
36 time = time + 1;
37 G[s].ftime = time;
38 return false;
39 }

```

MD5: 0829da7a5f49d16eeb886174e5d45213 |  $\mathcal{O}(|V| + |E|)$

### 3.19 Strongly Connected Components

```

1 public static void fDFS(Vertex u, LinkedList<Integer>
   sorting) {
2     //compare with TS
3     u.vis = true;
4     for(Vertex v : u.out)
5         if(!v.vis)
6             fDFS(v, sorting);
7     sorting.addFirst(u.id);
8     return sorting;
9 }
10
11
12 public static void sDFS(Vertex u, int cnt) {
13     //basic DFS, all visited vertices get cnt
14     u.vis = true;
15     u.comp = cnt;
16     for(Vertex v : u.in)
17         if(!v.vis)
18             sDFS(v, cnt);
19 }
20
21 public static void doubleDFS(Vertex[] G) {
22     //first calc a topological sort by first DFS
23     LinkedList<Integer> sorting = new LinkedList<Integer>
24     >();
25     for(int i = 0; i < G.length; i++)
26         if(!G[i].vis)
27             fDFS(G[i], sorting);
28     for(int i = 0; i < G.length; i++)
29         G[i].vis = false;
30     //then go through the sort and do another DFS on G^T
31     //each tree is a component and gets a unique number
32     int cnt = 0;
33     for(int i : sorting)
34         if(!G[i].vis)
35             sDFS(G[i], cnt++);
36 }

```

MD5: 1e023258a9249a1bc0d6898b670139ea |  $\mathcal{O}(|V| + |E|)$

### 3.20 Suurballe

Finds the min cost of two edge disjoint paths in a graph. If vertex disjoint needed, split vertices.

Input: Graph  $G$ , Source  $s$ , Target  $t$

Output: Min cost as int

```

1 public static int suurballe(Vertex[] G, int s, int t){
2     //this uses the usual dijkstra implementation with
   stored predecessors
3     dijkstra(G, s);
4     //Modifying weights
5     for(int i = 0; i < G.length; i++)
6         for(Edge e : G[i].adj)
7             e.dist = e.dist - e.t.dist + G[i].dist;
8     //reversing path and storing used edges
9     int old = t;
10    int pre = G[t].pre;
11    HashMap<Integer, Integer> hm = new HashMap<Integer,
   Integer>();
12    while(pre != -1) {
13        for(int i = 0; i < G[pre].adj.size(); i++) {
14            if(G[pre].adj.get(i).t.id == old) {
15                hm.put(pre * G.length + old, G[pre].adj.get(i)
   .tdist);
16                G[pre].adj.remove(i);
17                break;
18            }
19        }
20        boolean found = false;
21        for(int i = 0; i < G[old].adj.size(); i++) {
22            if(G[old].adj.get(i).t.id == pre) {
23                G[old].adj.get(i).dist = 0;
24                found = true;
25                break;
26            }
27        }
28        if(!found)
29            G[old].adj.add(new Edge(G[pre], 0));
30        old = pre;
31        pre = G[pre].pre;
32    }
33    //reset graph
34    for(int i = 0; i < G.length; i++) {
35        G[i].pre = -1;
36        G[i].dist = Integer.MAX_VALUE;
37        G[i].vis = false;
38    }
39    dijkstra(G, s);
40    //store edges of second path
41    old = t;
42    pre = G[t].pre;
43    while(pre != -1) {
44        //store edges and remove if reverse
45        for(int i = 0; i < G[pre].adj.size(); i++) {
46            if(G[pre].adj.get(i).t.id == old) {
47                if(!hm.containsKey(pre + old * G.length))
48                    hm.put(pre * G.length + old, G[pre].adj.get(
   i).tdist);
49            }
50            else
51                hm.remove(pre + old * G.length);
52            break;
53        }
54        old = pre;
55        pre = G[pre].pre;
56    }
57    //sum up weights
58    int sum = 0;
59    for(int i : hm.keySet())
60        sum += hm.get(i);
61 }

```

```

62 return sum;
63 }

```

MD5: 222dac2a859273efbbdd0ec0d6285dd7 |  $\mathcal{O}(V \log V + E)$

### 3.21 Kahns Algorithm for TS

Gives the specific TS where Vertices first in G are first in the sorting

```

1 public static LinkedList<Integer> TS(Vertex[] G) {
2     LinkedList<Integer> sorting = new LinkedList<Integer>
3         >();
4     PriorityQueue<Vertex> p = new PriorityQueue<Vertex>
5         >();
6     //inc counts the number of incoming edges, if they
7     //are zero put the vertex in the queue
8     for(int i = 0; i < G.length; i++) {
9         if(G[i].inc == 0) {
10             p.add(G[i]);
11             G[i].vis = true;
12         }
13     }
14     while(!p.isEmpty()) {
15         Vertex u = p.poll();
16         sorting.add(u.id);
17         //update inc
18         for(Vertex v : u.out) {
19             if(v.vis) continue;
20             v.inc--;
21             if(v.inc == 0) {
22                 p.add(v);
23                 v.vis = true;
24             }
25         }
26     }
27     return sorting;
28 }

```

MD5: e53d13c7467873d1c5d210681f4450d8 |  $\mathcal{O}(V + E)$

### 3.22 Topological Sort

```

1 public static LinkedList<Integer> TS(Vertex[] G) {
2     LinkedList<Integer> sorting = new LinkedList<Integer>
3         >();
4     for(int i = 0; i < G.length; i++)
5         if(!G[i].vis)
6             recTS(G[i], sorting);
7     //check sorting for a -1 if the graph is not
8     //necessarily dag
9     //maybe checking if there are too many values in
10    //sorting is easier?!
11    return sorting;
12 }
13
14 public static LinkedList<Integer> recTS(Vertex u,
15     LinkedList<Integer> sorting) {
16     u.vis = true;
17     for(Vertex v : u.adj)
18         if(v.vis)
19             //the -1 indicates that it will not be possible
20             //to find an TS
21             //there might be a much faster and elegant way (
22             //flag?!

```

```

17     sorting.addFirst(-1);
18     else
19         recTS(v, sorting);
20     sorting.addFirst(u.id);
21     return sorting;
22 }

```

MD5: f6459575bf0d53344ddd9e5daf1dfbb8 |  $\mathcal{O}(|V| + |E|)$

### 3.23 Tuple

Simple tuple class used for priority queue in Dijkstra and Prim

```

1 class Tuple implements Comparable<Tuple> {
2
3     int id;
4     int dist;
5
6     public Tuple(int id, int dist) {
7         this.id = id;
8         this.dist = dist;
9     }
10
11     public int compareTo(Tuple other) {
12         return Integer.compare(this.dist, other.dist);
13     }
14 }

```

MD5: fb1aa32dc32b9a2bac6f44a84e7f82c7 |  $\mathcal{O}(1)$

### 3.24 Reference for Vertex classes

Used in many graph algorithms, implements a vertex with its edges. Needs testing.

```

1 class Vertex {
2
3     int id;
4     boolean vis = false;
5     int pre = -1;
6
7     //for dijkstra and prim
8     int dist = Integer.MAX_VALUE;
9
10    //for SCC store number indicating the dedicated
11    //component
12    int comp = -1;
13
14    //for DFS we could store the start and finishing
15    //times
16    int dtime = -1;
17    int ftime = -1;
18
19    //use an ArrayList of Edges if those information are
20    //needed
21    ArrayList<Edge> adj = new ArrayList<Edge>();
22    //use an ArrayList of Vertices else
23    ArrayList<Vertex> adj = new ArrayList<Vertex>();
24    //use two ArrayLists for SCC
25    ArrayList<Vertex> in = new ArrayList<Vertex>();
26    ArrayList<Vertex> out = new ArrayList<Vertex>();
27
28    //for EdmondsKarp we need a HashMap to store Edges,
29    //Integer is target
30    HashMap<Integer, Edge> adj = new HashMap<Integer,
31    Edge>();

```

```

27
28 //for bipartite graph check
29 int color = -1;
30
31 //we store as key the target
32 public Vertex(int id) {
33     this.id = id;
34 }
35 }

```

MD5: 90e8120ce9f665b07d4388e30395dd36 |  $\mathcal{O}(1)$

### 3.25 Dijkstra

Finds the shortest paths from one vertex to every other vertex in the graph (SSSP).

For negative weights, add  $|\min|+1$  to each edge, later subtract from result.

To get a different shortest path when edges are ints, add an  $\varepsilon = \frac{1}{k+1}$  on each edge of the shortest path of length  $k$ , run again.

*Input:* A source vertex  $s$  and an adjacency list  $G$ .

*Output:* Modified adj. list with distances from  $s$  and predecessor vertices set.

```

1 int mxi = (1 << 25);
2
3 bool cmp(pair<int, int> a, pair<int, int> b)
4 {
5     return (a.second > b.second);
6 }
7
8 int dijkstra(vector<vector<pair<int, int>>> &g, int N)
9 {
10     priority_queue<pair<int, int>, vector<pair<int,
11         int>>, decltype(cmp) *> pq(cmp);
12     vector<int> dist(N, mxi);
13     dist[0] = 0;
14     pq.push({0, 0});
15     while(!pq.empty()) {
16         int u = pq.top().first;
17         int d = pq.top().second;
18         pq.pop();
19         if(d > dist[u]) continue;
20         if(u == N-1) return d;
21         for(auto it = g[u].begin(); it != g[u].end();
22             ++it) {
23             int v = it->first;
24             int w = it->second;
25             if(w + dist[u] < dist[v]) {
26                 dist[v] = w + dist[u];
27                 pq.push({v, dist[v]});
28             }
29         }
30     }
31     return dist[N-1];
32 }

```

MD5: b4e62c815fb25574ef371d1913584c6c |  $\mathcal{O}(|E| \log |V|)$

### 3.26 EdmondsKarp

Finds the greatest flow in a graph. Capacities must be positive.

```

2 #include<vector>
3 #include<queue>
4 #include<unordered_map>
5 #include<cmath>
6
7 using namespace std;
8
9 bool bfs(vector<unordered_map<int, long long>> &g, int
10     s, int t, vector<int> &pre)
11 {
12     int n = g.size();
13     for(int i = 0; i < n; ++i) {
14         pre[i] = -1;
15     }
16     vector<bool> vis(n);
17     queue<int> q;
18     vis[s] = true;
19     q.push(s);
20     while(!q.empty()) {
21         int u = q.front();
22         q.pop();
23         if(u == t) return true;
24         for(auto v = g[u].begin(); v != g[u].end(); ++
25             v) {
26             if(!vis[v->first] && (v->second) > 0) {
27                 vis[v->first] = true;
28                 pre[v->first] = u;
29                 q.push(v->first);
30             }
31         }
32     }
33     return vis[t];
34 }
35
36 long long ed_karp(vector<unordered_map<int, long long
37     >> &g, int s, int t)
38 {
39     long long mxf = 0;
40     int n = g.size();
41     vector<int> pre(n);
42     while(bfs(g, s, t, pre)) {
43         long long pf = (1L << 58);
44         for(int v = t; v != s; v = pre[v]) {
45             int u = pre[v];
46             pf = min(pf, g[u][v]);
47         }
48         for(int v = t; v != s; v = pre[v]) {
49             int u = pre[v];
50             g[u][v] -= pf;
51             g[v][u] += pf;
52         }
53         mxf += pf;
54     }
55     return mxf;
56 }

```

MD5: 7ea28f50383117106939588171692efe |  $\mathcal{O}(|V|^2 \cdot |E|)$

## 4 Math

### 4.1 Binomial Coefficient

Gives binomial coefficient ( $n$  choose  $k$ )

```

1 public static long bin(int n, int k) {
2     if (k == 0)

```

```

3   return 1;
4   else if (k > n/2)
5       return bin(n, n-k);
6   else
7       return n*bin(n-1, k-1)/k;
8 }

```

MD5: 32414ba5a444038b9184103d28fa1756 |  $\mathcal{O}(k)$

## 4.2 Binomial Matrix

Gives binomial coefficients for all  $K \leq N$ .

```

1 public static long[][] binomial_matrix(int N, int K) {
2     long[][] B = new long[N+1][K+1];
3     for (int k = 1; k <= K; k++)
4         B[0][k] = 0;
5     for (int m = 0; m <= N; m++)
6         B[m][0] = 1;
7     for (int m = 1; m <= N; m++)
8         for (int k = 1; k <= K; k++)
9             B[m][k] = B[m-1][k-1] + B[m-1][k];
10    return B;
11 }

```

MD5: e6f103bd9852173c02a1ec64264f4448 |  $\mathcal{O}(N \cdot K)$

## 4.3 Divisability

Calculates (alternating) k-digitSum for integer number given by M.

```

1 public static long digit_sum(String M, int k, boolean
2     alt) {
3     long dig_sum = 0;
4     int vz = 1;
5     while (M.length() > k) {
6         if (alt) vz *= -1;
7         dig_sum += vz*Integer.parseInt(M.substring(M.
8             length()-k));
9         M = M.substring(0, M.length()-k);
10    }
11    if (alt)
12        vz *= -1;
13    dig_sum += vz*Integer.parseInt(M);
14    return dig_sum;
15 }
16 // example: divisibility of M by 13
17 public static boolean divisible13(String M) {
18     return digit_sum(M, 3, true)%13 == 0;
19 }

```

MD5: 33b3094ebf431e1e71cd8e8db3c9cdd6 |  $\mathcal{O}(|M|)$

## 4.4 Graham Scan

Multiple unresolved issues: multiple points as well as collinearity.  
 $N$  denotes the number of points

```

1 public static Point[] grahamScan(Point[] points) {
2     //find leftmost point with lowest y-coordinate
3     int xmin = Integer.MAX_VALUE;
4     int ymin = Integer.MAX_VALUE;
5     int index = -1;
6     for(int i = 0; i < points.length; i++) {

```

```

7         if(points[i].y < ymin || (points[i].y == ymin &&
8             points[i].x < xmin)) {
9             xmin = points[i].x;
10            ymin = points[i].y;
11            index = i;
12        }
13    }
14    //get that point to the start of the array
15    Point tmp = new Point(points[index].x, points[index
16        ].y);
17    points[index] = points[0];
18    points[0] = tmp;
19    for(int i = 1; i < points.length; i++)
20        points[i].src = points[0];
21    Arrays.sort(points, 1, points.length);
22    //for collinear points eliminate all but the
23    farthest
24    boolean[] isElem = new boolean[points.length];
25    for(int i = 1; i < points.length-1; i++) {
26        Point a = new Point(points[i].x - points[i].src.x,
27            points[i].y - points[i].src.y);
28        Point b = new Point(points[i+1].x - points[i+1].
29            src.x, points[i+1].y - points[i+1].src.y);
30        if(Calc.crossProd(a, b) == 0)
31            isElem[i] = true;
32    }
33    //works only if there are more than three non-
34    collinear points
35    Stack<Point> s = new Stack<Point>();
36    int i = 0;
37    for(; i < 3; i++) {
38        while(isElem[i++]);
39        s.push(points[i]);
40    }
41    for(; i < points.length; i++) {
42        if(isElem[i]) continue;
43        while(true) {
44            Point first = s.pop();
45            Point second = s.pop();
46            s.push(second);
47            Point a = new Point(first.x - second.x, first.y
48                - second.y);
49            Point b = new Point(points[i].x - second.x,
50                points[i].y - second.y);
51            //use >= if straight angles are needed
52            if(Calc.crossProd(a, b) > 0) {
53                s.push(first);
54                s.push(points[i]);
55                break;
56            }
57        }
58    }
59    Point[] convexHull = new Point[s.size()];
60    for(int j = s.size()-1; j >= 0; j--)
61        convexHull[j] = s.pop();
62    return convexHull;
63    /*Sometimes it might be necessary to also add points
64        to the convex hull that form a straight angle.
65        The following lines of code achieve this. Only
66        at the first and last diagonal we have to add
67        those. Of course the previous return-statement
68        has to be deleted as well as allowing straight
69        angles in the above implementation. */

```

```

}
class Point implements Comparable<Point> {
    Point src; //set separately in GrahamScan method
    int x;
    int y;

```



```

61
62 public Point(int x, int y) {
63     this.x = x;
64     this.y = y;
65 }
66
67 //might crash if one point equals src
68 //major issues with multiple points on same location
69 !
69 public int compareTo(Point cmp) {
70     Point a = new Point(this.x - src.x, this.y - src.y);
71     Point b = new Point(cmp.x - src.x, cmp.y - src.y);
72     //checks if points are identical
73     if(a.x == b.x && a.y == b.y) return 0;
74     //if same angle, sort by dist
75     if(Calc.crossProd(a, b) == 0 && Calc.dotProd(a, b) >
76         0)
77         return Integer.compare(Calc.dotProd(a, a), Calc.
78             dotProd(b, b));
79     //angle of a is 0, thus b>a
80     if(a.y == 0 && a.x > 0) return -1;
81     //angle of b is 0, thus a>b
82     if(b.y == 0 && b.x > 0) return 1;
83     //a ist between 0 and 180, b between 180 and 360
84     if(a.y > 0 && b.y < 0) return -1;
85     if(a.y < 0 && b.y > 0) return 1;
86     //return negative value if cp larger than zero
87     return Integer.compare(0, Calc.crossProd(a, b));
88 }
89
90 class Calc {
91     public static int crossProd(Point p1, Point p2) {
92         return p1.x * p2.y - p2.x * p1.y;
93     }
94     public static int dotProd(Point p1, Point p2) {
95         return p1.x * p2.x + p1.y * p2.y;
96     }
97 }

```

MD5: 2555d858fadcf8cb404a9c52420545d |  $\mathcal{O}(N \log N)$

## 4.5 Iterative EEA

Berechnet den ggT zweier Zahlen  $a$  und  $b$  und deren modulare Inverse  $x = a^{-1} \bmod b$  und  $y = b^{-1} \bmod a$ .

```

1 // Extended Euclidean Algorithm - iterativ
2 public static long[] eea(long a, long b) {
3     if (b > a) {
4         long tmp = a;
5         a = b;
6         b = tmp;
7     }
8     long x = 0, y = 1, u = 1, v = 0;
9     while (a != 0) {
10        long q = b / a, r = b % a;
11        long m = x - u * q, n = y - v * q;
12        b = a; a = r; x = u; y = v; u = m; v = n;
13    }
14    long gcd = b;
15    // x = a^-1 % b, y = b^-1 % a
16    // ax + by = gcd
17    long[] erg = { gcd, x, y };
18    return erg;
19 }

```

MD5: 81fe8cd4adab21329dcbe1ce0499ee75 |  $\mathcal{O}(\log a + \log b)$

## 4.6 Polynomial Interpolation

```

1 public class interpol {
2
3     // divided differences for points given by vectors x
4     // and y
5     public static rat[] divDiff(rat[] x, rat[] y) {
6         rat[] temp = y.clone();
7         int n = x.length;
8         rat[] res = new rat[n];
9         res[0] = temp[0];
10        for (int i=1; i < n; i++) {
11            for (int j = 0; j < n-i; j++) {
12                temp[j] = (temp[j+1].sub(temp[j])).div(x[j+1].
13                    sub(x[j]));
14            }
15            res[i] = temp[0];
16        }
17        return res;
18    }
19
20    // evaluates interpolating polynomial p at t for
21    // given
22    // x-coordinates and divided differences
23    public static rat p(rat t, rat[] x, rat[] dD) {
24        int n = x.length;
25        rat p = new rat(0);
26        for (int i = n-1; i > 0; i--) {
27            p = (p.add(dD[i])).mult(t.sub(x[i-1]));
28        }
29        p = p.add(dD[0]);
30        return p;
31    }
32 }

```

// implementation of rational numbers

```

32 class rat {
33
34     public long c;
35     public long d;
36
37     public rat (long c, long d) {
38         this.c = c;
39         this.d = d;
40         this.shorten();
41     }
42
43     public rat (long c) {
44         this.c = c;
45         this.d = 1;
46     }
47
48     public static long ggT(long a, long b) {
49         while (b != 0) {
50             long h = a%b;
51             a = b;
52             b = h;
53         }
54         return a;
55     }
56
57     public static long kgV(long a, long b) {
58         return a*b/ggT(a,b);
59     }
60 }

```



```

59 }
60
61 public static rat[] commonDenominator(rat[] c) {
62     long kgV = 1;
63     for (int i = 0; i < c.length; i++) {
64         kgV = kgV(kgV, c[i].d);
65     }
66     for (int i = 0; i < c.length; i++) {
67         c[i].c *= kgV/c[i].d;
68         c[i].d *= kgV/c[i].d;
69     }
70     return c;
71 }
72
73 public void shorten() {
74     long ggT = ggT(this.c, this.d);
75     this.c = this.c / ggT;
76     this.d = this.d / ggT;
77     if (d < 0) {
78         this.d *= -1;
79         this.c *= -1;
80     }
81 }
82
83 public String toString() {
84     if (this.d == 1) return ""+c;
85     return ""+c+"/"+d;
86 }
87
88 public rat mult(rat b) {
89     return new rat(this.c*b.c, this.d*b.d);
90 }
91
92 public rat div(rat b) {
93     return new rat(this.c*b.d, this.d*b.c);
94 }
95
96 public rat add(rat b) {
97     long new_d = kgV(this.d, b.d);
98     long new_c = this.c*(new_d/this.d) + b.c*(new_d/b.
99     d);
100     return new rat(new_c, new_d);
101 }
102
103 public rat sub(rat b) {
104     return this.add(new rat(-b.c, b.d));
105 }

```

MD5: e7b408030f7e051e93a8c55056ba930b |  $\mathcal{O}(?)$

## 4.7 Root of permutation

Calculates the K'th root of permutation of size N. Number at place i indicates where this dancer ended. needs commenting

```

1 public static int[] rop(int[] perm, int N, int K) {
2     boolean[] incyc = new boolean[N];
3     int[] cntcyc = new int[N+1];
4     int[] g = new int[N+1];
5     int[] needed = new int[N+1];
6     for (int i = 1; i < N+1; i++) {
7         int j = i;
8         int k = K;
9         int div;
10        while (k > 1 && (div = gcd(k, i)) > 1) {
11            k /= div;

```

```

12        j *= div;
13    }
14    needed[i] = j;
15    g[i] = gcd(K, j);
16 }
17
18 HashMap<Integer, ArrayList<Integer>> hm = new
19     HashMap<Integer, ArrayList<Integer>>();
20 for (int i = 0; i < N; i++) {
21     if (incyc[i]) continue;
22     ArrayList<Integer> cyc = new ArrayList<Integer>();
23     cyc.add(i);
24     incyc[i] = true;
25     int newelem = perm[i];
26     while (newelem != i) {
27         cyc.add(newelem);
28         incyc[newelem] = true;
29         newelem = perm[newelem];
30     }
31     int len = cyc.size();
32     cntcyc[len]++;
33     if (hm.containsKey(len)) {
34         hm.get(len).addAll(cyc);
35     } else {
36         hm.put(len, cyc);
37     }
38 }
39 boolean end = false;
40 for (int i = 1; i < N+1; i++) {
41     if (cntcyc[i] % g[i] != 0) end = true;
42 }
43 if (end) {
44     //not possible
45     return null;
46 } else {
47     int[] out = new int[N];
48     for (int length = 0; length < N; length++) {
49         if (!hm.containsKey(length)) continue;
50         ArrayList<Integer> p = hm.get(length);
51         int totalsize = p.size();
52         int diffcyc = totalsize / needed[length];
53         for (int i = 0; i < diffcyc; i++) {
54             int[] c = new int[needed[length]];
55             for (int it = 0; it < needed[length]; it++) {
56                 c[it] = p.get(it + i * needed[length]);
57             }
58             int move = K / (needed[length]/length);
59             int[] rewind = new int[needed[length]];
60             for (int set = 0; set < needed[length]/length;
61                 set++) {
62                 int pos = set * length;
63                 for (int it = 0; it < length; it++) {
64                     rewind[pos] = c[it + set * length];
65                     pos = ((pos - set * length + move) %
66                         length) + set * length;
67                 }
68             }
69             int[] merge = new int[needed[length]];
70             for (int it = 0; it < needed[length]/length; it++) {
71                 for (int set = 0; set < length; set++) {
72                     merge[set * needed[length] / length + it]
73                         = rewind[it * length + set];
74                 }
75             }
76             for (int it = 0; it < needed[length]; it++) {
77                 out[merge[it]] = merge[(it+1) % needed[
78                     length]];
79             }
80         }
81     }
82 }

```

```

74     }
75     }
76 }
77 return out;
78 }
79 }

```

MD5: b446a7c21eddf7d14dbdc71174e8d498 |  $\mathcal{O}(?)$

## 4.8 Sieve of Eratosthenes

Calculates Sieve of Eratosthenes.

*Input:* A integer  $N$  indicating the size of the sieve.

*Output:* A boolean array, which is true at an index  $i$  iff  $i$  is prime.

```

1 public static boolean[] sieveOfEratosthenes(int N) {
2     boolean[] isPrime = new boolean[N+1];
3     for (int i=2; i<=N; i++) isPrime[i] = true;
4     for (int i = 2; i*i <= N; i++)
5         if (isPrime[i])
6             for (int j = i*i; j <= N; j+=i)
7                 isPrime[j] = false;
8     return isPrime;
9 }

```

MD5: 95704ae7c1fe03e91adeb8d695b2f5bb |  $\mathcal{O}(n)$

## 4.9 Greatest Common Divisor

Calculates the gcd of two numbers  $a$  and  $b$  or of an array of numbers *input*.

*Input:* Numbers  $a$  and  $b$  or array of numbers *input*

*Output:* Greatest common divisor of the input

```

1 private static long gcd(long a, long b) {
2     while (b > 0) {
3         long temp = b;
4         b = a % b; // % is remainder
5         a = temp;
6     }
7     return a;
8 }
9
10 private static long gcd(long[] input) {
11     long result = input[0];
12     for(int i = 1; i < input.length; i++)
13         result = gcd(result, input[i]);
14     return result;
15 }

```

MD5: 48058e358a971c3ed33621e3118818c2 |  $\mathcal{O}(\log a + \log b)$

## 4.10 Least Common Multiple

Calculates the lcm of two numbers  $a$  and  $b$  or of an array of numbers *input*.

*Input:* Numbers  $a$  and  $b$  or array of numbers *input*

*Output:* Least common multiple of the input

```

1 private static long lcm(long a, long b) {
2     return a * (b / gcd(a, b));
3 }
4

```

```

5 private static long lcm(long[] input) {
6     long result = input[0];
7     for(int i = 1; i < input.length; i++)
8         result = lcm(result, input[i]);
9     return result;
10 }

```

MD5: 3cfaab4559ea05c8434d6cf364a24546 |  $\mathcal{O}(\log a + \log b)$

## 4.11 GEV

```

1 #include <vector>
2 #include <algorithm>
3 #include <string>
4 #include <cmath>
5 #include <cstdio>
6 #include <cstring>
7
8 using namespace std;
9
10 template<int M> class vec
11 {
12 public:
13     double co[M];
14
15     vec<M>() { memset(co, 0, M * sizeof(double)); }
16
17     double* operator[](int i) { return &co[i]; }
18
19     vec<M> operator+(vec<M> v)
20     {
21         vec<M> r;
22         for(int i = 0; i < M; ++i)
23             *r[i] = co[i] + *v[i];
24         return r;
25     }
26
27     vec<M> operator-(vec<M> v)
28     {
29         vec<M> r;
30         for(int i = 0; i < M; ++i)
31             *r[i] = co[i] - *v[i];
32         return r;
33     }
34
35     vec<M> operator-()
36     {
37         vec<M> r;
38         for(int i = 0; i < M; ++i)
39             *r[i] = -co[i];
40         return r;
41     }
42
43     vec<M> operator*(double s)
44     {
45         vec<M> r;
46         for(int i = 0; i < M; ++i)
47             *r[i] = s * co[i];
48         return r;
49     }
50
51     // Kreuzprodukt
52     vec<3> cross(vec<3> v)
53     {
54         vec<3> r;
55         *r[0] = co[1] * *v[2] - co[2] * *v[1];
56         *r[1] = co[2] * *v[0] - co[0] * *v[2];

```

```

57     *r[2] = co[0] * *v[1] - co[1] * *v[0];
58     return r;
59 }
60 };
61
62 template<int M, int N> class mat
63 {
64 public:
65     double el[M][N];
66
67     mat<M, N>() { memset(el, 0, M * N * sizeof(double)); }
68
69     double* operator[](int i) { return el[i]; } // Gib
70     // Zeile i
71     // MxN-Matrix mal Nx1-Vektor = Nx1-Vektor
72     vec<M> operator*(vec<N> v)
73     {
74         vec<M> r;
75         for(int i = 0; i < M; ++i)
76             for(int j = 0; j < N; ++j)
77                 *r[i] += el[i][j] * v[j]; // r ist durch
78                 // Konstruktor genullt
79         return r;
80     }
81
82     // Gauß-Jordan-Algorithmus-Aufruf für MxN-Matrix und
83     // Mx1-Vektor
84     // Setzt voraus, dass Lösung existiert! => Nur bei
85     // MxM-Matrizen sinnvoll
86     vec<M> solveLGS(vec<M> in)
87     {
88         mat<M, N> inp;
89         for(int i = 0; i < M; ++i)
90             inp[i][0] = *in[i];
91         mat<M, N> re = gaussJordan(inp);
92         vec<M> r;
93         for(int i = 0; i < M; ++i)
94             *r[i] = re[i][0];
95         return r;
96     }
97
98     // Gauß-Jordan-Algorithmus für zwei MxN-Matrizen
99     // Setzt voraus, dass Lösung existiert! => Nur bei
100    // MxM-Matrizen sinnvoll
101    mat<M, N> gaussJordan(mat<M, N> in)
102    {
103        // Erweiterte Matrix erstellen
104        double ext[M][N << 1];
105        for(int i = 0; i < M; ++i)
106        {
107            memcpy(ext[i], el[i], N * sizeof(double));
108            memcpy(ext[i] + N, in[i], N * sizeof(double));
109        }
110
111        // Für jede Restmatrix Schritte durchführen
112        for(int LC = 0; LC < M && LC < N; ++LC)
113        {
114            // Finde Spalte mit Zelle != 0
115            int c = LC;
116            int l = LC;
117            for(; c < N; ++c, l = LC)
118                for(; l < M; ++l)
119                    if(!(ext[l][c] == 0))
120                        goto br;
121
122            // Zeile mit gewähltem Element nach oben
123            // schieben und alle anderen Elemente durch
124            // dieses teilen
125            br:
126            double tmp[N << 1];
127            double top = ext[l][c];
128            //if(top == 0) // Dies ist erforderlich, wenn
129            // keine Lösung existiert oder das System
130            // überbestimmt ist
131            // break;
132            if(l > LC)
133                memcpy(tmp, ext[LC], (N << 1) * sizeof(double));
134            for(int j = LC; j < (N << 1); ++j)
135                ext[LC][j] = ext[l][j] / top;
136            if(l > LC)
137                memcpy(ext[l], tmp, (N << 1) * sizeof(double));
138
139            // Erstes Element jeder Zeile durch Subtraktion
140            // von Vielfachen der ersten Zeile auf 0
141            // bringen
142            for(int i = LC + 1; i < M; ++i)
143                for(int j = (N << 1) - 1; j >= c; --j)
144                    ext[i][j] -= ext[i][c] * ext[LC][j];
145        }
146
147        // Aus oberer Dreiecksmatrix Einheitsmatrix
148        // erstellen
149        for(int i = M - 1; i > 0; --i)
150            for(int i2 = i - 1; i2 >= 0; --i2)
151                for(int j = (N << 1) - 1; j > i2; --j)
152                    ext[i2][j] -= ext[i2][i] * ext[i][j];
153
154        // Ergebnismatrix erstellen
155        mat<M, N> r;
156        for(int i = 0; i < M; ++i)
157            memcpy(r[i], ext[i] + N, N * sizeof(double));
158        return r;
159    }
160 };
161
162 int main()
163 {
164     int T;
165     cin >> T;
166     while(T --> 0)
167     {
168         mat<7, 7> m;
169         for(int i = 0; i < 7; ++i)
170             for(int j = 0; j < 7; ++j)
171                 cin >> m[i][j];
172
173         mat<7, 7> unit;
174         for(int i = 0; i < 7; ++i)
175             unit[i][i] = 1;
176
177         mat<7, 7> res = m.gaussJordan(unit); // Inverses
178         // berechnen
179         for(int i = 0; i < 7; ++i)
180         {
181             for(int j = 0; j < 7; ++j)
182                 printf("%.03f\\t", res[i][j]);
183             cout << endl;
184         }
185         cout << endl;
186     }
187 }

```

```

176 mat<3, 3> m2;
177 m2[0][0] = 1;
178 m2[0][1] = 1;
179 m2[0][2] = 1;
180 m2[1][0] = 4;
181 m2[1][1] = 2;
182 m2[1][2] = 1;
183 m2[2][0] = 9;
184 m2[2][1] = 3;
185 m2[2][2] = 1;
186
187 vec<3> v2;
188 *v2[0] = 0;
189 *v2[1] = 1;
190 *v2[2] = 3;
191
192 vec<3> result = m2.solveLGS(v2);
193 cout << *result[0] << "␣" << *result[1] << "␣" << *
    result[2] << endl;
194 }

```

MD5: 64ad7c6d25151de23cb4502b90629cc6 |  $\mathcal{O}(?)$

## 4.12 Fourier transform

```

1 #include<complex>
2 #include<vector>
3 #include<algorithm>
4 #include<cmath>
5
6 using namespace std;
7
8 void iterativefft(const vector<long long> &pol, vector
    <complex<double>> &fft, int n, bool inv)
9 {
10     //copy pol into fft
11     if(!inv) {
12         for(int i = 0; i < n; ++i) {
13             complex<double> cp (pol[i], 0);
14             fft[i] = cp;
15         }
16     }
17     //swap positions accordingly
18     for(int i = 0, j = 0; i < n; ++i) {
19         if(i < j) swap(fft[i], fft[j]);
20         int m = n >> 1;
21         while(1 <= m && m <= j) j -= m, m >>= 1;
22         j += m;
23     }
24     for(int m = 1; m <= n; m <= 1) { //<= or <
25         double theta = (inv ? -1 : 1) * 2 * M_PI / m;
26         complex<double> wm(cos(theta), sin(theta));
27         for(int k = 0; k < n; k += m) {
28             complex<double> w = 1;
29             for(int j = 0; j < m/2; ++j) {
30                 complex<double> t = w * fft[k + j + m
                    /2];
31                 complex<double> u = fft[k + j];
32                 fft[k + j] = u + t;
33                 fft[k + j + m/2] = u - t;
34                 w = w*wm;
35             }
36         }
37     }
38     if(inv) {
39         for(int i = 0; i < n; ++i) {
40             fft[i] /= complex<double> (n);

```

```

41     }
42 }
43 }
44
45 int main()
46 {
47     int N;
48     cin >> N;
49     vector<long long> pol (262144);
50     int min = 60000;
51     int max = -60000;
52     for(int i = 0; i < N; ++i) {
53         int ind;
54         cin >> ind;
55         if(ind < min) min = ind;
56         if(ind > max) max = ind;
57         ++pol[ind+65536];
58     }
59     vector<complex<double>> fft (262144);
60     iterativefft(pol, fft, 262144, false);
61     for(int i = 0; i < 262144; ++i) {
62         fft[i] *= fft[i];
63     }
64     iterativefft(pol, fft, 262144, true);
65     long long sum = 0;
66     for(int i = 81072; i <= 181072; ++i) {
67         int ind = i - 131072;
68         if(ind < min) continue;
69         if(ind > max) break;
70         long long resi = round(fft[i].real());
71         if(ind % 2 == 0 && ind != 0) {
72             resi -= pol[ind/2 + 65536] * pol[ind/2 +
                65536];
73             resi += pol[ind/2 + 65536]*(pol[ind/2 +
                65536]-1);
74         }
75         resi *= pol[ind + 65536];
76         if(ind != 0) {
77             resi -= 2*pol[65536] * pol[ind + 65536] *
                pol[ind + 65536];
78             resi += 2*pol[65536] * pol[ind + 65536] *
                (pol[ind + 65536]-1);
79         }
80         sum += resi;
81     }
82     sum -= pol[65536] * pol[65536] * pol[65536];
83     sum += pol[65536] * (pol[65536] - 1) * (pol[65536]
        - 2);
84     cout << sum << endl;
85 }

```

MD5: fd9669c4967b6f26c13f464f98bdfb2a |  $\mathcal{O}(?)$

## 4.13 calculates geometric series with parameters a, n modulo mod

```

1 long long powmod(long long base, long long exp, long
    long mod) {
2     base %= mod;
3     long long res = 1;
4     while (exp > 0) {
5         if (exp & 1) res = (res * base) % mod;
6         base = (base * base) % mod;
7         exp >>= 1;
8     }
9     return res;

```

```

10 }
11
12 long long geomod(long long a, long long n, long long
    mod) {
13     long long factor = 1, sum = 0;
14     while(n > 0 && a != 0) {
15         if(n % 2 == 0) {
16             long long tmp = (factor * powmod(a, n, mod)) %
                mod;
17             sum = (sum + tmp) % mod;
18             --n;
19         }
20         factor = (((1 + a) % mod) * factor) % mod;
21         a = a*a % mod;
22         n = n / 2;
23     }
24     return sum + factor % mod;
25 }

```

MD5: 4723f66dfe349677c9c0ca3cf57d0dde |  $\mathcal{O}(?)$ 

## 4.14 Matrix exponentiation

```

1 void mult(int a[][nos], int b[][nos], int N)
2 {
3     int res[nos][nos] = {0};
4     for(int i = 0; i < N; i++) {
5         for(int j = 0; j < N; j++) {
6             for(int k = 0; k < N; k++) {
7                 res[i][j] = (res[i][j] + a[i][k]*b[k][
                    j]) % 10000;
8             }
9         }
10    }
11    for(int i = 0; i < N; i++) {
12        for(int j = 0; j < N; j++) {
13            a[i][j] = res[i][j];
14        }
15    }
16 }
17
18 //start with g^L by succ squaring
19 int res[nos][nos] = {0};
20 for(int i = 0; i < N; i++) {
21     for(int j = 0; j < N; j++) {
22         if(i == j) res[i][j] = 1;
23     }
24 }
25 for(int i = 0; (1 << i) <= L; i++) {
26     if(((1 << i) & L) == (1 << i)) {
27         mult(res, g, N);
28     }
29     mult(g, g, N);
30 }

```

MD5: dcabdd3a0beceb4221f4c41071ac9b6d |  $\mathcal{O}(?)$ 

## 4.15 phi function calculator

takes sqrt(n) time

```

1 int phi(int n)
2 {
3     double result = n;
4     for(int p = 2; p * p <= n; ++p) {
5         if(n % p == 0) {
6             while(n % p == 0) n /= p;

```

```

7         result *= (1.0 - (1.0 / (double) p));
8     }
9 }
10 if(n > 1) result *= (1.0 - (1.0 / (double) n));
11 return round(result);
12 }

```

MD5: 2ec930cc10935f1638700bb74e3439d9 |  $\mathcal{O}(?)$ 

## 4.16 prints farey seq

```

1 def farey( n, asc=True ):
2     """Python function to print the nth Farey sequence
3     , either ascending or descending."""
4     if asc:
5         a, b, c, d = 0, 1, 1, n # (*)
6     else:
7         a, b, c, d = 1, 1, n-1, n # (*)
8     print "%d/%d" % (a,b)
9     while (asc and c <= n) or (not asc and a > 0):
10        k = int((n + b)/d)
11        a, b, c, d = c, d, k*c - a, k*d - b
12        print "%d/%d" % (a,b)

```

MD5: 5fe50f5717cb7d4e3eb91c8c8f6a1e85 |  $\mathcal{O}(?)$ 

## 5 Misc

### 5.1 Binary Search

Binary searches for an element in a sorted array.

*Input:* sorted *array* to search in, amount  $N$  of elements in *array*, element to search for  $a$ *Output:* returns the index of  $a$  in *array* or  $-1$  if *array* does not contain  $a$ 

```

1 public static int BinarySearch(int[] array,
2                                int N, int a) {
3     int lo = 0;
4     int hi = N-1;
5     // a might be in interval [lo,hi] while lo <= hi
6     while(lo <= hi) {
7         int mid = (lo + hi) / 2;
8         // if a > elem in mid of interval,
9         // search the right subinterval
10        if(array[mid] < a)
11            lo = mid+1;
12        // else if a < elem in mid of interval,
13        // search the left subinterval
14        else if(array[mid] > a)
15            hi = mid-1;
16        // else a is found
17        else
18            return mid;
19    }
20    // array does not contain a
21    return -1;
22 }

```

MD5: 203da61f7a381564ce3515f674fa82a4 |  $\mathcal{O}(\log n)$

## 5.2 Next number with n bits set

From  $x$  the smallest number greater than  $x$  with the same amount of bits set is computed. Little changes have to be made, if the calculated number has to have length less than 32 bits.

*Input:* number  $x$  with  $n$  bits set ( $x = (1 \ll n) - 1$ )

*Output:* the smallest number greater than  $x$  with  $n$  bits set

```
1 public static int nextNumber(int x) {
2     //break when larger than limit here
3     if(x == 0) return 0;
4     int smallest = x & -x;
5     int ripple = x + smallest;
6     int new_smallest = ripple & -ripple;
7     int ones = ((new_smallest/smallest) >> 1) - 1;
8     return ripple | ones;
9 }
```

MD5: 2d8a79cb551648e67fc3f2f611a4f63c |  $\mathcal{O}(1)$

## 5.3 Next Permutation

Returns true if there is another permutation. Can also be used to compute the nextPermutation of an array.

*Input:* String  $a$  as char array

*Output:* true, if there is a next permutation of  $a$ , false otherwise

```
1 public static boolean nextPermutation(char[] a) {
2     int i = a.length - 1;
3     while(i > 0 && a[i-1] >= a[i])
4         i--;
5     if(i <= 0)
6         return false;
7     int j = a.length - 1;
8     while (a[j] <= a[i-1])
9         j--;
10    char tmp = a[i - 1];
11    a[i - 1] = a[j];
12    a[j] = tmp;
13
14    j = a.length - 1;
15    while(i < j) {
16        tmp = a[i];
17        a[i] = a[j];
18        a[j] = tmp;
19        i++;
20        j--;
21    }
22    return true;
23 }
```

MD5: 7d1fe65d3e77616dd2986ce6f2af089b |  $\mathcal{O}(n)$

## 5.4 Greedy-Scheduling

```
1 public class ebox {
2
3     public static void main(String[] args) {
4         Scanner s = new Scanner(System.in);
5         int n = s.nextInt();
6         int k = s.nextInt();
7         Show[] S = new Show[n];
8         for(int i = 0; i < n; i++) {
```

```
        Show cur = new Show(s.nextInt(), s.nextInt());
        S[i] = cur;
    }
    Arrays.sort(S);
    TreeSet<Band> t = new TreeSet<Band>();
    for(int i = 0; i < k; i++) {
        t.add(new Band(0, i));
    }
    int sum = 0;
    for(int i = 0; i < n; i++) {
        Band cmp = new Band(S[i].s, Integer.MAX_VALUE);
        Band rm = t.floor(cmp);
        if(rm == null) continue;
        int id = rm.id;
        t.remove(rm);
        t.add(new Band(S[i].f, id));
        sum++;
    }
    System.out.println(sum);
}
```

```
class Show implements Comparable<Show> {
    int s;
    int f;

    public Show(int s, int f) {
        this.s = s;
        this.f = f;
    }

    public int compareTo(Show o) {
        if(Integer.valueOf(this.f).compareTo(Integer.valueOf(o.f)) != 0) {
            return Integer.valueOf(this.f).compareTo(Integer.valueOf(o.f));
        } else {
            return Integer.valueOf(this.s).compareTo(Integer.valueOf(o.s));
        }
    }
}
```

```
class Band implements Comparable<Band> {
    int lt;
    int id;

    public Band(int lt, int id) {
        this.lt = lt;
        this.id = id;
    }

    public int compareTo(Band o) {
        if(Integer.valueOf(this.lt).compareTo(Integer.valueOf(o.lt)) != 0) {
            return Integer.valueOf(this.lt).compareTo(Integer.valueOf(o.lt));
        } else {
            return Integer.valueOf(this.id).compareTo(Integer.valueOf(o.id));
        }
    }
}
```

MD5: 3269c711c682fc93f2c3837d2c755714 |  $\mathcal{O}(?)$

## 5.5 comparator in C++

```

1 bool myfunction (int i, int j) {return (i<j); }
2
3 int main() {
4     vector<int> vec;
5     sort(vec.begin(), vec.end(), myfunction);
6     priority_queue<int, vector<int>, decltype(
7         myfunction) *> pq(myfunction);
8 }

```

MD5: f4beb6e197be08977fd4f74b2537ae09 |  $\mathcal{O}(?)$

## 5.6 hashing pair in C++

```

1 struct pairhash {
2 public:
3     template <typename T, typename U>
4     std::size_t operator()(const std::pair<T, U> &x)
5         const
6     {
7         return std::hash<T>()(x.first) ^ std::hash<U>()(x.
8             second);
9     }
10 };
11
12 int main() {
13     unordered_map<pair<unsigned int, char>, double,
14         pairhash> T;
15 }

```

MD5: 49bde857f5a8078349cf97308bd8144c |  $\mathcal{O}(?)$

## 5.7 Mo's algorithm

Works for queries on intervals. Sort queries and add, remove on borders in  $\mathcal{O}(1)$ . Thus only usable when this is possible for the task.

```

1 #include<vector>
2 #include<utility>
3 #include<algorithm>
4
5 using namespace std;
6
7 int BLOCK_SIZE;
8 int cur_answer;
9 vector<int> lmen;
10 vector<int> lwomen;
11 vector<int> cmen;
12 vector<int> cwomen;
13
14 bool cmp(const pair<pair<int, int>, int> &i, const
15     pair<pair<int, int>, int> &j) {
16     if(i.first.first / BLOCK_SIZE != j.first.first /
17         BLOCK_SIZE) {
18         return i.first.first < j.first.first;
19     }
20     return i.first.second < j.first.second;
21 }
22
23 void add(int i, int j) {
24     //adds values i, j to function
25     cur_answer -= min(cmen[i], cwomen[i]);
26     cur_answer -= min(cmen[j], cwomen[j]);
27     if(i == j) cur_answer += min(cmen[j], cwomen[j]);
28 }

```

```

26 ++cmen[i];
27 ++cwomen[j];
28 cur_answer += min(cmen[i], cwomen[i]);
29 cur_answer += min(cmen[j], cwomen[j]);
30 if(i == j) cur_answer -= min(cmen[j], cwomen[j]);
31 }
32
33 void remove(int i, int j) {
34     //removes values i, j from function
35     cur_answer -= min(cmen[i], cwomen[i]);
36     cur_answer -= min(cmen[j], cwomen[j]);
37     if(i == j) cur_answer += min(cmen[j], cwomen[j]);
38     --cmen[i];
39     --cwomen[j];
40     cur_answer += min(cmen[i], cwomen[i]);
41     cur_answer += min(cmen[j], cwomen[j]);
42     if(i == j) cur_answer -= min(cmen[j], cwomen[j]);
43 }
44
45 int main()
46 {
47     int N, M, K;
48     cin >> N >> M >> K;
49     lmen.resize(N);
50     lwomen.resize(N);
51     cmen.resize(K);
52     cwomen.resize(K);
53     BLOCK_SIZE = static_cast<int>(sqrt(N));
54     vector<pair<pair<int, int>, int>> queries(M);
55     vector<int> answers(M);
56     for(int i = 0; i < N; ++i) {
57         cin >> lmen[i];
58     }
59     for(int i = 0; i < N; ++i) {
60         cin >> lwomen[i];
61     }
62     for(int i = 0; i < M; ++i) {
63         cin >> queries[i].first.first >> queries[i].
64             first.second;
65         queries[i].second = i;
66     }
67     //sort the queries into buckets
68     sort(queries.begin(), queries.end(), cmp);
69     int mo_left = 0, mo_right = -1;
70     for(int i = 0; i < M; ++i) {
71         int left = queries[i].first.first;
72         int right = queries[i].first.second;
73         while(mo_right < right) {
74             ++mo_right;
75             add(lmen[mo_right], lwomen[mo_right]);
76         }
77         while(mo_right > right) {
78             remove(lmen[mo_right], lwomen[mo_right]);
79             --mo_right;
80         }
81         while(mo_left < left) {
82             remove(lmen[mo_left], lwomen[mo_left]);
83             ++mo_left;
84         }
85         while(mo_left > left) {
86             --mo_left;
87             add(lmen[mo_left], lwomen[mo_left]);
88         }
89         answers[queries[i].second] = cur_answer;
90     }
91     for(int i = 0; i < M; ++i) {
92         cout << answers[i] << endl;
93     }
94 }

```



```
93 }
MD5: a7af72b67f95a76818d1dabadf4f9e5c |  $\mathcal{O}(?)$ 
```

## 5.8 Ternary Search

```
MD5: d41d8cd98f00b204e9800998ecf8427e |  $\mathcal{O}(?)$ 
```

## 6 String

### 6.1 Knuth-Morris-Pratt

*Input:* String  $s$  to be searched, String  $w$  to search for.

*Output:* Array with all starting positions of matches

```
1 public static ArrayList<Integer> kmp(String s, String
  w) {
2     ArrayList<Integer> ret = new ArrayList<>();
3     //Build prefix table
4     int[] N = new int[w.length()+1];
5     int i=0; int j = -1; N[0]=-1;
6     while (i<w.length()) {
7         while (j>=0 && w.charAt(j) != w.charAt(i))
8             j = N[j];
9         i++; j++; N[i]=j;
10    }
11    //Search string
12    i=0; j=0;
13    while (i<s.length()) {
14        while (j>=0 && s.charAt(i) != w.charAt(j))
15            j = N[j];
16        i++; j++;
17        if (j==w.length()) { //match found
18            ret.add(i-w.length()); //add its start index
19            j = N[j];
20        }
21    }
22    return ret;
23 }
```

```
MD5: 3cb03964744db3b14b9bff265751c84b |  $\mathcal{O}(n+m)$ 
```

### 6.2 Levenshtein Distance

Calculates the Levenshtein distance for two strings (minimum number of insertions, deletions, or substitutions).

*Input:* A string  $a$  and a string  $b$ .

*Output:* An integer holding the distance.

```
1 public static int levenshteinDistance(String a, String
  b) {
2     a = a.toLowerCase();
3     b = b.toLowerCase();
4     int[] costs = new int[b.length() + 1];
5
6     for (int j = 0; j < costs.length; j++)
7         costs[j] = j;
8
9     for (int i = 1; i <= a.length(); i++) {
10        costs[0] = i;
11        int nw = i - 1;
12        for (int j = 1; j <= b.length(); j++) {
```

```
    int cj = Math.min(1 + Math.min(costs[j], costs[j]
      - 1)),
      a.charAt(i - 1) == b.charAt(j - 1) ? nw : nw +
      1);
    nw = costs[j];
    costs[j] = cj;
  }
}
return costs[b.length()];
}
```

```
MD5: 79186003b792bc7fd5c1ffbbcf2b1c6 |  $\mathcal{O}(|a| \cdot |b|)$ 
```

### 6.3 Longest Common Subsequence

Finds the longest common subsequence of two strings.

*Input:* Two strings  $string1$  and  $string2$ .

*Output:* The LCS as a string.

```
1 public static String longestCommonSubsequence(String
  string1, String string2) {
2     char[] s1 = string1.toCharArray();
3     char[] s2 = string2.toCharArray();
4     int[][] num = new int[s1.length + 1][s2.length + 1];
5     // Actual algorithm
6     for (int i = 1; i <= s1.length; i++)
7         for (int j = 1; j <= s2.length; j++)
8             if (s1[i - 1] == s2[j - 1])
9                 num[i][j] = 1 + num[i - 1][j - 1];
10            else
11                num[i][j] = Math.max(num[i - 1][j], num[i][j -
12                    1]);
13    // System.out.println("length of LCS = " + num[s1.
14        length][s2.length]);
15    int s1position = s1.length, s2position = s2.length;
16    List<Character> result = new LinkedList<Character>();
17    while (s1position != 0 && s2position != 0) {
18        if (s1[s1position - 1] == s2[s2position - 1]) {
19            result.add(s1[s1position - 1]);
20            s1position--;
21            s2position--;
22        } else if (num[s1position][s2position - 1] >= num[
23            s1position][s2position])
24            s1position--;
25        else
26            s2position--;
27    }
28    Collections.reverse(result);
29    char[] resultString = new char[result.size()];
30    int i = 0;
31    for (Character c : result) {
32        resultString[i] = c;
33        i++;
34    }
35    return new String(resultString);
36 }
```

```
MD5: 4dc4ee3af14306bea5724ba8a859d5d4 |  $\mathcal{O}(n \cdot m)$ 
```

### 6.4 Longest common substring

gets two String and finds all LCSs and returns them in a set

```
1 public static TreeSet<String> LCS(String a, String b)
  {
```

```

2  int[][] t = new int[a.length()+1][b.length()+1];
3  for(int i = 0; i <= b.length(); i++)
4      t[0][i] = 0;
5
6  for(int i = 0; i <= a.length(); i++)
7      t[i][0] = 0;
8
9  for(int i = 1; i <= a.length(); i++)
10     for(int j = 1; j <= b.length(); j++)
11         if(a.charAt(i-1) == b.charAt(j-1))
12             t[i][j] = t[i-1][j-1] + 1;
13         else
14             t[i][j] = 0;
15
16  int max = -1;
17  for(int i = 0; i <= a.length(); i++)
18     for(int j = 0; j <= b.length(); j++)
19         if(max < t[i][j])
20             max = t[i][j];
21
22  if(max == 0 || max == -1)
23     return new TreeSet<String>();
24  TreeSet<String> res = new TreeSet<String>();
25  for(int i = 0; i <= a.length(); i++)
26     for(int j = 0; j <= b.length(); j++)
27         if(max == t[i][j])
28             res.add(a.substring(i-max, i));
29  return res;

```

MD5: 9de393461e1faebe99af3ff8db380bde |  $\mathcal{O}(|a| * |b|)$

## 7 auto

## 8 Math

### 8.1 Tree

Diameter: BFS from any node, then BFS from last visited node.  
Max dist is then the diameter. Center: Middle vertex in second step from above.

### 8.2 Divisability Explanation

$D \mid M \Leftrightarrow D \mid \text{digit\_sum}(M, k, \text{alt})$ , refer to table for values of  $D, k, \text{alt}$ .

### 8.3 Combinatorics

- Variations (ordered):  $k$  out of  $n$  objects (permutations for  $k = n$ )
  - without repetition:  
 $M = \{(x_1, \dots, x_k) : 1 \leq x_i \leq n, x_i \neq x_j \text{ if } i \neq j\}$ ,  
 $|M| = \frac{n!}{(n-k)!}$
  - with repetition:  
 $M = \{(x_1, \dots, x_k) : 1 \leq x_i \leq n\}$ ,  $|M| = n^k$
- Combinations (unordered):  $k$  out of  $n$  objects
  - without repetition:  $M = \{(x_1, \dots, x_n) : x_i \in \{0, 1\}, x_1 + \dots + x_n = k\}$ ,  $|M| = \binom{n}{k}$
  - with repetition:  $M = \{(x_1, \dots, x_n) : x_i \in \{0, 1, \dots, k\}, x_1 + \dots + x_n = k\}$ ,  $|M| = \binom{n+k-1}{k}$

- Ordered partition of numbers:  $x_1 + \dots + x_k = n$  (i.e.  $1+3=3+1=4$  are counted as 2 solutions)
  - #Solutions for  $x_i \in \mathbb{N}_0$ :  $\binom{n+k-1}{k-1}$
  - #Solutions for  $x_i \in \mathbb{N}$ :  $\binom{n-1}{k-1}$
- Unordered partition of numbers:  $x_1 + \dots + x_k = n$  (i.e.  $1+3=3+1=4$  are counted as 1 solution)
  - #Solutions for  $x_i \in \mathbb{N}$ :  $P_{n,k} = P_{n-k,k} + P_{n-1,k-1}$  where  $P_{n,1} = P_{n,n} = 1$
- Derangements (permutations without fixed points):  $!n = n! \sum_{k=0}^n \frac{(-1)^k}{k!} = \lfloor \frac{n!}{e} + \frac{1}{2} \rfloor$

## 8.4 Polynomial Interpolation

### 8.4.1 Theory

Problem: for  $\{(x_0, y_0), \dots, (x_n, y_n)\}$  find  $p \in \Pi_n$  with  $p(x_i) = y_i$  for all  $i = 0, \dots, n$ .

Solution:  $p(x) = \sum_{i=0}^n \gamma_{0,i} \prod_{j=0}^{i-1} (x - x_j)$  where  $\gamma_{j,k} = y_j$  for  $k = 0$

and  $\gamma_{j,k} = \frac{\gamma_{j+1,k-1} - \gamma_{j,k-1}}{x_{j+k} - x_j}$  otherwise.

Efficient evaluation of  $p(x)$ :  $b_n = \gamma_{0,n}$ ,  $b_i = b_{i+1}(x - x_i) + \gamma_{0,i}$  for  $i = n-1, \dots, 0$  with  $b_0 = p(x)$ .

## 8.5 Fibonacci Sequence

### 8.5.1 Binet's formula

$$\begin{pmatrix} f_n \\ f_{n+1} \end{pmatrix} = \begin{pmatrix} 0 & 1 \\ 1 & 1 \end{pmatrix}^n \begin{pmatrix} 0 \\ 1 \end{pmatrix} \Rightarrow f_n = \frac{1}{\sqrt{5}}(\phi^n - \tilde{\phi}^n) \text{ where } \phi = \frac{1+\sqrt{5}}{2} \text{ and } \tilde{\phi} = \frac{1-\sqrt{5}}{2}.$$

### 8.5.2 Generalization

$$g_n = \frac{1}{\sqrt{5}}(g_0(\phi^{n-1} - \tilde{\phi}^{n-1}) + g_1(\phi^n - \tilde{\phi}^n)) = g_0 f_{n-1} + g_1 f_n \text{ for all } g_0, g_1 \in \mathbb{N}_0$$

### 8.5.3 Pisano Period

Both  $(f_n \bmod k)_{n \in \mathbb{N}_0}$  and  $(g_n \bmod k)_{n \in \mathbb{N}_0}$  are periodic.

## 8.6 Reihen

$$\begin{aligned} \sum_{i=1}^n i &= \frac{n(n+1)}{2}, \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}, \sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4} \\ \sum_{i=0}^n c^i &= \frac{c^{n+1}-1}{c-1}, c \neq 1, \sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \sum_{i=1}^n c^i = \frac{c}{1-c}, |c| < 1 \\ \sum_{i=0}^n i c^i &= \frac{nc^{n+2} - (n+1)c^{n+1} + c}{(c-1)^2}, c \neq 1, \sum_{i=0}^{\infty} i c^i = \frac{c}{(1-c)^2}, |c| < 1 \end{aligned}$$

## 8.7 Binomialkoeffizienten

$$\begin{aligned} \binom{n}{k} &= \binom{n-1}{k} + \binom{n-1}{k-1}, \quad \binom{n}{m} \binom{m}{k} = \binom{n}{k} \binom{n-k}{m-k}, \\ \binom{m+n}{r} &= \sum_{k=0}^r \binom{m}{k} \binom{n}{r-k} \text{ and in general, } n_1 + \dots + n_p = \sum_{k_1+\dots+k_p=m} \binom{n_1}{k_1} \dots \binom{n_p}{k_p} \end{aligned}$$

## 8.8 Catalanzahlen

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, C_{n+1} = \sum_{k=0}^n C_k C_{n-k}, C_{n+1} = \frac{4n+2}{n+2} C_n$$

## 8.9 Geometrie

**Polygonfläche:**  $A = \frac{1}{2}(x_1y_2 - x_2y_1 + x_2y_3 - x_3y_2 + \dots + x_{n-1}y_n - x_ny_{n-1} + x_ny_1 - x_1y_n)$

## 8.10 Zahlentheorie

**Chinese Remainder Theorem:** Es existiert eine Zahl  $C$ , sodass:

$$C \equiv a_1 \pmod{n_1}, \dots, C \equiv a_k \pmod{n_k}, \text{ggT}(n_i, n_j) = 1, i \neq j$$

Fall  $k = 2$ :  $m_1n_1 + m_2n_2 = 1$  mit EEA finden.

Lösung ist  $x = a_1m_2n_2 + a_2m_1n_1$ .

Allgemeiner Fall: iterative Anwendung von  $k = 2$

**Eulersche  $\varphi$ -Funktion:**  $\varphi(n) = n \prod_{p|n} (1 - \frac{1}{p})$ ,  $p$  prim

$$\varphi(p) = p - 1, \varphi(pq) = \varphi(p)\varphi(q), p, q \text{ prim}$$

$$\varphi(p^k) = p^k - p^{k-1}, p, q \text{ prim}, k \geq 1$$

**Eulers Theorem:**  $a^{\varphi(n)} \equiv 1 \pmod{n}$

**Fermats Theorem:**  $a^p \equiv a \pmod{p}$ ,  $p$  prim

## 8.11 Faltung

$$(f * g)(n) = \sum_{m=-\infty}^{\infty} f(m)g(n-m) = \sum_{m=-\infty}^{\infty} f(n-m)g(m)$$

# 9 Java Knowhow

## 9.1 System.out.printf() und String.format()

**Syntax:** %[flags][width][.precision][conv]

**flags:**

- left-justify (default: right)
- + always output number sign
- 0 zero-pad numbers
- (space) space instead of minus for pos. numbers
- , group triplets of digits with ,

**width** specifies output width

**precision** is for floating point precision

**conv:**

- d byte, short, int, long
- f float, double
- c char (use C for uppercase)
- s String (use S for all uppercase)

## 9.2 Modulo: Avoiding negative Integers

```
1 int mod = (((nums[j] % D) + D) % D);
```

## 9.3 Speed up IO

Use

```
1 BufferedReader br = new BufferedReader(new
2 InputStreamReader(System.in));
```

Use

```
1 Double.parseDouble(Scanner.next());
```