

# translations

V1.0 2013/07/15

a simple translator

Clemens NIEDERBERGER

<https://github.com/cgnieder/translations/>  
[contact@mychemistry.eu](mailto:contact@mychemistry.eu)

English documentation

## Contents

		3.3.2 The ‘fallback’ language .	5
		3.4 Dictionaries . . . . .	5
		3.4.1 Own Dictionaries . . . .	5
		3.4.2 <b>TRANSLATIONS</b> ’ Basic	
		Dictionaries . . . . .	6
<b>1</b>	<b>Motivation</b>	<b>1</b>	
<b>2</b>	<b>License and Requirements</b>	<b>2</b>	
<b>3</b>	<b>Usage</b>	<b>2</b>	
	3.1 Available Commands . . . . .	2	
	3.2 A Small Example . . . . .	3	
	3.3 Usage in Packages . . . . .	4	
	3.3.1 Basic Structure . . . . .	4	
<b>4</b>	<b>Defined Languages</b>	<b>8</b>	
<b>5</b>	<b>Implementation</b>	<b>10</b>	
	<b>Index</b>	<b>21</b>	

## 1 Motivation

This package provides means for package authors to have an easy interface for internationalization of their packages. The functionality of this package is in many parts also covered by the package translator (part of the beamer<sup>1</sup> bundle). Internationalization is also possible with babel<sup>2</sup> and it’s `\addto\captions<language>` mechanism or KOMA-Script’s `\providecaptionname`. However, I believe that **TRANSLATIONS** is more flexible than all of these. Unlike translator it detects the used (babel or polyglossia<sup>3</sup>) language itself and provides expandable retrieving of the translated key. **TRANSLATIONS** also provides support for language dialects which means package authors can for example distinguish between British, Australian, Canadian and US English.

The first draft of the package was written since I missed an expandable version of translator’s `\translate` command. Once I had the package available I began using it in various of my other packages so it got extended to the needs I faced there.

---

<sup>1</sup> on CTAN: beamer   <sup>2</sup> on CTAN: babel   <sup>3</sup> on CTAN: polyglossia

## 2 License and Requirements

**TRANSLATIONS** is placed under the terms of the L<sup>A</sup>T<sub>E</sub>X Project Public License, version 1.3 or later (<http://www.latex-project.org/lppl.txt>). It has the status “maintained.”

**TRANSLATIONS** requires the packages etoolbox<sup>4</sup> and scrfile (part of the KOMA-Script bundle<sup>5</sup>).

## 3 Usage

### 3.1 Available Commands

Below the commands provided by **TRANSLATIONS** are explained. The symbol ► means that the command is expandable, ► means that it isn’t.

- **\DeclareLanguage**{<lang>}  
Declare a language that can be used by **TRANSLATIONS**. If the language already exists it will be silently redefined. This command can only be used in the preamble.
- **\DeclareLanguageAlias**{<lang2>}{<lang1>}  
Declares <lang2> to be an alias of <lang1>. If <lang1> doesn’t exist yet a warning will be raised and it will be defined. This command can only be used in the preamble.
- **\DeclareLanguageDialect**{<dialect>}{<lang>}  
Declares <dialect> to be a dialect of language <lang>. If a translation for <dialect> is provided it is used by the translation macros. If there is none the corresponding translation for <lang> is used instead.
- **\NewTranslation**{<lang>}{<key>}{<translation>}  
Defines a translation of key <key> for the language <lang>. An error will be raised if a translation of <key> already exists. This command can only be used in the preamble.
- **\RenewTranslation**{<lang>}{<key>}{<translation>}  
Redefines a translation of key <key> for the language <lang>. An error will be raised if no translation of <key> exists. This command can only be used in the preamble.
- **\DeclareTranslation**{<lang>}{<key>}{<translation>}  
Defines a translation of key <key> for the language <lang>. No error will be raised if a translation of <key> already exists. This command can only be used in the preamble.
- **\DeclareTranslationFallback**{<key>}{<fallback>}  
Defines a fallback translation for key <key> that is used in case no translation of <key> for the currently active language has been provided. No error will be raised if a fallback for <key> already exists. This command can only be used in the preamble.
- **\GetTranslationFor**{<lang>}{<key>}  
Fetches and prints the translation of <key> for the language <lang>. This command is expandable.
- **\GetTranslation**{<key>}  
Fetches and prints the translation of <key> for the currently active language (as for example set by babel). This command is expandable.

---

<sup>4</sup> on CTAN: etoolbox    <sup>5</sup> on CTAN: koma-script

- **\GetTranslationForWarn**{<lang>}{<key>}

Introduced in version 1.0      Fetches and prints the translation of <key> for the language <lang>. Issues a warning if no translation is available.
- **\GetTranslationWarn**{<key>}

Introduced in version 1.0      Fetches and prints the translation of <key> for the currently active language (as for example set by babel). Issues a warning if no translation is available.
- **\SaveTranslationFor**{<cmd>}{<lang>}{<key>}

Fetches and saves the translation of <key> for the language <lang> in the macro <cmd>.
- **\SaveTranslation**{<cmd>}{<key>}

Fetches and saves the translation of <key> for the currently active language (as for example set by babel) in the macro <cmd>.
- **\LoadDictionary**{<name>}

Loads a file named <name>-<lang>.trsl where <lang> corresponds to the lowercase name of the current language as defined with **\DeclareLanguage**. This file should contain the translations for the specified language.
- **\LoadDictionaryFor**{<lang>}{<name>}

Loads a file named <name>-<lang>.trsl.
- **\DeclareDictTranslation**{<key>}{<translation>}

This command is to be used in a dictionary file and picks up the language of that file, see section 3.4 for an example.
- **\ProvideDictionaryFor**{<lang>}{<name>}[<date>]

Needs to be in a dictionary file. This command tells **TRANSLATIONS** that the file indeed is a dictionary and also sets the language for the dictionary which is used by **\DeclareDictTranslation**.
- **\PrintDictionaryFor**{<lang>}{<name>}{<pre>}{<mid>}{<post>}

Introduced in version 1.0      Prints all entries of dictionary <name> in language <lang> in the order the entries have been declared. For every entry the code

<pre><key><mid><translation><post>

is printed. The dictionary must have been loaded of course.

### 3.2 A Small Example

This section demonstrates with two short examples how the macros are used. The first example covers the basics: declaring of translations and then retrieving and typesetting them.

```

1 % in the preamble:
2 % \DeclareTranslation{English}{Kueche}{kitchen}
3 % \DeclareTranslation{German}{Kueche}{K\"uche}
4 % \DeclareTranslation{Spanish}{Kueche}{cocina}
5 % \DeclareTranslation{French}{Kueche}{cuisine}
6
7 \GetTranslation{Kueche}
8 \SaveTranslation\kitchen{Kueche}
9 \SaveTranslationFor\cuisine{french}{Kueche}
10
11 \selectlanguage{ngerman}
12 \GetTranslation{Kueche} \kitchen\ \GetTranslationFor{spanish}{Kueche}
13 \cuisine

kitchen
Küche kitchen cocina cuisine

```

The next example demonstrates the use of dialects and how they fall back to the translation for the main language if no extra translation was declared:

```

1 % in the preamble:
2 % \DeclareTranslation{English}{farbe}{color}
3 % \DeclareTranslation{British}{farbe}{colour}
4
5 \GetTranslationFor{English}{farbe} \
6 \GetTranslationFor{British}{farbe} \
7 \GetTranslationFor{American}{farbe}

color
colour
color

```

### 3.3 Usage in Packages

#### 3.3.1 Basic Structure

A typical usage in a package would look as follows:

```

1 \RequirePackage{translations}
2 \DeclareTranslationFallback{mypackage-title}{Nice Title}
3 \DeclareTranslation{English}{mypackage-title}{Nice Title}
4 \DeclareTranslation{French}{mypackage-title}{Beau Titre}
5 \DeclareTranslation{German}{mypackage-title}{Sch\"o{ner Titel}
6 ...
7 \def\mypackage@title{\GetTranslation{mypackage-title}}

```

That is, a package defines some unique key for an expression and at least defines a fallback translation. Additionally translations for as many languages as the author wants are defined. A user then may add `\DeclareTranslation{<language>}{<translation>}` if they find their translation missing.

### 3.3.2 The ‘fallback’ language

If a user has neither loaded `babel` nor `polyglossia` `TRANSLATIONS` will use English as language and translate to English if the translation was provided. If the user *has* loaded one of the language packages but has chosen a language for which no translation is defined the language ‘fallback’ will be used, i.e., the translation provided with `\DeclareTranslationFallback`. If no fallback translation is provided either the translation will expand to the literal string.

The following three examples should make this concept clear:

```

1 \documentclass{article}
2 \DeclareTranslation{German}{foo-literal}{bar}
3 \begin{document}
4 \GetTranslation{foo-literal} => `foo-literal'
5 \end{document}

```

```

1 \documentclass{article}
2 \DeclareTranslationFallback{foo-literal}{foo}
3 \DeclareTranslation{German}{foo-literal}{bar}
4 \begin{document}
5 \GetTranslation{foo-literal} => `foo'
6 \end{document}

```

```

1 \documentclass{article}
2 \usepackage[ngerman]{babel}
3 \DeclareTranslation{German}{foo-literal}{bar}
4 \begin{document}
5 \GetTranslation{foo-literal} => `bar'
6 \end{document}

```

## 3.4 Dictionaries

### 3.4.1 Own Dictionaries

A typical dictionary file should look as follows:

```

1 % this is file housing-german.trsl
2 \ProvideDictionaryFor{German}{housing}[-<version info>]
3 \DeclareDictTranslation{kitchen (housing)}{K\"uche}
4 \DeclareDictTranslation{bathroom (housing)}{Bad}
5 \DeclareDictTranslation{living room (housing)}{Wohnzimmer}
6 \DeclareDictTranslation{bedroom (housing)}{Schlafzimmer}
7 ...
8 \endinput

```

The usage is similar to the one in a package: unique keys are given translations, this time for the language the dictionary file is declared for only.

### 3.4.2 TRANSLATIONS' Basic Dictionaries

**TRANSLATIONS** already provides a basic dictionary for the languages English, French, German and Spanish. This dictionary is loaded automatically if the document language is one of these four. If you'd like to contribute and add the basic dictionary in your language this is more than welcome and highly appreciated! The easiest way to do this would be to copy one of the existing files `translations-basic-dictionary-<lang>.trsl` and modify the file accordingly. You can then send me the file via email and I'll add it to **TRANSLATIONS**.

Table 1 lists all words provided by the basic dictionary for German.

TABLE 1: All entries of **TRANSLATIONS**' basic dictionary in German.

| key             | translation          |
|-----------------|----------------------|
| Abstract        | Zusammenfassung      |
| Addresses       | Adressen             |
| addresses       | Adressen             |
| Address         | Adresse              |
| address         | Adresse              |
| and             | und                  |
| Appendix        | Anhang               |
| Authors         | Autoren              |
| authors         | Autoren              |
| Author          | Autor                |
| author          | Autor                |
| Bibliography    | Literaturverzeichnis |
| cc              | Verteiler            |
| Chapters        | Kapitel              |
| chapters        | Kapitel              |
| Chapter         | Kapitel              |
| chapter         | Kapitel              |
| Conclusion      | Zusammenfassung      |
| conclusion      | Zusammenfassung      |
| Contents        | Inhaltsverzeichnis   |
| Continuation    | Fortsetzung          |
| continuation    | Fortsetzung          |
| cont            | Forts                |
| encl (plural)   | Anlagen              |
| encl (singular) | Anlage               |
| encl            | Anlage(n)            |
| Figures         | Abbildungen          |
| figures         | Abbildungen          |
| Figure          | Abbildung            |

*continues*

| key                        | translation                         |
|----------------------------|-------------------------------------|
| figure                     | Abbildung                           |
| From                       | Von                                 |
| from                       | von                                 |
| Glossary                   | Glossar                             |
| Index                      | Index                               |
| Introduction               | Einleitung                          |
| introduction               | Einleitung                          |
| List of Figures and Tables | Abbildungs- und Tabellenverzeichnis |
| List of Figures            | Abbildungsverzeichnis               |
| List of Tables             | Tabellenverzeichnis                 |
| or                         | oder                                |
| Outline                    | Gliederung                          |
| Overview                   | Übersicht                           |
| Pages                      | Seiten                              |
| pages                      | Seiten                              |
| Page                       | Seite                               |
| page                       | Seite                               |
| Paragraphs                 | Absätze                             |
| paragraphs                 | Absätze                             |
| Paragraph                  | Absatz                              |
| paragraph                  | Absatz                              |
| Parts                      | Teile                               |
| parts                      | Teile                               |
| Part                       | Teil                                |
| part                       | Teil                                |
| Preface                    | Vorwort                             |
| Proofs                     | Beweise                             |
| proofs                     | Beweise                             |
| Proof                      | Beweis                              |
| proof                      | Beweis                              |
| References                 | Literatur                           |
| Related work               | Verwandte Arbeiten                  |
| Related Work               | Verwandte Arbeiten                  |
| Sections                   | Abschnitte                          |
| sections                   | Abschnitte                          |
| Section                    | Abschnitt                           |
| section                    | Abschnitt                           |
| See also                   | Siehe auch                          |
| see also                   | siehe auch                          |
| See                        | Siehe                               |
| see                        | siehe                               |
| Sketch of Proofs           | Beweisskizzen                       |
| Sketch of proofs           | Beweisskizzen                       |

*continues*

| key             | translation     |
|-----------------|-----------------|
| Sketch of Proof | Beweisskizze    |
| Sketch of proof | Beweisskizze    |
| Subsections     | Unterabschnitte |
| subsections     | Unterabschnitte |
| Subsection      | Unterabschnitt  |
| subsection      | Unterabschnitt  |
| Summary         | Zusammenfassung |
| Tables          | Tabellen        |
| tables          | Tabellen        |
| Table           | Tabelle         |
| table           | Tabelle         |
| To              | An              |
| to              | an              |

## 4 Defined Languages

Quite a number of languages already are defined, either directly or via an alias. So, before you define a language you should take a look at the tables below if the language doesn't already exist. **TRANSLATIONS** currently has these languages defined, "fallback" being a dummy language used for fallback translations. Table 2 lists all base languages.

TABLE 2: Languages defines by **TRANSLATIONS**.

|           |           |               |            |
|-----------|-----------|---------------|------------|
| fallback  | albanian  | bulgarian     | catalan    |
| croatian  | czech     | danish        | dutch      |
| english   | finnish   | french        | german     |
| greek     | hebrew    | hungarian     | icelandic  |
| italian   | norwegian | polish        | portuges   |
| romanian  | russian   | serbocroatian | slovak     |
| slovenian | spanish   | swedish       | turkish    |
| ukrainian | canadien  | american      | australian |
| british   | canadian  | austrian      | naustrian  |
| magyar    | brazil    | swissgerman   |            |

To every one of these languages at least one alias exists, the uppercase variant. This is due to the fact that it is common to write language names uppercased. All defined aliases are listed in table 3.

TABLE 3: All language aliases defined by **TRANSLATIONS**.

| alias    | language | alias    | language |
|----------|----------|----------|----------|
| Fallback | fallback | Albanian | albanian |

*continues*



#### 4 Defined Languages

| alias      | language    | alias           | language      |
|------------|-------------|-----------------|---------------|
| Bulgarian  | bulgarian   | Catalan         | catalan       |
| Croatian   | croatian    | Czech           | czech         |
| Danish     | danish      | Dutch           | dutch         |
| Finnish    | finnish     | francais        | french        |
| Francais   | francais    | Canadien        | canadien      |
| French     | french      | American        | american      |
| Australian | australian  | British         | british       |
| Canadian   | canadian    | English         | english       |
| UKenglish  | british     | USenglish       | american      |
| Austrian   | austrian    | German          | german        |
| germanb    | german      | ngerman         | german        |
| Greek      | greek       | polutonikogreek | greek         |
| Hebrew     | hebrew      | Hungarian       | hungarian     |
| Magyar     | magyar      | Icelandic       | icelandic     |
| Italian    | italian     | norsk           | norwegian     |
| Norsk      | norsk       | Norwegian       | norwegian     |
| nynorsk    | norwegian   | Nynorsk         | nynorsk       |
| Polish     | polish      | Brazil          | brazil        |
| brazilian  | brazil      | Brazilian       | brazilian     |
| Portuges   | portuges    | portuguese      | portuges      |
| Portuguese | portuguese  | Romanian        | romanian      |
| Russian    | russian     | Serbocroatian   | serbocroatian |
| Slovak     | slovak      | Slovenian       | slovenian     |
| Spanish    | spanish     | Swedish         | swedish       |
| Swiss      | swissgerman | Swissgerman     | swissgerman   |
| Turkish    | turkish     | Ukrainian       | ukrainian     |

**TRANSLATIONS** also defines a few dialects. They are listed in table 4.

TABLE 4: All dialects defined by **TRANSLATIONS**.

| dialect    | language | dialect     | language  |
|------------|----------|-------------|-----------|
| canadien   | french   | american    | english   |
| australian | english  | british     | english   |
| canadian   | english  | austrian    | german    |
| naustrian  | austrian | magyar      | hungarian |
| brazil     | portuges | swissgerman | german    |

These languages should cover all languages which are currently covered by babel and polyglossia.

## 5 Implementation

In the following code the lines 1–30 have been omitted. They only repeat the license statement which has already been mentioned in section 2.

```

31 \def\@trnslt@date{2013/07/15}
32 \def\@trnslt@version{v1.0}
33
34 \ProvidesPackage{translations}[\@trnslt@date\space \@trnslt@version\space a simple
   translator]
35 \RequirePackage{etoolbox,scrfile}
36
37 % -----
38 % message handling
39 \def\@trnslt@error@message{%
40   For details have a look at the `translations' manual.}
41
42 \def\@trnslt@create@message#1{%
43   \ifstrequal{#1}{Error}
44     {%
45       \lowercase{\csdef{\@trnslt@#1}}##1{%
46         \csuse{Package#1}{translations}{##1}{\@trnslt@error@message}}%
47     }{%
48       \lowercase{\csdef{\@trnslt@#1}}##1{%
49         \csuse{Package#1}{translations}{##1}}%
50     }}
51 \@trnslt@create@message{Error}
52 \@trnslt@create@message{Warning}
53 \@trnslt@create@message{WarningNoLine}
54 \@trnslt@create@message{Info}
55
56 \def\@trnslt@err@unknown@lang#1{%
57   \@trnslt@error{Unknown language `#1'}}
58
59 \def\@trnslt@warn@unknown@lang#1{%
60   \@trnslt@warning{Unknown language `#1'}}
61
62 \def\@trnslt@err@already@defined#1#2{%
63   \@trnslt@error{The #2 translation for `#1' is already defined.}}
64
65 \def\@trnslt@err@not@defined#1#2{%
66   \@trnslt@error{The \@trnslt@language{#2} translation for `#1' is not defined yet.}}
67
68 % -----
69 % check if babel or polyglossia is used
70 \AtEndPreamble{
71   \ifpackageloaded{babel}{}{
72     \ifpackageloaded{polyglossia}{}
73       {\@trnslt@warning{No language package found. I am going to use `english'
74         as default language.}}
75   }
76   \ifdef\language{}

```

## 5 Implementation

```

77     {\def\language\english}}
78 \def\@trns\@current\language{\language}
79 \ifdef\bb\@afterfi{}
80     {\long\def\bb\@afterfi#1\fi{\fi#1}}
81 }
82
83 % -----
84 % book keeping: the following macros will be used as 'etoolbox' lists that
85 % keep record of defined languages, dialects and aliases
86 \def\@trns\@languages{}% all languages
87 \def\@trns\@aliases\@pair{}% all aliases and their base
88 \def\@trns\@aliases\@single{}% all aliases
89 \def\@trns\@dialects\@pair{}% all dialects and their base
90 \def\@trns\@dialects\@single{}% all dialects
91
92 % -----
93 % \DeclareLanguage and \DeclareLanguageAlias
94 % #1: language
95 \newrobustcmd*\DeclareLanguage[1]{%
96     \@trns\@declare\@language{#1}}
97 \@onlypreamble\DeclareLanguage
98
99 \def\@trns\@declare\@language#1{%
100     \@trns\@if\@language{#1}
101     }{%
102         \csdef{\@trns\@language@#1}{#1}%
103         \listadd\@trns\@languages{#1}%
104     }%
105 }
106
107 \def\@trns\@language#1{%
108     \csuse{\@trns\@language@#1}}
109
110 \def\@trns\@if\@language#1{%
111     \ifcsundef{\@trns\@language@#1}
112     {\expandafter\@secondoftwo}
113     {\expandafter\@firstoftwo}%
114 }
115
116 % #1: dialect
117 % #2: language
118 \newrobustcmd*\DeclareLanguageDialect[2]{%
119     \@trns\@declare\@language\@dialect{#1}{#2}}
120 \@onlypreamble\DeclareLanguageDialect
121
122 \def\@trns\@declare\@language\@dialect#1#2{%
123     \@trns\@if\@language{#2}
124     }{%
125         \@trns\@warn\@unknown\@lang{#2}%
126         \@trns\@declare\@language{#2}%
127     }%
128     \@trns\@if\@dialect{#1}

```

## 5 Implementation

```

129   {% => ist schon als dialect definiert => irgendwelche weiteren checks?
130   }
131   {%
132     \@trnslt@if@alias{#2}
133     {%
134       \csedef{@trnslt@dialect@#1}{\@trnslt@alias{#2}{#1}}%
135       \@trnslt@declare@language{#1}%
136       \listeadadd\@trnslt@dialects@single{#1}%
137       \listeadadd\@trnslt@dialects@pair{#1}{\@trnslt@alias{#2}}}%
138     }
139     {%
140       \csdef{@trnslt@dialect@#1}{#2}{#1}%
141       \@trnslt@declare@language{#1}%
142       \listeadadd\@trnslt@dialects@single{#1}%
143       \listeadadd\@trnslt@dialects@pair{#1}{#2}}%
144     }%
145   }%
146 }
147
148 \def\@trnslt@dialect#1{%
149   \csuse{@trnslt@dialect@#1}}
150
151 \def\@trnslt@dialect@of#1{%
152   \expandafter\expandafter\expandafter
153   \@trnslt@dialect@of@aux
154   \csname @trnslt@dialect@#1\endcsname\@empty
155 }
156 \def\@trnslt@dialect@of@aux#1#2{\ifx\relax#1\@empty\else#1\fi}
157
158 \def\@trnslt@if@dialect#1{%
159   \ifcsundef{@trnslt@dialect@#1}
160     {\expandafter\@secondoftwo}
161     {\expandafter\@firstoftwo}%
162 }
163
164 % #1: alias
165 % #2: language
166 \newrobustcmd*\DeclareLanguageAlias[2]{%
167   \@trnslt@declare@languagealias{#1}{#2}}
168 \@onlypreamble\DeclareLanguageAlias
169
170 \def\@trnslt@declare@languagealias#1#2{%
171   \@trnslt@if@language{#2}
172   {%}%
173   \@trnslt@warn@unknown@lang{#2}%
174   \@trnslt@declare@language{#2}%
175   }%
176   \csletcs{@trnslt@language@#1}{@trnslt@language@#2}%
177   \@trnslt@if@dialect{#2}
178   {\csletcs{@trnslt@dialect@#1}{@trnslt@dialect@#2}}
179   {%}%
180   \ifinlist{#1}\@trnslt@aliases@single

```

## 5 Implementation

```

181   {}{%
182     \csdef{@trnslt@alias@#1}{#2}%
183     \listeadadd{@trnslt@aliases@pair}{#1}{#2}}%
184     \listeadadd{@trnslt@aliases@single}{#1}%
185   }%
186 }
187
188 \def{@trnslt@alias#1{%
189   \csuse{@trnslt@alias@#1}}
190
191 \def{@trnslt@if@alias#1{%
192   \ifcsundef{@trnslt@alias@#1}
193     {\expandafter\@secondoftwo}
194     {\expandafter\@firstoftwo}%
195 }
196
197 % dummy language: `fallback':
198 \DeclareLanguage{fallback}
199 \DeclareLanguageAlias{Fallback}{fallback}
200
201 % -----
202 % \DeclareTranslation, \NewTranslation and \RenewTranslation
203 % #1: language
204 % #2: word
205 % #3: replacement
206 \newrobustcmd*{\DeclareTranslation[3]{%
207   \@trnslt@declare@translation{#2}{#1}{#3}}
208 \@onlypreamble\DeclareTranslation
209
210 \newrobustcmd*{\DeclareTranslationFallback[2]{%
211   \@trnslt@declare@translation{#1}{fallback}{#2}}
212 \@onlypreamble\DeclareTranslationFallback
213
214 \newrobustcmd*{\NewTranslation[3]{%
215   \@trnslt@new@translation{#2}{#1}{#3}}
216 \@onlypreamble\NewTranslation
217
218 \newrobustcmd*{\RenewTranslation[3]{%
219   \@trnslt@renew@translation{#2}{#1}{#3}}
220 \@onlypreamble\RenewTranslation
221
222 % #1: word
223 % #2: language
224 % #3: replacement
225 \def{@trnslt@declare@translation#1#2#3{%
226   \@trnslt@if@language{#2}
227   {%
228     % save the <word> as <word>:
229     \csdef{@trnslt@word@#1@literal}{#1}%
230     % check if the language is a dialect:
231     \@trnslt@if@dialect{#2}
232     {\csdef{@trnslt@word@#1@{trnslt@dialect}{#2}}{#3}}

```

## 5 Implementation

```

233     {}%
234     % check if translation already exists:
235     \@trnslt@if@translation{#1}{#2}
236     {}
237     {\csdef{@trnslt@word@#1@\@trnslt@language{#2}}{#3}}%
238 }
239 {\@trnslt@err@unknown@lang{#2}}%
240 }
241
242 \def\@trnslt@if@translation#1#2{%
243   \ifcsundef{@trnslt@word@#1@\@trnslt@language{#2}}
244   {%
245     \@trnslt@if@dialect{#2}
246     {%
247       \ifboolexpe{
248         test {\ifcsundef{@trnslt@word@#1@\@trnslt@dialect{#2}}} or
249         test {\ifcsundef{@trnslt@word@#1@\@trnslt@dialect@of{#2}}}
250       }
251       {\expandafter\@firstoftwo}
252       {\expandafter\@secondoftwo}%
253     }
254     {\expandafter\@secondoftwo}%
255   }
256   {\expandafter\@firstoftwo}%
257 }
258
259 \def\@trnslt@new@translation#1#2#3{%
260   \@trnslt@if@translation{#1}{#2}
261   {\@trnslt@err@already@defined{#1}{#2}}
262   {\@trnslt@declare@translation{#1}{#2}{#3}}
263 }
264
265 \def\@trnslt@renew@translation#1#2#3{%
266   \@trnslt@if@translation{#1}{#2}
267   {\@trnslt@declare@translation{#1}{#2}{#3}}
268   {\@trnslt@err@not@defined{#1}{#2}}
269 }
270
271 % -----
272 % \GetTranslationFor and \GetTranslation
273 % these need to be expandable!
274 % #1: language
275 % #2: word
276 \newcommand*\GetTranslationFor[2]{%
277   \@trnslt@checkandget@translation@for{#2}{#1}}
278
279 \newcommand*\GetTranslation[1]{%
280   \@trnslt@checkandget@translation@for{#1}{\@trnslt@current@language}}
281
282 % unexpandable version of the commands that raise a warning if no translation
283 % is available:
284 \newcommand*\GetTranslationForWarn[2]{%
285   \@trnslt@getandwarn@translation@for{#2}{#1}}

```

## 5 Implementation

```

285 \newcommand*\GetTranslationWarn[1]{%
286   \@trnslt@getandwarn@translation@for{#1}{\@trnslt@current@language}}
287
288 % #1: word #2: language
289 \def\@trnslt@get@translation@for#1#2{%
290   \@trnslt@if@dialect{#2}
291   {%
292     \ifcsdef{@trnslt@word@#1\@trnslt@dialect{#2}}
293     {\csuse{@trnslt@word@#1\@trnslt@dialect{#2}}}
294     {\csuse{@trnslt@word@#1\@trnslt@dialect@of{#2}}}%
295   }
296   {\csuse{@trnslt@word@#1\@trnslt@language{#2}}}%
297 }
298
299 \def\@trnslt@checkandget@translation@for#1#2{%
300   \@trnslt@if@translation{#1}{#2}
301   {\@trnslt@get@translation@for{#1}{#2}}
302   {%
303     \@trnslt@if@translation{#1}{fallback}
304     {\csuse{@trnslt@word@#1@fallback}}
305     {\csuse{@trnslt@word@#1@literal}}%
306   }%
307 }
308
309 % this is not expandable!
310 \protected\def\@trnslt@getandwarn@translation@for#1#2{%
311   \@trnslt@if@translation{#1}{#2}
312   {\@trnslt@get@translation@for{#1}{#2}}
313   {%
314     \@trnslt@warning{Translation for `#1' in #2 unknown. You may try to use
315       \string\DeclareTranslation{#2}{#1}{ ... } in your preamble.}%
316     \@trnslt@if@translation{#1}{fallback}
317     {%
318       \@trnslt@info{Using fallback translation for `#1'}%
319       \csuse{@trnslt@word@#1@fallback}
320     }
321     {\csuse{@trnslt@word@#1@literal}}%
322   }%
323 }
324
325 % -----
326 % \SaveTranslationFor and \SaveTranslation
327 \newrobustcmd*\SaveTranslationFor[3]{%
328   \@trnslt@save@translation@for{#1}{#3}{#2}}
329
330 \newrobustcmd*\SaveTranslation[2]{%
331   \@trnslt@save@translation@for{#1}{#2}{\@trnslt@current@language}}
332
333 \def\@trnslt@save@translation@for#1#2#3{%
334   \edef#1{%
335     \@trnslt@if@translation{#2}{#3}
336     {\csuse{@trnslt@word@#2\@trnslt@language{#3}}}%

```

## 5 Implementation

```

337     {}%
338   }}
339
340 % -----
341 % \LoadDictionary and \LoadDictionaryFor
342 \newrobustcmd*\LoadDictionary[1]{%
343   \@trnslt@load@dictionary@for{#1}{\@trnslt@current@language}}
344 \@onlypreamble\LoadDictionary
345
346 \newrobustcmd*\LoadDictionaryFor[2]{%
347   \@trnslt@load@dictionary@for{#2}{#1}}
348 \@onlypreamble\LoadDictionaryFor
349
350 % #1: name
351 % #2: lang
352 \def\@trnslt@load@dictionary@for#1#2{%
353   \AtBeginDocument{%
354     \InputIfFileExists{#1-\@trnslt@language{#2}.trsl}
355     {\@trnslt@check@dictionary{#1}{#2}}
356     {\@trnslt@warning{dictionary file `#1-\@trnslt@language{#2}.trsl' not
357       found.}}}%
358   }}
359
360 \def\@trnslt@check@dictionary#1#2{%
361   \AfterFile{#1-\@trnslt@language{#2}.trsl}
362   {%
363     \ifcsdef{\@trnslt@dictionary@#1\@trnslt@language{#2}}
364     {\@trnslt@info{loading dictionary `#1' for `#2'.}}
365     {%
366       \@trnslt@warning{file `#1-\@trnslt@language{#2}.trsl' does not
367         appear to be a dictionary}%
368     }%
369   }%
370 }
371
372 \def\@trnslt@load@dictionary@silent@for#1#2{%
373   \AtBeginDocument{\InputIfFileExists{#1-\@trnslt@language{#2}.trsl}{}}{}%
374
375 \newrobustcmd*\ProvideDictionaryFor[2]{%
376   \@trnslt@provide@dictionary@for{#1}{#2}}
377 \@onlypreamble\ProvideDictionaryFor
378
379 \def\@trnslt@provide@dictionary@for#1#2{%
380   \def\@trnslt@dictionary@name{#2}%
381   \edef\@trnslt@dictionary@lang{\@trnslt@language{#1}}%
382   % this macro can be used to check if we have a dictionary and will also be
383   % used as a list for the dictionary entries:
384   \csdef{\@trnslt@dictionary@\@trnslt@dictionary@name @\@trnslt@dictionary@lang}{}%
385   \ifnextchar[
386     {\@trnslt@provide@dictionary@version}
387     {
388       \ProvidesFile

```



## 5 Implementation

```

389         {\@trnslt@dictionary@lang.trsl}%
390         [(\@trnslt@dictionary@lang\space translation file `#2')]
391     }%
392 }
393
394 \def\@trnslt@provide@dictionary@version[#1]{%
395     \ProvidesFile
396     {\@trnslt@dictionary@name-\@trnslt@dictionary@lang.trsl}%
397     [(\@trnslt@dictionary@lang\space translation file \@trnslt@dictionary@name') #1]}
398
399 % \@trnslt@dictionary@language
400 \newrobustcmd*\DeclareDictTranslation[2]{%
401     \listcsadd
402     {\@trnslt@dictionary@\@trnslt@dictionary@name \@trnslt@dictionary@lang}
403     {{#1}{#2}}}%
404     \@trnslt@declare@translation{#1}{\@trnslt@dictionary@lang}{#2}%
405 }
406 \@onlypreamble\DeclareDictTranslation
407
408 % \PrintDictionaryFor
409 % #1: lang
410 % #2: name
411 % #3: pre
412 % #4: mid
413 % #5: post
414 \newcommand*\PrintDictionaryFor[5]{%
415     \@trnslt@print@dictionary@for{#1}{#2}{#3}{#4}{#5}}
416
417 % #1: lang
418 % #2: name
419 % #3: pre
420 % #4: mid
421 % #5: post
422 \def\@trnslt@print@dictionary@for#1#2#3#4#5{%
423     \forlistcsloop
424     {\@trnslt@print@dictionary@entry{#3}{#4}{#5}}
425     {\@trnslt@dictionary@#2@\@trnslt@language{#1}}}%
426 }
427
428 % #1: pre
429 % #2: mid
430 % #3: post
431 % #4: {key}{translation}
432 \def\@trnslt@print@dictionary@entry#1#2#3#4{%
433     \@trnslt@print@dictionary@entry@aux{#1}{#2}{#3}{#4}}
434
435 % #1: pre
436 % #2: mid
437 % #3: post
438 % #4: key
439 % #5: translation
440 \def\@trnslt@print@dictionary@entry@aux#1#2#3#4#5{#1#4#2#5#3}

```

## 5 Implementation

```
441
442 % -----
443 % predefined languages
444 \DeclareLanguage{albanian}
445 \DeclareLanguage{bulgarian}
446 \DeclareLanguage{catalan}
447 \DeclareLanguage{croatian}
448 \DeclareLanguage{czech}
449 \DeclareLanguage{danish}
450 \DeclareLanguage{dutch}
451 \DeclareLanguage{english}
452 \DeclareLanguage{finnish}
453 \DeclareLanguage{french}
454 \DeclareLanguage{german}
455 \DeclareLanguage{greek}
456 \DeclareLanguage{hebrew}
457 \DeclareLanguage{hungarian}
458 \DeclareLanguage{icelandic}
459 \DeclareLanguage{italian}
460 \DeclareLanguage{norwegian}
461 \DeclareLanguage{polish}
462 \DeclareLanguage{portuges}
463 \DeclareLanguage{romanian}
464 \DeclareLanguage{russian}
465 \DeclareLanguage{serbocroatian}
466 \DeclareLanguage{slovak}
467 \DeclareLanguage{slovenian}
468 \DeclareLanguage{spanish}
469 \DeclareLanguage{swedish}
470 \DeclareLanguage{turkish}
471 \DeclareLanguage{ukrainian}
472
473 % -----
474 % aliases and dialects:
475 \DeclareLanguageAlias {Albanian}{albanian}
476 \DeclareLanguageAlias {Bulgarian}{bulgarian}
477 \DeclareLanguageAlias {Catalan}{catalan}
478 \DeclareLanguageAlias {Croatian}{croatian}
479 \DeclareLanguageAlias {Czech}{czech}
480 \DeclareLanguageAlias {Danish}{danish}
481 \DeclareLanguageAlias {Dutch}{dutch}
482 \DeclareLanguageAlias {Finnish}{finnish}
483 \DeclareLanguageAlias {français}{french}
484 \DeclareLanguageAlias {Français}{français}
485 \DeclareLanguageDialect{canadien}{french}
486 \DeclareLanguageAlias {Canadien}{canadien}
487 \DeclareLanguageAlias {French}{french}
488 \DeclareLanguageDialect{american}{english}
489 \DeclareLanguageAlias {American}{american}
490 \DeclareLanguageDialect{australian}{english}
491 \DeclareLanguageAlias {Australian}{australian}
492 \DeclareLanguageDialect{british}{english}
```

## 5 Implementation

```
493 \DeclareLanguageAlias {British}{british}
494 \DeclareLanguageDialect{canadian}{english}
495 \DeclareLanguageAlias {Canadian}{canadian}
496 \DeclareLanguageAlias {English}{english}
497 \DeclareLanguageAlias {UKenglish}{british}
498 \DeclareLanguageAlias {USenglish}{american}
499 \DeclareLanguageDialect{austrian}{german}
500 \DeclareLanguageAlias {Austrian}{austrian}
501 \DeclareLanguageAlias {German}{german}
502 \DeclareLanguageAlias {germanb}{german}
503 \DeclareLanguageDialect{naustrian}{austrian}
504 \DeclareLanguageAlias {ngerman}{german}
505 \DeclareLanguageAlias {Greek}{greek}
506 \DeclareLanguageAlias {polutonikogreek}{greek}
507 \DeclareLanguageAlias {Hebrew}{hebrew}
508 \DeclareLanguageAlias {Hungarian}{hungarian}
509 \DeclareLanguageDialect{magyar}{hungarian}
510 \DeclareLanguageAlias {Magyar}{magyar}
511 \DeclareLanguageAlias {Icelandic}{icelandic}
512 \DeclareLanguageAlias {Italian}{italian}
513 \DeclareLanguageAlias {norsk}{norwegian}
514 \DeclareLanguageAlias {Norsk}{norsk}
515 \DeclareLanguageAlias {Norwegian}{norwegian}
516 \DeclareLanguageAlias {nynorsk}{norwegian}
517 \DeclareLanguageAlias {Nynorsk}{nynorsk}
518 \DeclareLanguageAlias {Polish}{polish}
519 \DeclareLanguageDialect{brazil}{portuges}
520 \DeclareLanguageAlias {Brazil}{brazil}
521 \DeclareLanguageAlias {brazilian}{brazil}
522 \DeclareLanguageAlias {Brazilian}{brazilian}
523 \DeclareLanguageAlias {Portuges}{portuges}
524 \DeclareLanguageAlias {portuguese}{portuges}
525 \DeclareLanguageAlias {Portuguese}{portuguese}
526 \DeclareLanguageAlias {Romanian}{romanian}
527 \DeclareLanguageAlias {Russian}{russian}
528 \DeclareLanguageAlias {Serbocroatian}{serbocroatian}
529 \DeclareLanguageAlias {Slovak}{slovak}
530 \DeclareLanguageAlias {Slovenian}{slovenian}
531 \DeclareLanguageAlias {Spanish}{spanish}
532 \DeclareLanguageAlias {Swedish}{swedish}
533 \DeclareLanguageDialect{swissgerman}{german}
534 % this maybe should be a language of it's own:
535 \DeclareLanguageAlias {Swiss}{swissgerman}
536 \DeclareLanguageAlias {Swissgerman}{swissgerman}
537 \DeclareLanguageAlias {Turkish}{turkish}
538 \DeclareLanguageAlias {Ukrainian}{ukrainian}
539
540 % -----
541 % load basic dictionary if available
542 \AtBeginDocument{%
543   \@trnslt@load@dictionary@silent@for
544   {translations-basic-dictionary}
```

## 5 Implementation

```
545     {\@trnslt@current@language}%
546 }
547
548 \endinput
549
550 % -----
551 % HISTORY:
552 2012/09/30 v0.2beta - first version (as part of the `exsheets' bundle)
553 2012/10/05 v0.2     - \LoadDictionary and \LoadDictionaryFor added and loads of
554                     languages defined.
555 2013/03/10 v0.8     - basic dictionaries for English, German, French and Spanish
556                     - new command \DeclareDictTranslation
557 2013/04/04 v0.8a    - bug fix in \DeclareDictTranslation
558 2013/04/07 v0.9     - slightly improved messages
559 2013/04/08 v0.9a    - changed fallback warning into info
560                     - synchronized version number with `exsheets' until now but
561                     won't any more
562 2013/06/22 v0.9b    - added Swiss
563 2013/06/28 v0.10    - declaring aliases of dialects now works as expected
564                     - declarings dialects of an alias now correctly declares
565                     the dialect to the correct base language
566                     - corrected a few erroneous language declarations
567 2013/07/12 v0.10a   - \GetTranslation gets two-folded fallback: use
568                     fallback-translation if no translation for the current
569                     language has been defined; use literal string if /no/
570                     language is used - this should never happen but /will/
571                     happen if neither `babel' nor `polyglossia' have been
572                     loaded, i.e., no language has been chosen /and/ the
573                     package writer did not provide an English translation
574 2013/07/15 v1.0     - removed from `exsheets' bundle - `translations' should
575                     be a package of it's own
576                     - load basic dictionary automatically if available
577                     - rudimentary check in \LoadDictionary if loaded file is a
578                     dictionary
579                     - new command \PrintDictionaryFor
```

# Index

Section titles are indicated **bold**, packages sans serif and commands \brown.

|                             |          |                        |   |
|-----------------------------|----------|------------------------|---|
| <b>B</b>                    |          |                        |   |
| babel                       | 1 ff., 5 |                        |   |
| beamer                      | 1        |                        |   |
| <b>C</b>                    |          |                        |   |
| \captions<language>         | 1        |                        |   |
| <b>D</b>                    |          |                        |   |
| \DeclareDictTranslation     | 3        |                        |   |
| \DeclareLanguage            | 2 f.     |                        |   |
| \DeclareLanguageAlias       | 2        |                        |   |
| \DeclareLanguageDialect     | 2        |                        |   |
| \DeclareTranslation         | 2, 4     |                        |   |
| \DeclareTranslationFallback | 2, 5     |                        |   |
| <b>Dictionaries</b>         | 5–8      |                        |   |
| basic                       | 6        |                        |   |
| own                         | 5        |                        |   |
| <b>E</b>                    |          |                        |   |
| etoolbox                    | 2        |                        |   |
| <b>G</b>                    |          |                        |   |
| \GetTranslation             | 2        |                        |   |
|                             |          | \GetTranslationFor     | 2 |
|                             |          | \GetTranslationForWarn | 3 |
|                             |          | \GetTranslationWarn    | 3 |
| <b>I</b>                    |          |                        |   |
| <b>Implementation</b>       | 10       |                        |   |
| <b>L</b>                    |          |                        |   |
| <b>Languages</b>            | 8 f.     |                        |   |
| \LoadDictionary             | 3        |                        |   |
| \LoadDictionaryFor          | 3        |                        |   |
| <b>M</b>                    |          |                        |   |
| <b>Motivation</b>           | 1        |                        |   |
| <b>N</b>                    |          |                        |   |
| \NewTranslation             | 2        |                        |   |
| <b>P</b>                    |          |                        |   |
| polyglossia                 | 1, 5     |                        |   |
| \PrintDictionaryFor         | 3        |                        |   |
| \providecaptionname         | 1        |                        |   |
| \ProvideDictionaryFor       | 3        |                        |   |
| <b>R</b>                    |          |                        |   |
| \RenewTranslation           | 2        |                        |   |
| <b>Requirements</b>         | 2        |                        |   |
| <b>S</b>                    |          |                        |   |
| \SaveTranslation            | 3        |                        |   |
| \SaveTranslationFor         | 3        |                        |   |
| scrfile                     | 2        |                        |   |
| <b>T</b>                    |          |                        |   |
| \translate                  | 1        |                        |   |
| translator                  | 1        |                        |   |
| <b>U</b>                    |          |                        |   |
| <b>Usage</b>                | 2–8      |                        |   |
| Commands                    | 2        |                        |   |
| Dictionaries                | 5        |                        |   |
| Example                     | 3        |                        |   |
| Packages                    | 4        |                        |   |
| fallback                    | 5        |                        |   |
| structure                   | 4        |                        |   |