

Transactions - 2

TABLE OF CONTENTS

1. Read Uncommitted
2. Read Committed
3. Repeatable Reads
4. Serialisable
5. Deadlocks



Notes

* 31st Hard day :

- A quick revision of session
- Assignment (MCQ)
- Revision / backlog



Isolation Levels


Isolation have different levels (4)

1. **Read Uncommitted**
2. **Read Committed**
3. **Repeatable Read**
4. **Serialisable**



1. Read Uncommitted


- It allows a transaction to read uncommitted data from other transaction running at the same time.
- Reads the latest data. (Committed / Uncommitted)





2. Read Committed

- It ensures that we read only committed data. (Latest committed data)



* Pros :

- We don't have dirty reads.

* Cons :

- Might not be efficient
- Non-Repeatable Read



Users

id	name	psp	mail_sent
1	A	75	F T
2	B	85	F
3	C	84 79	F T
4	D	98	F

- Send mail to learners $psp < 80$

Steps :


1. Get data of users having $psp < 80$ (A)
2. Send e-mails. (5 mins) (A)
3. Update email_sent col^m. (if $psp < 80 \rightarrow T$) (A, C)

When a transaction reads the same data of some row with different value \rightarrow Non-Repeatable Read.



3. Repeatable Reads (Default in MySQL)

- For first read in a transaction it reads latest committed value of current row.
- After that in the same transaction it will read the same value.



Advantage :

- We don't have non-repeatable read issue here.


Disadvantage :

→ 'Phantom Read'

- * If a new entry is added in the table during the transaction & we perform some update operation on this new entry then this row magically gets read resulting in Phantom Read.



4. Serializable



 $A \longrightarrow B$ `bank_transfer (A, B, 500) {` $A \longrightarrow X \text{ (1000)}$ `If (X >= 500)` $A \longleftarrow X - 500$ $B \longrightarrow X \text{ (5000)} \rightarrow \text{lock } \updownarrow$ $B \longleftarrow 5000 + 500$ $B \longleftarrow 5500$ `Commit;` $C \longrightarrow B$ `bank_transfer (C, B, 10000) {` $C \longrightarrow X \text{ (15,000)}$ `If (X >= 10000)` $C \longleftarrow X - 10000$ $B \longrightarrow X \text{ (5500)}$ $B \longleftarrow 5500 + 10000$ $B \longleftarrow 15500$ `Commit;`

	Initial		final
A	1000		500
B	5000		15500
C	<u>15000</u>		<u>5000</u>
	21,000	😊	21,000



Deadlock

