

A modern conference room with large windows and a long table. The room is empty, with several chairs arranged around the table. The view outside the windows shows a cityscape. The image has a blue tint and a stylized, torn-paper-like border.

Introduction to Aggregate Functions

Introduction to Aggregate Functions

aggregate functions

they are applied on *multiple rows* of *a single column* of a table and *return* an output of *a single value*

Introduction to Aggregate Functions



COUNT()

Introduction to Aggregate Functions

COUNT()

counts the number of non-null records in a field

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

sums all the non-null values in a column

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

sums all the non-null values in a column

- **MIN()**

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

sums all the non-null values in a column

- **MIN()**

returns the minimum value from the entire list

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

sums all the non-null values in a column

- **MIN()**

returns the minimum value from the entire list

- **MAX()**

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

sums all the non-null values in a column

- **MIN()**

returns the minimum value from the entire list

- **MAX()**

returns the maximum value from the entire list

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

sums all the non-null values in a column

- **MIN()**

returns the minimum value from the entire list

- **MAX()**

returns the maximum value from the entire list

- **AVG()**

Introduction to Aggregate Functions

- **COUNT()**

counts the number of non-null records in a field

- **SUM()**

sums all the non-null values in a column

- **MIN()**

returns the minimum value from the entire list

- **MAX()**

returns the maximum value from the entire list

- **AVG()**

calculates the average of all non-null values belonging to a certain column of a table

Introduction to Aggregate Functions

COUNT()

counts the number of non-null records in a field

Introduction to Aggregate Functions

COUNT()

counts the number of non-null records in a field

- it is frequently used in combination with the reserved word “DISTINCT”

Introduction to Aggregate Functions

COUNT()



SQL

```
SELECT COUNT(column_name)
FROM table_name;
```

Introduction to Aggregate Functions

COUNT()



SQL

```
SELECT COUNT(column_name)  
FROM table_name;
```

the parentheses after COUNT() must start right after the keyword, not after a whitespace

Introduction to Aggregate Functions

COUNT(DISTINCT)



SQL

```
SELECT COUNT(DISTINCT column_name)
FROM table_name;
```

Introduction to Aggregate Functions

aggregate functions

they are applied on *multiple rows* of *a single column* of a table and *return* an output of *a single value*

- they ignore NULL values unless told not to