



So far:

#### So far:

- Theory of Relational Databases
- SQL Theory
- Creating SQL Databases and Tables
- Creating SQL Constraints

#### So far:

- Theory of Relational Databases
- SQL Theory
- Creating SQL Databases and Tables
- Creating SQL Constraints

#### In this section:

#### So far:

- Theory of Relational Databases
- SQL Theory
- Creating SQL Databases and Tables
- Creating SQL Constraints

#### In this section:

- Data Manipulation

the **SELECT** statement

the <u>SELECT</u> statement
allows you to extract a fraction of the entire data set

- the <u>SELECT</u> statement
  allows you to extract a fraction of the entire data set
- used to retrieve data from database objects, like tables

- the <u>SELECT</u> statement
  allows you to extract a fraction of the entire data set
- used to retrieve data from database objects, like tables
- used to "query data from a database"



SELECT column\_1, column\_2,... column\_n
FROM table\_name;



```
SELECT column_1, column_2,... column_n
FROM table_name;
```

- when extracting information, SELECT goes with FROM



SELECT column\_1, column\_2,... column\_n
FROM table\_name;

```
SELECT column_1, column_2,... column_n

FROM table_name;

SELECT first_name, last_name

FROM employees;
```



SELECT \* FROM employees;

\* - a wildcard character, means "all" and "everything"