Extending SDN to the Data Plane

Anirudh Sivaraman, Keith Winstein, Suvinay Subramanian,
Hari Balakrishnan

M.I.T.

http://web.mit.edu/anirudh/www/sdn-data-plane.html

November 7, 2013

Switch Data Planes today

Two key decisions on a per-packet basis:

- Scheduling: Which packet should be transmitted next?
- Queue Management: How long can queues grow? Which packet to drop?

The Data Plane is continuously evolving

- The long lineage of in-network algorithms:



- Each scheme wins in its own evaluation.

- Some believe in a "silver bullet" knobless in-network method.

We disagree: There is no silver bullet!

- Different applications care about different objectives.
- Applications use different transport protocols.
- Networks are heterogeneous.

Early symptoms

- Hard to configure wired AQM for wireless links
- Several distinct point solutions for datacenters
  - DCTCP, HULL, D3, DeTail, PDQ, pFabric
- No consensus on the "right metric"
  - Minimizing missed deadlines
  - Flow Completion Time
  - Latency
  - Throughput
  - Tail Latency
  - ...

Quantifying "No Silver Bullet": Network Configurations

Configuration	Description
CoDel+FCFS	One shared FCFS queue with CoDel
CoDel+FQ	Per-flow fair queueing with CoDel on each queue
Bufferbloat+FQ	Per-flow fair queueing with deep buffers on each queue

Quantifying "No Silver Bullet": Workloads and Objectives

Workload	**Description**	**Objective**
Bulk	Long-running TCP flow	Maximize throughput
Web	Switched TCP flow with ON and OFF periods	Minimize 99.9 %ile flow completion time
Interactive	Long-running real-time streaming app	Maximize $\frac{\text{throughput}}{\text{delay}}$, i.e., "power"

Quantifying "No Silver Bullet"



Quantifying "No Silver Bullet"



Quantifying "No Silver Bullet"



Quantifying "No Silver Bullet"



Quantifying "No Silver Bullet"



Quantifying "No Silver Bullet"



Quantifying "No Silver Bullet"



Why is no single data plane configuration the best?

- Bufferbloat on variable-rate links helps throughput!
  - Variable-rate links have an inherent delay-throughput tradeoff
- FCFS is preferable to Fair Queuing in some cases
  - When equally aggressive flows compete, they don't need protection from each other
  - Helps reduce tail packet delay
- Fair Queuing is required in some cases
  - When competing flows aren't equally aggressive, isolation helps

So what should the network designer do?

Architect a flexible data plane

- Programmable queue management and scheduling
- Not just for selecting among pre-built choices, but to change behavior in the field
- Because there is no silver bullet and innovation will continue!

Controlled flexibility: Want performance, security

(Or, why this isn't the same as "active networks")

- Provide interfaces only to the head and tail of queues
- Operators specify only queue-management/scheduling logic
- No access to packet payloads (for now)

Building such a data plane in four parts

- Hardware gadgets
  - Random number generators (RED, BLUE)
  - Binary tree of comparators (pFabric, SRPT)
- I/O interfaces
  - Drop/mark head/tail of queue
  - Interrupts for enqueue/dequeue
- State maintenance
  - Per-flow (WFQ, DRR)
  - Per-dst address (PF)
- A domain-specific instruction set
  - Expresses control flow
  - Implements new functions unavailable in hardware

Feasibility study: CoDel

Synthesis numbers on Xilinx Kintex-7:

Resource	**Usage**	**Fraction of FPGA**
Slice logic	1,256	1%
Slice logic dist.	1,975	2%
IO/GTX ports	27	2%
DSP slices	0	0%
Maximum speed	12.9 $\times 10^6$ pkts/s ~10gbps	

- Small fraction of the FPGA's resources.
- Can be improved by pipelining or parallelizing.

Conclusion

- There is no silver bullet to in-network resource control because of application and network diversity
- Algorithms will continue to evolve: the data plane should help
- Directions to reproduce results: http://web.mit.edu/anirudh/www/sdn-data-plane.html

Limitations and Practical Considerations:

- Cannot express several network functions that need payloads.
- How do applications signal objectives to the network?
- Feasibility at 10G on high port-density switches.
- Mechanism to map flows onto per-port queues.
- Energy and Area overheads.