

Neural Nets

Brain Computer Interaction- S2022


Acknowledgements: berkeley.edu

Feature Vectors


 x $f(x)$ y

Hello,

Do you want free printer
cartridges? Why pay more
when you can get them
ABSOLUTELY FREE! Just




# free	: 2
YOUR_NAME	: 0
MISSPELLED	: 2
FROM_FRIEND	: 0
...	




SPAM
or
+

2





PIXEL-7,12	: 1
PIXEL-7,13	: 0
...	
NUM_LOOPS	: 1
...	



"2"

Some (Simplified) Biology

- Very loose inspiration: human neurons




Linear Classifiers

- Inputs are **feature values**
- Each feature has a **weight**
- Sum is the **activation**


$$\text{activation}_w(x) = \sum_i w_i \cdot f_i(x) = w \cdot f(x)$$

- If the activation is:
 - Positive, output +1
 - Negative, output -1



Weights

- Binary case: compare features to a weight vector
- Learning: figure out the weight vector from examples





Binary Decision Rule

- In the space of feature vectors
 - Examples are points
 - Any weight vector is a hyperplane
 - One side corresponds to $Y=+1$
 - Other corresponds to $Y=-1$




w

BIAS	:	-3
free	:	4
money	:	2
...		



Learning: Binary Perceptron

- Start with weights = 0
- For each training instance:
 - Classify with current weights
- If correct (i.e., $y=y^*$), no change!
- If wrong: adjust the weight vector




Learning: Binary Perceptron

- Start with weights = 0
- For each training instance:
 - Classify with current weights

$$y = \begin{cases} +1 & \text{if } w \cdot f(x) \geq 0 \\ -1 & \text{if } w \cdot f(x) < 0 \end{cases}$$


- If correct (i.e., $y=y^*$), no change!
- If wrong: adjust the weight vector by adding or subtracting the feature vector. Subtract if y^* is -1.

$$w = w + y^* \cdot f$$



Examples: Perceptron

- Separable Case



Multiclass Decision Rule

- If we have multiple classes:
 - A weight vector for each class:


$$w_y$$

- Score (activation) of a class y:

$$w_y \cdot f(x)$$

- Prediction highest score wins

$$y = \arg \max_y w_y \cdot f(x)$$



Binary = multiclass where the negative class has weight zero

Learning: Multiclass Perceptron


- Start with all weights = 0
- Pick up training examples one by one
- Predict with current weights

$$y = \arg \max_y w_y \cdot f(x)$$

- If correct, no change!
- If wrong: lower score of wrong answer, raise score of right answer

$$w_y = w_y - f(x)$$

$$w_{y^*} = w_{y^*} + f(x)$$




Properties of Perceptrons


- Separability: true if some parameters get the training set perfectly correct
- Convergence: if the training is separable, perceptron will eventually converge (binary case)
- Mistake Bound: the maximum number of mistakes (binary case) related to the *margin* or degree of separability

$$\text{mistakes} < \frac{k}{\delta^2}$$

Separable






Non-Separable




Problems with the Perceptron

- Noise: if the data isn't separable, weights might thrash
 - Averaging weight vectors over time can help (averaged perceptron)
- Mediocre generalization: finds a “barely” separating solution
- Overtraining: test / held-out accuracy usually rises, then falls
 - Overtraining is a kind of overfitting




Non-Separable Case: Deterministic Decision

Even the best linear boundary makes at least one mistake



Non-Separable Case: Probabilistic Decision




How to get probabilistic decisions?

$$z = w \cdot f(x)$$

- Perceptron scoring:
- If $z = w \cdot f(x)$ very positive \rightarrow want probability going to 1
- If $z = w \cdot f(x)$ very negative \rightarrow want probability going to 0

- Sigmoid function

$$\phi(z) = \frac{1}{1 + e^{-z}}$$



Best w ?

- Maximum likelihood estimation:

$$\max_w ll(w) = \max_w \sum_i \log P(y^{(i)} | x^{(i)}; w)$$



with:

$$P(y^{(i)} = +1 | x^{(i)}; w) = \frac{1}{1 + e^{-w \cdot f(x^{(i)})}}$$



$$P(y^{(i)} = -1 | x^{(i)}; w) = 1 - \frac{1}{1 + e^{-w \cdot f(x^{(i)})}}$$

= Logistic Regression


Separable Case: Deterministic Decision – Many Options



Separable Case: Probabilistic Decision – Clear Preference



A 1D Example




$$P(\text{red}|x) = \frac{e^{w_{\text{red}} \cdot x}}{e^{w_{\text{red}} \cdot x} + e^{w_{\text{blue}} \cdot x}}$$

probability increases exponentially as we move away from boundary

normalizer

The Soft Max



$$P(\text{red}|x) = \frac{e^{w_{\text{red}} \cdot x}}{e^{w_{\text{red}} \cdot x} + e^{w_{\text{blue}} \cdot x}}$$

Multiclass Logistic Regression

- Recall Perceptron:


- A weight vector for each class:

$$w_y$$

- Score (activation) of a class y :

$$w_y \cdot f(x)$$

- Prediction highest score wins $y = \arg \max_y w_y \cdot f(x)$



- How to make the scores into probabilities?

$$\underbrace{z_1, z_2, z_3}_{\text{original activations}} \rightarrow \underbrace{\frac{e^{z_1}}{e^{z_1} + e^{z_2} + e^{z_3}}, \frac{e^{z_2}}{e^{z_1} + e^{z_2} + e^{z_3}}, \frac{e^{z_3}}{e^{z_1} + e^{z_2} + e^{z_3}}}_{\text{softmax activations}}$$

Best w ?

- Maximum likelihood estimation:

$$\max_w ll(w) = \max_w \sum_i \log P(y^{(i)} | x^{(i)}; w)$$

with:

$$P(y^{(i)} | x^{(i)}; w) = \frac{e^{w_{y^{(i)}} \cdot f(x^{(i)})}}{\sum_y e^{w_y \cdot f(x^{(i)})}}$$

= Multi-Class Logistic Regression

- Optimization


- i.e., how do we solve:

$$\max_w ll(w) = \max_w \sum_i \log P(y^{(i)} | x^{(i)}; w)$$

Hill Climbing

- General idea
 - Start wherever
 - Repeat: move to the best neighboring state
 - If no neighbors better than current, quit
- What's particularly tricky when hill-climbing for multiclass logistic regression?
 - Optimization over a continuous space
 - Infinitely many neighbors!
 - How to do this efficiently?

1-D Optimization




- Could evaluate $g(w_0 + h)$
 - Then step in best direction

- Or, evaluate derivative:

$$\frac{\partial g(w_0)}{\partial w} = \lim_{h \rightarrow 0} \frac{g(w_0 + h) - g(w_0 - h)}{2h}$$

- Tells which direction to step into

2-D Optimization



Gradient Ascent

- Perform update in uphill direction for each coordinate
- The steeper the slope (i.e. the higher the derivative) the bigger the step for that coordinate
- E.g., consider: $g(w_1, w_2)$

- Updates:

$$w_1 \leftarrow w_1 + \alpha * \frac{\partial g}{\partial w_1}(w_1, w_2)$$

$$w_2 \leftarrow w_2 + \alpha * \frac{\partial g}{\partial w_2}(w_1, w_2)$$

- Updates in vector notation:


$$w \leftarrow w + \alpha * \nabla_w g(w)$$

$$\text{with: } \nabla_w g(w) = \begin{bmatrix} \frac{\partial g}{\partial w_1}(w) \\ \frac{\partial g}{\partial w_2}(w) \end{bmatrix} = \text{gradient}$$

Gradient Ascent

• Idea:

- Start somewhere
- Repeat: Take a step in the gradient direction



What is the Steepest Direction?

$$\max_{\Delta: \Delta_1^2 + \Delta_2^2 \leq \varepsilon} g(w + \Delta)$$

- First-Order Taylor Expansion:
$$g(w + \Delta) \approx g(w) + \frac{\partial g}{\partial w_1} \Delta_1 + \frac{\partial g}{\partial w_2} \Delta_2$$

- Steepest Ascent Direction:
$$\max_{\Delta: \Delta_1^2 + \Delta_2^2 \leq \varepsilon} g(w) + \frac{\partial g}{\partial w_1} \Delta_1 + \frac{\partial g}{\partial w_2} \Delta_2$$

- Recall:
$$\max_{\Delta: \|\Delta\| \leq \varepsilon} \Delta^\top a \qquad \Delta = \varepsilon \frac{a}{\|a\|}$$

- Hence, solution:
$$\Delta = \varepsilon \frac{\nabla g}{\|\nabla g\|}$$
 Gradient direction = steepest direction!

$$\nabla g = \begin{bmatrix} \frac{\partial g}{\partial w_1} \\ \frac{\partial g}{\partial w_2} \end{bmatrix}$$

Gradient in n dimensions

$$\nabla g = \begin{bmatrix} \frac{\partial g}{\partial w_1} \\ \frac{\partial g}{\partial w_2} \\ \dots \\ \frac{\partial g}{\partial w_n} \end{bmatrix}$$

Optimization Procedure: Gradient Ascent

```
• init  $w$   
• for iter = 1, 2, ...  
  
   $w \leftarrow w + \alpha * \nabla g(w)$ 
```

- α : learning rate --- tweaking parameter that needs to be chosen carefully
- How? Try multiple choices
 - Crude rule of thumb: update changes w about 0.1 – 1 %

Batch Gradient Ascent on the Log Likelihood Objective

$$\max_w ll(w) = \max_w \underbrace{\sum_i \log P(y^{(i)} | x^{(i)}; w)}_{g(w)}$$

- init w
- for iter = 1, 2, ...

$$w \leftarrow w + \alpha * \sum_i \nabla \log P(y^{(i)} | x^{(i)}; w)$$

What will gradient ascent do?

$$w \leftarrow w + \alpha * \sum_i \nabla \log P(y^{(i)} | x^{(i)}; w)$$

$$P(y^{(i)} | x^{(i)}; w) = \frac{e^{w_{y^{(i)}} \cdot f(x^{(i)})}}{\sum_y e^{w_y \cdot f(x^{(i)})}}$$

$$\nabla w_{y^{(i)}} f(x^{(i)}) - \nabla \log \sum_y e^{w_y f(x^{(i)})}$$

adds to the correct
class weights

$$\frac{1}{\sum_y e^{w_y f(x^{(i)})}} \sum_y \left(e^{w_y f(x^{(i)})} [0^T f(x^{(i)})^T 0^T]^T \right)$$

for y' weights: $\frac{1}{\sum_y e^{w_y f(x^{(i)})}} e^{w_{y'} f(x^{(i)})} f(x^{(i)})$

$P(y' | x^{(i)}; w) f(x^{(i)})$ subtracts f from y' weights in proportion to the probability current weights give to y'

Stochastic Gradient Ascent on the Log Likelihood Objective

$$\max_w ll(w) = \max_w \sum_i \log P(y^{(i)} | x^{(i)}; w)$$

Observation: once gradient on one training example has been computed, might as well incorporate before computing next one

- `init w`
- `for iter = 1, 2, ...`
 - `pick random j`

$$w \leftarrow w + \alpha * \nabla \log P(y^{(j)} | x^{(j)}; w)$$

Mini-Batch Gradient Ascent on the Log Likelihood Objective

$$\max_w ll(w) = \max_w \sum_i \log P(y^{(i)} | x^{(i)}; w)$$


Observation: gradient over small set of training examples (=mini-batch) can be computed in parallel, might as well do that instead of a single one

- `init w`
- `for iter = 1, 2, ...`
 - `pick random subset of training examples J`


$$w \leftarrow w + \alpha * \sum_{j \in J} \nabla \log P(y^{(j)} | x^{(j)}; w)$$

Multi-class Logistic Regression


- = special case of neural network




Deep Neural Network = Also learn the features!



Deep Neural Network = Also learn the features!




...




$$z_i^{(k)} = g\left(\sum_j W_{i,j}^{(k-1,k)} z_j^{(k-1)}\right)$$

g = nonlinear activation function

Deep Neural Network = Also learn the features!



...




$$z_i^{(k)} = g\left(\sum_j W_{i,j}^{(k-1,k)} z_j^{(k-1)}\right)$$

g = nonlinear activation function

Common Activation Functions


Sigmoid Function



$$g(z) = \frac{1}{1 + e^{-z}}$$

$$g'(z) = g(z)(1 - g(z))$$


Hyperbolic Tangent



$$g(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

$$g'(z) = 1 - g(z)^2$$

Rectified Linear Unit (ReLU)



$$g(z) = \max(0, z)$$

$$g'(z) = \begin{cases} 1, & z > 0 \\ 0, & \text{otherwise} \end{cases}$$

Deep Neural Network: Also Learn the Features!

- Training the deep neural network is just like logistic regression:
just w tends to be a much, much larger vector 😊

$$\max_w ll(w) = \max_w \sum_i \log P(y^{(i)} | x^{(i)}; w)$$

→ just run gradient ascent

+ stop when log likelihood of hold-out data starts to decrease

Neural Networks Properties

- Theorem (Universal Function Approximators). A two-layer neural network with a sufficient number of neurons can approximate any continuous function to any desired accuracy.
- Practical considerations
 - Can be seen as learning the features
 - Large number of neurons
 - Danger for overfitting
 - (hence early stopping!)

Universal Function Approximation Theorem*

Hornik theorem 1: Whenever the activation function is *bounded and nonconstant*, then, for any finite measure μ , standard multilayer feedforward networks can approximate any function in $L^p(\mu)$ (the space of all functions on R^k such that $\int_{R^k} |f(x)|^p d\mu(x) < \infty$) arbitrarily well, provided that sufficiently many hidden units are available.

Hornik theorem 2: Whenever the activation function is *continuous, bounded and non-constant*, then, for arbitrary compact subsets $X \subseteq R^k$, standard multilayer feedforward networks can approximate any continuous function on X arbitrarily well with respect to uniform distance, provided that sufficiently many hidden units are available.

- In words: Given any continuous function $f(x)$, if a 2-layer neural network has enough hidden units, then there is a choice of weights that allow it to closely approximate $f(x)$.

Cybenko (1989) "Approximations by superpositions of sigmoidal functions"

Hornik (1991) "Approximation Capabilities of Multilayer Feedforward Networks"

Leshno and Schocken (1991) "Multilayer Feedforward Networks with Non-Polynomial Activation Functions Can Approximate Any Function"

Universal Function Approximation Theorem*

Math. Control Signals Systems (1989) 2: 303–314

Mathematics of Control,
Signals, and Systems
© 1989 Springer-Verlag New York Inc.

Approximation by Superpositions of a Sigmoidal Function*

G. Cybenko†

Abstract. In this paper we demonstrate that finite linear combinations of compositions of a fixed, univariate function and a set of affine functionals can uniformly approximate any continuous function of n real variables with support in the unit hypercube; only mild conditions are imposed on the univariate function. Our results settle an open question about representability in the class of single hidden layer neural networks. In particular, we show that arbitrary decision regions can be arbitrarily well approximated by continuous feedforward neural networks with only a single internal, hidden layer and any continuous sigmoidal nonlinearity. The paper discusses approximation properties of other possible types of nonlinearities that might be implemented by artificial neural networks.

Key words. Neural networks, Approximation, Completeness.

1. Introduction

A number of diverse application areas are concerned with the representation of general functions of an n -dimensional real variable, $x \in \mathbb{R}^n$, by finite linear combinations of the form

$$\sum_{j=1}^N \alpha_j \sigma(y_j^T x + \theta_j), \quad (1)$$

where $y_j \in \mathbb{R}^n$ and $\alpha_j, \theta_j \in \mathbb{R}$ are fixed. (y^T is the transpose of y so that $y^T x$ is the inner product of y and x .) Here the univariate function σ depends heavily on the context of the application. Our major concern is with so-called sigmoidal σ 's:

$$\sigma(t) \rightarrow \begin{cases} 1 & \text{as } t \rightarrow +\infty, \\ 0 & \text{as } t \rightarrow -\infty. \end{cases}$$

Such functions arise naturally in neural network theory as the activation function of a neural node (or unit as is becoming the preferred term) [L1], [RHM]. The main result of this paper is a demonstration of the fact that sums of the form (1) are dense in the space of continuous functions on the unit cube if σ is any continuous sigmoidal

* Date received: October 21, 1988. Date revised: February 17, 1989. This research was supported in part by NSF Grant DCR-8619103, ONR Contract N000-86-G-0202 and DOE Grant DE-FG02-85ER25001.

† Center for Supercomputing Research and Development and Department of Electrical and Computer Engineering, University of Illinois, Urbana, Illinois 61801, U.S.A.

Neural Networks, Vol. 4, pp. 251–257, 1991
Printed in the USA. All rights reserved.

0893-6080/91 \$3.00 + .00
Copyright © 1991 Pergamon Press plc

ORIGINAL CONTRIBUTION

Approximation Capabilities of Multilayer Feedforward Networks

KURT HORNIK

Technische Universität Wien, Vienna, Austria

(Received 30 January 1990; revised and accepted 25 October 1990)

Abstract.—We show that standard multilayer feedforward networks with as few as a single hidden layer and arbitrary bounded and nonconstant activation function are universal approximators with respect to $L^p(\mu)$ performance criteria, for arbitrary finite input environment measures μ , provided only that sufficiently many hidden units are available. If the activation function is continuous, bounded and nonconstant, then continuous mappings can be learned uniformly over compact input sets. We also give very general conditions ensuring that networks with sufficiently smooth activation functions are capable of arbitrarily accurate approximation to a function and its derivatives.

Keywords.—Multilayer feedforward networks, Activation function, Universal approximation capabilities, Input environment measure, $L^p(\mu)$ approximation, Uniform approximation, Sobolev spaces, Smooth approximation.

1. INTRODUCTION

The approximation capabilities of neural network architectures have recently been investigated by many authors, including Carroll and Dickinson (1989), Cybenko (1989), Funahashi (1989), Gallant and White (1988), Hecht-Nielsen (1989), Hornik, Stinchcombe, and White (1989, 1990), Irie and Miyake (1988), Lapedes and Farber (1988), Stinchcombe and White (1989, 1990). (This list is by no means complete.)

If we think of the network architecture as a rule for computing values at l output units given values at k input units, hence implementing a class of mappings from \mathbb{R}^k to \mathbb{R}^l , we can ask how well arbitrary mappings from \mathbb{R}^k to \mathbb{R}^l can be approximated by the network, in particular, if as many hidden units as required for internal representation and computation may be employed.

How to measure the accuracy of approximation depends on how we measure closeness between functions, which in turn varies significantly with the specific problem to be dealt with. In many applications, it is necessary to have the network perform simultaneously well on all input samples taken from some compact input set X in \mathbb{R}^k . In this case, closeness is

measured by the uniform distance between functions on X , that is,

$$\rho_{\infty}(f, g) = \sup_{x \in X} |f(x) - g(x)|.$$

In other applications, we think of the inputs as random variables and are interested in the average performance where the average is taken with respect to the input environment measure μ , where $\mu(\mathbb{R}^k) < \infty$. In this case, closeness is measured by the $L^p(\mu)$ distances

$$\rho_p(f, g) = \left[\int_X |f(x) - g(x)|^p d\mu(x) \right]^{1/p}.$$

$1 \leq p < \infty$, the most popular choice being $p = 2$, corresponding to mean square error.

Of course, there are many more ways of measuring closeness of functions. In particular, in many applications, it is also necessary that the derivatives of the approximating function implemented by the network closely resemble those of the function to be approximated, up to some order. This issue was first taken up in Hornik et al. (1990), who discuss the sources of need of smooth functional approximation in more detail. Typical examples arise in robotics (learning of smooth movements) and signal processing (analysis of chaotic time series); for a recent application to problems of nonparametric inference in statistics and econometrics, see Gallant and White (1989).

All papers establishing certain approximation ca-

Requests for reprints should be sent to Kurt Hornik, Institut für Statistik und Wahrscheinlichkeitstheorie, Technische Universität Wien, Wiedner Hauptstraße 8-10/107, A-1040 Wien, Austria.

MULTILAYER FEEDFORWARD NETWORKS WITH NON-POLYNOMIAL ACTIVATION FUNCTIONS CAN APPROXIMATE ANY FUNCTION

by

Moshe Leshno
Faculty of Management
Tel Aviv University
Tel Aviv, Israel 69978

and

Shimon Schocken
Leonard N. Stern School of Business
New York University
New York, NY 10003

September 1991

Center for Research on Information Systems
Information Systems Department
Leonard N. Stern School of Business
New York University

Working Paper Series

STERN IS-91-26

Appeared previously as Working Paper No. 21/91 at The Israel Institute Of Business Research

Cybenko (1989) "Approximations by superpositions of sigmoidal functions"
Hornik (1991) "Approximation Capabilities of Multilayer Feedforward Networks"
Leshno and Schocken (1991) "Multilayer Feedforward Networks with Non-Polynomial Activation Functions Can Approximate Any Function"

How about computing all the derivatives?

- Derivatives tables:

$$\frac{d}{dx}(a) = 0$$

$$\frac{d}{dx}(x) = 1$$

$$\frac{d}{dx}(au) = a \frac{du}{dx}$$

$$\frac{d}{dx}(u + v - w) = \frac{du}{dx} + \frac{dv}{dx} - \frac{dw}{dx}$$

$$\frac{d}{dx}(uv) = u \frac{dv}{dx} + v \frac{du}{dx}$$

$$\frac{d}{dx}\left(\frac{u}{v}\right) = \frac{1}{v} \frac{du}{dx} - \frac{u}{v^2} \frac{dv}{dx}$$

$$\frac{d}{dx}(u^n) = nu^{n-1} \frac{du}{dx}$$

$$\frac{d}{dx}(\sqrt{u}) = \frac{1}{2\sqrt{u}} \frac{du}{dx}$$

$$\frac{d}{dx}\left(\frac{1}{u}\right) = -\frac{1}{u^2} \frac{du}{dx}$$

$$\frac{d}{dx}\left(\frac{1}{u^n}\right) = -\frac{n}{u^{n+1}} \frac{du}{dx}$$

$$\frac{d}{dx}[f(u)] = \frac{d}{du}[f(u)] \frac{du}{dx}$$

$$\frac{d}{dx}[\ln u] = \frac{d}{dx}[\log_e u] = \frac{1}{u} \frac{du}{dx}$$

$$\frac{d}{dx}[\log_a u] = \log_a e \frac{1}{u} \frac{du}{dx}$$

$$\frac{d}{dx}e^u = e^u \frac{du}{dx}$$

$$\frac{d}{dx}a^u = a^u \ln a \frac{du}{dx}$$

$$\frac{d}{dx}(u^v) = vu^{v-1} \frac{du}{dx} + \ln u \cdot u^v \frac{dv}{dx}$$

$$\frac{d}{dx} \sin u = \cos u \frac{du}{dx}$$

$$\frac{d}{dx} \cos u = -\sin u \frac{du}{dx}$$

$$\frac{d}{dx} \tan u = \sec^2 u \frac{du}{dx}$$

$$\frac{d}{dx} \cot u = -\csc^2 u \frac{du}{dx}$$

$$\frac{d}{dx} \sec u = \sec u \tan u \frac{du}{dx}$$

$$\frac{d}{dx} \csc u = -\csc u \cot u \frac{du}{dx}$$

How about computing all the derivatives?

- But neural net f is never one of those?
 - No problem: CHAIN RULE:

If $f(x) = g(h(x))$


Then $f'(x) = g'(h(x))h'(x)$

→ Derivatives can be computed by following well-defined procedures

Automatic Differentiation

- Automatic differentiation software
 - e.g. PyTorch, TensorFlow, JAX
 - Only need to program the function $g(x,y,w)$
 - Can automatically compute all derivatives w.r.t. all entries in w
 - This is typically done by caching info during forward computation pass of f , and then doing a backward pass = “backpropagation”
 - Autodiff / Backpropagation can often be done at computational cost comparable to the forward pass

Training a Network (setting weights)




$$z_i^{(k)} = g\left(\sum_j W_{i,j}^{(k-1,k)} z_j^{(k-1)}\right)$$

g = nonlinear activation function

Training a Network

Key words:

- Forward
- Backwards
- Gradient
- Backprop




g = nonlinear activation function

Back Propagation:

- Suppose we have g and want the gradient at
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$ and $\frac{\partial g}{\partial w_2}$.


• ,



Back Propagation:

- Suppose we have g and want the gradient at
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$ and $\frac{\partial g}{\partial w_2}$.


• ,



Back Propagation:

- Suppose we have g and want the gradient at
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$ and $\frac{\partial g}{\partial w_2}$.


• ,



Back Propagation:

- Suppose we have g and want the gradient at w_1
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$


• ,



Back Propagation:

- Suppose we have g and want the gradient at w_1
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$


• ,



Back Propagation:

- Suppose we have g and want the gradient at w_1
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$

• ,




Interpretation: A tiny increase in w_1 will result in an approximately increase in g due to this cube function.

Back Propagation:

- Suppose we have g and want the gradient at $\frac{\partial g}{\partial w_1}$
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$ and $\frac{\partial g}{\partial w_2}$.

• ,




Hint: may be useful.

Back Propagation:

- Suppose we have g and want the gradient at w_1
- Think of the function as a composition of many functions.
 - Can use derivative chain rule to compute $\frac{\partial g}{\partial w_1}$


• ,



Back Propagation:

- Suppose we have and want the gradient at
- Think of the function as a composition of many functions, use chain rule.

• ,




How do we reconcile this seeming contradiction?
 Top partial derivative means cube function contributes
 and bottom p.d. means product contributes so add
 them.

Back Propagation:

- Suppose we have g and want the gradient at
- Think of the function as a composition of many functions, use chain rule.

• ,



$$\nabla g = \left[\frac{\partial g}{\partial w_1}, \frac{\partial g}{\partial w_2} \right] = [39, 8]$$