

Betatron tune measurement in the LHC damper using GPU

Frédéric Dubouchet

January 8, 2013

Abstract

This paper describes the betatron tune measurement in the Large Hadron Collider (LHC) at the European organization for nuclear research (CERN) including the present hardware and the future possible implementations using the Accelerating Damper Transverse (ADT) acquisitions. The ADT data have to be processed to be able to extract the betatron tune. This paper studies the use of Graphic Processing Units (GPUs) to process bunch position acquisition data.

Acknowledgements

Thanks everyone from CERN and from Heppia (TODO).

Contents

Acknowledgements	1
1 Introduction	6
1.1 State of knowledge	6
1.2 Tune measurement in the LHC	6
1.3 Proposed system	7
1.3.1 DSP on VME board	7
1.3.2 FPGA pre-processing on VME board	7
1.3.3 GPU off-board computing	7
1.4 Problem definition	8
1.4.1 Algorithm	8
1.4.2 Hardware	8
1.4.3 Timing	8
2 Results	9
2.1 Implemented System	9
2.2 Notch filter	9
2.3 FFT	9
2.3.1 FFTW	9
2.3.2 FFT with OpenCL on GPU	9
2.3.3 FFT with OpenCL on CPU	9
2.4 Amplitude	9
2.5 SVD	14
2.6 Performances	14
2.6.1 Pipelining	14
2.6.2 Memory	14
2.6.3 Time	14
3 Discussion	15
3.1 Observation	15
3.1.1 Without Damper	15
3.1.2 With Damper	15
3.2 Feasibility	15
3.2.1 Hardware	15
3.2.2 Software	15
3.2.3 Estimated Cost	15
4 Conclusion	17

5 Experimental	18
5.1 Estimation of the amount of data	18
5.2 Measurement with the ADT	18
5.3 Experimental Set-up	19
5.3.1 Hardware	19
5.3.2 Software	19
5.4 FFT	19
5.5 SVD	19
5.6 Machine development sessions	19
5.6.1 First session	19
5.6.2 Second session	19
5.6.3 Third session	19
Glossary	20
Acronyms	21

List of Figures

2.1	Time flow with different implementations and with 3000 bunches of 2048 points each.	10
2.2	Spectrogram of the beam position taken on the 16 October 2012 using FFTW	11
2.3	Spectrogram of the beam position taken on the 16 October 2012 using OpenCL on GPU	12
2.4	Spectrogram of the beam position taken on the 16 October 2012 using OpenCL on CPU	13
3.1	Acquisition data flow	16
5.1	ADT acquisition hardware	19

List of Tables

Chapter 1

Introduction

1.1 State of knowledge

In a particle accelerator, the charged particles circulate around the ring and oscillate due to the magnets and the accelerating structures. The accelerating structures, in the LHC supra-conducting cavities apply a strong electrical field that oscillates at the RF frequency (f_0) to particles in order to collect and accelerate particles in bunches inside a frequency bucket.

The particles inside a bucket are oscillating longitudinally along the ring and transversally in the vertical and horizontal plane. The longitudinal oscillations are damped by the beam control system. But the transversal oscillations must be damped by a separate system : the ADT[5, 9].

One of the key parameters of the accelerator is the betatron tune. The betatron tune, Q , is the quotient of the betatron oscillation and the particle frequencies.

$$f_\beta = Q * f_0$$

This value allow us to check if the particle beam is stable and don't reach any dangerous instabilities.

1.2 Tune measurement in the LHC

In order to measure the betatron tune in an accelerator we use Beam Position Monitors (BPMs). These monitors are able to measure the position of the beam in the vacuum chamber.

In the present setup Beam Instrumentation (BI) group is using their diode-based base-band-tune (BBQ) [2] system to acquire the tune over a certain number of machine turn (256 to 128'000). This can work as a passive instrument or as an on demand system by exciting 12 bunches in the beam with the tune kicker (MKQA). ADT has also been used for tune measurement excitation[4].

In normal operation, as the ADT is active, it is difficult to have a good picture of the excited bunches and make a fine tune measurement : the oscillations created by the MKQA are damped by the ADT. There have been studies to disable the ADT for a certain number of bunches in order to get a better tune measurement[6], but this may not be sufficient.

1.3 Proposed system

The ADT also have BPMs and these can have per bunch measurement[8]. This could allow a much precise measurement. But due to the high amount of data to be processed (estimated to 640 mega bytes per seconds for each BPM) dedicated hardware is needed to compute the correct tune[7].

In order to be able to apply direct correction to beam oscillation the betatron tune has to be measured at a high frequency, this has been estimated by BI to be between 5 and 10[Hz], once every 100 to 200[ms].

During the 2012 normal operation of the LHC, data has been acquired using the ADT acquisition system and data processing techniques have been tried to assess the modification that will be needed in order to make a reliable betatron tune measurement at a reasonable rate[7].

The current VMEbus implementation has some serious issues in particular the bus is quite slow the data rate of the bus is around 40 megabits per seconds. The data need to either be processed on the acquisition board or to be off-loaded to another computer using the serial link available on the board[1].

1.3.1 DSP on VME board

Digital Signal Processors (DSPs) are able to compute Fast Fourier Transforms (FFTs) at high rate and these are used already in the machine at different places to make high speed feedback loops. The question is : is it fast enough to compute all the FFTs needed, DSPs are two orders of magnitude slower than GPUs. We also would have to develop a completely new system in order to be able to use them, in fact we don't have DSPs in the present ADT. The cost of development and the complexity of the deployment should also be studied.

1.3.2 FPGA pre-processing on VME board

Like in the approach using DSPs on VME boards, the question of computing power is still unsolved. We already have in house experience and we already have a lot of Field-Programmable Gate Array (FPGA) installed in the ADT. But if we want to do it we will have to create a new card able to replace the existing one and to make the computation. This means creating a potential problem in the existing setup. The cost is also to be studied we have to develop a new card, test it and install it in the LHC. Also the number of cards and FPGAs is not well understood, it could be anywhere between 4 and 3000 (FIXME).

1.3.3 GPU off-board computing

This solution can be integrated easily in the present setup. The present acquisition cards already have a digital output and could be used to transfer the data in another crate that could do the computations. The GPUs are cheap (compare to the price of developing a new VMEbus card) and easily scalable. The GPU should have largely enough computing power to be able to make the FFTs. Another interesting aspect of this solution is the ability to test it using Central Processing Unit (CPU).

1.4 Problem definition

Implement a GPU based system that can deliver a tune value for each beam and planes at a frequency that allow the system to be responsive enough to allow tune correction to be applied automatically.

1.4.1 Algorithm

We need the tune frequency and we have the tune position per bunch, we have to calculate the FFT to move from time to frequency domain. Then we need to identify the tune in the transformation.

1.4.2 Hardware

Per bunch position measurement has to be available to the system for each beam and each plane. This should be provided from the ADTDSU card and has to be transferred through a serial link to the CPU/GPU crate for computation.

We need a card in the CPU/GPU crate to unserialize the data and transfer them to the GPU memory. It may be possible to copy from the acquisition card directly to the GPU memory.

And finally fast enough GPU to process the data. The number and the type of card should be looked at. The possibility for expansion should be kept as the possibility to implement other algorithms.

1.4.3 Timing

According to BI we have to provide the tune measurement between 5 Hz and 10 Hz. This means that the transfer and the computation has to be made in less than 200 ms.

At a higher frequency because of the acquisition frequency (11 kHz) the precision may be unsufficient (NyquistShannon sampling theorem).

Chapter 2

Results

2.1 Implemented System

2.2 Notch filter

Just used to cut the low frequencies this doesn't change anything on the high frequencies and was just used to allow a better imaging on the spectrogram, it won't be used in the final version (quite slow because of sequencial).

2.3 FFT

Some words about FFTs.

2.3.1 FFTW

Some words that explain what is FFTW and why is was chosen as a reference

2.3.2 FFT with OpenCL on GPU

Some words on the implementation used for calculating FFT on OpenCL reference to the image of the spectrogram.

2.3.3 FFT with OpenCL on CPU

Some words on the fact that you can run the code on the CPU as well and then reference on the figure.

Also talk about the fact that there is less noise in the OpenCL CPU version than the OpenCL GPU version.

2.4 Amplitude

Amplitude calculation formula, explain the figures tell why it has to be done before accumulation and show this is very fast reference to the table of perf.

Figure 2.1: Time flow with different implementations and with 3000 bunches of 2048 points each.




Figure 2.2: Spectrogram of the beam position taken on the 16 October 2012 using FFTW




Figure 2.3: Spectrogram of the beam position taken on the 16 October 2012 using OpenCL on GPU





Figure 2.4: Spectrogram of the beam position taken on the 16 October 2012 using OpenCL on CPU



2.5 SVD

Problem is not directly solvable with the number of bunch observed cite Hofle and Rama need a lot more bunches to make a good smooth[3].

Talk about the performances issues and cite the paper on SVD on GPU as a future implementation (could go to discussion?)

2.6 Performances

Calculation made by accumulation to simulate the number of bunches that could be present in the final version (2880).

2.6.1 Pipelining

Pipelining was tested and used in the process and it was possible to win around 15% in performances around it.

2.6.2 Memory

Copy of memory from and to the GPU discussion.

2.6.3 Time

Add table with time performances and discussion.

Chapter 3

Discussion

3.1 Observation

3.1.1 Without Damper

Clear view of the tune

3.1.2 With Damper

The tune is inverted speak about cite the hofle paper mathematic morphology more processing needed but should be quite low.

3.2 Feasibility

3.2.1 Hardware

ADT Aquisition boards

Serial link interface

GPUs

3.2.2 Software


Drivers

OpenCL

Front-end

3.2.3 Estimated Cost

Figure 3.1: Acquisition data flow



Chapter 4

Conclusion

This project looks like a nice place to try using GPUs in accelerators. The possibilities are promising and the gain for the stability of the LHC could allow more physic time. GPUs could prove to be useful and be used in other places in accelerators where computing power is needed.

Chapter 5

Experimental

5.1 Estimation of the amount of data

Presently the LHC is working with an interval of 50ns between bunches this correspond to a bunch every 10 buckets. But the Operation (OP) is planning to move to 25ns bunches spacing this would mean 5 buckets between bunches. With the RF frequency (f_0) we can compute the number of acquisitions per seconds.

$$\text{for } 50 \text{ ns} : \frac{400.789M}{20} = 20'039'450 \leq 2^{25}$$

$$\text{for } 25 \text{ ns} : \frac{400.789M}{10} = 40'078'900 \leq 2^{26}$$

This represent the amount of data for one pickup (BPM), in the case of ADT we have two of them per beam and per plane so as the LHC has two rings and for each ring there are two transversal plane and there are two pickups per plane. This means we still have to multiply this value by eight.

$$\text{for } 50 \text{ ns} : 2^{25} * 8 = 2^{28}$$

$$\text{for } 25 \text{ ns} : 2^{26} * 8 = 2^{29}$$


As FFTs on GPUs start to be faster than CPUs around 2^{15} acquisitions it seems interesting to study this kind of system to compute the betatron tune.

5.2 Measurement with the ADT

In order to check the feasibility of the system and to have a good prototype the first test will be to excite some of the bunches and acquire the betatron tune using the ADT during the end of 2012 run.

A piece of software has been developed that will acquire the bunch by bunch acquisition and compute various algorithm on the data using the CPU and the FFTW library in the CERN infrastructure using Control (CO) group control system and the OP group infrastructure.

Figure 5.1: ADT acquisition hardware
ADT acquisition system



5.3 Experimental Set-up

5.3.1 Hardware

The experimental set up is not presently able to acquire more than a certain number of bunches due to memory limitation 16k and interrupt frequency so during the Machine Developments (MDs) only 6 bunches were acquired by bunch by planes.

5.3.2 Software

5.4 FFT

5.5 SVD

5.6 Machine development sessions

Using the ADT BPMs we acquired data in the machine during 3 independant MDs. Most of the data taking was done in parallel to other normal LHC operation or during ADT dedicated MD time.

5.6.1 First session

Night session of the 11 october 2012.

5.6.2 Second session

Parasitic session of the 16 october 2012

5.6.3 Third session

Ramp acquisition of the 14 november 2012

Glossary

betatron tune the betatron tune is the frequency of the oscillations of the bunches divided by the RF frequency (f_0). 1, 7, 18

bucket at every Radio Frequency (RF) period in the RF frequency (f_0) there is a bucket, in each of these bucket a particles bunch can potentially be stored in the ring. 6, 18

bunch particules trapped inside an RF bucket circulating in the machine. 1, 6, 18, 20

cavity RF structure made to accelerate the particles, it uses a high power radio frequency into a resonating structure to increase the energy of the particles. 6, 20

damper machine in an accelerator that damp the transverse oscillation of the beam by applying a transverse electric field. 1, 21

FFTW is a C subroutine library for computing the discrete Fourier transform (DFT) in one or more dimensions, of arbitrary input size, and of both real and complex data (as well as of even/odd data, i.e. the discrete cosine/sine transforms or DCT/DST). 18

kicker machine in an accelerator that can kick the beam transversally, used to kick the beam in or out (injection or extraction kicker) of the beam pipe but also in our case excite the beam transversally. 6, 21

RF frequency (f_0) the base frequency of the RF in the cavities in the case of the LHC this frequency is 400.789MHz, this frequency dictate the number of bucket that the machine can have. 6, 18, 20

VMEbus a computer bus standard widespread at CERN, in the case of the LHC RF the bus has a larger board and some of the pins are used to route custom signals between cards. 7

Acronyms

ADT Accelerating Damper Transverse. 1, 6, 7, 18, 19

BBQ diode-based base-band-tune. 6

BI Beam Instrumentation. 6–8

BPM Beam Position Monitor. 6, 7, 18, 19

CERN European organization for nuclear research. 1, 18

CO Control. 18

CPU Central Processing Unit. 7, 18

DSP Digital Signal Processor. 7

FFT Fast Fourier Transform. 7, 18

FPGA Field-Programmable Gate Array. 7

GPU Graphic Processing Unit. 1, 7, 17, 18

LHC Large Hadron Collider. 1, 6, 7, 17, 18

MD Machine Development. 19

MKQA tune kicker. 6

OP Operation. 18

RF Radio Frequency. 20

Bibliography

- [1] P Baudrenghien, Wolfgang Hofle, G Kotzian, and V Rossi. Digital signal processing for the multi-bunch lhc transverse feedback system. oai:cds.cern.ch:1124094. (LHC-PROJECT-Report-1151. CERN-LHC-PROJECT-Report-1151):4, Sep 2008.
- [2] A Boccardi, M Gasior, R Jones, P Karlsson, and RJ Steinhagen. First results from the lhc bbq tune and chromaticity systems. Technical Report LHC-Performance-Note-007. CERN-LHC-Performance-Note-007, CERN, Geneva, Jan 2009.
- [3] Rama Calaga. *Linear Beam Dynamics and Ampere Class Superconducting RF Vavities at RHIC*. PhD thesis, Stony Brook University, 2006.
- [4] Wolfgang Hofle. Lhc transverse damper observations versus expectations. In *Evian 2010 proceedings*, 2010. https://espace.cern.ch/acc-tec-sector/Evian/Papers-Dec2010/3.3_WH.pdf.
- [5] Wolfgang Hofle. Lhc transverse damper from commissioning to routine. *Beams Department newsletter*, 1:6–7, 2011. https://espace.cern.ch/be-dep/BEDepartmentalDocuments/BE/BE_Newsletter/BE_Newsletter_001.pdf.
- [6] Wolfgang Hofle. Transverse feedback : high intensity operation, abort gap cleaning, injection gap cleaning and lessons for 2012. In *Evian 2011 proceedings*, 2011. <https://indico.cern.ch/>.
- [7] Wolfgang Hofle. Transverse damper. In *Chamonix 2012 proceedings*, 2012. <https://indico.cern.ch/>.
- [8] Daniel Valuch. Beam phase measurement and transverse position measurement module for the lhc, 2007. Poster from the Low Level RF workshop 2007. Available "<https://edms.cern.ch/document/929563/1>".
- [9] V M Zhabitsky, E V Gorbachev, N I Lebedev, A A Makarov, N V Pilyar, S V Rabtsun, R A Smolkov, P Baudrenghien, Wolfgang Hofle, F Killing, I Kojevnikov, G Kotzian, R Louwerse, E Montesinos, V Rossi, M Schokker, E Thepenier, and D Valuch. Lhc transverse feedback system: First results of commissionning. oai:cds.cern.ch:1141925. Technical Report LHC-PROJECT-Report-1165. CERN-LHC-PROJECT-Report-1165, CERN, Geneva, Sep 2008.