

MATH FUNCTIONS

Round x to y decimal places	<code>round(x, [y])</code>
Return modulo of x % y	<code>mod(x, y)</code>
Computes value of x^y	<code>pow(x, y)</code> <code>power(X, y)</code>
Returns square root of x	<code>sqrt(x)</code>
Truncates x to integer value	<code>trunc(x)</code>
Returns first int >= x	<code>floor(x)</code>
Returns first int <= x	<code>ceil(x)</code> <code>ceiling(x)</code>
Returns absolute value of x	<code>abs(x)</code>

DATE FUNCTIONS

Returns the date as text in the format 'YYYY-MM-DD'	<code>date(time-value, modifier, ...)</code>
Returns time as text in the format 'HH:MM:SS'	<code>time(time-value, modifier, ...)</code>
Returns the date and time as text in the format: 'YYYY-MM-DD HH:MM:SS'	<code>datetime(time-value, modifier, ...)</code>
Returns the Julian day	<code>julianday(time-value, modifier, ...)</code>
Returns a unix timestamp	<code>unixepoch(time-value, modifier, ...)</code>
Returns the date formatted according to the format string specified as the first argument.	<code>strftime(format, time-value, modifier, ...)</code>
Returns a string that describes the amount of time that must be added to time-value2 in order to reach time-value1.	<code>timediff(time-value1, time-value2)</code>

FORMATTING STRINGS	
Day of month: 00	%d
Fractional seconds: SS.SSS	\$f
Hour: 00-24	%H
Day of year: 001-366	%j
Julian day number	%J
Month: 01-12	%m
Minute: 00-59	%M
Unix time	%s
Seconds: 00-59	%S
Day of week: 0-6 (Sunday=0)	%w
Week of year: 00-53	%W
Year: 0000-9999	%Y
TIME VALUES	
T is a character separating the time and date (ex: 2013-10-07T08:23)	YYYY-MM-DD [HH:MM][:SS][.SSS] YYYY-MM-DDTHH:MM[:SS][.SSS]
The date of 2000-01-01 is used	HH:MM[:SS][.SSS]
Current UTC date	now
Julian day number (int or float)	DDDDDDDDDD
TIME VALUES	
Add or subtract x corresponding time from the time value	x days / hours / minutes / seconds / months / years
Add or subtract HH:MM from time value	HH:MM[:SS]
Add or subtract from time value	± YYYY-MM-DD [HH][:MM][:SS]
Shift time value back to start of date value	start of month / year / day
Advances time value to next weekday x	weekday x

OTHER FUNCTIONS

Returns number of rows changed by last DML statement	<code>changes()</code>
Returns total number of row changes caused by DML since connection opened	<code>total_changes()</code>
Returns copy of first non-NULL argument or NULL if both are NULL	<code>ifnull(x, y)</code>
Returns number of characters in x	<code>length(x)</code>
Returns a pseudo-random integer	<code>random()</code>
Returns datatype of expression x	<code>typeof(x)</code>

CASE/IIF

CASE equality syntax	<pre> CASE expression WHEN value_1 THEN result_1 WHEN value_2 THEN result_2 ... [ELSE result_else] END </pre>
Boolean comparison CASE syntax	<pre> CASE WHEN bool_expression_1 THEN result_1 WHEN bool_expression_2 THEN result_2 ... [ELSE result_else] END </pre>
Multiple conditions	<pre> CASE WHEN expr_1 AND expr_2 THEN ... WHEN expr_3 OR expr_4 THEN ... </pre>
If check is true, returns x, else returns y	<code>iif(check, x, y)</code>
Example:	<code>IIF(milliseconds <= 300000, 'Short', 'Long')</code>
Nested iif statements	<pre> IFF(condition_1, evaluates_to_true, IIF(condition_2, evaluates_to_true, IIF(condition_3, evaluates_to_true, all_false))) </pre>