Angular ngStyle Directive

Leave a Comment / 3 minutes of reading

⟵ ngClass Directive ngFor Trackby ⟶

The Angular ngStyle directive allows us to set the many inline style of a HTML element using an expression. The expression can be evaluated at run time allowing us to dynamically change the style of our HTML element. In this tutorial, we learn how to use the ngStyle with an example.

Table of Content

ngStyle Syntax
ngStyle Example
  Change Style Dynamically
  ngStyle multiple attributes
  Specifying CSS Units in ngStyle
  Using object from Controller
  Change Style using Style Property Binding

ngStyle Syntax

```
<element [ngStyle]="{'styleNames': styleExp}">...</element>
```

Where

`element` is the DOM element to which style is being applied

`styleNames` are style names (ex: 'font-size', 'color' etc). with an optional suffix (ex: 'top.px', 'font-style.em'),

`styleExp` is the expression, which is evaluated and assigned to the `styleNames`

We can add more than one key value pairs `'styleNames': styleExp` each separated by comma.

In the following example, `some-element` gets the style of `font-size` of `20px`.

```
<some-element [ngStyle]="{'font-size': '20px'}">Set Font size to 20px</some-element>
```

The units (for example `px`, `em`) are prefixed to the `styleName`.

```
Syntax:
<element [ngStyle]="{'styleName.unit': widthExp}">...</element>

Example:
<some-element[ngStyle]="{'font-size.em': '3'}">...</some-element>
```

ngStyle Example

Change Style Dynamically

Initialize a variable `color` and add it to your component

```
color: string= 'red';
```

And in your template, add the following

```
<input [(ngModel)]="color" />
<div [ngStyle]="{'color': color}">Change my color</div>
```

In the above example, we apply `ngStyle` directive to the `div` element. We assign JavaScript object `{'color': color}` to the `ngStyle` directive. The variable `color` is dynamically changed by the user input and it is applied instantly to the `div` element

The following code uses the ternary operator to set the background color to **red** if the `status` variables indicator is set to "error" else **blue**.

```
div [ngStyle]="{'background-color':status === 'error' ? 'red' : 'blue' }"></<div>
```

ngStyle multiple attributes

We can change multiple style as shown in the following example

```
<p [ngStyle]="{'color': 'purple',
               'font-size': '20px',
               'font-weight': 'bold'}">
     Multiple styles
</p>
```

The JavaScript object is assigned to the `ngStyle` directive containing multiple properties. Each property name of the object acts as a class name. The value of the property is the value of the style.

BEST ANGULAR BOOKS

The Top 8 Best Angular Books, which helps you to get started with Angular

Specifying CSS Units in ngStyle

CSS has several units for expressing a length, size etc. The units can be `em`, `ex`, `%`, `px`, `cm`, `mm`, `in`, `pt`, `PC` etc. We prefix the units to the `StyleName` as shown below.

```
<input [(ngModel)]="size" />
<div [ngStyle]="{'font-size.px': size}">Change my size</div>
```

Using object from Controller

Create a class as shown below

```
class StyleClass {
   'color': string= 'blue';
   'font-size.px': number= 20;
   'font-weight': string= 'bold';
}
```

And in controller initialize the class

```
styleClass: StyleClass = new StyleClass();
```

Then you can refer it in your template as shown below

```
<div [ngStyle]="styleClass">size & Color</div>
```

Change Style using Style Property Binding

We can also change the Styles using the Style Binding. .

Further Reading on Angular Styles

- Angular ngStyle Directive
- ngClass Directive
- Angular Global Styles
- Angular Component Styles
- View Encapsulation in Angular
- Angular Directives

You can download the source code from GitHub

⟵ ngClass Directive ngFor Trackby ⟶

Leave a Comment

Your email address will not be published.

Type here..

Name*

Email*

Website

Post Comment »

This site uses Akismet to reduce spam. Learn how your comment data is processed.

Copyright © 2021 TekTutorialsHub |