Style binding in Angular

Leave a Comment / 2 minutes of reading

⟵ View Encapsulation Class Binding ⟶

We can set the inline styles of a HTML element using the style binding in angular. The syntax resembles the syntax of the property binding. You can add styles conditionally to an element, hence creating a dynamically styled element.

Further Reading on Angular Styles

- Angular ngStyle Directive
- class bindng
- ngClass Directive
- Angular Global Styles
- Angular Component Styles
- View Encapsulation in Angular

Applies to: Angular 2 to the latest edition of i.e. Angular 8. Angular 9, Angular 10, Angular 11

Table of Content

Syntax
Style binding Example
    Conditionally setting the styles
    Setting the units
    Setting Multiple styles
Summary

Syntax

The syntax of the style binding is similar to the property binding.

```

[style.style-property] = "style-value"

```

The Style Binding uses the `[]` brackets. Place the CSS Style property (binding target) inside the square bracket. The CSS Style property must begin with 'Style' followed by a dot (.) and then style name.

For Example, to set the color of `p` element.

```

<p [style.color]="'red'">Give me red</p>

```

Style binding Example

Setting the background color of a paragraph

```

<p [style.background-color]="'grey'">some paragraph with grey background</p>

```

Setting the border style of a button.

```

<button [style.border]="'5px solid yellow'">Save</button>

```

BEST ANGULAR BOOKS

The Top 8 Best Angular Books, which helps you to get started with Angular

Conditionally setting the styles

Define a variable status in the component

```

status:string='error';

```

And use that variable in the template to set the `color` of button either to **red** and **blue** depending on the value of the `status` variable.

```

<button [style.color]="status=='error' ? 'red': 'blue'">Button 1</button>

```

Another way is to create the `getColor()` method and use it in the template as shown below.

```

getColor() {
  return 'yellow';
}

```

```

<button [style.color]="getColor()">Button 2</button>

```

Setting the units

The styles like `font-size`, `width` etc have unit extension. The following example conditionally sets the `font-size` in `"px"` unit

```

<button [style.font-size.px]="'20'" >Big Button</button>

```

The *style property* name can be written in either dash-case (font-size), as shown in above example, or camelCase (fontSize) as shown below.

```

<button [style.fontSize.px]="'20'" >Big Button</button>

```

Setting Multiple styles

To change the multiple styles, we need to add each one separately as shown below.

```

<p [style.color]="getColor()"
   [style.font-size.px]="'20'"
   [style.background-color]="status=='error' ? 'red': 'blue'">
   paragraph with multiple styles
</p>

```

The style binding is the easy way to set a single style of a HTML element. Although you can use it to set several inline styles as shown in the above example, the better way is to use the ngStyle directive.

Summary

The style binding is one of the several ways you can use styles in angular. You can refer to the following tutorials.

- Angular ngStyle Directive
- Class binding
- ngClass Directive
- Angular Global Styles
- Angular Component Styles
- View Encapsulation in Angular

⟵ View Encapsulation Class Binding ⟶

Leave a Comment

Your email address will not be published.

Type here..

Name*

Email*

Website

Post Comment »

This site uses Akismet to reduce spam. Learn how your comment data is processed.

Copyright © 2021 TekTutorialsHub |