Finding the percentage

HackerRank

The provided code stub will read in a dictionary containing key/value pairs of name:[marks] for a list of students. Print the average of the marks array for the student name provided, showing 2 places after the decimal.

Example
$\textbf{marks key:value pairs are}$
$\textbf{'alpha': } [20, 30, 40]$
$\textbf{'beta': } [30, 50, 70]$
$\textbf{query\_name} = \textbf{'beta'}$

The **query_name** is 'beta'. beta's average score is $(30 + 50 + 70)/3 = 50.0$.

Input Format

The first line contains the integer n, the number of students' records. The next n lines contain the names and marks obtained by a student, each value separated by a space. The final line contains **query_name**, the name of a student to query.

Constraints

- $2 \leq n \leq 10$
- $0 \leq marks[i] \leq 100$
- $\textbf{length of marks arrays} = 3$

Output Format

Print one line: The average of the marks obtained by the particular student correct to 2 decimal places.

Sample Input 0

```
3
Krishna 67 68 69
Arjun 70 98 63
Malika 52 56 60
Malika
```

Sample Output 0

```
56.00
```

Explanation 0

Marks for Malika are $\{52, 56, 60\}$ whose average is $\frac{52+56+60}{3} \Rightarrow 56$

Sample Input 1

```
2
Harsh 25 26.5 28
Anurag 26 28 30
Harsh
```

Sample Output 1

```
26.50
```