

# Correcting a Single Deletion in Reads from a Nanopore Sequencer


Anisha Banerjee<sup>1</sup>

**Joint work with**  
Yonatan Yehezkeally<sup>1</sup>, Antonia Wachter-Zeh<sup>1</sup>,  
and Eitan Yaakobi<sup>2</sup>

<sup>1</sup>Technical University of Munich  
Institute for Communications Engineering

<sup>2</sup>Technion – Israel Institute of Technology  
Department of Computer Science

July 8, 2024



# Outline

Introduction

Channel Model

Minimum Redundancy

Multiple Reads

Conclusion

Introduction

Channel Model

Minimum Redundancy

Multiple Reads

Conclusion

# Motivation

- Need for dense, reliable, robust storage media
  - ▶ Molecular storage paradigms *e.g.*, *DNA storage*.<sup>1</sup>



<sup>1</sup> R. Heckel *et al.*, “A characterization of the DNA data storage channel,” *Scientific Reports*, 2019

<sup>2</sup> D. Deamer *et al.*, “Three decades of nanopore sequencing,” *Nat. Biotech.*, 2016

<sup>2</sup> A. H. Laszlo *et al.*, “Decoding long nanopore sequencing reads of natural DNA,” *Nat. Biotech.*, 2014

# Motivation

- Need for dense, reliable, robust storage media
  - ▶ Molecular storage paradigms *e.g.*, *DNA storage*.<sup>1</sup>
- Faster, cheaper sequencers in development.




<sup>1</sup> R. Heckel *et al.*, “A characterization of the DNA data storage channel,” *Scientific Reports*, 2019

<sup>2</sup> D. Deamer *et al.*, “Three decades of nanopore sequencing,” *Nat. Biotech.*, 2016

<sup>2</sup> A. H. Laszlo *et al.*, “Decoding long nanopore sequencing reads of natural DNA,” *Nat. Biotech.*, 2014

# Motivation

- Need for dense, reliable, robust storage media
  - ▶ Molecular storage paradigms *e.g.*, *DNA storage*.<sup>1</sup>
- Faster, cheaper sequencers in development.
- Nanopore sequencing<sup>2</sup>:
  - + Can read longer DNA strands
  - + More portable
  - High error rates



Source: "Decoding DNA with a pocket-sized sequencer," *Science in School*. <https://www.scienceinschool.org/article/2018/decoding-dna-pocket-sized-sequencer/>


<sup>1</sup> R. Heckel *et al.*, "A characterization of the DNA data storage channel," *Scientific Reports*, 2019

<sup>2</sup> D. Deamer *et al.*, "Three decades of nanopore sequencing," *Nat. Biotech.*, 2016

<sup>2</sup> A. H. Laszlo *et al.*, "Decoding long nanopore sequencing reads of natural DNA," *Nat. Biotech.*, 2014

# Motivation

- Need for dense, reliable, robust storage media
  - Molecular storage paradigms *e.g.*, *DNA storage*.<sup>1</sup>
- Faster, cheaper sequencers in development.
- Nanopore sequencing<sup>2</sup>:
  - + Can read longer DNA strands
  - + More portable
  - High error rates
- *Aim*: Design coding techniques tailored for nanopore sequencing!




Source: "Decoding DNA with a pocket-sized sequencer," *Science in School*. <https://www.scienceinschool.org/article/2018/decoding-dna-pocket-sized-sequencer/>

<sup>1</sup> R. Heckel *et al.*, "A characterization of the DNA data storage channel," *Scientific Reports*, 2019

<sup>2</sup> D. Deamer *et al.*, "Three decades of nanopore sequencing," *Nat. Biotech.*, 2016

<sup>2</sup> A. H. Laszlo *et al.*, "Decoding long nanopore sequencing reads of natural DNA," *Nat. Biotech.*, 2014

# Nanopore Sequencing



Source: "What is Oxford Nanopore Technology (ONT) sequencing?," <https://www.yourgenome.org/facts/what-is-oxford-nanopore-technology-ont-sequencing/>

- Sources of noise [MDK18] :
  - ▶ Nanopore holds  $\ell > 1$  nucleotides at a time  $\rightarrow$  Intersymbol interference (ISI)!
  - ▶ Strand moves irregularly  $\rightarrow$  backtracking & skipping.
  - ▶ Noisy measurements

[MDK18] W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018



# Prior Work

- [MDK18] → Mathematical model, capacity bounds.
- [HCW21] → Algorithm to compute capacity of an abstracted, deterministic channel model.
- [MVS22] → Finite-state semi-Markov channel model with major noise sources.

---

[MDK18] [W. Mao \*et al.\*](#), “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

[HCW21] [R. Hulett \*et al.\*](#), “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, 2021

[MVS22] [B. McBain \*et al.\*](#), “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, 2022

[CVVY21] [Y. M. Chee \*et al.\*](#), “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

[BYWY24] [A. Banerjee \*et al.\*](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

[YEY24] [O. Yerushalmi \*et al.\*](#), “The capacity of the weighted read channel,” in *ISIT*, 2024

[CIV24] [Y. M. Chee \*et al.\*](#), “Coding scheme for noisy nanopore sequencing with backtracking and skipping errors,” in *ISIT*,

2024

# Prior Work

- [MDK18] → Mathematical model, capacity bounds.
- [HCW21] → Algorithm to compute capacity of an abstracted, deterministic channel model.
- [MVS22] → Finite-state semi-Markov channel model with major noise sources.
- [CVVY21] considered a similar channel for racetrack memories:  
→ Computed information limits, proposed error-correcting codes.

---

[MDK18] [W. Mao \*et al.\*](#), “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

[HCW21] [R. Hulett \*et al.\*](#), “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, 2021

[MVS22] [B. McBain \*et al.\*](#), “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, 2022

[CVVY21] [Y. M. Chee \*et al.\*](#), “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

[BYWY24] [A. Banerjee \*et al.\*](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

[YEY24] [O. Yerushalmi \*et al.\*](#), “The capacity of the weighted read channel,” in *ISIT*, 2024

[CIV24] [Y. M. Chee \*et al.\*](#), “Coding scheme for noisy nanopore sequencing with backtracking and skipping errors,” in *ISIT*,

2024

# Prior Work

- [MDK18] → Mathematical model, capacity bounds.
- [HCW21] → Algorithm to compute capacity of an abstracted, deterministic channel model.
- [MVS22] → Finite-state semi-Markov channel model with major noise sources.
- [CVVY21] considered a similar channel for racetrack memories:  
→ Computed information limits, proposed error-correcting codes.
- [BYWY24] → Optimal single-substitution-correcting code for this channel.

---

[MDK18] [W. Mao \*et al.\*](#), “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

[HCW21] [R. Hulett \*et al.\*](#), “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, 2021

[MVS22] [B. McBain \*et al.\*](#), “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, 2022

[CVVY21] [Y. M. Chee \*et al.\*](#), “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

[BYWY24] [A. Banerjee \*et al.\*](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

[YEY24] [O. Yerushalmi \*et al.\*](#), “The capacity of the weighted read channel,” in *ISIT*, 2024

[CIV24] [Y. M. Chee \*et al.\*](#), “Coding scheme for noisy nanopore sequencing with backtracking and skipping errors,” in *ISIT*,

2024

# Prior Work

- [MDK18] → Mathematical model, capacity bounds.
- [HCW21] → Algorithm to compute capacity of an abstracted, deterministic channel model.
- [MVS22] → Finite-state semi-Markov channel model with major noise sources.
- [CVVY21] considered a similar channel for racetrack memories:  
→ Computed information limits, proposed error-correcting codes.
- [BYWY24] → Optimal single-substitution-correcting code for this channel.
- At ISIT'24 → [YFY24] , [CIV24] , ...

---

[MDK18] [W. Mao et al.](#), “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

[HCW21] [R. Hulett et al.](#), “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, 2021

[MVS22] [B. McBain et al.](#), “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, 2022

[CVVY21] [Y. M. Chee et al.](#), “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

[BYWY24] [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

[YFY24] [O. Yerushalmi et al.](#), “The capacity of the weighted read channel,” in *ISIT*, 2024

[CIV24] [Y. M. Chee et al.](#), “Coding scheme for noisy nanopore sequencing with backtracking and skipping errors,” in *ISIT*,

2024

Introduction


**Channel Model**

Minimum Redundancy

Multiple Reads

Conclusion


# Simplified Model




---

W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

---

W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model



We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

---

W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018



# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:

- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.


## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018



# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:


- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model




We model

- ISI as length- $\ell$ -sliding window
- Skipping effects as deletions

Assumptions:

- Input  $\mathbf{x} \in \{0, 1\}^n$
- DMC maps  $\ell$ -mers to Hamming weights.

## Example ( $\ell = 3$ )



W. Mao *et al.*, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018

# Simplified Model

## Definition

The  $\ell$ -**read vector** of any  $\mathbf{x} \in \Sigma_2^n$  is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where  $\text{wt}(\cdot)$  denotes Hamming weight.

---

Y. M. Chee *et al.*, “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

# Simplified Model

## Definition

The  $\ell$ -**read vector** of any  $\mathbf{x} \in \Sigma_2^n$  is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where  $\text{wt}(\cdot)$  denotes Hamming weight.

## Our Results

- $\geq \log n - \ell - o(1)$  min redundancy to correct 1 deletion.

---

Y. M. Chee *et al.*, “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

# Simplified Model

## Definition

The  $\ell$ -**read vector** of any  $\mathbf{x} \in \Sigma_2^n$  is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where  $\text{wt}(\cdot)$  denotes Hamming weight.

## Our Results

- $\geq \log n - \ell - o(1)$  min redundancy to correct 1 deletion.
- 1-deletion correcting code, optimal up to additive constant.

---

Y. M. Chee *et al.*, “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

# Simplified Model

## Definition

The  $\ell$ -**read vector** of any  $\mathbf{x} \in \Sigma_2^n$  is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n))$$

where  $\text{wt}(\cdot)$  denotes Hamming weight.

## Our Results

- $\geq \log n - \ell - o(1)$  min redundancy to correct 1 deletion.
- 1-deletion correcting code, optimal up to additive constant.
- No redundancy to reconstruct from two noisy  $\ell$ -read vectors.

---

Y. M. Chee *et al.*, “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

# Error-correcting Code

## Definition

$\mathcal{C}$  is a  $t$ - **deletion**  $\ell$ -**read code** if for all  $\mathbf{x}, \mathbf{y} \in \mathcal{C}$ ,

$$D_t(\mathcal{R}(\mathbf{x})) \cap D_t(\mathcal{R}(\mathbf{y})) = \emptyset,$$

where  $D_t(\cdot)$  is the  $t$ -deletion ball.

# Error-correcting Code

## Definition

$\mathcal{C}$  is a  $t$ - **deletion**  $\ell$ -**read code** if for all  $\mathbf{x}, \mathbf{y} \in \mathcal{C}$ ,

$$D_t(\mathcal{R}(\mathbf{x})) \cap D_t(\mathcal{R}(\mathbf{y})) = \emptyset,$$

where  $D_t(\cdot)$  is the  $t$ -deletion ball.

- *Aim*: Find an optimal 1-deletion  $\ell$ -read code.



# Naive Deletion Correction

## Definition (Read vector)

The  $\ell$ -read vector of any  $\mathbf{x} \in \Sigma_2^n$  is of length  $n + \ell - 1$  and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here  $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$  where for  $j \notin [n]$ , let  $x_j = 0$ .

# Naive Deletion Correction

## Definition (Read vector)

The  $\ell$ -read vector of any  $\mathbf{x} \in \Sigma_2^n$  is of length  $n + \ell - 1$  and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here  $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$  where for  $j \notin [n]$ , let  $x_j = 0$ .

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}.$

# Naive Deletion Correction

## Definition (Read vector)

The  $\ell$ -read vector of any  $\mathbf{x} \in \Sigma_2^n$  is of length  $n + \ell - 1$  and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here  $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$  where for  $j \notin [n]$ , let  $x_j = 0$ .

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$ .
- $\mathbf{x}$  uniquely determined from the  $n$ -prefix of  $\mathcal{R}(\mathbf{x})$ .

# Naive Deletion Correction

## Definition (Read vector)

The  $\ell$ -read vector of any  $\mathbf{x} \in \Sigma_2^n$  is of length  $n + \ell - 1$  and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here  $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$  where for  $j \notin [n]$ , let  $x_j = 0$ .

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$ .
- $\mathbf{x}$  uniquely determined from the  $n$ -prefix of  $\mathcal{R}(\mathbf{x}) \bmod 2$ .

# Naive Deletion Correction

## Definition (Read vector)

The  $\ell$ -read vector of any  $\mathbf{x} \in \Sigma_2^n$  is of length  $n + \ell - 1$  and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here  $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$  where for  $j \notin [n]$ , let  $x_j = 0$ .

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$ .
- $\mathbf{x}$  uniquely determined from the  $n$ -prefix of  $\mathcal{R}(\mathbf{x}) \bmod 2$ .  $\leftarrow$  Use VT code!

# Naive Deletion Correction

## Definition (Read vector)

The  $\ell$ -read vector of any  $\mathbf{x} \in \Sigma_2^n$  is of length  $n + \ell - 1$  and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here  $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$  where for  $j \notin [n]$ , let  $x_j = 0$ .

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$ .
- $\mathbf{x}$  uniquely determined from the  $n$ -prefix of  $\mathcal{R}(\mathbf{x}) \bmod 2$ .  $\leftarrow$  Use VT code!

## Construction

$$\mathcal{C}(n, \ell, a) = \{\mathbf{x} \in \Sigma_2^n : \sum_{i=1}^n i(\mathcal{R}(\mathbf{x})_i \bmod 2) = a \pmod{n+1}\},$$

where  $a \in \{0, \dots, n\}$ .

# Naive Deletion Correction

## Definition (Read vector)

The  $\ell$ -read vector of any  $\mathbf{x} \in \Sigma_2^n$  is of length  $n + \ell - 1$  and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here  $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$  where for  $j \notin [n]$ , let  $x_j = 0$ .

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$ .
- $\mathbf{x}$  uniquely determined from the  $n$ -prefix of  $\mathcal{R}(\mathbf{x}) \bmod 2$ .  $\leftarrow$  Use VT code!

## Construction

$$\mathcal{C}(n, \ell, a) = \{\mathbf{x} \in \Sigma_2^n : \sum_{i=1}^n i(\mathcal{R}(\mathbf{x})_i \bmod 2) = a \pmod{n+1}\},$$

where  $a \in \{0, \dots, n\}$ .

$\rightarrow$  Requires  $\log_2(n+1)$  redundant bits.

Introduction

Channel Model

Minimum Redundancy

Multiple Reads

Conclusion



# Connection to Sticky Deletion

- $\ell$ -sticky deletion  $\rightarrow$  delete in a run with  $\geq \ell$  bits.

# Connection to Sticky Deletion

- **$\ell$ -sticky deletion**  $\rightarrow$  delete in a run with  $\geq \ell$  bits.

## Example ( $\ell = 3$ )

$$\mathbf{x} = (1, 0, \underline{1, 1, 1, 1}, 0, 0, 0)$$

$$\mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, \boxed{3, 3}, 2, 1, 0, 0, 0)$$

# Connection to Sticky Deletion

- $\ell$ -sticky deletion  $\rightarrow$  delete in a run with  $\geq \ell$  bits.

## Example ( $\ell = 3$ )

$$\mathbf{x} = (1, 0, \underline{1, 1, 1, 1}, 0, 0, 0) \xrightarrow[\text{deletion}]{\ell\text{-sticky}} \mathbf{x}' = (1, 0, \underline{1, 1, 1}, 0, 0, 0)$$

$$\mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, \boxed{3, 3}, 2, 1, 0, 0, 0) \xrightarrow{\ell\text{-deletion}} \mathcal{R}(\mathbf{x}') = (1, 1, 2, 2, \boxed{3}, 2, 1, 0, 0, 0)$$

# Connection to Sticky Deletion

- $\ell$ -sticky deletion  $\rightarrow$  delete in a run with  $\geq \ell$  bits.

## Example ( $\ell = 3$ )

$$\mathbf{x} = (1, 0, 1, 1, 1, 1, \underline{0, 0, 0}) \xrightarrow[\text{deletion}]{\ell\text{-sticky}} \mathbf{x}' = (1, 0, 1, 1, 1, 1, \underline{0, 0})$$

$$\mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, 3, 3, 2, 1, \boxed{0, 0, 0}) \xrightarrow{0\text{-deletion}} \mathcal{R}(\mathbf{x}') = (1, 1, 2, 2, 3, 3, 2, 1, \boxed{0, 0})$$

# Connection to Sticky Deletion

- **$\ell$ -sticky deletion**  $\rightarrow$  delete in a run with  $\geq \ell$  bits.

## Example ( $\ell = 3$ )

$$\begin{aligned} \mathbf{x} = (1, 0, 1, 1, 1, 1, \underline{0, 0, 0}) &\xrightarrow[\text{deletion}]{\ell\text{-sticky}} \mathbf{x}' = (1, 0, 1, 1, 1, 1, \underline{0, 0}) \\ \mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, 3, 3, 2, 1, \underline{0, 0, 0}) &\xrightarrow{0\text{-deletion}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 2, 3, 3, 2, 1, \underline{0, 0}) \end{aligned}$$

- $\ell$ -Sticky deletion in  $\mathbf{x} \rightarrow 0/\ell$ -deletion in  $\mathcal{R}(\mathbf{x})!$ 
  - A 1-deletion  $\ell$ -read code also corrects an  $\ell$ -sticky deletion in message.

# Minimum Redundancy

## Lemma

Any single-deletion  $\ell$ -read code is also a single- $\ell$ -sticky-deletion-correcting code.

---

[FVY15] [A. Fazeli et al.](#), “Generalized sphere packing bound,” *TIT*, 2015

# Minimum Redundancy

## Lemma

Any single-deletion  $\ell$ -read code is also a single- $\ell$ -sticky-deletion-correcting code.

From [FVY15] and concentration arguments,

## Theorem

The redundancy of any single- $\ell$ -sticky-deletion-correcting code is bounded from below by

$$\log_2 n - \ell - o(1).$$

---

[FVY15] [A. Fazeli et al.](#), “Generalized sphere packing bound,” *TIT*, 2015

# Minimum Redundancy

## Lemma

Any single-deletion  $\ell$ -read code is also a single- $\ell$ -sticky-deletion-correcting code.

From [FVY15] and concentration arguments,

## Theorem

The redundancy of any single-deletion  $\ell$ -read code is bounded from below by

$$\log_2 n - \ell - o(1).$$


---

[FVY15] [A. Fazeli et al.](#), “Generalized sphere packing bound,” *TIT*, 2015



# Minimum Redundancy

## Lemma

Any single-deletion  $\ell$ -read code is also a single- $\ell$ -sticky-deletion-correcting code.

From [FVY15] and concentration arguments,

## Theorem

The redundancy of any single-deletion  $\ell$ -read code is bounded from below by

$$\log_2 n - \ell - o(1).$$

→ Naive VT-like construction optimal up to additive constant!

---

[FVY15] A. Fazeli *et al.*, “Generalized sphere packing bound,” *TIT*, 2015

Introduction

Channel Model

Minimum Redundancy

**Multiple Reads**

Conclusion

# Comparison with Classical Channel

- 'Classical'  $\rightarrow \ell = 1$ .
- 'Nanopore'  $\rightarrow \ell \geq 2$ .

# Comparison with Classical Channel

- ‘Classical’  $\rightarrow \ell = 1$ .
- ‘Nanopore’  $\rightarrow \ell \geq 2$ .

|                | Classical | Nanopore                   |
|----------------|-----------|----------------------------|
| 1 substitution | $\log n$  | <sup>1</sup> $\log \log n$ |
| 1 deletion     | $\log n$  | $\log n - \ell$            |

<sup>1</sup> A. Banerjee *et al.*, “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

# Comparison with Classical Channel

- 'Classical'  $\rightarrow \ell = 1$ .
- 'Nanopore'  $\rightarrow \ell \geq 2$ .

|                | Classical | Nanopore                   |
|----------------|-----------|----------------------------|
| 1 substitution | $\log n$  | <sup>1</sup> $\log \log n$ |
| 1 deletion     | $\log n$  | $\log n - \ell$            |



<sup>1</sup> A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

# Comparison with Classical Channel

- 'Classical'  $\rightarrow \ell = 1$ .
- 'Nanopore'  $\rightarrow \ell \geq 2$ .

|                     | Classical                  | Nanopore                   |
|---------------------|----------------------------|----------------------------|
| 1 substitution      | $\log n$                   | <sup>1</sup> $\log \log n$ |
| 1 deletion          | $\log n$                   | $\log n - \ell$            |
| 1 deletion, 2 reads | <sup>2</sup> $\log \log n$ | ?                          |



<sup>1</sup> A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

<sup>2</sup> J. Chrisnata *et al.*, "Correcting deletions with multiple reads," *TIT*, 2022

# Comparison with Classical Channel

- 'Classical'  $\rightarrow \ell = 1$ .
- 'Nanopore'  $\rightarrow \ell \geq 2$ .

|                     | Classical                  | Nanopore                   |
|---------------------|----------------------------|----------------------------|
| 1 substitution      | $\log n$                   | <sup>1</sup> $\log \log n$ |
| 1 deletion          | $\log n$                   | $\log n - \ell$            |
| 1 deletion, 2 reads | <sup>2</sup> $\log \log n$ | 0                          |



<sup>1</sup> A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

<sup>2</sup> J. Chrisnata *et al.*, "Correcting deletions with multiple reads," *TIT*, 2022

# Correction with Two Reads

## Lemma

When  $\ell \geq 2$ , for any two distinct  $\mathbf{x}, \mathbf{y} \in \Sigma_2^n$ ,

$$|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 1.$$

---

[L01] [V. Levenshtein](#), “Efficient reconstruction of sequences,” *TIT*, 2001

[BYWY24] [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

[CMNY22] [K. Cai et al.](#), “Coding for sequence reconstruction for single edits,” *TIT*, 2022



# Correction with Two Reads

## Lemma

When  $\ell \geq 2$ , for any two distinct  $\mathbf{x}, \mathbf{y} \in \Sigma_2^n$ ,

$$|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 1.$$

Proof sketch:

- [L01]  $\rightarrow$  Distinct  $\mathbf{x}, \mathbf{y}$  have  $|D_1(\mathbf{x}) \cap D_1(\mathbf{y})| \leq 2$ .

---

[L01] V. Levenshtein, "Efficient reconstruction of sequences," *TIT*, 2001

[BYWY24] A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

[CMNY22] K. Cai *et al.*, "Coding for sequence reconstruction for single edits," *TIT*, 2022

# Correction with Two Reads

## Lemma

When  $\ell \geq 2$ , for any two distinct  $\mathbf{x}, \mathbf{y} \in \Sigma_2^n$ ,

$$|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 1.$$

Proof sketch:

- [L01]  $\rightarrow$  Distinct  $\mathbf{x}, \mathbf{y}$  have  $|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 2$ .

---

[L01] V. Levenshtein, "Efficient reconstruction of sequences," *TIT*, 2001

[BYWY24] A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

[CMNY22] K. Cai *et al.*, "Coding for sequence reconstruction for single edits," *TIT*, 2022

# Correction with Two Reads

## Lemma

When  $\ell \geq 2$ , for any two distinct  $\mathbf{x}, \mathbf{y} \in \Sigma_2^n$ ,

$$|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 1.$$

Proof sketch:

- [L01]  $\rightarrow$  Distinct  $\mathbf{x}, \mathbf{y}$  have  $|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 2$ .
- [BYWY24]  $\rightarrow$  For  $\ell \geq 2$ , distinct  $\mathbf{x}$  and  $\mathbf{y}$  satisfy  $d_H(\mathcal{R}(\mathbf{x}), \mathcal{R}(\mathbf{y})) \geq 2$ .

---

[L01] [V. Levenshtein](#), “Efficient reconstruction of sequences,” *TIT*, 2001

[BYWY24] [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

[CMNY22] [K. Cai et al.](#), “Coding for sequence reconstruction for single edits,” *TIT*, 2022

# Correction with Two Reads

## Lemma

When  $\ell \geq 2$ , for any two distinct  $\mathbf{x}, \mathbf{y} \in \Sigma_2^n$ ,

$$|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 1.$$

Proof sketch:

- [L01]  $\rightarrow$  Distinct  $\mathbf{x}, \mathbf{y}$  have  $|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 2$ .
- [BYWY24]  $\rightarrow$  For  $\ell \geq 2$ , distinct  $\mathbf{x}$  and  $\mathbf{y}$  satisfy  $d_H(\mathcal{R}(\mathbf{x}), \mathcal{R}(\mathbf{y})) \geq 2$ .
- [CMNY22]  $\rightarrow |D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| = 2$  holds iff

$$\mathcal{R}(\mathbf{x}) = ( \mathbf{a} \ \alpha\beta\alpha\beta \dots \alpha\beta \ \mathbf{b} )$$

$$\mathcal{R}(\mathbf{y}) = ( \mathbf{a} \ \beta\alpha\beta\alpha \dots \beta\alpha \ \mathbf{b} )$$

[L01] V. Levenshtein, "Efficient reconstruction of sequences," *TIT*, 2001

[BYWY24] A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

[CMNY22] K. Cai *et al.*, "Coding for sequence reconstruction for single edits," *TIT*, 2022

# Correction with Two Reads

## Lemma

When  $\ell \geq 2$ , for any two distinct  $\mathbf{x}, \mathbf{y} \in \Sigma_2^n$ ,

$$|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 1.$$

Proof sketch:

- [L01]  $\rightarrow$  Distinct  $\mathbf{x}, \mathbf{y}$  have  $|D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| \leq 2$ .
- [BYWY24]  $\rightarrow$  For  $\ell \geq 2$ , distinct  $\mathbf{x}$  and  $\mathbf{y}$  satisfy  $d_H(\mathcal{R}(\mathbf{x}), \mathcal{R}(\mathbf{y})) \geq 2$ .
- [CMNY22]  $\rightarrow |D_1(\mathcal{R}(\mathbf{x})) \cap D_1(\mathcal{R}(\mathbf{y}))| = 2$  holds iff

$$\mathcal{R}(\mathbf{x}) = ( \mathbf{a} \ \alpha\beta\alpha\beta \dots \alpha\beta \ \mathbf{b} )$$

$$\mathcal{R}(\mathbf{y}) = ( \mathbf{a} \ \beta\alpha\beta\alpha \dots \beta\alpha \ \mathbf{b} )$$

$\rightarrow$  Never occurs!

[L01] V. Levenshtein, "Efficient reconstruction of sequences," *TIT*, 2001

[BYWY24] A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

[CMNY22] K. Cai *et al.*, "Coding for sequence reconstruction for single edits," *TIT*, 2022

# Reconstruction from Two Reads

- Can reconstruct from two noisy reads with no additional redundancy!

---

[BYWY23] [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” in *ISIT*, 2023

# Reconstruction from Two Reads

- Can reconstruct from two noisy reads with no additional redundancy!

---

**Algorithm:** Reconstruct

---

**Input:**  $n, \ell$ , set  $\{\mathcal{R}', \mathfrak{R}'\} \subseteq D_1(\mathcal{R}(\mathbf{x}))$  for some  $\mathbf{x} \in \Sigma_2^n$

**Output:**  $\mathcal{R}(\mathbf{x})$

---



---

[BYWY23] [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” in *ISIT*, 2023

# Reconstruction from Two Reads

- Can reconstruct from two noisy reads with no additional redundancy!

---

**Algorithm:** Reconstruct

---

**Input:**  $n, \ell$ , set  $\{\mathcal{R}', \mathfrak{R}'\} \subseteq D_1(\mathcal{R}(\mathbf{x}))$  for some  $\mathbf{x} \in \Sigma_2^n$

**Output:**  $\mathcal{R}(\mathbf{x})$

---

```

1 init
2   Let  $i$  and  $j$  be the first and last indices at which  $\mathcal{R}'$  and  $\mathfrak{R}'$  disagree.
3    $\hat{\mathcal{R}}(\mathbf{x}) \leftarrow (\mathcal{R}'_1, \dots, \mathcal{R}'_{i-1}, \mathfrak{R}'_i, \mathcal{R}'_i, \dots, \mathcal{R}'_{n+\ell-2})$ ;
4    $\tilde{\mathcal{R}}(\mathbf{x}) \leftarrow (\mathcal{R}'_1, \dots, \mathcal{R}'_j, \mathfrak{R}'_j, \mathcal{R}'_{j+1}, \dots, \mathcal{R}'_{n+\ell-2})$ .

```

---



---

[BYWY23] [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” in *ISIT*, 2023



# Reconstruction from Two Reads

- Can reconstruct from two noisy reads with no additional redundancy!

---

**Algorithm:** Reconstruct

---

**Input:**  $n, \ell$ , set  $\{\mathcal{R}', \mathfrak{R}'\} \subseteq D_1(\mathcal{R}(\mathbf{x}))$  for some  $\mathbf{x} \in \Sigma_2^n$

**Output:**  $\mathcal{R}(\mathbf{x})$

---

```

1 init
2   Let  $i$  and  $j$  be the first and last indices at which  $\mathcal{R}'$  and  $\mathfrak{R}'$  disagree.
3    $\hat{\mathcal{R}}(\mathbf{x}) \leftarrow (\mathcal{R}'_1, \dots, \mathcal{R}'_{i-1}, \mathfrak{R}'_i, \mathcal{R}'_i, \dots, \mathcal{R}'_{n+\ell-2})$ ;
4    $\tilde{\mathcal{R}}(\mathbf{x}) \leftarrow (\mathcal{R}'_1, \dots, \mathcal{R}'_j, \mathfrak{R}'_j, \mathcal{R}'_{j+1}, \dots, \mathcal{R}'_{n+\ell-2})$ .
5   if  $\hat{\mathcal{R}}(\mathbf{x})$  is the  $\ell$ -read vector of any vector in  $\Sigma_2^n$  then
6      $\mathcal{R}(\mathbf{x}) \leftarrow \hat{\mathcal{R}}(\mathbf{x})$ .

```

---

- Efficient verification process [BYWY23] .

---

[BYWY23] A. Banerjee *et al.*, “Error-correcting codes for nanopore sequencing,” in *ISIT*, 2023

# Reconstruction from Two Reads

- Can reconstruct from two noisy reads with no additional redundancy!

---

**Algorithm:** Reconstruct

---

**Input:**  $n, \ell$ , set  $\{\mathcal{R}', \mathfrak{R}'\} \subseteq D_1(\mathcal{R}(\mathbf{x}))$  for some  $\mathbf{x} \in \Sigma_2^n$

**Output:**  $\mathcal{R}(\mathbf{x})$

---

```

1 init
2   Let  $i$  and  $j$  be the first and last indices at which  $\mathcal{R}'$  and  $\mathfrak{R}'$  disagree.
3    $\hat{\mathcal{R}}(\mathbf{x}) \leftarrow (\mathcal{R}'_1, \dots, \mathcal{R}'_{i-1}, \mathfrak{R}'_i, \mathcal{R}'_i, \dots, \mathcal{R}'_{n+\ell-2})$ ;
4    $\tilde{\mathcal{R}}(\mathbf{x}) \leftarrow (\mathcal{R}'_1, \dots, \mathcal{R}'_j, \mathfrak{R}'_j, \mathcal{R}'_{j+1}, \dots, \mathcal{R}'_{n+\ell-2})$ .
5   if  $\hat{\mathcal{R}}(\mathbf{x})$  is the  $\ell$ -read vector of any vector in  $\Sigma_2^n$  then
6      $\mathcal{R}(\mathbf{x}) \leftarrow \hat{\mathcal{R}}(\mathbf{x})$ .
7   else
8      $\mathcal{R}(\mathbf{x}) \leftarrow \tilde{\mathcal{R}}(\mathbf{x})$ .

```

---

- Efficient verification process [BYWY23] .

---

[BYWY23] [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” in *ISIT*, 2023

Introduction

Channel Model

Minimum Redundancy

Multiple Reads

Conclusion

# Summary

## Results

For a simplified model of nanopore sequencing, we show

- $\log n - \ell - o(1)$  min redundancy needed to correct 1 deletion.
- Explicit construction, optimal up to additive constant.
- $\ell \geq 2 \rightarrow$  No redundancy to recover from two noisy reads.

# Summary

## Results

For a simplified model of nanopore sequencing, we show

- $\log n - \ell - o(1)$  min redundancy needed to correct 1 deletion.
- Explicit construction, optimal up to additive constant.
- $\ell \geq 2 \rightarrow$  No redundancy to recover from two noisy reads.

## Future work

- Multiple deletions & combination with substitutions.
- Levenshtein's sequence reconstruction for  $\ell$ -read vectors.

# Summary

## Results

For a simplified model of nanopore sequencing, we show

- $\log n - \ell - o(1)$  min redundancy needed to correct 1 deletion.
- Explicit construction, optimal up to additive constant.
- $\ell \geq 2 \rightarrow$  No redundancy to recover from two noisy reads.

## Future work

- Multiple deletions & combination with substitutions.
- Levenshtein's sequence reconstruction for  $\ell$ -read vectors.

Thank you!

# References I

- [1] R. Heckel, G. Mikutis, and R. N. Grass, “A characterization of the DNA data storage channel,” *Scientific Reports*, vol. 9, no. 9663, Jul. 2019.
- [2] D. Deamer, M. Akeson, and D. Branton, “Three decades of nanopore sequencing,” *Nat. Biotech.*, vol. 34, no. 5, pp. 518–524, May 2016.
- [3] A. H. Laszlo *et al.*, “Decoding long nanopore sequencing reads of natural DNA,” *Nat. Biotech.*, vol. 32, no. 8, pp. 829–833, Aug. 2014.
- [4] W. Mao, S. N. Diggavi, and S. Kannan, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, vol. 64, no. 4, pp. 3216–3236, Apr. 2018.
- [5] R. Hulett, S. Chandak, and M. Wootters, “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, Jul. 2021, pp. 2465–2470.
- [6] B. McBain, E. Viterbo, and J. Saunderson, “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, Jun. 2022, pp. 216–221.
- [7] Y. M. Chee, A. Vardy, V. K. Vu, and E. Yaakobi, “Coding for transverse-reads in domain wall memories,” in *ISIT*, Jul. 2021, pp. 2924–2929.

## References II

- [8] A. Banerjee, Y. Yehezkeally, A. Wachter-Zeh, and E. Yaakobi, “Error-correcting codes for nanopore sequencing,” *TIT*, 2024.
- [9] O. Yerushalmi, T. Etzion, and E. Yaakobi, “The capacity of the weighted read channel,” in *ISIT*, 2024, (arXiv preprint arXiv:2401.15368).
- [10] Y. M. Chee, K. A. Schouhamer Immink, and V. K. Vu, “Coding scheme for noisy nanopore sequencing with backtracking and skipping errors,” in *ISIT*, 2024.
- [11] A. Fazeli, A. Vardy, and E. Yaakobi, “Generalized sphere packing bound,” *TIT*, vol. 61, no. 5, pp. 2313–2334, May 2015.
- [12] J. Chrisnata, H. M. Kiah, and E. Yaakobi, “Correcting deletions with multiple reads,” *TIT*, vol. 68, no. 11, pp. 7141–7158, Nov. 2022.
- [13] V. Levenshtein, “Efficient reconstruction of sequences,” *TIT*, vol. 47, no. 1, pp. 2–22, Jan. 2001.
- [14] K. Cai, H. M. Kiah, T. T. Nguyen, and E. Yaakobi, “Coding for sequence reconstruction for single edits,” *TIT*, vol. 68, no. 1, pp. 66–79, Jan. 2022.
- [15] A. Banerjee, Y. Yehezkeally, A. Wachter-Zeh, and E. Yaakobi, “Error-correcting codes for nanopore sequencing,” in *ISIT*, Jun. 2023, pp. 364–369.