

Sequential Decoding of Multiple Traces Over the Syndrome Trellis for Synchronization Errors


Anisha Banerjee¹

Joint work with Lorenz Welter¹, Alexandre Graell i Amat²,
Antonia Wachter-Zeh¹ and Eirik Rosnes³

¹Technical University of Munich, Germany

²Chalmers University of Technology, Sweden

³Simula UiB, Norway



April 11, 2025

Outline

Introduction

Channel Model

Reducing Decoder Complexity

Results & Conclusion

Introduction


Channel Model

Reducing Decoder Complexity

Results & Conclusion

Motivation


- Insertions and deletion errors occur
 - ▶ due to improper synchronization.



-
- [HMG19] [R. Heckel et al.](#), “A Characterization of the DNA Data Storage Channel,” *en, Scientific Reports*, 2019
- [F63] [R. Fano](#), “A heuristic discussion of probabilistic decoding,” *TIT*, 1963
- [J69] [F. Jelinek](#), “Fast sequential decoding algorithm using a stack,” *IBM Journal of Research and Development*, 1969

Motivation

- Insertions and deletion errors occur
 - ▶ due to improper synchronization.
 - ▶ in molecular storage paradigms, e.g. DNA storage [HMG19].




[HMG19] [R. Heckel et al.](#), “A Characterization of the DNA Data Storage Channel,” *en, Scientific Reports*, 2019

[F63] [R. Fano](#), “A heuristic discussion of probabilistic decoding,” *TIT*, 1963

[J69] [F. Jelinek](#), “Fast sequential decoding algorithm using a stack,” *IBM Journal of Research and Development*, 1969

Motivation

- Insertions and deletion errors occur
 - ▶ due to improper synchronization.
 - ▶ in molecular storage paradigms, e.g. DNA storage [HMG19].
- May use **convolutional codes** for error correction.




[HMG19] [R. Heckel et al.](#), "A Characterization of the DNA Data Storage Channel," *en, Scientific Reports*, 2019

[F63] [R. Fano](#), "A heuristic discussion of probabilistic decoding," *TIT*, 1963

[J69] [F. Jelinek](#), "Fast sequential decoding algorithm using a stack," *IBM Journal of Research and Development*, 1969

Motivation


- Insertions and deletion errors occur
 - ▶ due to improper synchronization.
 - ▶ in molecular storage paradigms, e.g. DNA storage [HMG19].
- May use **convolutional codes** for error correction.
- **Problem:** High complexity of conventional decoders.



-
- [HMG19] R. Heckel *et al.*, "A Characterization of the DNA Data Storage Channel," *en, Scientific Reports*, 2019
- [F63] R. Fano, "A heuristic discussion of probabilistic decoding," *TIT*, 1963
- [J69] F. Jelinek, "Fast sequential decoding algorithm using a stack," *IBM Journal of Research and Development*, 1969

Motivation

- Insertions and deletion errors occur
 - ▶ due to improper synchronization.
 - ▶ in molecular storage paradigms, e.g. DNA storage [HMG19].
- May use **convolutional codes** for error correction.
- **Problem:** High complexity of conventional decoders.
- **Solution:** Use **sequential decoders**! [F63, J69]
 - ▶ Greedy-ish: only examine 'promising' codewords.
 - ▶ Sub-optimal, but fast.



[HMG19] R. Heckel *et al.*, "A Characterization of the DNA Data Storage Channel," *en, Scientific Reports*, 2019
 [F63] R. Fano, "A heuristic discussion of probabilistic decoding," *TIT*, 1963
 [J69] F. Jelinek, "Fast sequential decoding algorithm using a stack," *IBM Journal of Research and Development*, 1969

Channel Coding

- Most channels corrupt the transmitted message.




Channel Coding

- Most channels corrupt the transmitted message.



- Error-correcting codes to detect & correct errors at receiver.
 - Add redundancy to message intended for transmission.




Channel Coding

- Most channels corrupt the transmitted message.




- Error-correcting codes to detect & correct errors at receiver.
 - Add redundancy to message intended for transmission.



- Ideal: low encoder & decoder complexity!

Convolutional Codes


- Subclass of linear codes:



$$\mathbf{c} = \mathbf{u} \cdot \mathbf{G}$$

Convolutional Codes

- Subclass of linear codes:




- The encoder of a (c, b, m) convolutional code

$$\mathbf{c} = \mathbf{u} \cdot \mathbf{G}$$

Convolutional Codes

- Subclass of linear codes:




- The encoder of a (c, b, m) convolutional code
 - takes b input bits and

$$\mathbf{c} = \mathbf{u} \cdot \mathbf{G}$$

Convolutional Codes

- Subclass of linear codes:




$$\mathbf{c} = \mathbf{u} \cdot \mathbf{G}$$

- The encoder of a (c, b, m) convolutional code
 - ▶ takes b input bits and
 - ▶ produces c output bits,

Convolutional Codes

- Subclass of linear codes:




$$\mathbf{c} = \mathbf{u} \cdot \mathbf{G}$$

- The encoder of a (c, b, m) convolutional code
 - ▶ takes b input bits and
 - ▶ produces c output bits,
 - ▶ which depend on last $b(m + 1)$ input bits (memory).

Convolutional Codes

- Subclass of linear codes:





$$\mathbf{c} = \mathbf{u} \cdot \mathbf{G}$$

- The encoder of a (c, b, m) convolutional code
 - ▶ takes b input bits and
 - ▶ produces c output bits,
 - ▶ which depend on last $b(m + 1)$ input bits (memory).
- Representable as a finite state machine with 2^m states.


Convolutional Codes: Encoding

Example: $[c=2, b=1, m=2]$ convolutional code




Convolutional Codes: Encoding

Example: $[c=2, b=1, m=2]$ convolutional code



Convolutional Codes: Encoding


Example: $[c=2, b=1, m=2]$ convolutional code




- Every path in trellis is a unique codeword.

Convolutional Codes: Encoding

Example: $[c=2, b=1, m=2]$ convolutional code



--- 0
— 1




$$\mathbf{u} = (1 \ 0 \ 1 \ 1 \ 0 \ 0 \ 0 \ 0)$$

$$\mathbf{c} = (11 \ 10 \ 00 \ 01 \ 01 \ 11 \ 00 \ 00)$$

- Every path in trellis is a unique codeword.


Convolutional Codes: Decoding

- Task of decoder: find $\hat{\mathbf{c}}$ closest to \mathbf{r} .




Convolutional Codes: Decoding

- Task of decoder: find $\hat{\mathbf{c}}$ closest to \mathbf{r} .




Example: $[c=2, b=1, m=2]$ convolutional code




Convolutional Codes: Decoding

- Task of decoder: find $\hat{\mathbf{c}}$ closest to \mathbf{r} .



Example: [c=2,b=1,m=2] convolutional code




$$\mathbf{r} = (11 \quad 10 \quad 00 \quad \underline{00} \quad 01 \quad 11 \quad 00)$$


$$\hat{\mathbf{c}} = (11 \quad 10 \quad 00 \quad \underline{01} \quad 01 \quad 11 \quad 00)$$

Convolutional Codes: Decoding

- Task of decoder: find $\hat{\mathbf{c}}$ closest to \mathbf{r} .



Example: $[c=2, b=1, m=2]$ convolutional code



$$\mathbf{r} = (\quad 11 \quad 10 \quad 00 \quad \underline{00} \quad 01 \quad 11 \quad 00 \quad)$$

$$\hat{\mathbf{c}} = (\quad 11 \quad 10 \quad 00 \quad \underline{01} \quad 01 \quad 11 \quad 00 \quad)$$

- BCJR decoder yields $P(c_i | \mathbf{r})$.

$$\begin{aligned} \text{Complexity} &\propto (\# \text{ Trellis states}) \cdot (\# \text{ Outgoing edges per state}) \\ &\propto 2^m \cdot 2^b \end{aligned}$$

Introduction

Channel Model

Reducing Decoder Complexity

Results & Conclusion

Channel Model

- Permits insertions, deletions and substitutions at random positions.
→ Denote as '**IDS channel**'.

[DM01] [M. C. Davey](#) and [D. J. C. MacKay](#), "Reliable communication over channels with insertions, deletions, and substitutions," *TIT*, 2001

Channel Model

- Permits insertions, deletions and substitutions at random positions.
→ Denote as '**IDS channel**'.
- Specified by insertion, deletion and substitution probabilities, i.e., p_I , p_D and p_S .

[DM01] [M. C. Davey](#) and [D. J. C. MacKay](#), "Reliable communication over channels with insertions, deletions, and substitutions," *TIT*, 2001


Channel Model

- Permits insertions, deletions and substitutions at random positions.
→ Denote as '**IDS channel**'.
- Specified by insertion, deletion and substitution probabilities, i.e., p_I , p_D and p_S .
- Modeled as **finite-state machine** [DM01].
 - ▶ Let channel input be $\mathbf{x} = (x_1, \dots, x_T)$.
 - ▶ When x_i awaits transmission, four events possible.

[DM01] [M. C. Davey and D. J. C. MacKay](#), "Reliable communication over channels with insertions, deletions, and substitutions," *TIT*, 2001

Channel Model

- Permits insertions, deletions and substitutions at random positions.
→ Denote as '**IDS channel**'.
- Specified by insertion, deletion and substitution probabilities, i.e., p_I , p_D and p_S .
- Modeled as **finite-state machine** [DM01].
 - ▶ Let channel input be $\mathbf{x} = (x_1, \dots, x_T)$.
 - ▶ When x_i awaits transmission, four events possible.



[DM01] [M. C. Davey and D. J. C. MacKay](#), "Reliable communication over channels with insertions, deletions, and substitutions," *TIT*, 2001

Adapting decoders

- **Aim:** To account for insertions & deletions, use '**drift state**' [DM01, BF15].
 → Let $d_t = \text{\#received bits} - \text{\#transmitted bits}$, at time t .

[DM01] M. C. Davey and D. J. C. MacKay, "Reliable communication over channels with insertions, deletions, and substitutions," *TIT*, 2001


[BF15] V. Buttigieg and N. Farrugia, "Improved bit error rate performance of convolutional codes with synchronization errors," in *Proc. Int. Conf. Comm.*, 2015

[MLWRA23] I. Maarouf *et al.*, "Concatenated codes for multiple reads of a dna sequence," *TIT*, 2023

Adapting decoders

- **Aim:** To account for insertions & deletions, use ‘**drift state**’ [DM01, BF15].

→ Let $d_t = \text{\#received bits} - \text{\#transmitted bits}$, at time t .



[DM01] M. C. Davey and D. J. C. MacKay, “Reliable communication over channels with insertions, deletions, and substitutions,” *TIT*, 2001



[BF15] V. Buttigieg and N. Farrugia, “Improved bit error rate performance of convolutional codes with synchronization errors,” in *Proc. Int. Conf. Comm.*, 2015

[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

Adapting decoders

- Aim:** To account for insertions & deletions, use ‘**drift state**’ [DM01, BF15].

→ Let $d_t = \text{\#received bits} - \text{\#transmitted bits}$, at time t .



- Decoding $M > 1$ received sequences jointly. [MLWRA23]

[DM01] M. C. Davey and D. J. C. MacKay, “Reliable communication over channels with insertions, deletions, and substitutions,” *TIT*, 2001



[BF15] V. Buttigieg and N. Farrugia, “Improved bit error rate performance of convolutional codes with synchronization errors,” in *Proc. Int. Conf. Comm.*, 2015

[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

Adapting decoders

- Aim:** To account for insertions & deletions, use ‘**drift state**’ [DM01, BF15].

→ Let $d_t = \text{\#received bits} - \text{\#transmitted bits}$, at time t .



- Decoding $M > 1$ received sequences jointly. [MLWRA23]

Complexity of BCJR decoding $\propto (\text{\# Trellis states}) \cdot (\text{\# Outgoing edges per state})$

$$\propto (2^m D^M) \cdot (2^b \delta^M),$$

where $D = \text{\#drift states}$ and $\delta = \text{\#insdels per edge}$.

[DM01] M. C. Davey and D. J. C. MacKay, “Reliable communication over channels with insertions, deletions, and substitutions,” *TIT*, 2001

[BF15] V. Buttigieg and N. Farrugia, “Improved bit error rate performance of convolutional codes with synchronization errors,” in *Proc. Int. Conf. Comm.*, 2015

[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

Introduction

Channel Model

Reducing Decoder Complexity

Results & Conclusion

Reducing decoder complexity

$$\text{Complexity} \propto 2^{m+b} \cdot D^M \cdot \delta^M$$

[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

[BLW24] A. Banerjee *et al.*, “Sequential decoding of multiple sequences for synchronization errors,” *TCOMM*, 2024

Reducing decoder complexity

$$\text{Complexity} \propto 2^{m+b} \cdot D^M \cdot \delta^M$$

- **Separate-BCJR** [MLWRA23]

- ▶ For each received sequence \mathbf{y}_i , computes $P(c_j|\mathbf{y}_i)$.
- ▶ Aggregates output of all M decoding operations.

$$\text{Complexity} \propto M \cdot 2^{m+b} \cdot D \cdot \delta$$

[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

[BLW24] A. Banerjee *et al.*, “Sequential decoding of multiple sequences for synchronization errors,” *TCOMM*, 2024

Reducing decoder complexity

$$\text{Complexity} \propto 2^{m+b} \cdot D^M \cdot \delta^M$$


- **Separate-BCJR** [MLWRA23]

- ▶ For each received sequence \mathbf{y}_i , computes $P(c_j|\mathbf{y}_i)$.
- ▶ Aggregates output of all M decoding operations.

$$\text{Complexity} \propto M \cdot 2^{m+b} \cdot D \cdot \delta$$

- **Joint sequential decoding** [BLW24]

- ▶ Suboptimal, greedy search in a *tree*.



[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

[BLW24] A. Banerjee *et al.*, “Sequential decoding of multiple sequences for synchronization errors,” *TCOMM*, 2024

Reducing decoder complexity

$$\text{Complexity} \propto 2^{m+b} \cdot D^M \cdot \delta^M$$


- **Separate-BCJR** [MLWRA23]

- For each received sequence \mathbf{y}_i , computes $P(c_j|\mathbf{y}_i)$.
- Aggregates output of all M decoding operations.

$$\text{Complexity} \propto M \cdot 2^{m+b} \cdot D \cdot \delta$$

- **Joint sequential decoding** [BLW24]

- Suboptimal, greedy search in a *tree*.



[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

[BLW24] A. Banerjee *et al.*, “Sequential decoding of multiple sequences for synchronization errors,” *TCOMM*, 2024

Reducing decoder complexity

$$\text{Complexity} \propto 2^{m+b} \cdot D^M \cdot \delta^M$$

- **Separate-BCJR** [MLWRA23]


- For each received sequence \mathbf{y}_i , computes $P(c_j|\mathbf{y}_i)$.
- Aggregates output of all M decoding operations.

$$\text{Complexity} \propto M \cdot 2^{m+b} \cdot D \cdot \delta$$

- **Joint sequential decoding** [BLW24]

- Suboptimal, greedy search in a *tree*.

Complexity $\propto 2^b \cdot \delta^M$



[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

[BLW24] A. Banerjee *et al.*, “Sequential decoding of multiple sequences for synchronization errors,” *TCOMM*, 2024

Reducing decoder complexity

Complexity $\propto 2^{m+b} \cdot D^M \cdot \delta^M$

- **Separate-BCJR** [MLWRA23]

- For each received sequence \mathbf{y}_i , computes $P(c_j|\mathbf{y}_i)$.
- Aggregates output of all M decoding operations.

$$\text{Complexity} \propto M \cdot 2^{m+b} \cdot D \cdot \delta$$


- **Joint sequential decoding** [BLW24]

- Suboptimal, greedy search in a *tree*.

Complexity $\propto 2^b \cdot \delta^M$

- **Problem:** Too complex for high-rate codes.

- **Solution:** Alternate representation of tree/trellis!



[MLWRA23] I. Maarouf *et al.*, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, 2023

[BLW24] A. Banerjee *et al.*, “Sequential decoding of multiple sequences for synchronization errors,” *TCOMM*, 2024

Syndrome Trellis


- Based on the dual space of the convolutional code. [S94]
 - ▶ Each edge denotes one codeword symbol $\rightarrow \leq 2$ outgoing edges per node.

[S94] V. Sidorenko and V. Zyablov, "Decoding of convolutional codes using a syndrome trellis," *TIT*, 1994

Syndrome Trellis

- Based on the dual space of the convolutional code. [S94]
 - Each edge denotes one codeword symbol $\rightarrow \leq 2$ outgoing edges per node.

Example: $[c=2, b=1, m=2]$ convolutional code




[S94] V. Sidorenko and V. Zyablov, "Decoding of convolutional codes using a syndrome trellis," *TIT*, 1994

Syndrome Trellis

- Based on the dual space of the convolutional code. [S94]
 - Each edge denotes one codeword symbol $\rightarrow \leq 2$ outgoing edges per node.

Example: $[c=2, b=1, m=2]$ convolutional code




[S94] V. Sidorenko and V. Zyablov, "Decoding of convolutional codes using a syndrome trellis," *TIT*, 1994

Syndrome Trellis

- Based on the dual space of the convolutional code. [S94]
 - Each edge denotes one codeword symbol $\rightarrow \leq 2$ outgoing edges per node.

Example: $[c=2, b=1, m=2]$ convolutional code




[S94] V. Sidorenko and V. Zyablov, "Decoding of convolutional codes using a syndrome trellis," *TIT*, 1994

Syndrome Trellis

- Based on the dual space of the convolutional code. [S94]
 - Each edge denotes one codeword symbol $\rightarrow \leq 2$ outgoing edges per node.

Example: $[c=2, b=1, m=2]$ convolutional code




- Complexity comparison
 - Separate-BCJR:** $M \cdot 2^{m+b} \cdot D \cdot \delta$
 - Joint sequential decoding:** $2^b \cdot \delta^M$

[S94] V. Sidorenko and V. Zyablov, "Decoding of convolutional codes using a syndrome trellis," *TIT*, 1994

Syndrome Trellis

- Based on the dual space of the convolutional code. [S94]
 - Each edge denotes one codeword symbol $\rightarrow \leq 2$ outgoing edges per node.

Example: $[c=2, b=1, m=2]$ convolutional code



- Complexity comparison
 - Separate-BCJR:** $M \cdot 2^{m+b} \cdot D \cdot \delta \rightarrow M \cdot 2^{m'+1} \cdot D \cdot \delta$
 - Joint sequential decoding:** $2^b \cdot \delta^M \rightarrow 2 \cdot \delta^M$

[S94] V. Sidorenko and V. Zyablov, "Decoding of convolutional codes using a syndrome trellis," *TIT*, 1994

Introduction


Channel Model

Reducing Decoder Complexity

Results & Conclusion

Bit Error Rates (BER)

$M = 2$, Deletions only




Code	$[c, b]$	d_{free}
CC1	$[10, 7]$	6
CC2	$[11, 9]$	5

Table: Code Parameters [RY04]


[RY04] E. Rosnes and Ø. Ytrehus, "On maximum length convolutional codes under a trellis complexity constraint," *Journal of Complexity*, 2004

BER & Complexity

CC2, $N = 139$



Complexity reduction wrt Sep.-BCJR



Conclusion

- Joint sequential decoding v/s separate-BCJR decoding.
 - ▶ Under low-noise, the latter wins.
 - ▶ At higher noise levels, the former can win.

Conclusion

- Joint sequential decoding v/s separate-BCJR decoding.
 - ▶ Under low-noise, the latter wins.
 - ▶ At higher noise levels, the former can win.
- Future work: theoretical analysis of computational complexity.

Conclusion

- Joint sequential decoding v/s separate-BCJR decoding.
 - ▶ Under low-noise, the latter wins.
 - ▶ At higher noise levels, the former can win.
- Future work: theoretical analysis of computational complexity.

Thank you!

References I

- [1] R. Heckel, G. Mikutis, and R. N. Grass, “A Characterization of the DNA Data Storage Channel,” *Scientific Reports*, vol. 9, no. 1, p. 9663, Dec. 2019.
- [2] R. Fano, “A heuristic discussion of probabilistic decoding,” *TIT*, vol. 9, no. 2, pp. 64–74, Apr. 1963.
- [3] F. Jelinek, “Fast sequential decoding algorithm using a stack,” *IBM Journal of Research and Development*, vol. 13, no. 6, pp. 675–685, Nov. 1969.
- [4] L. Bahl, J. Cocke, F. Jelinek, and J. Raviv, “Optimal decoding of linear codes for minimizing symbol error rate,” *TIT*, vol. 20, no. 2, pp. 284–287, Mar. 1974.
- [5] M. C. Davey and D. J. C. MacKay, “Reliable communication over channels with insertions, deletions, and substitutions,” *TIT*, vol. 47, no. 2, pp. 687–698, Feb. 2001.
- [6] V. Buttigieg and N. Farrugia, “Improved bit error rate performance of convolutional codes with synchronization errors,” in *Proc. Int. Conf. Comm.*, Jun. 2015, pp. 4077–4082.
- [7] I. Maarouf, A. Lenz, L. Welter, A. Wachter-Zeh, E. Rosnes, and A. G. i Amat, “Concatenated codes for multiple reads of a dna sequence,” *TIT*, vol. 69, no. 2, pp. 910–927, Feb. 2023.

References II

- [8] A. Banerjee, A. Lenz, and A. Wachter-Zeh, “Sequential decoding of multiple sequences for synchronization errors,” *TCOMM*, vol. 72, no. 11, pp. 6660–6676, Nov. 2024.
- [9] V. Sidorenko and V. Zyablov, “Decoding of convolutional codes using a syndrome trellis,” *TIT*, vol. 40, no. 5, pp. 1663–1666, Sep. 1994.
- [10] E. Rosnes and Ø. Ytrehus, “On maximum length convolutional codes under a trellis complexity constraint,” *Journal of Complexity*, vol. 20, no. 2-3, pp. 372–403, Apr. 2004.