


Correcting Multiple Substitutions in Nanopore-Sequencing Reads

Anisha Banerjee¹, **Yonatan Yehezkeally**²,
Antonia Wachter-Zeh¹, and Eitan Yaakobi³

¹Technical University of Munich
Institute for Communications Engineering

²Newcastle University, School of Computing

³Technion – Israel Institute of Technology
Department of Computer Science



TUM Uhrenturm



Funded by
the European Union



Biotechnology and
Biological Sciences
Research Council

June 24, 2025

Outline

Introduction

Channel Model

Minimum Redundancy

Conclusion

Introduction

Channel Model

Minimum Redundancy

Conclusion

Motivation

- Need for dense, reliable, robust storage media
 - ▶ Molecular storage paradigms e.g., *DNA storage*.¹



¹ R. Heckel *et al.*, “A characterization of the DNA data storage channel,” *Scientific Reports*, 2019

² D. Deamer *et al.*, “Three decades of nanopore sequencing,” *Nat. Biotech.*, 2016

² A. H. Laszlo *et al.*, “Decoding long nanopore sequencing reads of natural DNA,” *Nat. Biotech.*, 2014

Motivation

- Need for dense, reliable, robust storage media
 - ▶ Molecular storage paradigms e.g., *DNA storage*.¹
- Faster, cheaper sequencers in development.




¹ R. Heckel *et al.*, “A characterization of the DNA data storage channel,” *Scientific Reports*, 2019

² D. Deamer *et al.*, “Three decades of nanopore sequencing,” *Nat. Biotech.*, 2016

² A. H. Laszlo *et al.*, “Decoding long nanopore sequencing reads of natural DNA,” *Nat. Biotech.*, 2014

Motivation

- Need for dense, reliable, robust storage media
 - ▶ Molecular storage paradigms e.g., *DNA storage*.¹
- Faster, cheaper sequencers in development.
- Nanopore sequencing²:
 - + Can read longer DNA strands
 - + More portable
 - High error rates



Source: "Decoding DNA with a pocket-sized sequencer," *Science in School*. <https://www.scienceinschool.org/article/2018/decoding-dna-pocket-sized-sequencer/>


¹ R. Heckel *et al.*, "A characterization of the DNA data storage channel," *Scientific Reports*, 2019

² D. Deamer *et al.*, "Three decades of nanopore sequencing," *Nat. Biotech.*, 2016

² A. H. Laszlo *et al.*, "Decoding long nanopore sequencing reads of natural DNA," *Nat. Biotech.*, 2014

Motivation

- Need for dense, reliable, robust storage media
 - ▶ Molecular storage paradigms e.g., *DNA storage*.¹
- Faster, cheaper sequencers in development.
- Nanopore sequencing²:
 - + Can read longer DNA strands
 - + More portable
 - High error rates
- *Aim*: Design coding techniques tailored for nanopore sequencing!




Source: "Decoding DNA with a pocket-sized sequencer," *Science in School*. <https://www.scienceinschool.org/article/2018/decoding-dna-pocket-sized-sequencer/>

¹ R. Heckel *et al.*, "A characterization of the DNA data storage channel," *Scientific Reports*, 2019

² D. Deamer *et al.*, "Three decades of nanopore sequencing," *Nat. Biotech.*, 2016

² A. H. Laszlo *et al.*, "Decoding long nanopore sequencing reads of natural DNA," *Nat. Biotech.*, 2014


Nanopore Sequencing



Source: "What is Oxford Nanopore Technology (ONT) sequencing?," <https://www.yourgenome.org/facts/what-is-oxford-nanopore-technology-ont-sequencing/>

[MDK18] W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Nanopore Sequencing



Source: "What is Oxford Nanopore Technology (ONT) sequencing?," <https://www.yourgenome.org/facts/what-is-oxford-nanopore-technology-ont-sequencing/>

- Sources of noise [MDK18] :
 - ▶ Nanopore holds $\ell > 1$ nucleotides at a time \rightarrow Intersymbol interference (ISI)!
 - ▶ Strand moves irregularly \rightarrow backtracking & skipping.
 - ▶ Noisy measurements

[MDK18] W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Prior Work

- Channel model & understanding capacity: [MDK18] , [HCW21] , [MVS22] , [RW25]

[MDK18] [W. Mao *et al.*](#), “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018
[HCW21] [R. Hulett *et al.*](#), “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, 2021
[MVS22] [B. McBain *et al.*](#), “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, 2022
[RW25] [A. Rameshwar and N. Weinberger](#), “On achievable rates over noisy nanopore channels,” in *ISIT*, 2025
[CVVY21] [Y. M. Chee *et al.*](#), “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

Prior Work

- Channel model & understanding capacity: [MDK18] , [HCW21] , [MVS22] , [RW25]
- Similar channel model for racetrack memories: [CVVY21]

[MDK18] [W. Mao *et al.*](#), “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018
[HCW21] [R. Hulett *et al.*](#), “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, 2021
[MVS22] [B. McBain *et al.*](#), “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, 2022
[RW25] [A. Rameshwar and N. Weinberger](#), “On achievable rates over noisy nanopore channels,” in *ISIT*, 2025
[CVVY21] [Y. M. Chee *et al.*](#), “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

Prior Work

- Channel model & understanding capacity: [MDK18] , [HCW21] , [MVS22] , [RW25]
- Similar channel model for racetrack memories: [CVVY21]
- [MDK18] & [CVVY21] inspired a **simplified model** of nanopore sequencing.

[MDK18] [W. Mao *et al.*](#), “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, 2018
[HCW21] [R. Hulett *et al.*](#), “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, 2021
[MVS22] [B. McBain *et al.*](#), “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, 2022
[RW25] [A. Rameshwar and N. Weinberger](#), “On achievable rates over noisy nanopore channels,” in *ISIT*, 2025
[CVVY21] [Y. M. Chee *et al.*](#), “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021


Introduction

Channel Model

Minimum Redundancy


Conclusion

Simplified Model



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model



We model


- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:

- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:

- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:


- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:


- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:


- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:


- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:


- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:


- Input $x \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:


- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:

- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model




We model

- ISI as length- ℓ -sliding window
- Measurement noise as substitutions

Assumptions:

- Input $\mathbf{x} \in \{0, 1\}^n$
- DMC maps ℓ -mers to Hamming weights.

Example ($\ell = 3$)



W. Mao *et al.*, "Models and information-theoretic bounds for nanopore sequencing," *TIT*, 2018

Simplified Model

Definition

The ℓ -**read vector** of any $\mathbf{x} \in \Sigma_2^n$ is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where $\text{wt}(\cdot)$ denotes Hamming weight.

Y. M. Chee *et al.*, "Coding for transverse-reads in domain wall memories," in *ISIT*, 2021

Simplified Model

Definition

The ℓ -**read vector** of any $\mathbf{x} \in \Sigma_2^n$ is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where $\text{wt}(\cdot)$ denotes Hamming weight.

- Read vectors have special properties.



Y. M. Chee *et al.*, "Coding for transverse-reads in domain wall memories," in *ISIT*, 2021

Simplified Model

Definition

The ℓ -**read vector** of any $\mathbf{x} \in \Sigma_2^n$ is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where $\text{wt}(\cdot)$ denotes Hamming weight.

- Read vectors have special properties.

$$\blacktriangleright |\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1}| \leq 1 \iff \mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$$



Y. M. Chee *et al.*, "Coding for transverse-reads in domain wall memories," in *ISIT*, 2021

Simplified Model

Definition

The ℓ -**read vector** of any $\mathbf{x} \in \Sigma_2^n$ is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where $\text{wt}(\cdot)$ denotes Hamming weight.

- Read vectors have special properties.

▶ $|\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1}| \leq 1$,

▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0 \iff \sum_i \mathcal{R}(\mathbf{x})_i = \ell \cdot \text{wt}(\mathbf{x})$



Y. M. Chee *et al.*, “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

Simplified Model

Definition

The ℓ -**read vector** of any $\mathbf{x} \in \Sigma_2^n$ is

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(x_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(x_n))$$

where $\text{wt}(\cdot)$ denotes Hamming weight.

- Read vectors have special properties.
 - ▶ $|\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1}| \leq 1$,
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$, etc.
- Can correct substitution errors of abs. value ≥ 2 .



Y. M. Chee *et al.*, “Coding for transverse-reads in domain wall memories,” in *ISIT*, 2021

Prior Work

- Error correction for the *read vector* channel
 - ▶ [BYWY24] , [BYWY25] , [CIV24] , [SG25] , [YYS25]
- *Weighted Read Vector channel* [YHEY24]

[BYWY24] A. Banerjee *et al.*, “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

[BYWY25] A. Banerjee *et al.*, “Correcting a single deletion in reads from a nanopore sequencer,” in *ISIT*, 2024

[CIV24] Y. M. Chee *et al.*, “Coding scheme for noisy nanopore sequencing with backtracking and skipping errors,” in *ISIT*, 2024

[SG25] Y. Sun and G. Ge, “Bounds and constructions of ℓ -read codes under the hamming metric,” *TIT*, 2025

[YYS25] W. Yu *et al.*, “On the asymptotic rate of optimal codes that correct tandem duplications for nanopore sequencing,” *TIT*, 2025

[YHEY24] O. Yerushalmi *et al.*, “The capacity of the weighted read channel,” in *ISIT*, 2024

ℓ -Read Codes

- Read vectors possess inherent redundancy.
 - ▶ May aid in error correction!

ℓ -Read Codes

- Read vectors possess inherent redundancy.
 - ▶ May aid in error correction!

Definition [Error-correcting Code]

\mathcal{C} is an ℓ -**read code** if for all $\mathbf{x}, \mathbf{y} \in \mathcal{C}$,

$$E(\mathcal{R}(\mathbf{x})) \cap E(\mathcal{R}(\mathbf{y})) = \emptyset,$$

where $E(\cdot)$ is the error ball.

Comparison with the Classical Channel

- Do ℓ -**read codes** require lesser redundancy?

¹⁵ [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

¹⁶ [A. Banerjee et al.](#), “Correcting a single deletion in reads from a nanopore sequencer,” in *ISIT*, 2024

Comparison with the Classical Channel

- Do ℓ -**read codes** require lesser redundancy?
 - ▶ ‘Classical’ $\rightarrow \ell = 1$.
 - ▶ ‘Nanopore’ $\rightarrow \ell \geq 2$.

¹⁵ [A. Banerjee et al.](#), “Error-correcting codes for nanopore sequencing,” *TIT*, 2024

¹⁶ [A. Banerjee et al.](#), “Correcting a single deletion in reads from a nanopore sequencer,” in *ISIT*, 2024

Comparison with the Classical Channel

- Do ℓ -read codes require lesser redundancy?
 - 'Classical' $\rightarrow \ell = 1$.
 - 'Nanopore' $\rightarrow \ell \geq 2$.

	Classical	Nanopore
1 substitution ¹⁵	$\log n$	$\log \log n$
1 deletion ¹⁶	$\log n$	$\log n - \ell$
1 deletion, 2 reads ¹⁶	$\log \log n$	0



¹⁵ A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

¹⁶ A. Banerjee *et al.*, "Correcting a single deletion in reads from a nanopore sequencer," in *ISIT*, 2024

Comparison with the Classical Channel

- Do ℓ -read codes require lesser redundancy?
 - ▶ 'Classical' $\rightarrow \ell = 1$.
 - ▶ 'Nanopore' $\rightarrow \ell \geq 2$.

	Classical	Nanopore
1 substitution ¹⁵	$\log n$	$\log \log n$
1 deletion ¹⁶	$\log n$	$\log n - \ell$
1 deletion, 2 reads ¹⁶	$\log \log n$	0
$t \geq 2$ substitutions	$t \log n$?



¹⁵ A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

¹⁶ A. Banerjee *et al.*, "Correcting a single deletion in reads from a nanopore sequencer," in *ISIT*, 2024

Comparison with the Classical Channel

- Do ℓ -read codes require lesser redundancy?
 - ▶ 'Classical' $\rightarrow \ell = 1$.
 - ▶ 'Nanopore' $\rightarrow \ell \geq 2$.

	Classical	Nanopore
1 substitution ¹⁵	$\log n$	$\log \log n$
1 deletion ¹⁶	$\log n$	$\log n - \ell$
1 deletion, 2 reads ¹⁶	$\log \log n$	0
$t \geq 2$ substitutions	$t \log n$	$t \log n$



¹⁵ A. Banerjee *et al.*, "Error-correcting codes for nanopore sequencing," *TIT*, 2024

¹⁶ A. Banerjee *et al.*, "Correcting a single deletion in reads from a nanopore sequencer," in *ISIT*, 2024

Introduction

Channel Model

Minimum Redundancy

Conclusion

Minimum Redundancy

Theorem

The redundancy of any **t -substitution ℓ -read code**, for $t, \ell \geq 2$, is bounded from below by

$$t \log n - O(1).$$

Minimum Redundancy

Theorem

The redundancy of any **t -substitution ℓ -read code**, for $t, \ell \geq 2$, is bounded from below by

$$t \log n - O(1).$$

- But for $t = 1$, we need $\log \log n - o(1)$ redundant bits.

Minimum Redundancy

Theorem

The redundancy of any **t -substitution ℓ -read code**, for $t, \ell \geq 2$, is bounded from below by

$$t \log n - O(1).$$

- But for $t = 1$, we need $\log \log n - o(1)$ redundant bits.

Why? 😓

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - ▶ $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - ▶ $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - ▶ $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1,$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0,$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1,$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2 \neq x_4$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2$ ✗
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2$ ✗
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

$$x'_6 = 0$$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2$ ✗
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

$$x'_5 = 0, x'_6 = 0$$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2$ ✗
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

$$x'_4 = 1, x'_5 = 0, x'_6 = 0$$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2 \neq 1$
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

$$x'_3 = 1, x'_4 = 1, x'_5 = 0, x'_6 = 0$$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2 \neq$
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

$$x'_2 = 1, x'_3 = 1, x'_4 = 1, x'_5 = 0, x'_6 = 0$$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2 \mathbf{x}$
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

- $x'_1 = 0, x'_2 = 1, x'_3 = 1, x'_4 = 1, x'_5 = 0, x'_6 = 0$

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2 \mathbf{X}$
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

- $x'_1 = 0, x'_2 = 1, x'_3 = 1, x'_4 = 1, x'_5 = 0, x'_6 = 0$
- No inconsistency, error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_8)$.

Reconstruction from Noisy Read Vector

- Recall that for any $\mathbf{x} \in \Sigma_2^n$,
 - $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ and $x_i = 0$ for $i \notin [1, n]$.
- Can reconstruct \mathbf{x} from $\mathcal{R}(\mathbf{x})$ with
 - $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.

Example ($\ell = 3$)

$$\mathcal{R}(\mathbf{x}) \xrightarrow{1\text{substitution}} \mathcal{R}(\mathbf{x})' = (1, 1, 2, 3, 2, 1, 0, 0)$$

Left to right reconstruction:

- $x'_1 = 1, x'_2 = 0, x'_3 = 1, x'_4 = 2 \mathbf{X}$
- Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Right to left reconstruction:

- $x'_1 = 0, x'_2 = 1, x'_3 = 1, x'_4 = 1, x'_5 = 0, x'_6 = 0$
- No inconsistency, error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_8)$.

Error in $(\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_4)$.

Reconstruction from Noisy Read Vector

- Recall that
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - ▶ Only ± 1 errors are non-trivial to correct.

Reconstruction from Noisy Read Vector

- Recall that
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - ▶ Only ± 1 errors are non-trivial to correct.
- Thus 1 substitution is detectable

Reconstruction from Noisy Read Vector

- Recall that
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - ▶ Only ± 1 errors are non-trivial to correct.
- Thus 1 substitution is detectable & **localizable!**

Reconstruction from Noisy Read Vector

- Recall that
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - ▶ Only ± 1 errors are non-trivial to correct.
- Thus 1 substitution is detectable & localizable!
 - ▶ *But not under multiple substitutions!*

Reconstruction from Noisy Read Vector

- Recall that
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - ▶ Only ± 1 errors are non-trivial to correct.
- Thus 1 substitution is detectable & localizable!
 - ▶ *But not under multiple substitutions!*

Example ($\ell = 3$)

$$\mathbf{x} = (1, 0, 1, 1, 0, 0), \quad \mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, 2, 1, 0, 0)$$

$$\mathbf{y} = (0, 1, 1, 0, 1, 0), \quad \mathcal{R}(\mathbf{y}) = (0, 1, 2, 2, 2, 1, 1, 0)$$

$$d_H(\mathcal{R}(\mathbf{x}), \mathcal{R}(\mathbf{y})) = 2$$

Reconstruction from Noisy Read Vector

- Recall that
 - $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - Only ± 1 errors are non-trivial to correct.
- Thus 1 substitution is detectable & localizable!
 - But not under multiple substitutions!*

Example ($\ell = 3$)

$$\mathbf{x} = (1, 0, 1, 1, 0, 0), \quad \mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, 2, 1, 0, 0)$$

$$\mathbf{y} = (0, 1, 1, 0, 1, 0), \quad \mathcal{R}(\mathbf{y}) = (0, 1, 2, 2, 2, 1, 1, 0)$$

$$d_H(\mathcal{R}(\mathbf{x}), \mathcal{R}(\mathbf{y})) = 2$$

Reconstruction from Noisy Read Vector

- Recall that
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - ▶ Only ± 1 errors are non-trivial to correct.
- Thus 1 substitution is detectable & localizable!
 - ▶ *But not under multiple substitutions!*

Example ($\ell = 3$)

$$\mathbf{x} = (1, 0, 1, 1, 0, 0), \quad \mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, 2, 1, 0, 0)$$

$$\mathbf{y} = (0, 1, 1, 0, 1, 0), \quad \mathcal{R}(\mathbf{y}) = (0, 1, 2, 2, 2, 1, 1, 0)$$

$$d_H(\mathcal{R}(\mathbf{x}), \mathcal{R}(\mathbf{y})) = 2$$

- 2 substitutions can lead to a valid ℓ -read vector

Reconstruction from Noisy Read Vector

- Recall that
 - ▶ $\sum_i \mathcal{R}(\mathbf{x})_i \bmod \ell = 0$
 - ▶ Only ± 1 errors are non-trivial to correct.
- Thus 1 substitution is detectable & localizable!
 - ▶ *But not under multiple substitutions!*

Example ($\ell = 3$)

$$\mathbf{x} = (1, 0, 1, 1, 0, 0), \quad \mathcal{R}(\mathbf{x}) = (1, 1, 2, 2, 2, 1, 0, 0)$$

$$\mathbf{y} = (0, 1, 1, 0, 1, 0), \quad \mathcal{R}(\mathbf{y}) = (0, 1, 2, 2, 2, 1, 1, 0)$$

$$d_H(\mathcal{R}(\mathbf{x}), \mathcal{R}(\mathbf{y})) = 2$$

- 2 substitutions can lead to a valid ℓ -read vector \implies can't localize!

Naive Construction

Definition (Read vector)

The ℓ -read vector of any $\mathbf{x} \in \Sigma_2^n$ is of length $n + \ell - 1$ and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ where for $j \notin [n]$, let $x_j = 0$.

Naive Construction

Definition (Read vector)

The ℓ -read vector of any $\mathbf{x} \in \Sigma_2^n$ is of length $n + \ell - 1$ and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ where for $j \notin [n]$, let $x_j = 0$.

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}.$

Naive Construction

Definition (Read vector)

The ℓ -read vector of any $\mathbf{x} \in \Sigma_2^n$ is of length $n + \ell - 1$ and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ where for $j \notin [n]$, let $x_j = 0$.

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.
- \mathbf{x} uniquely determined from n -prefix of $\mathcal{R}(\mathbf{x})$.

Naive Construction

Definition (Read vector)

The ℓ -read vector of any $\mathbf{x} \in \Sigma_2^n$ is of length $n + \ell - 1$ and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ where for $j \notin [n]$, let $x_j = 0$.

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.
- \mathbf{x} uniquely determined from n -prefix of $\mathcal{R}(\mathbf{x}) \bmod 2$

Naive Construction

Definition (Read vector)

The ℓ -read vector of any $\mathbf{x} \in \Sigma_2^n$ is of length $n + \ell - 1$ and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ where for $j \notin [n]$, let $x_j = 0$.

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.
- \mathbf{x} uniquely determined from n -prefix of $\mathcal{R}(\mathbf{x}) \bmod 2 \leftarrow$ Use any t -substitution-correcting code!

Naive Construction

Definition (Read vector)

The ℓ -read vector of any $\mathbf{x} \in \Sigma_2^n$ is of length $n + \ell - 1$ and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ where for $j \notin [n]$, let $x_j = 0$.

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.
- \mathbf{x} uniquely determined from n -prefix of $\mathcal{R}(\mathbf{x}) \bmod 2 \leftarrow$ Use any t -substitution-correcting code!

Construction (t -substitution- ℓ -read code)

$$\{\mathbf{x} \in \Sigma_2^n : (\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_n) \bmod 2 \in \mathcal{C}(n, t)\},$$

where $\mathcal{C}(n, t) \subset \Sigma_2^n$ is a t -substitution-correcting code.

Naive Construction

Definition (Read vector)

The ℓ -read vector of any $\mathbf{x} \in \Sigma_2^n$ is of length $n + \ell - 1$ and denoted by

$$\mathcal{R}(\mathbf{x}) = (\text{wt}(\mathbf{x}_1), \text{wt}(\mathbf{x}_1^2), \dots, \text{wt}(\mathbf{x}_{n-1}^n), \text{wt}(\mathbf{x}_n)).$$

Here $\mathcal{R}(\mathbf{x})_i = \text{wt}(\mathbf{x}_{i-\ell+1}^i)$ where for $j \notin [n]$, let $x_j = 0$.

- $\mathcal{R}(\mathbf{x})_i - \mathcal{R}(\mathbf{x})_{i-1} = x_i - x_{i-\ell}$.
- \mathbf{x} uniquely determined from n -prefix of $\mathcal{R}(\mathbf{x}) \bmod 2 \leftarrow$ Use any t -substitution-correcting code!

Construction (t -substitution- ℓ -read code)

$$\{\mathbf{x} \in \Sigma_2^n : (\mathcal{R}(\mathbf{x})_1, \dots, \mathcal{R}(\mathbf{x})_n) \bmod 2 \in \mathcal{C}(n, t)\},$$

where $\mathcal{C}(n, t) \subset \Sigma_2^n$ is a t -substitution-correcting code.

Introduction

Channel Model

Minimum Redundancy

Conclusion

Summary

Results

For a simplified model of nanopore sequencing, we show

- $t \log n - O(1)$ min redundancy needed to correct $t \geq 2$ substitutions.
- Naive construction, optimal up to additive constant.

Summary

Results

For a simplified model of nanopore sequencing, we show

- $t \log n - O(1)$ min redundancy needed to correct $t \geq 2$ substitutions.
- Naive construction, optimal up to additive constant.

Future work

- Multiple deletions & combination with substitutions.
- Weighted read vectors

Summary

Results

For a simplified model of nanopore sequencing, we show

- $t \log n - O(1)$ min redundancy needed to correct $t \geq 2$ substitutions.
- Naive construction, optimal up to additive constant.

Future work

- Multiple deletions & combination with substitutions.
- Weighted read vectors

Thank you!

References I

- [1] R. Heckel, G. Mikutis, and R. N. Grass, “A characterization of the DNA data storage channel,” *Scientific Reports*, vol. 9, no. 9663, Jul. 2019.
- [2] D. Deamer, M. Akeson, and D. Branton, “Three decades of nanopore sequencing,” *Nat. Biotech.*, vol. 34, no. 5, pp. 518–524, May 2016.
- [3] A. H. Laszlo *et al.*, “Decoding long nanopore sequencing reads of natural DNA,” *Nat. Biotech.*, vol. 32, no. 8, pp. 829–833, Aug. 2014.
- [4] W. Mao, S. N. Diggavi, and S. Kannan, “Models and information-theoretic bounds for nanopore sequencing,” *TIT*, vol. 64, no. 4, pp. 3216–3236, Apr. 2018.
- [5] R. Hulett, S. Chandak, and M. Wootters, “On coding for an abstracted nanopore channel for DNA storage,” in *ISIT*, Jul. 2021, pp. 2465–2470.
- [6] B. McBain, E. Viterbo, and J. Saunderson, “Finite-state semi-markov channels for nanopore sequencing,” in *ISIT*, Jun. 2022, pp. 216–221.

References II

- [7] A. Rameshwar and N. Weinberger, “On achievable rates over noisy nanopore channels,” in *ISIT*, 2025, (arXiv preprint arXiv:2501.02917).
- [8] Y. M. Chee, A. Vardy, V. K. Vu, and E. Yaakobi, “Coding for transverse-reads in domain wall memories,” in *ISIT*, Jul. 2021, pp. 2924–2929.
- [9] A. Banerjee, Y. Yehezkeally, A. Wachter-Zeh, and E. Yaakobi, “Error-correcting codes for nanopore sequencing,” *TIT*, 2024.
- [10] A. Banerjee, Y. Yehezkeally, A. Wachter-Zeh, and E. Yaakobi, “Correcting a single deletion in reads from a nanopore sequencer,” in *ISIT*, Jul. 2024, pp. 103–108.
- [11] Y. M. Chee, K. A. Schouhamer Immink, and V. K. Vu, “Coding scheme for noisy nanopore sequencing with backtracking and skipping errors,” in *ISIT*, 2024.
- [12] Y. Sun and G. Ge, “Bounds and constructions of ℓ -read codes under the hamming metric,” *TIT*, pp. 1–1, 2025.
- [13] W. Yu, Z. Ye, and M. Schwartz, “On the asymptotic rate of optimal codes that correct tandem duplications for nanopore sequencing,” *TIT*, vol. 71, no. 5, pp. 3569–3581, May 2025.

References III



- [14] O. Yerushalmi, T. Etzion, and E. Yaakobi, “The capacity of the weighted read channel,” in *ISIT*, 2024, (arXiv preprint arXiv:2401.15368).