

Question **1**

Correct

Marked out of  
3.00

🚩 Flag question

### Objective

This is a simple challenge to help you practice printing to stdout.

---

We're starting out by printing the most famous computing phrase of all time! In the editor below, use either `printf` or `cout` to print the string ***Hello, World!*** to stdout.

### Input Format

You do not need to read any input in this challenge.

### Output Format

Print ***Hello, World!*** to stdout.

### Sample Output

Hello, World!

**Answer:** (penalty regime: 0 %)

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main ()
3 {
4     printf("Hello, World!");
5     return (0);
6 }
```

	Expected	Got	
✓	Hello, World!	Hello, World!	✓

Passed all tests! ✓

Marked out of  
5.00

🚩 Flag question

This challenge will help you to learn how to take a character, a string and a sentence as input in C.

To take a single character **ch** as input, you can use `scanf("%c", &ch);` and `printf("%c", ch)` writes a character specified by the argument `ch` to `stdout`:

```
char ch;  
scanf("%c", &ch);  
printf("%c", ch);
```

This piece of code prints the character **ch**.

#### Task

You have to print the character, **ch**.

#### Input Format

Take a character, **ch** as input.

#### Output Format

Print the character, **ch**.

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char ch;
5     scanf("%c",&ch);
6     printf("%c",ch);
7     return(0);
8 }
9
10
11
```

	Input	Expected	Got	
✓	c	c	c	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of  
7.00

🚩 Flag question

### Objective

The fundamental data types in c are int, float and char. Today, we're discussing int and float data types.

The printf() function prints the given statement to the console. The syntax is printf("format string",argument\_list);. In the function, if we are using an integer, character, string or float as argument, then in the format string we have to write %d (integer), %c (character), %s (string), %f (float) respectively.

The scanf() function reads the input data from the console. The syntax is scanf("format string",argument\_list);. For ex:  
The scanf("%d",&number) statement reads integer number from the console and stores the given value in variable **number**.

To input two integers separated by a space on a single line, the command is scanf("%d %d", &n, &m), where **n** and **m** are the two integers.

### Task

Your task is to take two numbers of **int data type**, two numbers of float data type as input and output their sum:

1. Declare **4** variables: two of type int and two of type float.
2. Read **2** lines of input from stdin (according to the sequence given in the 'Input Format' section below) and initialize your **4** variables.
3. Use the + and - operator to perform the following operations:
  - o Print the sum and difference of two int variable on a new line.
  - o Print the sum and difference of two float variable rounded to one decimal place on a new line.

### Input Format

The first line contains two integers.

The second line contains two floating point numbers.

### Constraints

- $1 \leq \text{integer variables} \leq 10^4$
- $1 \leq \text{float variables} \leq 10^4$

### Output Format

Print the sum and difference of both integers separated by a space on the first line, and the sum and difference of both float (scaled to **1** decimal place) separated by a space on the second line.

### Sample Input

10 4

4.0 2.0

### Sample Output

### Sample Output

14 6

6.0 2.0

### Explanation

When we sum the integers **10** and **4**, we get the integer **14**. When we subtract the second number **4** from the first number **10**, we get **6** as their difference.

When we sum the floating-point numbers **4.0** and **2.0**, we get **6.0**. When we subtract the second number **2.0** from the first number **4.0**, we get **2.0** as their difference.

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     float x,y;
6     scanf("%d %d",&a,&b);
7     scanf("%f %f",&x,&y);
8     printf("%d %d\n",a+b,a-b);
9     printf("%.1f %.1f",x+y,x-y);
10    return(0);
11 }
12
```

```

1 #include<stdio.h>
2 int main()
3 {
4     int a,b;
5     float x,y;
6     scanf("%d %d",&a,&b);
7     scanf("%f %f",&x,&y);
8     printf("%d %d\n",a+b,a-b);
9     printf("%.1f %.1f",x+y,x-y);
10    return(0);
11 }
12

```

	Input	Expected	Got	
✓	10 4 4.0 2.0	14 6 6.0 2.0	14 6 6.0 2.0	✓
✓	20 8 8.0 4.0	28 12 12.0 4.0	28 12 12.0 4.0	✓

Passed all tests! ✓