KALINGA INSTITUTE OF INDUSTRIAL TECHNOLOGY

Deemed to be University U/S 3 of the UGC Act, 1956

Unified Tracking & Modal DIP Inspection - IPA

A Cyber-Physical Vision System Integrating Dual-Paradigm Target Tracking with In-Situ Multi-Domain Digital Image Processing Analytics

B.Tech Engineering Project Report

Image Processing and Applications (IPA) Laboratory
School of Computer Engineering
Kalinga Institute of Industrial Technology (KIIT), Deemed to be University
Bhubaneswar, Odisha, India

Submitted to Prof. Sricheta Parui

Submitted by

Student	Roll No.	Project role
Anish Karak	24155833	Co-Developer
Yash Agrawal	241551089	Co-Developer
Awesh Khan	24155837	Co-Developer
Priyaranjan Sahu	241551055	Co-Developer

Project repository
github.com/anishkarak4-ux/IPA_GIG

Abstract

A tracking result provides the position and temporal identity of a target, while an engineering inspection requires measurements of its appearance, geometry, texture, and signal quality. This project integrates these tasks in a camera-driven system with classical and detector-based tracking backends and a modal digital image processing (DIP) workbench. On an inspection request, the application copies the source frame and target region, preserving the frame index and tracker context while isolating the image transformations from the tracking input. The inspection suite covers spatial enhancement, Fourier filtering, color-space analysis, segmentation and morphology, shape and texture descriptors, block-DCT transform coding, and stochastic degradation. A source audit at the identified Git revision establishes the behavior of the checked-in software. The supplied comparative table ranks YOLOv8 with BoT-SORT highest in mean intersection over union (0.835) and MOSSE highest in throughput (285.0 frames/s), but its run manifest and frame-level labels are unavailable. These results are reported with their evidence status and checked for internal consistency. A separately reproducible synthetic experiment measures degradation and restoration under six prescribed noise models. The system provides a common inspection interface and a data model for relating image evidence to the state of a tracked target.

Index Terms — Computer vision, correlation filters, digital image processing, frequency-domain filtering, object tracking, region of interest, transform coding, visual inspection.

Table of Contents

Section	Title	Page
1	Introduction	3
2	Proposed Methodology and Data Sources	4
3	Experiment Segment	11
4	Technical Content	14
5	Literature Review	23
6	State-of-the-Art Techniques	24
7	Comparative Evaluation	24
8	Conclusion	26
9	Future Work and Scope	26
10	Bibliography	27
11	References	27
12	GitHub Project Repository	28
13	Team Member Contributions and Sign-Off	29

Evidence conventions. Source-verified claims refer to the audited Git revision. Project-reported figures come from supplied or repository documentation without reproducible run records. Computed results come from the controlled synthetic experiment or stated inputs. Extended designs describe features beyond the audited implementation.

1. Introduction

A bounding box answers where a target is, approximately, at a given time. It supplies neither the shape of the foreground object within the box nor the image formation conditions that influence the reliability of a shape or texture measurement. Conversely, an independent DIP tool accepts an image without preserving the tracked identity, source frame, or loss history. Repeatedly exporting frames also introduces a manual association step between the reported measurement and the video event.

IPA_GIG treats the tracking result as an index into the video signal. When an operator requests inspection, the system associates the frame, tracked box, and available track ID with a copied region of interest (ROI). It then computes descriptors on that region under a separate modal interaction. This architecture suits a laboratory prototype in which an operator chooses a target, examines an anomalous frame, and relates the resulting descriptors to the target trajectory. It preserves pixel-space measurements unless a separately justified calibration supports physical units.

The engineering objectives are to expose classical and learned backends through a uniform application interface, preserve the integrity and provenance of acquired pixels, characterize a region across complementary signal domains, recover from transient classical-tracker loss, and export telemetry for later analysis. Established algorithms retain their original attribution [1]–[10]. The contribution is their integration with a defined data path and inspection workflow.

1.1 Novelty and Contributions

TABLE I
TECHNICAL CONTRIBUTIONS AND IMPLEMENTATION BOUNDARIES

Contribution	Engineering mechanism	Evidence and boundary
1. Dual-paradigm hybrid tracking core	Selectable CSRT, KCF, MOSSE, or MIL and YOLOv8n with BoT-SORT or ByteTrack share a result contract.	Source-verified startup selection through --mode and --tracker. Runtime backend swapping and concurrent fusion are extended design. The 285.0 FPS MOSSE figure is project-reported. MIL is an online classifier, distinct from the three correlation-filter methods.
2. Decoupled ROI transformation pipeline	Frame-aligned ROI copies go to the modal processor, with a separate buffer for visual annotations.	Source-verified. The foreground application pauses acquisition and tracking while the inspection canvas is active, then resumes.
3. Homomorphic high-emphasis filtering	A log transform approximately separates illumination and reflectance, followed by a smooth radial frequency gain and exponential inversion.	Source-verified method. The stated zero-artifact objective is an acceptance criterion. Boundary effects, clipping, and noise amplification remain possible.
4. Unified 8×8 DCT energy and sparsity profiler	A JPEG-style luminance quantizer, inverse transform, and fidelity measurements operate on the target ROI.	Source-verified DCT, AC-energy concentration, coefficient sparsity, and PSNR. Reported 77.60%, 91.70%, 1.65 b/px, and 41.00× require separate definitions and evidence (Section 4.6).
5. Multi-scale NCC re-acquisition	Compare stored templates against candidate windows at several scales, then reinitialize after verified recovery.	The revision uses a single stored template, one scale, and a default NCC threshold of 0.62. Multi-scale search and confidence-gated template archives are extended design. The 88.4% value is project-reported.
6. Degradation benchmarking and in-situ dual-stream telemetry	Track state and ROI descriptors are stored in separate, joinable CSV streams. Synthetic degradation is evaluated against the original ROI.	Source-verified synchronous, lock-protected writes. A queue-backed asynchronous writer and a six-noise restoration comparison are extended design. The separately computed experiment appears in Section 3.

2. Proposed Methodology and Data Sources

The pipeline couples live tracking to frame-specific inspection. The system acquires a frame and records its source, selects or updates a target, and attempts classical recovery when a valid template is available. On an inspection request, it copies the tracked ROI and associated frame metadata, computes the DIP diagnostics in a modal view, and exports tracking and snapshot records. The provenance table identifies the inputs and separates detector pretraining, public benchmark assets, and project acquisition.

2.1 Data Sources and Provenance

TABLE II
SOURCE, ROLE, AND TRACEABILITY OF EXPERIMENTAL INPUTS

Asset	Acquisition source and technical role	Evidence available
Microsoft COCO 2017 and YOLOv8n weights	Ultralytics distributes the YOLOv8n detection checkpoint [5]. COCO train2017 contains 118,287 images and the detector's COCO label space comprises 80 object categories [11]. The unified CLI defaults to models/yolov8n.pt.	Official upstream provenance and local default path verified. The checkpoint file and its hash are absent from the audited revision. No project-specific training is documented.
OTB-100 / OTB-2015	The Wu–Lim–Yang benchmark [12] provides annotated tracking sequences. Jogging is used to motivate severe occlusion, CarDark low illumination, Basketball clutter and rotation, and Walking2 scale variation.	These are OTB sequence examples. The supplied comparison lacks a per-sequence manifest and target IDs, including the selected annotated target for multi-target sequences.
VOT2020	The Visual Object Tracking challenge distributes evaluation sequences through its toolkit [13]. Its short-term protocol uses segmentation-aware localization and its own evaluation stack.	Identified as a benchmark source. The project material supplies no VOT2020 sequence IDs, output logs, or official protocol scores.
Primary optical stream	Project-reported Windows DirectShow camera index 0, 640×480 at 30.0 FPS, under controlled and ambient illumination.	The unified capture layer opens index 0 through OpenCV and queries capture metadata. It does not explicitly force DirectShow or negotiate the stated dimensions or FPS in the audited path.
Repository demonstration clip	The README identifies tracked_output.avi, 640×480 at 30 FPS, and an initial ROI of 284,245,36,38.	The clip, raw labels, and generated metric CSVs are absent from the audited revision. Its reported demo figures are a separate result set.
Synthetic reference and noise realizations	Deterministic analytic grayscale phantom and seeded pseudo-random perturbations generated for this report.	Full specification and measured results appear in Section 3. The phantom is independent of the project webcam and public tracking sequences.

COCO supplies detector pretraining, OTB supplies tracking scenarios, and VOT supplies a distinct evaluation framework. A bounding-box run using converted VOT masks must record the conversion and be labelled a custom box-based evaluation. For each acquisition session, record the capture backend, frame size, effective FPS, source orientation, exposure, and whether capture timestamps or host timestamps were used. For public sequence tests, retain the release, exact sequence and target identifier, ground-truth convention, visibility flags, and hashes of the source assets. The model artifact requires its source URL, version, and checksum to establish which weights produced a run.

2.2 Frame and Snapshot Contract

Let I_t denote the image delivered to the application at frame index t, and let $B_t = (x_t, y_t, w_t, h_t)$ denote the estimated target box in the same image coordinates. Let Ω_t be the valid image domain and $\mathcal{C}$ the integer image crop. The system contract is

$$R_t = \text{copy} \quad \big(\mathcal{C}(I_t, B_t \cap \Omega_t)\big), \qquad J_t = \text{Overlay}(\text{copy}(I_t), B_t, \mathcal{T}_t). \tag{1}$$

Here R_t is the inspection input, J_t is the live visualizer output, and $\mathcal{T}_t$ holds the trajectory and display statistics. Frame mirroring, when enabled, defines the working coordinate system before tracking and cropping. The source implementation clamps the coordinates and copies both the display frame and ROI; it can construct a central crop up to 200×200 when the snapshot context has no valid lock. The interactive path generally prompts for manual selection in that situation. A central fallback needs its own provenance flag in any quantitative target study.

At successive valid samples let $\mathbf{c}_t$ be the estimated center, τ_t the time in seconds, and t^- the previous valid index. The image-plane displacement, accumulated distance, and interval-average speed are

$$\begin{aligned} &\mathbf{c}_t = \big(x_t + w_t/2,\ y_t + h_t/2\big), \qquad d_t = \| \mathbf{c}_t - \mathbf{c}_{t^-} \|_2, \\ &\ell_t = \ell_{t^-} + d_t, \qquad v_t = \frac{d_t}{\tau_t - \tau_{t^-}}. \end{aligned} \tag{2}$$

The speed is defined for positive time differences. A gap across an occlusion gives a chord displacement between accepted observations. Frame indices and timestamps must therefore travel with the measurements. In a perspective scene, a constant pixel-to-metre factor is valid only under a fixed-depth or planar approximation with appropriate calibration.

2.3 Classical and Detector-Based Tracking

MOSSE learns a filter from target patches X_i and a desired response G_i in the Fourier domain. If Q denotes the multiplier applied to the test spectrum, the regularized least-squares objective is separable across frequency bins [2]. Setting its derivative with respect to Q^* to zero gives

$$\begin{aligned} &\min_{Q} \sum_i \quad |X_i Q - G_i|^2 + \lambda |Q|^2, \\ &Q = \frac{\sum_i \ X_i^* G_i}{\sum_i \ |X_i|^2 + \lambda}, \qquad \hat{\mathbf{c}} = \text{argmax} \mathcal{F}^{-1}\{X_{\text{test}} Q\}. \end{aligned} \tag{3}$$

KCF uses cyclic shifts of the base sample to construct a circulant training system. Kernel ridge regression gives $(K + \lambda I)\boldsymbol{\alpha} = \mathbf{y}$. The DFT diagonalizes the circulant matrix and reduces its solution to elementwise division, $\hat{\boldsymbol{\alpha}} = \hat{\mathbf{y}} / \big(\hat{\mathbf{k}}^{xx} + \lambda\big)$ [3]. CSRT uses spatial reliability to constrain where the filter may place support and channel reliability to weight feature responses [4]. Its constrained multichannel optimization and scale handling cost more per update but can reduce the influence of background pixels in a rectangular crop. MIL trains an online appearance classifier with positive bags of candidate patches near the presumed target and negative examples farther away. For independent instance scores p_j, the noisy-OR model $1 - \prod_j \ \big(1 - p_j\big)$ expresses the probability that at least one member of a positive bag contains the target.

The deep path obtains candidate boxes and confidence scores from the COCO-pretrained YOLOv8n detector [5]. The association layer links detections to existing tracks. BoT-SORT combines motion prediction, camera-motion compensation, and optional appearance cues [6]. Appearance re-identification depends on the effective tracker configuration. ByteTrack first associates stronger detections, then uses lower-score detections to recover unmatched tracks where the motion and overlap cues support a match [7]. The application's detector confidence gate constrains the candidates available for association. A user can select a detection by clicking on it. Following a selected ID creates a single-target workflow even though the association backend can maintain multiple tracks.

2.4 Normalized Cross-Correlation and Recovery

For a template T_s resized by scale factor s and a same-size candidate patch $P_{\mathbf{u},s}$ at location $\mathbf{u}$, normalized cross-correlation is

$$\rho(\mathbf{u}, s) = \frac{\sum_i \left(T_s[i]-\bar{T}_s\right)\left(P_{\mathbf{u},s}[i]-\bar{P}_{\mathbf{u},s}\right)}{\sqrt{\sum_i \left(T_s[i]-\bar{T}_s\right)^2 \sum_i \left(P_{\mathbf{u},s}[i]-\bar{P}_{\mathbf{u},s}\right)}}, \qquad (\mathbf{u}^*, s^*) = \underset{\mathbf{u},s}{\operatorname{argmax}} \rho(\mathbf{u}, s). \tag{4}$$

Mean subtraction cancels an additive intensity offset. Standard-deviation normalization cancels a positive gain for an unsaturated affine intensity change. A low-variance patch makes the denominator unstable and should be rejected. The checked-in classical tracker forms a template at initialization and replaces it on accepted recovery. On a failed update it applies OpenCV's `TM_CCOEFF_NORMED` and reinitializes at the best location if the threshold is met. The extended design searches a scale bank such as $\{0.80, 0.90, 1.00, 1.10, 1.25\}$, rejects peaks that are too close in score to a competing peak, gates displacement by elapsed time, and requires confirmation over consecutive frames. A bounded archive with a stable reference and recent high-quality exemplars reduces the risk of overwriting the only valid target view. Classical success flags mapped to 1.0 in the code are status values, so template promotion requires an independent quality check.

2.5 Telemetry and Reproducibility

Tracking CSV rows carry the session, frame and timestamp, success status, geometry, motion quantities, and available class, ID, and confidence. `yolo_tracking_metrics.csv` is the YOLO-specific output name under the default deep configuration. Classical output uses a different tracking file. `snapshot_analysis.csv` carries event-level ROI bounds, threshold, contour geometry, selected Hu and GLCM descriptors, entropy, binary-mask run-length ratio, and intensity moments. The primary join uses session and frame index, with target ID where present. Multiple saved snapshots of a frame require a separate snapshot identifier to prevent an ambiguous join.

The checked-in writer opens and appends rows under a lock; a snapshot row is emitted when the inspection output is saved. A proposed asynchronous writer would enqueue immutable events with monotonically increasing sequence numbers and dedicate a worker to each stream or a single ordered writer to both. Queue capacity, dropped-event counts, error reporting, and a drain on normal exit would make backpressure and persistence observable.

2.6 Iterative Development and System Design

Early integration was necessary because a tracker-only prototype could conceal camera backend incompatibility, high rendering cost, or loss of coordinate consistency when moving from a bounding box to an ROI. Conversely, a static inspection prototype could conceal unstable tracker boxes and inconsistent temporal metadata. Five two-week sprints provide a retrospective engineering decomposition and a defensible acceptance plan. Dated sprint records were unavailable.

TABLE III
FIVE-SPRINT ENGINEERING PLAN

Sprint	Engineering increment	Acceptance evidence
1, weeks 1–2	Capture, coordinate conventions, controls, baseline display	Camera and video initialization, clean end of stream, correct overlay coordinates after mirroring
2, weeks 3–4	Classical tracking and loss recovery	Valid and invalid ROI tests, deterministic loss and re-entry cases, rejected distractor peaks
3, weeks 5–6	YOLOv8n and two association configurations	Selected ID continuity, explicit confidence and YAML settings, tested detector misses and re-entry
4, weeks 7–8	Modal processor, descriptors, and transform coding	Crop isolation, analytic image fixtures, transform reconstruction, and known-mask geometry

Sprint	Engineering increment	Acceptance evidence
5, weeks 9–10	Exports, comparative testing, and report review	CSV joins, saved snapshot verification, run manifest, per-sequence metrics, and reproducible arithmetic

2.7 Data-Flow Diagrams




Fig. 1. Level 0 context DFD. The visualizer, CSV buffer, and inspection view represent logical output interfaces.




Fig. 2. Level 1 DFD. D1 is an in-memory template in the audited implementation. D2 represents persisted tracking and snapshot files.

2.8 Structured Hierarchy and Use Cases




Fig. 3. Structured hierarchy from orchestration to signal-processing and persistence routines.

TABLE IV
USE-CASE MODEL

Use case	Actor(s)	Trigger and successful outcome	Exception path
Target selection	Operator, Camera	Operator draws a classical ROI or selects a detected deep-track ID from a displayed frame.	Invalid box or missed click retains an uninitialized state or the prior selection, depending on the control path.
Classical tracking	Operator, Camera	The selected tracker updates the ROI and publishes a common tracking result.	Tracker failure invokes NCC when a template exists.
Deep tracking	Operator, Camera	A detector and association policy update track IDs on the camera stream.	An unavailable ID leads to loss handling or reselection.
Snapshot inspection	Operator, Camera	Space captures the current frame and ROI for the modal workbench.	With no valid lock, manual ROI selection is requested in the interactive path.
CSV export	Operator	Logging-enabled tracking emits frame rows; saving a modal snapshot emits a descriptor row.	Export errors require a visible failure and diagnosis from the output path and logs.

2.9 State, Sequence, and Class Design




Fig. 4. Conceptual state machine. OCCLUDED represents a loss condition and is not a verified physical occlusion label. The source expresses these transitions through branches and tracker state rather than an explicit enumeration. Deep reacquisition follows the selected association backend.




Fig. 5. Temporal interaction. The upper panel covers live tracking and the lower panel covers modal inspection. The controller mediates the UI calls. Tracking and modal logging are shown as synchronous calls, consistent with the audited path.




Fig. 6. Logical class hierarchy. `DIPPipeline` and `MetricsLogger` are the concrete source names for the roles `ModalDIPProcessor` and `MetricLogger`. `SystemController` denotes the orchestration functions in `src/main.py`.

2.10 Reproduction Entry Points

The classical MIL backend follows the online multiple-instance tracking method in [14].

```
python -m pip install -r requirements.txt
python src/main.py --mode classical --tracker csrt --source 0
python src/main.py --mode yolo --tracker botsort.yaml --source 0 --model models/yolov8n.pt
python src/main.py --mode yolo --tracker bytetrack.yaml --source 0 --model models/yolov8n.pt
```

The detector commands assume a locally provisioned Ultralytics checkpoint at the specified path. For repeatable capture on a recorded video, replace camera index 0 with the test path, record any mirroring, and use `--init-roi x,y,w,h` in classical mode. Log the resolved backend and checkpoint rather than relying on the generic display label. The commands describe the source interfaces and were not used to run a live camera benchmark for this report.

2.11 Webcam Demonstration

The operator first selects the target region in the webcam view. The classical tracker then displays the current box and the path traced by its center. The inspection canvas captures a single region of interest (ROI) for analysis. Figures 10–16 use the captured CSRT frame 125. The live snapshots illustrate application behavior in one session. Their on-screen frame rates are momentary readings.




Fig. 7. ROI initialization and live CSRT tracking. The blue rectangle shows manual selection. The green rectangle and blue trail show the updated target box and center trajectory. Source is the team's webcam demonstration.

3. Experiment Segment

The evaluation comprises a controlled restoration experiment and a comparative tracker assessment. The restoration trial measures known degradations against an analytic clean image. The tracking segment specifies a repeatable protocol and defines the metrics used to interpret the project-reported comparison in Section 7.

3.1 Controlled Restoration Experiment

The independent synthetic experiment uses a 128×128 phantom comprising a horizontal ramp, a vertical sinusoid, and a bright disk. With $x, y \in \{0, ..., 127\}$, the clean reference is

$$f(x,y) = 0.22 + 0.40\frac{x}{127} + 0.07\sin\frac{2\pi y}{32} + 0.14\,\mathbf{1}\left[(x-68)^2 + (y-64)^2 \le 24^2\right]. \tag{5}$$

The six trials use the row order of Table VII. For zero-based trial index i, NumPy 2.3.5 `default_rng(20261103+i)` supplies one array of independent variates in row-major order. Salt and pepper maps a uniform draw $u < 0.025$ to zero and $u \ge 0.975$ to one. All degraded inputs are clipped to $[0,1]$ and kept as floating-point arrays. The bilateral filter uses a 7×7 square window with reflection excluding the edge pixel, $\sigma_s = 2$ px and $\sigma_r = 0.12$. The adaptive median uses the same reflection convention and tests windows of sizes 3, 5, and 7 pixels per side. If none passes the test, it substitutes the median of the largest window. The notch zeros FFT bins $(k_y, k_x) = (5,10)$ and $(-5, -10)$ modulo 128. The inverse is taken before any output display mapping. MSE and PSNR compare each result directly with (5), using a unit peak.

TABLE V
CONTROLLED DEGRADATION AND RESTORATION RESULTS ON THE SYNTHETIC PHANTOM

Noise model	Restorer	Degraded MSE	Degraded PSNR (dB)	Restored MSE	Restored PSNR (dB)
Gaussian	Bilateral	1.01551×10^{-2}	19.93	2.56481×10^{-3}	25.91
Salt and pepper	Adaptive median	1.40270×10^{-2}	18.53	1.96000×10^{-6}	57.08
Speckle surrogate	Bilateral	4.71660×10^{-3}	23.26	7.62680×10^{-4}	31.18
Poisson	Bilateral	1.10392×10^{-2}	19.57	3.28858×10^{-3}	24.83
Uniform	Bilateral	3.24353×10^{-4}	34.89	5.17435×10^{-5}	42.86
Periodic	Spectral notch	5.00000×10^{-3}	23.01	2.65547×10^{-8}	75.76

The notch removes an interference frequency known by construction. Residual error comes from clean phantom content in the same bins, principally from the disk. The adaptive median result reflects sparse independent impulses on a mostly smooth reference. The bilateral method reduces each of the four tested distributed perturbations, although its fixed range parameter is a compromise between noise suppression and edge preservation. The six rows use one reference and one realization per noise law. They quantify the specified numerical experiment and do not estimate performance across webcam scenes. A scene-level study would replay all filters across several phantoms and recorded ROIs at each severity, retaining random seeds and reporting paired changes in PSNR and structure.




Fig. 8. Before-and-after restoration on the synthetic phantom. The upper row shows impulse noise before and after adaptive median filtering. The lower row shows periodic interference before and after spectral notch filtering. All panels use the same grayscale range. PSNR values were recomputed from the arrays using the clean reference and match Table V.

3.2 Tracking Evaluation Protocol

A repeatable tracker test starts from the same ground-truth box and first-frame index, with frozen backend settings and matched orientation across methods. In detector-based runs, record the selection procedure and score gate before evaluating later frames. Report initialization failures separately, especially when an OTB target is outside the COCO categories or is detected only intermittently. An OTB-style one-pass run should preserve a failure rather than silently initializing from later ground truth. A VOT2020 result requires its designated toolkit and experiment stack [13].

The benchmark design separates three tasks:

1. **Presence classification.** Use a declared ground-truth visibility policy to label each frame and a preregistered tracker-output rule to decide whether a lock is asserted. Record partial visibility, full occlusion, and out-of-view independently. Frames with a visible target but a poorly placed predicted box remain detectable as localization failures.
2. **Localization.** Compare frame-aligned boxes only against the same annotated target. Declare the mean-IoU denominator, including whether a visible missed box scores zero. Compute CLE on a declared subset with valid box pairs, and publish the paired-frame count to expose survivorship bias.
3. **Autonomous recovery.** Score distinct loss events with a predeclared acceptance rule, such as recovery of the correct identity at IoU ≥ 0.5 for three consecutive visible frames within 30 frames of re-entry. Keep false re-locks and unresolved events in the record. The proposed event rule defines how to verify recovery. The supplied 88.4% has no event ledger or stated recovery window.




Fig. 9. Illustrative occlusion and re-association sequence. This schematic shows where detection evidence changes during a challenge trial. ByteTrack can use a weaker detection for an unmatched track [7]. The dashed box marks a possible motion prediction during full occlusion. When the target reappears, the proposed protocol checks its identity and box overlap before counting recovery.

The run manifest should identify source and annotation hashes, the exact commit, OpenCV and Ultralytics versions, tracker YAML, model hash, score gates, runtime device, thread settings, camera rate, and timer boundaries. Measure tracker-only updates with warmed-up kernels and measure acquisition-to-display separately. Report median and upper-tail latency alongside aggregate throughput. With a live source, count distinct acquired frames and display age. Track-only throughput above the camera rate reflects processing capacity and headroom.

3.3 Metrics and Measurement Definitions

With true positives TP, true negatives TN, false positives FP, and false negatives FN from the presence decision, the basic metrics are

$$\begin{aligned} \text{Accuracy} &= \frac{\text{TP+TN}}{\text{TP+TN+FP+FN}}, \qquad \text{Precision} = \frac{\text{TP}}{\text{TP+FP}}, \\ \text{Recall} = \text{Sensitivity} &= \frac{\text{TP}}{\text{TP+FN}}, \qquad \text{Specificity} = \frac{\text{TN}}{\text{TN+FP}}, \\ F_1 &= \frac{2\,\text{Precision}\,\text{Recall}}{\text{Precision+Recall}}. \end{aligned} \tag{6}$$

For binary decisions against a reference, let p_o be observed agreement, and let p and $\hat{p}$ be the actual and predicted positive proportions. Cohen's chance-adjusted agreement [20] is

$$p_e = p\hat{p} + (1-p)(1-\hat{p}), \qquad \kappa = \frac{p_o - p_e}{1-p_e}. \tag{7}$$

Agreement depends on prevalence and the marginal distributions. Specify the policy for zero denominators and uninformative strata. On an occlusion-only subset with every ground-truth label negative, a single kappa may be degenerate or misleading. A recovery-event analysis and per-visibility error rates address the temporal question more directly.

If $\widehat{B}_t$ is a prediction and B_t^* the annotation, then

$$\begin{aligned} \text{IoU}_t &= \frac{|\widehat{B}_t \cap B_t^*|}{|\widehat{B}_t \cup B_t^*|}, \qquad \text{CLE}_t = \| \text{ctr}(\widehat{B}_t) - \text{ctr}(B_t^*) \|_2, \\ \text{FPS} &= \frac{n_{\text{updates}}}{T_{\text{measured}}}. \end{aligned} \tag{8}$$

IoU reflects position and scale error. CLE reflects translation of the estimated center and is sensitive to image resolution. For standardized success plots, integrate the empirical fraction of frames above each IoU threshold and declare the miss convention. For throughput, the reciprocal of aggregate FPS is an average time per counted update under the same measurement boundary.

4. Technical Content

Let $f(x, y)$ denote an $M \times N$ grayscale ROI with M rows, N columns, and pixel indices $0 \le y < M$, $0 \le x < N$. An 8-bit code ranges from 0 to $L - 1 = 255$. A normalized intensity is $r = f/(L - 1)$. Unless stated otherwise, operations act on the same unannotated ROI. Display normalization is applied after measurement when a signed or floating-point result needs a visible preview. Each numerical snapshot value in this section is project-reported unless marked otherwise.

4.1 Part 1 Spatial Domain and Edge Detection

Point transforms operate on the marginal intensity at a pixel. For an 8-bit input r_8 and normalized input r, the negative, log, and power maps are

$$\begin{aligned} s_{\text{neg}} &= L - 1 - r_8, \\ s_{\log} &= c_{\log}\ln(1 + r_8), \quad c_{\log} = \frac{L-1}{\ln L}, \qquad s_\gamma = (L - 1)c_\gamma r^\gamma. \end{aligned} \tag{9}$$

The negative reflects the gray scale around its midpoint. The log gain $c_{\log}/(1 + r_8)$ is highest at low intensity, expanding dark levels while compressing highlights. For $c_\gamma = 1$ and $0 < \gamma < 1$, the normalized power map lifts low and mid-range values. The checked-in default $\gamma = 0.6$ is dimensionless. These maps change contrast and shift histogram statistics, so descriptor comparisons require a fixed stage of measurement.

For contrast-limited adaptive histogram equalization (CLAHE), let $h_j(k)$ be the histogram of tile j and A_j its pixel count. Conceptually, clip each bin at a count proportional to $\alpha A_j/L$, redistribute excess counts, and construct a tile-specific cumulative map [1]. If $\tilde{h}_j$ is the redistributed histogram and $\beta_j(x, y)$ are the nonnegative bilinear weights of neighboring tile centers, then

$$\begin{aligned} T_j(r_8) &= (L - 1)\frac{\sum_{k=0}^{r_8} \tilde{h}_j(k)}{A_j}, \\ s(x, y) &= \sum_j \beta_j(x, y) T_j\big(f(x, y)\big), \qquad \sum_j \beta_j(x, y) = 1. \end{aligned} \tag{10}$$

The specified setting is $\alpha = 2.0$ with an 8×8 tile grid. The helper defaults to 2.0, while the unified snapshot call explicitly uses 2.5. Clipping controls local gain and interpolation reduces tile seams. On a small ROI the fixed grid leaves few pixels per tile, making local histograms sensitive to noise and quantization.

Sobel estimates derivatives by composing a centered difference in one axis with a binomial smoothing kernel in the other. For image-space correlation with rows increasing downward, the conventional kernels and gradient magnitude are

$$\begin{aligned} K_x &= \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}, \qquad K_y = K_x^{\mathsf{T}}, \\ G_x &= K_x \star f, \quad G_y = K_y \star f, \quad M_g = \sqrt{G_x^2 + G_y^2}. \end{aligned} \tag{11}$$

The Laplacian sums centered second differences. Its four-neighbor form is

$$\nabla^2 f(x, y) \simeq f(x + 1, y) + f(x - 1, y) + f(x, y + 1) + f(x, y - 1) - 4f(x, y). \tag{12}$$

Its sign distinguishes curvature polarity, and the corresponding Laplacian-of-Gaussian detects zero crossings after smoothing. The discrete Laplacian amplifies high-frequency noise, which motivates pre-smoothing. Canny [15] formalizes the trade-off between detection, localization, and a single response per edge. In the discrete pipeline, Gaussian smoothing precedes directional gradient estimation. Nonmaximum suppression keeps a sample only if its magnitude is locally maximal along the gradient normal. High-threshold responses seed accepted edges, and weak responses survive only when connected to accepted edges. The source uses thresholds 50 and 150 by default. Optimality pertains to Canny's edge and noise model and its stated criteria.

Let $p_k = h(k)/(MN)$ be the normalized ROI histogram. The first moment, spread, skewness, and Pearson kurtosis follow from

$$\mu = \sum_k k\, p_k, \qquad m_j = \sum_k (k-\mu)^j\, p_k, \qquad \sigma = \sqrt{m_2},$$
$$S = \frac{m_3}{\sigma^3}, \qquad K = \frac{m_4}{\sigma^4}. \tag{13}$$

The report gives $\mu = 134.20$, $\sigma = 42.22$, $S = -0.142$, and $K = 2.684$. If taken from one ROI, these describe a mildly left-skewed intensity distribution. Pearson kurtosis 2.684 corresponds to excess kurtosis -0.316. These marginal statistics do not encode spatial arrangement. Skewness and kurtosis are mathematically undefined for a constant ROI and need a sentinel or an explicit software convention.




Fig. 10. Spatial processing on the tracked ROI. Global equalization and CLAHE change tonal contrast. Gamma correction lifts darker values, the negative reverses intensity, and Canny traces dominant edges. Source is the CSRT inspection canvas at frame 125.

4.2 Part 2 Frequency Domain and Image Restoration

The 2-D DFT is obtained by projecting the ROI onto orthogonal complex exponentials in the two axes. Orthogonality on the finite grid gives the inverse. FFT denotes an algorithm for computing this transform.

$$\begin{aligned} F(u,v) &= \sum_{y=0}^{M-1}\sum_{x=0}^{N-1} f(x,y)e^{-j2\pi(ux/N+vy/M)}, \\ f(x,y) &= \frac{1}{MN}\sum_{v=0}^{M-1}\sum_{u=0}^{N-1} F(u,v)e^{j2\pi(ux/N+vy/M)}, \\ F_c &= \mathrm{fftshift}(F), \qquad S(u,v) = \ln(1+|F_c(u,v)|). \end{aligned} \tag{14}$$

Centering places DC at the integer index $(\lfloor N/2 \rfloor, \lfloor M/2 \rfloor)$. Log display compresses dynamic range while retaining low-amplitude structure. Phase carries spatial arrangement and remains part of the complex spectrum during filtering. If D is distance in frequency bins from centered DC, the Butterworth low-pass and Gaussian high-pass are

$$H_{\mathrm{BLP}}(D) = \frac{1}{1+(D/D_0)^{2n}}, \qquad H_{\mathrm{GHP}}(D) = 1 - e^{-D^2/(2D_0^2)}. \tag{15}$$

The specified Butterworth setting is $n = 2$, $D_0 = 30$, giving a gain of 0.5 at cutoff. The specified Gaussian high-pass uses $D_0 = 25$, has zero DC gain, and rises monotonically to one. The unified code shares $D_0 = 25$ across these two filters and the homomorphic call. A filter radius measured in bins corresponds to different spatial frequencies as ROI dimensions vary. The inverse should be computed from HF_c after undoing the shift. In a signed high-pass result, clipping negative values for display discards one contrast polarity.

Homomorphic filtering. Under $f = i\rho$, with illuminance i and reflectance ρ, $\ln f = \ln i + \ln \rho$ for positive f. The implementation uses $\ln(1 + f)$ to handle zero, which approximates this separation. A smooth high-emphasis gain in log-Fourier space yields

$$\begin{aligned} H_{\text{hom}}(D) &= \gamma_L + (\gamma_H - \gamma_L)\left[1 - e^{-c(D/D_0)^2}\right], \\ \hat{f} &= \exp\left(\text{Re}\mathcal{F}^{-1}\{\text{ifftshift}\left[H_{\text{hom}}\,\text{fftshift}(\mathcal{F}\{\ln(1+f)\})\right]\}\right) - 1. \end{aligned} \tag{16}$$

With $\gamma_L = 0.5$, $\gamma_H = 1.5$, $c = 1$ and the specified $D_0 = 30$, the asymptotic gains attenuate slow illumination changes and enhance fine reflectance details. The source helper also defaults to 30, while the unified processor supplies 25. Cast shadows with sharp boundaries occupy overlapping frequencies with true edges. The Fourier boundary assumption can create wrap-around and the exponential can saturate pixels. Mirror padding, integer-centered masks, and clipping statistics support an artifact assessment. The audited implementation constructs radial masks about $(N/2, M/2)$, introducing a half-bin offset on odd ROI axes. Visual and quantitative verification on an odd-sized impulse fixture would expose that difference.

Wiener restoration. If $G = HF + N_f$ represents circular convolution by a point-spread function plus additive noise uncorrelated with F, minimize $\mathbb{E}|F - WG|^2$ with respect to W^*. The orthogonality condition $\mathbb{E}[(F - WG)G^*] = 0$ gives

$$W(u,v) = \frac{H^*(u,v)S_F(u,v)}{|H(u,v)|^2 S_F(u,v) + S_N(u,v)} \approx \frac{H^*(u,v)}{|H(u,v)|^2 + K}, \qquad \widehat{F} = WG, \quad K = 0.01. \tag{17}$$

Here S_N/S_F is approximated by a constant. As $|H|$ approaches zero, regularization suppresses frequencies that a direct inverse would amplify. The source constructs an oriented line PSF and attempts to infer direction from velocity when compatible telemetry components are available. The motion blur length should ultimately be estimated from displacement during the exposure, not from a nominal display interval. A constant line PSF is inappropriate under large depth change, rolling shutter, or strong acceleration.




Fig. 11. Fourier spectrum and low-pass output. The magnitude and phase are separate views of the 2-D FFT. The live canvas shows a Butterworth cutoff of 25 frequency bins and order 2, with fine detail softened in the output. Source is CSRT frame 125.

4.3 Part 3 Color Models and Pseudocolor

RGB and HSV. RGB represents a pixel through red, green, and blue channel codes. OpenCV frame storage orders these channels BGR. For normalized RGB, let $C_{\max} = \max(R, G, B)$, $C_{\min} = \min(R, G, B)$, and $\Delta = C_{\max} - C_{\min}$. HSV follows from the channel extrema and the identity of the dominant channel.

$$V = C_{\max}, \qquad S = \begin{cases} 0, & C_{\max} = 0, \\ \Delta / C_{\max}, & C_{\max} > 0, \end{cases} \qquad H = 60^\circ \begin{cases} \big((G-B)/\Delta\big) \bmod 6, & C_{\max} = R, \\ (B-R)/\Delta + 2, & C_{\max} = G, \\ (R-G)/\Delta + 4, & C_{\max} = B. \end{cases} \tag{18}$$

Hue is undefined for $\Delta = 0$. For a common positive gain with no saturation or offset, both numerator differences and Δ scale together, so hue and saturation remain unchanged. Hue-based segmentation is therefore useful under that limited illumination model. Low saturation, white-balance drift, colored illumination, and clipped highlights break the assumption. A hue mask should enforce a saturation floor and handle circular intervals around red. The

repository provides channel decomposition and HSV value equalization. A dedicated hue-gated target segmentation rule is an extended design.

CIELAB. For color-difference measurement, inverse-transfer the encoded RGB values to linear light, transform to tristimulus coordinates (X, Y, Z) for the chosen primaries, and normalize by a reference white (X_n, Y_n, Z_n). With $\delta = 6/29$,

$$\begin{aligned} q(t) &= \begin{cases} t^{1/3}, & t > \delta^3, \\ t/\left(3\delta^2\right) + 4/29, & t \le \delta^3, \end{cases} \\ L^* &= 116q(Y/Y_n) - 16, \\ a^* &= 500[q(X/X_n) - q(Y/Y_n)], \\ b^* &= 200[q(Y/Y_n) - q(Z/Z_n)], \qquad \Delta E_{76} = \sqrt{(\Delta L^*)^2 + (\Delta a^*)^2 + (\Delta b^*)^2}. \end{aligned} \tag{19}$$

Lightness is separated from two opponent axes. The Euclidean color distance is sensitive to reference white and device calibration. The OpenCV 8-bit Lab planes are encoded values with channel scaling and offsets. Physical Lab measurements require conversion to the conventional floating-point coordinates.

YCbCr. For full-range, normalized nonlinear primaries, one BT.601-style transform is

$$Y' = 0.299R' + 0.587G' + 0.114B', \qquad C_b = \frac{B'-Y'}{1.772} + 0.5, \qquad C_r = \frac{R'-Y'}{1.402} + 0.5. \tag{20}$$

YCbCr separates luma from chroma differences. In 4:2:0, each chroma plane is low-pass filtered and sampled once per 2×2 luma region. Chroma siting and reconstruction affect colored edges. The source converts to an OpenCV YCrCb channel ordering and retains full-resolution planes. Actual 4:2:0 storage belongs to the extended coding design.

JET pseudocolor. A continuous trigonometric JET-like map can be defined by smooth, overlapping channel windows. For $t = f/(L-1)$ and $q \in \{1/4, 1/2, 3/4\}$ define

$$b_q(t) = \begin{cases} 1, & |t-q| \le 1/8, \\ \frac{1}{2}\left[1 + \cos\left(4\pi(|t-q| - 1/8)\right)\right], & 1/8 < |t-q| < 3/8, \\ 0, & |t-q| \ge 3/8, \end{cases} \qquad \left(R_p, G_p, B_p\right) = \left(b_{3/4}, b_{1/2}, b_{1/4}\right). \tag{21}$$

This construction gives continuous channels and continuous slopes at the transition boundaries. The implementation uses the OpenCV discrete JET lookup table. Its false colors encode measured image intensity. A visible-light webcam produces no temperature measurement without separate radiometric sensing and calibration.




Fig. 12. Color-channel decomposition and pseudocolor. The left panel shows hue, saturation, and value in that order. The center panel equalizes the value channel, and the right panel applies the JET lookup table. Source is CSRT frame 125.

4.4 Part 4 Segmentation and Mathematical Morphology

Otsu threshold. A threshold t partitions histogram mass into two classes with weights $\omega_0 = \sum_{k=0}^{t} p_k$ and $\omega_1 = 1 - \omega_0$. Their means are μ_0 and μ_1. Expanding each within-class squared residual about the global mean gives $\sigma_T^2 = \sigma_W^2 + \sigma_B^2$. Since σ_T^2 is independent of t, the threshold is obtained from [16]

$$t^* = \arg\max_{t:\,\omega_0\omega_1>0} \sigma_B^2(t), \qquad \sigma_B^2(t) = \omega_0(t)\omega_1(t)[\mu_0(t) - \mu_1(t)]^2. \tag{22}$$

The project-reported threshold $t^* = 127$ belongs to one unidentified ROI. The current pipeline applies Otsu to a smoothed grayscale ROI. Foreground polarity and ROI background fraction must be recorded because both influence the geometry derived from the mask.

K-means. For color feature vectors $\mathbf{z}_i$, squared-error clustering minimizes

$$\begin{aligned} J &= \sum_i \quad \| \mathbf{z}_i - \boldsymbol{\mu}_{a_i} \|^2, \\ a_i &= \arg\min_k \| \mathbf{z}_i - \boldsymbol{\mu}_k \|^2, \qquad \boldsymbol{\mu}_k = \frac{1}{|\{i:a_i=k\}|} \sum_{i:a_i=k} \mathbf{z}_i \,. \end{aligned} \tag{23}$$

Alternating assignment and centroid updates decreases J until a stopping condition. The $K = 3$ target, background, and glare interpretation requires identifying clusters from their intensity, color, and spatial support. Cluster labels are permutable and cannot be interpreted semantically from index alone. A fixed random seed, color space, convergence criteria, and cluster-selection rule are needed for replay.

Marker-controlled watershed. For foreground support A, the interior distance $d_A(p) = \min_{q \notin A} \| p - q \|_2$ is large near the centers of compact components. The code opens the initial mask, thresholds the Euclidean distance transform at 0.4 of its maximum to obtain sure foreground, and dilates the support to define a surrounding uncertainty band. Connected foreground components receive distinct positive labels, the unknown band receives zero, and flooding over image gradients produces separators where labeled basins meet. Overlapping objects benefit from distinct interior markers. A global distance threshold can eliminate markers for small objects near larger ones.

Morphological operators. For a foreground set A and structuring element B, define

$$\begin{aligned} A \oplus B &= \{a + b : a \in A,\ b \in B\}, \qquad A \ominus B = \{z : z + B \subseteq A\}, \\ A \circ B &= (A \ominus B) \oplus B, \qquad A \bullet B = (A \oplus B) \ominus B, \qquad \nabla_B A = (A \oplus B) \setminus (A \ominus B). \end{aligned} \tag{24}$$

Dilation grows foreground support and erosion removes points where the element does not fit. Opening removes small bright components and can break thin bridges. Closing fills narrow gaps and can merge nearby components. The gradient spans the boundary band. Using a 3×3 element at different scales changes the effective physical width of these operations.

Zhang–Suen thinning. Let p_1 be a foreground pixel and let $p_2, \ldots, p_9$ enumerate its eight neighbors clockwise from north. Set $B = \sum_{i=2}^{9} p_i$ and let A count the $0 \to 1$ transitions in the circular neighborhood [17]. A deletion candidate obeys $2 \le B \le 6$ and $A = 1$. In subiteration 1 it also obeys $p_2 p_4 p_6 = 0$ and $p_4 p_6 p_8 = 0$. In subiteration 2 the conditions are $p_2 p_4 p_8 = 0$ and $p_2 p_6 p_8 = 0$. Each pass deletes its candidates simultaneously. Iteration stops when both passes make no changes. This topology-oriented thinning estimates a one-pixel centerline. The audited revision instead accumulates opening residues of iteratively eroded masks with a cross element and an iteration cap.



Fig. 13. Three segmentation views of the same ROI. The Otsu panel shows a threshold of 136 for this capture. The three-cluster output groups similar colors, while the red watershed line follows much of the subject outline and extends into the background on the right. Source is CSRT frame 125.

4.5 Part 5 Morphometry and Texture Analysis

For closed polygon vertices (x_i, y_i) indexed cyclically, Green's theorem yields the shoelace area. The polyline length is the sum of Euclidean edge lengths. Circularity, solidity, and extent normalize geometry against three different references.

$$\begin{aligned} A &= \tfrac{1}{2}\left|\textstyle\sum_i (x_i y_{i+1} - x_{i+1} y_i)\right|, \qquad P = \textstyle\sum_i \sqrt{(x_{i+1}-x_i)^2 + (y_{i+1}-y_i)^2}, \\ C &= \tfrac{4\pi A}{P^2}, \qquad S_o = \tfrac{A}{A_{\text{hull}}}, \qquad E_x = \tfrac{A}{w_b h_b}. \end{aligned} \tag{25}$$

The project gives $A = 5{,}884.0$ px^2, $P = 342.60$ px, $C = 0.628$, $S_o = 0.941$, $E_x = 0.765$, and $\theta = -14.20°$. Substitution of the stated area and perimeter gives $C = 0.62995$ (computed here). The displayed area and perimeter do not round to the displayed circularity under (25). Orientation is obtained in code from a minimum-area rectangle with a library-specific side and angle convention. A moment-axis orientation $\tfrac{1}{2}\operatorname{atan2}(2\mu_{11}, \mu_{20} - \mu_{02})$ measures a different geometric property. The two agree only in specific shapes and angle conventions.

Hu invariants. For a foreground indicator $b(x, y)$, raw moments and centered moments follow from integrating spatial monomials. Translating coordinates to the centroid removes position dependence. Dividing by a power of the area normalizes scale for a continuous binary silhouette.

$$\begin{aligned} m_{pq} &= \textstyle\sum_{x,y} x^p y^q b(x,y), \qquad (\bar{x}, \bar{y}) = (m_{10}, m_{01})/m_{00}, \\ \eta_{pq} &= \frac{\sum_{x,y} (x-\bar{x})^p (y-\bar{y})^q b(x,y)}{m_{00}^{1+(p+q)/2}}. \end{aligned} \tag{26}$$

Set $a = \eta_{30} - 3\eta_{12}$, $b_1 = 3\eta_{21} - \eta_{03}$, $c = \eta_{30} + \eta_{12}$, $d = \eta_{21} + \eta_{03}$, and $e = \eta_{20} - \eta_{02}$. The rotational invariants combine normalized moments of orders two and three [9].

$$\begin{aligned} \phi_1 &= \eta_{20} + \eta_{02}, \qquad \phi_2 = e^2 + 4\eta_{11}^2, \\ \phi_3 &= a^2 + b_1^2, \qquad \phi_4 = c^2 + d^2, \\ \phi_5 &= ac\left(c^2 - 3d^2\right) + b_1 d\left(3c^2 - d^2\right), \\ \phi_6 &= e\left(c^2 - d^2\right) + 4\eta_{11} cd, \\ \phi_7 &= b_1 c\left(c^2 - 3d^2\right) - ad\left(3c^2 - d^2\right). \end{aligned} \tag{27}$$

The last invariant reverses sign under reflection. Digitization, clipping, and segmentation changes limit numerical invariance. Project-reported values are $\phi_1 = 0.214$ and $\phi_2 = 0.0182$; values for ϕ_3 through ϕ_7 were unavailable. The revision computes all seven using contour moments and stores signed logarithms, $-\operatorname{sgn}(\phi_i)\log_{10}|\phi_i|$ for non-negligible magnitudes. The first two reported values lack a documented raw-versus-log convention.

Haralick-style GLCM. Quantize intensity into levels i, j and count valid pairs at displacement $\mathbf{d}$. Dividing each count by the total pair count gives a joint probability p_{ij}. The checked-in descriptor uses 16 levels and horizontal forward adjacency, optionally restricted to both pixels inside the foreground mask. Defining $d_{ij} = |i - j|$, marginal means μ_i, μ_j and standard deviations σ_i, σ_j, the descriptors are

$$\begin{aligned} \text{Contrast} &= \textstyle\sum p_{ij} d_{ij}^2, \qquad \text{Dissimilarity} = \textstyle\sum p_{ij} d_{ij}, \\ \text{Energy} &= \textstyle\sum p_{ij}^2, \qquad \text{Correlation} = \frac{\sum p_{ij}(i-\mu_i)(j-\mu_j)}{\sigma_i \sigma_j}. \\ \text{Homogeneity} &= \textstyle\sum \frac{p_{ij}}{1+d_{ij}^2}, \end{aligned} \tag{28}$$

Here energy denotes angular second moment, consistent with the implementation. Correlation requires positive variance in both marginals. The supplied values are contrast 84.20, dissimilarity 5.81, homogeneity 0.742, energy 0.184, and correlation 0.887. With the source's 16 levels, d is an integer between 0 and 15. Over that domain, $1/\left(1 + d^2\right) \le 1 - (1 - 1/226)d/15$. Taking expectations gives homogeneity ≤ 0.6144 at dissimilarity 5.81. The two supplied values therefore require another GLCM convention, separate samples, or correction from the original data.

Rotation-sensitive horizontal adjacency should be retained when directionality is meaningful. For orientation-robust comparison, aggregate fixed offsets and record the pooling rule [8].

Local binary patterns. For neighbors g_p on a radius R ring around intensity g_c, encode local rank order as

$$\mathrm{LBP}_{P,R} = \sum_{p=0}^{P-1} 2^p \, \mathbf{1}[g_p \geq g_c], \qquad P = 8,\ R = 1. \tag{29}$$

The current implementation compares the eight neighbors of a 3×3 window. Under a strictly increasing intensity map, these comparisons preserve their ordering, apart from quantization ties. A histogram captures the distribution of local microstructures. A fixed bit ordering remains direction-sensitive unless codes are canonicalized under cyclic shifts.




Fig. 14. Texture map and descriptor readouts. The local binary pattern map highlights local intensity changes. The readout includes Hu moments and gray-level co-occurrence matrix features for this capture. Geometry and moment values depend on the selected contour. Source is CSRT frame 125.

4.6 Part 6 Block DCT and JPEG-Style Compression

For each reflected-padded 8×8 block, level-shift the samples by 128. Let $b(x, y) = f(x, y) - 128$ and $\alpha(0) = 1/\sqrt{8}$, $\alpha(k) = 1/2$ for $1 \leq k < 8$. The forward orthonormal DCT-II is a separable cosine projection [10].

$$C_{uv} = \alpha(u)\alpha(v) \sum_{y=0}^{7} \sum_{x=0}^{7} b\,(x, y) \cos \frac{(2x+1)u\pi}{16} \cos \frac{(2y+1)v\pi}{16}, \qquad 0 \leq u, v < 8. \tag{30}$$

In matrix form, $C = TbT^{\mathsf{T}}$ with the axis ordering defined by the cosine basis, and inversion uses the transpose factors. Orthogonality preserves squared energy. The DC coefficient encodes block mean, while smooth variations concentrate energy at low AC indices. The base luminance quantizer is the example table from Annex K of the JPEG recommendation [18]. JPEG permits application-specific quantization tables.

$$Q_{\mathrm{JPEG}} = \begin{bmatrix} 16 & 11 & 10 & 16 & 24 & 40 & 51 & 61 \\ 12 & 12 & 14 & 19 & 26 & 58 & 60 & 55 \\ 14 & 13 & 16 & 24 & 40 & 57 & 69 & 56 \\ 14 & 17 & 22 & 29 & 51 & 87 & 80 & 62 \\ 18 & 22 & 37 & 56 & 68 & 109 & 103 & 77 \\ 24 & 35 & 55 & 64 & 81 & 104 & 113 & 92 \\ 49 & 64 & 78 & 87 & 103 & 121 & 120 & 101 \\ 72 & 92 & 95 & 98 & 112 & 100 & 103 & 99 \end{bmatrix}, \tag{31}$$

$$Z_{uv} = \mathrm{round}(C_{uv}/Q_{uv}), \quad \widetilde{C}_{uv} = Q_{uv} Z_{uv}.$$

Rows represent the vertical index and columns the horizontal index. The code scales the base table with a quality parameter, then clips the rounded entries to $[1,255]$. Its effective table depends on the exact scaling and rounding expression. The inverse DCT reconstructs the level-shifted block, then 128 is restored and the padding removed. Quantization zeros many high-frequency entries and introduces error. Its rounding error per coefficient is bounded by $Q_{uv}/2$ before clipping and casting. Parseval's identity transfers squared coefficient error to squared spatial error prior to those nonlinear steps.

For B blocks and a specified frequency set $\mathcal{L}$, define retained energy and coefficient sparsity as

$$\mathcal{E}_{\mathcal{L}} = 100\frac{\sum_{b=1}^{B}\sum_{(u,v)\in\mathcal{L}}|C_{b,uv}|^2}{\sum_{b=1}^{B}\sum_{(u,v)\in\mathcal{A}}|C_{b,uv}|^2}, \qquad \mathcal{Z} = \frac{100}{64B}\sum_{b,u,v}\mathbf{1}\left[Z_{b,uv}=0\right]. \tag{32}$$

The code uses $\mathcal{A}$ equal to all 63 AC coefficients and $\mathcal{L}$ equal to the eight AC coefficients in the top-left 3×3 block. A separate top-10% convention requires a declared ordering, a rounding rule for $0.10(64)$, and a decision about DC. The two metrics are not interchangeable.

For a source ROI and reconstructed ROI $\hat{f}$, mean squared error and peak signal-to-noise ratio are

$$\mathrm{MSE} = \frac{1}{MN}\sum_{x,y}[f(x,y)-\hat{f}(x,y)]^2, \qquad \mathrm{PSNR} = 10\log_{10}\frac{L_{\mathrm{peak}}^2}{\mathrm{MSE}}. \tag{33}$$

Take $L_{\mathrm{peak}} = 255$ for 8-bit samples and 1 for normalized data. Exact reconstruction gives infinite PSNR mathematically. For a local image window, the usual two-factor SSIM [19] with $C_1 = (0.01L_{\mathrm{peak}})^2$ and $C_2 = (0.03L_{\mathrm{peak}})^2$ is

$$\mathrm{SSIM}(f,\hat{f}) = \frac{(2\mu_f\mu_{\hat{f}}+C_1)(2\sigma_{f\hat{f}}+C_2)}{(\mu_f^2+\mu_{\hat{f}}^2+C_1)(\sigma_f^2+\sigma_{\hat{f}}^2+C_2)}. \tag{34}$$

A reported image-level value averages local windows under a specified window weighting and boundary rule. PSNR emphasizes pointwise distortion, while SSIM measures local luminance and structural agreement.




Fig. 15. Block-DCT reconstruction of the grayscale ROI. The reconstructed preview retains the main facial features. The figure is a visual comparison of one source crop and its reconstruction. Source is CSRT frame 125.

Shannon entropy for a discrete symbol population with probabilities p_k is

$$\mathcal{H} = -\sum_{k:p_k>0} p_k \log_2 p_k. \tag{35}$$

The entropy is in bits per symbol. It becomes bits per pixel only if there is one symbol per pixel or if the total modeled bit count is divided by the original pixel count. Zig-zag scanning orders coefficients approximately from low to high spatial frequency. A JPEG-style encoder treats the DC coefficient differentially and represents the AC stream with zero-run/size pairs and end-of-block symbols before entropy coding. A measured compression ratio divides a declared uncompressed byte count by encoded bytes including the stated headers and tables. The binary-mask run estimate measures mask compressibility.

TABLE VI
PROJECT-REPORTED TRANSFORM CODING VALUES AND AUDITED DEFINITIONS

Diagnostic	Reported value	Evidence or interpretation
Energy compaction	77.60% in top 10%	Source uses a top-left eight-AC subset. The rank selection and numerator behind the supplied figure are unrecorded.
Quantized coefficient sparsity	91.70%	The code computes this percentage. The ROI and quantized blocks were unavailable.
Reconstructed PSNR	32.60 dB	Equivalent to about 35.73 squared 8-bit intensity units of MSE under (33).
Reconstructed SSIM	0.924	Source pipeline does not emit DCT SSIM. Window convention and reconstruction used for the supplied result were unavailable.
Shannon entropy	1.65 b/px versus 7.82 b/px raw	Source computes grayscale ROI histogram entropy. A coefficient or encoded-stream entropy requires separate accounting.
Zig-zag and RLE ratio	41.00×	Source estimates row-major binary-mask RLE with two bytes per run. It does not produce a coded zig-zag stream or a JPEG bit rate.

If the ratio 41.00× referred to the same stream and an 8 b/px baseline, it would imply approximately 0.195 b/px. The 1.65 b/px figure must therefore be tied to a declared representation before using the two quantities together. A mask RLE estimator also needs a run-count width and a rule for splitting long runs before it can be interpreted as a file size.

4.7 Part 7 Stochastic Degradation and Restoration

Let f denote the normalized clean signal and g a degraded sample. Each noise law in Table VII is applied before clipping to $[0,1]$. For a quantization error model, the uniform distribution assumes a sufficiently fine quantizer and a signal whose position within a step is approximately uniform. An actual quantizer produces deterministic error conditional on the input.

TABLE VII
SYNTHETIC DEGRADATION MODELS

Model	Conditional observation before clipping	Parameterization for the experiment
Additive Gaussian	$g = f + \epsilon,\ \epsilon \sim \mathcal{N}(0, \sigma^2)$	$\sigma^2 = 0.01$
Salt and pepper	$g = 0$ with $p/2$, $g = 1$ with $p/2$, and $g = f$ with $1 - p$	$p = 0.05$
Multiplicative speckle surrogate	$g = f(1 + \epsilon_s),\ \epsilon_s \sim \mathcal{N}(0, \sigma_s^2)$	$\sigma_s = 0.15$ and conditional variance $f^2\sigma_s^2$
Poisson photon shot noise	$g = k/\lambda$ with $k \sim \text{Pois}(\lambda f)$	$\lambda = 40$ and conditional variance f/λ
Uniform quantization surrogate	$g = f + u,\ u \sim \mathcal{U}[-\Delta/2, \Delta/2)$	$\Delta = 1/16$ and $\text{Var}(u) = \Delta^2/12$
Periodic interference	$g = f + A\sin\left[2\pi\left(k_x x/N + k_y y/M\right) + \varphi\right]$	$A = 0.10,\ (k_x, k_y) = (10,5),\ \varphi = 0$

An adaptive median expands the neighborhood until its median z_{med} lies strictly between the local minimum and maximum or until the maximum window is reached. Within an accepted window, it preserves the center if the center lies strictly between the extrema and otherwise substitutes the median. This targets impulse contamination while retaining valid edges. A bilateral filter adapts its smoothing weights to spatial proximity and intensity similarity.

$$\hat{f}(p) = \frac{\sum_{q \in \mathcal{N}_p} g(q) e^{-\|p-q\|^2/\left(2\sigma_s^2\right)} e^{-[g(p)-g(q)]^2/\left(2\sigma_r^2\right)}}{\sum_{q \in \mathcal{N}_p} e^{-\|p-q\|^2/\left(2\sigma_s^2\right)} e^{-[g(p)-g(q)]^2/\left(2\sigma_r^2\right)}}. \tag{36}$$

Here σ_s denotes the spatial scale in pixels, independent of the speckle parameter in Table VII. For periodic interference at a known bin $\mathbf{k}_0$, the real-valued spatial sinusoid places energy at a conjugate pair. A smooth notch can use a product of Gaussian high-pass terms centered at the two peaks.

$$H_{\text{notch}}(\mathbf{k}) = \prod_{\mathbf{a} \in \{\mathbf{k}_0, -\mathbf{k}_0\}} \left[1 - \exp\left(-\|\mathbf{k} - \mathbf{a}\|^2/\left(2D_n^2\right)\right)\right]. \tag{37}$$

For integer-bin interference in the controlled experiment, set just the two peak coefficients to zero. A broad notch removes adjacent image structure and is justified only when there is spectral leakage or drift. Neither bilateral filtering nor notching guarantees recovery of signal components lost through clipping or transfer-function zeros.

The checked-in degradation canvas contains a clean panel and five corrupted cases. Its comparative generator uses Gaussian noise with $\sigma = 25$ intensity codes, 8% impulse noise, centered Rayleigh noise, additive uniform noise, and periodic interference. The speckle and Poisson laws, adaptive median, and spectral notch form the extended benchmark. The application uses the captured ROI as its reference, including any sensor noise already present.




Fig. 16. Noise and degradation previews from the webcam session. The clean ROI is shown with Gaussian, salt-and-pepper, Rayleigh, uniform, and periodic interference. The salt-and-pepper panel has isolated black and white impulses, while the periodic panel has diagonal bands. These webcam previews are separate from the synthetic phantom experiment in Section 3.1. Source is CSRT frame 125.

5. Literature Review

Classical tracking studies establish two complementary approaches. Bolme et al. [2] and Henriques et al. [3] use correlation filters to reduce the cost of local search. Lukežič et al. [4] address background contamination by constraining filter support and weighting channels. Babenko et al. [14] instead formulate online tracking as multiple-instance learning, allowing uncertainty about which sampled patch best represents the target.

Detector-based approaches distinguish detection confidence from temporal association. Aharon et al. [6] combine motion and camera compensation in BoT-SORT, with appearance cues available under supported configurations. Zhang et al. [7] use low-score detections in a second association stage to recover otherwise unmatched tracks.

These studies motivate the selectable backend design. The project adds inspection and telemetry at the application level.

The DIP work follows the spatial and frequency methods organized by Gonzalez and Woods [1]. Canny [15] and Otsu [16] provide edge and thresholding methods. Haralick et al. [8] and Hu [9] characterize texture and shape. Ahmed et al. [10] and the JPEG recommendation [18] motivate the transform-coding profiler, while Wang et al. [19] define structural similarity. These sources support the mathematical methods. The project evaluation concerns their use on frame-aligned tracked regions.

6. State-of-the-Art Techniques

The project compares mature single-object trackers with detection-and-association methods. MOSSE and KCF favor economical local updates. CSRT is designed to improve localization where the initial box includes clutter. MIL offers a classifier-based classical baseline. YOLOv8n with BoT-SORT or ByteTrack adds semantic detection and identity association. These approaches have different initialization requirements. Classical trackers can start from an operator-selected region, while the deep path depends on a detector candidate and its association settings.

The OTB benchmark [12] supports annotated single-target box evaluation. The VOT2020 toolkit [13] defines a separate challenge protocol. Results published under those protocols, or in the original association papers [6], [7], are contextual evidence. Direct comparison of accuracy, F1, Cohen's kappa, sensitivity, specificity, IoU, or FPS requires matched labels, thresholds, timing boundaries, and hardware. Section 7 keeps those project metrics within the supplied common comparison.

7. Comparative Evaluation

TABLE VIII
SUPPLIED COMPARATIVE EVALUATION OF CLASSICAL AND DETECTOR-BASED TRACKERS

Tracker Model	Accuracy	Precision	Recall	F1-Score	Cohen's Kappa κ	Sensitivity	Specificity	Mean IoU	CLE (px)	FPS
CSRT	91.8%	92.4%	89.1%	90.7%	0.824	89.1%	94.6%	0.742	8.4 px	42.8
KCF	84.2%	85.1%	79.6%	82.2%	0.698	79.6%	91.2%	0.651	14.2 px	118.5
MOSSE	75.6%	76.8%	71.3%	73.9%	0.582	71.3%	88.0%	0.573	21.6 px	285.0
MIL	77.4%	78.9%	74.2%	76.5%	0.615	74.2%	89.1%	0.598	19.1 px	31.4
YOLOv8 + BoT-SORT	96.1%	96.8%	94.5%	95.6%	0.918	94.5%	98.2%	0.835	4.6 px	33.2
YOLOv8 + ByteTrack	94.8%	95.2%	93.8%	94.5%	0.895	93.8%	97.4%	0.812	5.3 px	38.6

Evidence designation: project-reported. Values are reproduced as supplied. The table has no accompanying frame-level labels, confusion matrices, run manifest, occlusion strata, or uncertainty estimates.

Compared with CSRT, the highest-scoring classical tracker in Table VIII, the reported BoT-SORT configuration gains 4.3 percentage points in accuracy, 4.9 in F1, 5.4 in sensitivity, and 3.6 in specificity. Cohen's kappa rises by 0.094 and mean IoU by 0.093, while throughput is 9.6 FPS lower. These are descriptive differences from the supplied table.

7.1 BoT-SORT agreement and the occlusion claim

The reported $\kappa = 0.918$ falls in the conventional "almost perfect" range [21] if computed from a valid comparison with reference labels. It is an agreement estimate for the frames and categories used in that comparison. Calling it inter-rater agreement requires independently defined ratings, and attributing it specifically to occlusion requires an occlusion-stratified analysis. No such breakdown accompanies the supplied result. BoT-SORT leads ByteTrack by 0.023 in mean IoU, 0.7 px in CLE, and 0.023 in κ in the supplied table. Its plausible advantages include consistent

motion prediction and camera-motion compensation. Optional appearance cues can help resolve identity after re-entry if enabled. An ablation with the same detector outputs is necessary to attribute those differences to specific association components.

A consistency check follows from Accuracy = p Sensitivity + $(1 - p)$ Specificity. The supplied BoT-SORT percentages yield $p = (0.982 - 0.961)/(0.982 - 0.945) \approx 0.568$. This implies precision of approximately 98.57% under one pooled confusion matrix, whereas the table gives 96.8%. Rounding to one decimal place cannot account for the gap. Different averaging conventions or frame subsets could produce such a pattern, so the original denominators and counts are necessary. Agreement estimates should be reported with confidence intervals that respect the temporal correlation of adjacent frames. A paired bootstrap over independent sequences or sessions is preferable to resampling individual video frames.

7.2 CSRT specificity and spatial reliability

The supplied specificity of 94.6% corresponds to a false-positive rate of 5.4% under the stated presence definition. CSRT is the highest-specificity classical tracker in the table. Spatial reliability restricts correlation-filter support to target-consistent regions within the learning window [4]. This can lower responses to clutter that occupies the bounding box during learning. Channel weighting can further reduce the contribution of weak or unstable features. The mechanism supports a hypothesis for the observed ordering, while specificity also depends on the lock criterion and negative frames. A causal test would compare identical sequences and preprocessing with and without the spatial reliability mask and retain counts for occlusion, distractors, and out-of-view intervals.

7.3 MOSSE throughput and localization drift

At 285.0 updates/s, the reciprocal mean time per counted update is $1000/285 \approx 3.51$ ms. This consumes approximately 10.5% of the 33.33 ms period of a 30 FPS camera if both refer to the same serial update scope. It excludes acquisition, annotation, persistence, any recovery search, and display unless those components were included in the timing. MOSSE's frequency-domain update is economical, while a weak representation of target scale and changes in appearance can yield broad or ambiguous peaks. Its reported CLE of 21.6 px is about 2.57 times CSRT's 8.4 px and about 4.70 times BoT-SORT's 4.6 px. A fast tracker may still be practical for coarse motion monitoring. Small-ROI texture analysis requires tighter spatial registration because box drift changes the sampled pixel population.

7.4 Separation from the repository demonstration figures

The README reports classical updates over 200 frames and a 60-frame CPU comparison for YOLO. It lists average rates of 35.88 FPS for CSRT, 309.18 for KCF, 19.25 for MIL, and 3125.46 for MOSSE. The corresponding CPU deep-path figures are 12.96 FPS for BoT-SORT and 17.23 FPS for ByteTrack. These are project-reported demo rates with a different scope from Table VIII. The README's classical success rate is a tracker-output statistic and does not establish presence accuracy or box overlap against annotations. No source-level basis establishes that the two tables used the same timer, device, or video. The values should remain separate pending the run manifests.

7.5 Discussion, Error Analysis, and Limitations

Occlusion exceeding three seconds. At 30 FPS, three seconds spans approximately 90 source frames. Motion uncertainty grows during the gap. A fixed classical template becomes less representative if the object changes scale or pose before re-entry, while the highest NCC score can correspond to a similar-looking distractor. In a deep path, the effective lifetime of unmatched tracks and the availability of appearance cues govern whether an old identity can be retained. Three seconds is a failure-analysis scenario. The source provides no measured universal duration threshold. Useful diagnostics include time to recovery, false locks per episode, and performance stratified by occlusion length.

Motion blur and spectral structure. Translational exposure blur convolves the image with a line PSF. Its frequency response is sinc-like, with direction-dependent attenuation and zeros. This suppresses bands in the Fourier spectrum and smears edges in the spatial domain. Rapid motion and rolling shutter can make that

degradation spatially varying. A Wiener filter reduces noise amplification near spectral nulls, while structural information lost at those nulls remains poorly identifiable. Centroid motion between delivered frames and motion integrated during exposure are distinct quantities.

Out-of-plane rotation. A planar view can change under a projective warp, while a three-dimensional target can self-occlude and expose surfaces absent from the reference. Multi-scale NCC compensates for isotropic resizing but cannot explain those appearance changes. Hu invariants handle ideal planar translation, scale, and rotation and do not preserve descriptors under arbitrary perspective. Axis-aligned boxes around a rotating object can admit a changing fraction of background, affecting entropy, GLCM, Otsu threshold, and contour area.

Segmentation-to-measurement error. Tracking gives a search window, and segmentation decides which samples represent the object. CLAHE, threshold polarity, morphology, and connected-component selection can dominate the resulting shape measurements. A tracker with acceptable mean IoU can still clip a diagnostically important edge. Testing should perturb each side of a fixed ROI, then measure the response of area, perimeter, texture, and DCT statistics. Baseline masks should include known polygons, holes, touching components, and an object near a crop boundary.

Operational limits. Interactive modal inspection blocks the unified tracking loop. A live subject may move while the operator inspects a frozen image, and capture buffering can affect the first frame after resume. Displacement across the pause may be poorly resolved. Copying is proportional to the frame or ROI area, while a 2-D FFT scales approximately as $O\big(MN\log(MN)\big)$ and a full-frame multiscale NCC search can dominate recovery time. Synchronous CSV output adds storage-dependent jitter. The system has a camera and operator feedback interface. Closed-loop actuator control and physical measurement calibration are outside the audited prototype.

Evidence limits. The project-reported figures lack the recordings, hashes, labels, configuration, and run logs needed for independent performance claims. The Hu and GLCM summaries require their originating contour and convention. The discrepancies in Sections 4.5–4.6 and §7.1 should be reconciled with frame-level evidence before drawing inferential conclusions. Table V has a complete analytic input and parameter specification.

8. Conclusion

IPA_GIG integrates target selection, classical and neural tracking, region-specific inspection, and telemetry through a common frame and target contract. Its primary engineering result is the ability to examine an unannotated crop of a tracked object across spatial, spectral, color, geometric, texture, compression, and degradation domains while retaining frame provenance. The repository implements startup backend selection, a copied modal ROI, single-template classical recovery, JPEG-style block reconstruction, and separate tracking and snapshot CSV streams.

The supplied benchmark indicates a trade-off between MOSSE's low update cost and localization error, with BoT-SORT leading the reported localization and agreement figures. Its absence of frame-level evidence limits the comparison to descriptive interpretation. The synthetic benchmark independently demonstrates restoration gains under six specified perturbations and shows why exceptionally high scores from known-frequency notching depend on the test conditions. The distinction between implemented behavior, reported values, and measured synthetic results establishes a basis for evaluating later improvements.

9. Future Work and Scope

Direction	Technical work and evaluation
Edge inference	Export YOLOv8n to an appropriate intermediate format and benchmark FP16 or calibrated INT8 using NVIDIA TensorRT on Jetson Orin. Evaluate Hailo-8 separately with the Hailo compiler and HailoRT toolchain. Measure detector accuracy, end-to-end latency, power, and thermal throttling under the same video replay. NVIDIA TensorRT · Hailo-8

Direction	Technical work and evaluation
3-D LiDAR or depth fusion	Calibrate camera intrinsics and intersensor extrinsics, synchronize timestamps, and project depth into the ROI. Fuse depth and image-plane motion in a state estimator and quantify registration and occlusion errors.
Multi-camera re-ID and MQTT handover	Publish timestamped track events over MQTT and associate identities using appearance embeddings and camera topology. Define event deduplication, TTL, clock error, access control, and handover latency.
Image-based visual servoing (IBVS)	Control an actuator using image-plane feature error and a calibrated interaction matrix. Include saturation, loss-of-track behavior, and a stop condition. Validate stability across control delays and intermittent observations.
Online contrastive adaptation	Form positive pairs from high-confidence observations of one target and maintain a replay bank of negative or competing tracks. Gate model updates and test identity switches, contamination, and catastrophic forgetting.
Runtime isolation and reproducible evaluation	Add a bounded event writer and separate live capture from inspection. Compare single- and multi-scale NCC by episode, then publish a benchmark manifest, per-sequence counts, sampled raw evidence, and timing distributions.

10. Bibliography

The foundational bibliography groups the works used to develop the report. Digital image processing and coding are covered by [1], [8]–[10], and [15]–[19]. Tracking and data association are covered by [2]–[7] and [14]. Dataset provenance and agreement methodology are documented in [11]–[13] and [20], [21]. The numbered citations below provide the full publication and source details.

11. References

Core references

[1] R. C. Gonzalez and R. E. Woods, *Digital Image Processing*, 4th ed. New York, NY, USA: Pearson, 2018.

[2] D. S. Bolme, J. R. Beveridge, B. A. Draper, and Y. M. Lui, “Visual object tracking using adaptive correlation filters,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2010, pp. 2544–2550, doi: 10.1109/CVPR.2010.5539960.

[3] J. F. Henriques, R. Caseiro, P. Martins, and J. Batista, “High-speed tracking with kernelized correlation filters,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 37, no. 3, pp. 583–596, Mar. 2015, doi: 10.1109/TPAMI.2014.2345390.

[4] A. Lukežič, T. Vojíř, L. Č. Zajc, J. Matas, and M. Kristan, “Discriminative correlation filter with channel and spatial reliability,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2017, pp. 4847–4856, doi: 10.1109/CVPR.2017.515.

[5] Ultralytics, “Ultralytics YOLOv8,” 2023. Accessed: Nov. 3, 2026. [Online]. Available: docs.ultralytics.com/models/yolov8.

[6] N. Aharon, R. Orfaig, and B.-Z. Bobrovsky, “BoT-SORT: Robust associations multi-pedestrian tracking,” *arXiv:2206.14651*, 2022. [Online]. Available: arxiv.org/abs/2206.14651.

[7] Y. Zhang *et al.*, “ByteTrack: Multi-object tracking by associating every detection box,” in *Proc. Eur. Conf. Comput. Vis. (ECCV)*, 2022, pp. 1–21. [Online]. Available: ECVA proceedings.

[8] R. M. Haralick, K. Shanmugam, and I. Dinstein, “Textural features for image classification,” *IEEE Trans. Syst., Man, Cybern.*, vol. SMC-3, no. 6, pp. 610–621, Nov. 1973, doi: 10.1109/TSMC.1973.4309314.

[9] M.-K. Hu, “Visual pattern recognition by moment invariants,” *IRE Trans. Inf. Theory*, vol. 8, no. 2, pp. 179–187, Feb. 1962, doi: 10.1109/TIT.1962.1057692.

[10] N. Ahmed, T. Natarajan, and K. R. Rao, “Discrete cosine transform,” *IEEE Trans. Comput.*, vol. C-23, no. 1, pp. 90–93, Jan. 1974, doi: 10.1109/T-C.1974.223784.

Data, standards, and supporting methods

[11] T.-Y. Lin *et al*., “Microsoft COCO: Common objects in context,” in *Proc. Eur. Conf. Comput. Vis. (ECCV)*, 2014, pp. 740–755. COCO 2017 split and detector classes documented by Ultralytics. COCO Detection Dataset.

[12] Y. Wu, J. Lim, and M.-H. Yang, “Object tracking benchmark,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 37, no. 9, pp. 1834–1848, Sep. 2015, doi: 10.1109/TPAMI.2014.2388226. OTB-2015 dataset.

[13] VOT Challenge, “VOT2020 datasets,” 2020. [Online]. Available: votchallenge.net/vot2020/dataset.html.

[14] B. Babenko, M.-H. Yang, and S. Belongie, “Visual tracking with online multiple instance learning,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2009, pp. 983–990, doi: 10.1109/CVPR.2009.5206737.

[15] J. Canny, “A computational approach to edge detection,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. PAMI-8, no. 6, pp. 679–698, Nov. 1986, doi: 10.1109/TPAMI.1986.4767851.

[16] N. Otsu, “A threshold selection method from gray-level histograms,” *IEEE Trans. Syst., Man, Cybern.*, vol. 9, no. 1, pp. 62–66, Jan. 1979, doi: 10.1109/TSMC.1979.4310076.

[17] T. Y. Zhang and C. Y. Suen, “A fast parallel algorithm for thinning digital patterns,” *Commun. ACM*, vol. 27, no. 3, pp. 236–239, Mar. 1984, doi: 10.1145/357994.358023.

[18] ITU-T, *Information Technology—Digital Compression and Coding of Continuous-Tone Still Images—Requirements and Guidelines*, Recommendation T.81, Sep. 1992. ITU-T T.81.

[19] Z. Wang, A. C. Bovik, H. R. Sheikh, and E. P. Simoncelli, “Image quality assessment: From error visibility to structural similarity,” *IEEE Trans. Image Process.*, vol. 13, no. 4, pp. 600–612, Apr. 2004, doi: 10.1109/TIP.2003.819861.

[20] J. Cohen, “A coefficient of agreement for nominal scales,” *Educ. Psychol. Meas.*, vol. 20, no. 1, pp. 37–46, Apr. 1960, doi: 10.1177/001316446002000104.

[21] J. R. Landis and G. G. Koch, “The measurement of observer agreement for categorical data,” *Biometrics*, vol. 33, no. 1, pp. 159–174, Mar. 1977, doi: 10.2307/2529310.

12. GitHub Project Repository

IPA_GIG project repository
https://github.com/anishkarak4-ux/IPA_GIG

Audited source revision
474498884b22ca5698bbfc57077f1ae107e0c704

The project identifies the public repository as its open-source release. A standalone license file was absent from the audited tree, so the applicable permissions should be established from the repository and dependency terms before redistribution.

13. Team Member Contributions and Sign-Off

TABLE IX
TEAM MEMBER ALLOCATION

Student	Roll No.	Role	Technical responsibility
Anish Karak	24155833	Co-Developer	Spatial transformations, contour geometry, and Haralick textures
Yash Agrawal	241551089	Co-Developer	Frequency-domain 2-D FFT and 8×8 block-DCT transform coding
Awesh Khan	24155837	Co-Developer	Multi-channel color representations and stochastic degradation modeling
Priyaranjan Sahu	241551055	Co-Developer	Segmentation, mathematical morphology, and comparative tracking

Each team member should sign and date the line corresponding to their name.

Student	Roll No.	Signature	Date
Anish Karak	24155833		
Yash Agrawal	241551089		
Awesh Khan	24155837		
Priyaranjan Sahu	241551055		

[BLANK SPACE RESERVED FOR DETAILED INDIVIDUAL WRITE-UPS, SUPERVISOR REMARKS, AND UNIVERSITY EVALUATION SIGN-OFF — TO BE COMPLETED BY TEAM MEMBERS]

Faculty supervisor signature _____ Date _____

Prof. Sricheta Parui | School of Computer Engineering