

DARHUB Backend | Mobile integration reference

Farmer Profile API Routes

Complete request, response, authentication, update, and error reference

Base path: /api/farmer | Route source: routes/farmerRoutes.js | Last verified: 2026-09-06

1. Overview

The farmer profile router exposes two routes. Both routes require the authenticated farmer's access token and resolve the farmer from the JWT subject. The profile tabs are selected with the tab query parameter.

Authentication: send `Authorization: Bearer <access_token>` on every request. The access token is verified with the backend JWT secret. Tokens are issued by the authentication flow and must not be hard-coded in the app.

Method	Path	Purpose
GET	/api/farmer/profile	Read one profile view selected by tab.
PATCH	/api/farmer/profile	Update the personal profile view. Currently only tab=personal is supported.

2. Shared Errors

Status	When	Response
401	Authorization header is missing, malformed, expired, or invalid.	<pre>{ "success": false, "code": "NO_TOKEN", "message": "No token provided. Unauthorized!"}</pre> or the same shape with code <code>TOKEN_EXPIRED</code> .
400	tab is missing or not supported.	<pre>{ "success": false, "message": "tab query parameter is required" }</pre> For GET, an unknown value returns <code>Invalid tab specified</code>. For PATCH, unsupported values return <code>Updating this tab is not supported yet</code>.

404	The user from the token does not exist.	{ "success": false, "message": "Farmer not found" }
500	Unexpected database or server error.	{ "success": false, "message": "Internal Server Error", "error": "..." }

3. GET Profile

GET /api/farmer/profile?tab={tab}

Returns the authenticated farmer's selected profile view.

Query parameter	Required	Allowed values
tab	Yes	main, personal, farm, address, bank

All successful GET responses use this envelope:

```
{
  "success": true,
  "data": { ... }
}
```

3.1 Main overview

Request: GET /api/farmer/profile?tab=main

```
{
  "success": true,
  "data": {
    "user_info": {
      "name": "Ramesh Yadav",
      "verified": true,
      "mobile_number": "9876543210",
      "email": "ramesh@example.com",
      "member_since": "2024-03-12T10:00:00.000Z",
      "account_type": "Farmer",
      "profile_image": "https://example.com/profile.jpg",
      "location": "Gondal, Rajkot"
    },
    "farm_summary": {
      "total_acres": "21.0",
      "active_crops": 3,
      "total_fields": 2,
      "upcoming_bookings": 2
    }
  }
}
```

Implementation note: total_acres is currently calculated as non-primary address count multiplied by 10.5 and returned as a string. active_crops is a derived placeholder. verified is currently always true.

3.2 Personal information

Request: GET /api/farmer/profile?tab=personal

```
{
  "success": true,
  "data": {
    "personal_info": {
      "first_name": "Ramesh",
      "last_name": "Yadav",
      "mobile_number": "9876543210",
      "email": "ramesh@example.com",
      "dob": "1990-05-12T00:00:00.000Z",
      "profile_image": "https://example.com/profile.jpg",
      "gender": "Male",
      "marital_status": "Married",
      "education": "Graduate",
      "occupation": "Farmer"
    },
    "address_details": {
      "lane_1": "Main Road",
      "lane_2": "",
      "state": 1,
      "district": 5,
      "block": 12,
      "village": "Gondal",
      "pincode": "360311"
    }
  }
}
```

If no primary address exists, address_details is null. Gender, marital status, education, and occupation are currently hard-coded response values.

3.3 Farm information

Request: GET /api/farmer/profile?tab=farm

```
{
  "success": true,
  "data": {
    "farms": [
      {
        "id": 102,
        "farm_name": "Yadav Farm",
        "farm_type": "Owner",
        "total_land_owned": 12.5,
        "irrigation_type": "Borewell",
        "primary_soil_type": "Clay Loam",
        "water_source": "Borewell",
        "description": "Agricultural farm focused on essential crops.",
        "address": {
          "lane_1": "Gondal Road", "lane_2": "", "state": 1,
          "district": 5, "block": 12, "village": "Gondal", "pincode": "360311"
        },
        "fields": [
          { "name": "Field A", "acres": 5, "soil_type": "Clay Loam", "irrigation": "Borewell" },
          { "name": "Field B", "acres": 7.5, "soil_type": "Sandy Loam", "irrigation": "Drip" }
        ]
      }
    ]
  }
}
```

```
}  
  ]  
}  
}
```

Only non-primary UserAddress records are mapped to farms. Farm and field attributes shown above are currently placeholder values generated by the controller; farm_name is derived from lane_1.

3.4 Address list

Request: GET /api/farmer/profile?tab=address

```
{
  "success": true,
  "data": {
    "addresses": [
      {
        "id": 101,
        "is_primary": true,
        "type": "Home",
        "lane_1": "House No 5, Gondal",
        "lane_2": "",
        "state": 1,
        "district": 5,
        "block": 12,
        "village": "Gondal",
        "pincode": "360001"
      },
      {
        "id": 102,
        "is_primary": false,
        "type": "Farm/Warehouse",
        "lane_1": "Aji GIDC",
        "lane_2": "",
        "state": 1,
        "district": 5,
        "block": 12,
        "village": "Gondal",
        "pincode": "360003"
      }
    ]
  }
}
```

3.5 Bank and UPI details

Request: GET /api/farmer/profile?tab=bank

```
{
  "success": true,
  "data": {
    "bank_accounts": [
      {
        "id": 15,
        "bank_name": "State Bank of India",
        "acc_holder_name": "Ramesh Yadav",
        "acc_number": "XXXX XXXX 1234",
        "ifsc_code": "SBIN0001234",
        "is_primary": true,
        "passbook_image_url": "https://example.com/passbook.jpg"
      }
    ],
    "upi_details": [
      { "id": 8, "upi_id": "rameshyadav@sbi" }
    ]
  }
}
```

Bank and UPI arrays are returned from the database. Treat bank account numbers as sensitive data and mask them in the UI.

4. PATCH Profile

PATCH /api/farmer/profile?tab=personal

Partially updates the authenticated farmer's personal details and primary address.

Content type: application/json. The request body may include either object or both objects. Omitted properties are preserved.

```
{
  "personal_info": {
    "first_name": "Ramesh",
    "last_name": "Yadav",
    "mobile_number": "9876543210",
    "email": "ramesh@example.com",
    "dob": "1990-05-12",
    "profile_image": "https://example.com/profile.jpg"
  },
  "address_details": {
    "lane_1": "Main Road",
    "lane_2": "Near Market",
    "state": 1,
    "district": 5,
    "block": 12,
    "village": "Gondal",
    "pincode": "360311"
  }
}
```

Body object	Supported fields	Behavior
personal_info	first_name, last_name, mobile_number, email, dob, profile_image	Updates User for mobile/email and UserProfile for the remaining supported fields.
address_details	lane_1, lane_2, state, district, block, village, pincode	Updates the existing primary address, or creates one with is_primary: true when none exists.

Successful response:

```
{
  "success": true,
  "message": "Personal profile updated successfully"
}
```

Current limitation: the PATCH handler does not update gender, marital status, education, occupation, bank details, UPI details, farm records, or non-primary addresses. PATCH requests using any tab other than personal return HTTP 400.

5. Integration Checklist

- Store the access token securely and attach it as a Bearer token.
- Send one of the five supported GET tab values exactly as documented.
- Handle `address_details`: `null` and empty arrays without assuming records exist.
- Display `total_acres` as a string for now; do not assume it is a numeric field.
- Mask account numbers in the UI and avoid logging bank responses.
- For profile edits, send only the fields being changed and use `tab=personal`.
- After a successful PATCH, refresh the personal tab because the update response is message-only.

Prepared from the live route and controller implementation. Sample names, IDs, URLs, and values are illustrative unless marked as implementation-derived.