

Code Problem Solutions

5/5/2026, 11:12:31 PM

ab mai tuze practicals ke probelm statements dunga aur codes bhi dunga tu bata kya vo codes sahi hai ya galat.	2
Design and implement Parallel Breadth First Search and Depth First Search based on existing algorithms using OpenMP. Use a Tree or an undirected graph for BFS and DFS . #include <iostream> #include <vector> #include <queue> #include <omp.h> using namespace std; // ----- PARALLEL BFS ----- void parallelBFS(vector<vector<int>>& graph, int start) { int n = graph.size(); vector<bool> visited(n, false); queue<int> q; visited[start] = true; q.push(start); cout << "BFS Traversal: "; while (!q.empty()) { int node; #pragma omp critical { node = q.front(); q.pop(); cout << node << " "; } #pragma omp parallel for.	2
isko kaise aur kaha run kre.	10
ubuntu pe krna hai to kaise aur kuch install krna hoga kya.	12
konsi 3.	14
anish@LAPTOP-3JPSGL7M:~/openmp_practical\$./bfs_dfs BFS Traversal: 0 1 2 3 4 BFS Execution Time: 0.0292641 seconds DFS Traversal: 0 1 3 2 4 DFS Execution Time: 0.0156932 seconds anish@LAPTOP-3JPSGL7M:~/openmp_practical\$ explain kr.	15
Write a program to implement Parallel Bubble Sort and Merge sort using OpenMP. Use existing algorithms and measure the performance of sequential and parallel algorithms. #include <iostream> #include <vector> #include <omp.h> #include <cstdlib> using namespace std; // ----- SEQUENTIAL BUBBLE SORT ----- void bubbleSortSequential(vector<int>& arr) { int n = arr.size(); for(int i = 0; i < n-1; i++) { for(int j = 0; j < n-i-1; j++) { if(arr[j] > arr[j+1]) { swap(arr[j], arr[j+1]); } } } // ----- PARALLEL BUBBLE SORT ----- void bubbleSortParallel(vector<int>& arr) { int n = arr.size(); for(in.	18
anish@LAPTOP-3JPSGL7M:~/sort_openmp\$./sort_openmp Sequential Bubble Sort Time: 4.96608 seconds Parallel Bubble Sort Time: 21.1619 seconds Sequential Merge Sort Time: 0.0202348 seconds Parallel Merge Sort Time: 0.027865 seconds anish@LAPTOP-3JPSGL7M:~/sort_openmp\$.	25
Implement Min, Max, Sum and Average operations using Parallel Reduction. #include <iostream> #include <vector> #include <omp.h> #include <cstdlib> using namespace std; int main() { int n = 1000000; // Input size vector<int> arr(n); // Generate random numbers for(int i = 0; i < n; i++) arr[i] = rand() % 1000; int min_val = arr[0]; int max_val = arr[0]; long long sum = 0; double start, end; // Parallel Reduction start = omp_get_wtime(); #pragma omp parallel for reduction(min:min_val) reduction(max:max_val) reduction(+:sum) for(int i = 0; i < n; i++) { if(arr[i] < min_val) min_val = arr[i]; if(arr[i] > max_val).	29
anish@LAPTOP-3JPSGL7M:~/min_max_sum_avg\$./reduction Minimum Value: 0 Maximum Value: 999 Sum: 499562283 Average: 499.562 Execution Time: 0.00728151 seconds anish@LAPTOP-3JPSGL7M:~/min_max_sum_avg\$.	34
Implement HPC application for AI/ML domain. #include <iostream> #include <vector> #include <cmath> #include <cstdlib> #include <omp.h> using namespace std; #define N 10000 #define K 3 #define MAX_ITER 100 struct Point { double x, y; int cluster; }; double distance(Point a, Point b) { return sqrt((a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y)); } int main() { vector<Point> points(N); vector<Point> centroids(K); for(int i = 0; i < N; i++) { points[i].x = rand() % 100; points[i].y = rand() % 100; points[i].cluster = 0; } for(int i = 0; i < K; i++) centroids[i] = points[i]; double start = omp_get_w.	37
anish@LAPTOP-3JPSGL7M:~/hpc_aiml\$./program K-Means Clustering Completed Execution Time: 0.0124322 seconds anish@LAPTOP-3JPSGL7M:~/hpc_aiml\$.	44
bostonhousednn.ipynbFilenow deep learning Linear regression by using Deep Neural network: Implement Boston housing price prediction problem by Linear regression using Deep Neural network. Use Boston House price prediction dataset.	47
what is output and explain the output.	52
samjha nhi house ka price ka kaise.	55
lekin vo input kya lega run krne ke baad matlab user se lega ya kaha se.	57
two.ipynbFileClassification using Deep neural network Binary classification using Deep Neural Networks Example: Classify movie reviews into positive" reviews and "negative" reviews, just based on the text content of the reviews. Use IMDB dataset now explain thisd.	59
to yaha kaise output aayega aur input kya lega.	64
three.ipynbFileConvolutional neural network (CNN) Use MNIST Fashion Dataset and create a classifier to classify fashion clothing into categories.	67
ye kaise output dega.	71
ab tak apn ne 7 practicals dekhe list out kro.	73
abhi sabhi ke liye viva mai kya kya puch skte hai aise 15 15 sawal har kisi ke do aur answer bhi based on practicals.	75

ab mai tuze practicals ke probelm statements dunga aur codes bhi dunga tu bata kya vo codes sahi hai ya galat

Perfect 👍

Tu problem statement + code bhej — main clearly bataunga:

- ✅ Code correct hai ya nahi
- ❌ Agar galat hai to kya issue hai
- 🔧 Kaise fix karna hai (with corrected code)
- 💡 Aur short explanation bhi dunga (taaki tu confidently explain kar sake)

Jab ready ho, first problem bhej 🚀

Design and implement Parallel Breadth First Search and Depth First Search based on existing algorithms using OpenMP. Use a Tree or an undirected graph for BFS and DFS .

```
#include <iostream>
#include <vector>
#include <queue>
#include <omp.h>

using namespace std;

// ----- PARALLEL BFS -----
void parallelBFS(vector<vector<int>>& graph, int start) {
    int n = graph.size();
    vector<bool> visited(n, false);
    queue<int> q;

    visited[start] = true;
    q.push(start);

    cout << "BFS Traversal: ";

    while (!q.empty()) {
        int node;

        #pragma omp critical
        {
            node = q.front();
            q.pop();
            cout << node << " ";
        }

        #pragma omp parallel for
        for (int i = 0; i < graph[node].size(); i++) {
            int neighbor = graph[node][i];
```

```

        #pragma omp critical
        {
            if (!visited[neighbor]) {
                visited[neighbor] = true;
                q.push(neighbor);
            }
        }
    }
}

// ----- PARALLEL DFS -----
void parallelDFS(vector<vector<int>>& graph, int node, vector<bool>& visited) {

    if (visited[node])
        return;

    #pragma omp critical
    {
        if (!visited[node]) {
            visited[node] = true;
            cout << node << " ";
        }
    }

    #pragma omp parallel for
    for (int i = 0; i < graph[node].size(); i++) {
        int neighbor = graph[node][i];

        if (!visited[neighbor]) {
            parallelDFS(graph, neighbor, visited);
        }
    }
}

// ----- MAIN FUNCTION -----
int main() {

    int n = 5;
    vector<vector<int>> graph(n);

    // Undirected Graph
    graph[0] = {1, 2};
    graph[1] = {0, 3, 4};
    graph[2] = {0};
    graph[3] = {1};
    graph[4] = {1};

    double start_time, end_time;

```

```
// ----- BFS -----
start_time = omp_get_wtime();
parallelBFS(graph, 0);
end_time = omp_get_wtime();

cout << "\nBFS Execution Time: " << end_time - start_time << " seconds\n\n";

// ----- DFS -----
vector<bool> visited(n, false);

cout << "DFS Traversal: ";
start_time = omp_get_wtime();
parallelDFS(graph, 0, visited);
end_time = omp_get_wtime();

cout << "\nDFS Execution Time: " << end_time - start_time << " seconds\n";

return 0;
}
```

isi code ka explanation dedo line wise

Thik hai — main **line-by-line explanation** deta hoon simple language mein, taaki tu exam ya viva mein confidently explain kar sake 🙌

◆ Header Files

C++
#include <iostream>

➡ Input-output ke liye (cout, cin)

C++
#include <vector>

➡ Graph ko store karne ke liye (adjacency list)

C++
#include <queue>

➡ BFS ke liye queue use hoti hai

C++
#include <omp.h>

➡ OpenMP library for parallel programming

◆ Namespace

C++

```
using namespace std;
```

→ Standard library ke functions directly use karne ke liye

=====

◆ PARALLEL BFS FUNCTION

=====

C++

```
void parallelBFS(vector<vector<int>>& graph, int start)
```

→ Function jo BFS perform karega

→ **graph** = adjacency list

→ **start** = starting node

C++

```
int n = graph.size();
```

→ Total number of nodes

C++

```
vector<bool> visited(n, false);
```

→ Sab nodes initially unvisited

C++

```
queue<int> q;
```

→ BFS ke liye queue

C++

```
visited[start] = true;  
q.push(start);
```

→ Start node ko visit mark kiya aur queue me dala

C++

```
cout << "BFS Traversal: ";
```

→ Output print

BFS Loop

C++

```
while (!q.empty())
```

→ Jab tak queue empty nahi hoti

C++

```
int node;
```

→ Current node store karne ke liye

C++

```
#pragma omp critical
{
    node = q.front();
    q.pop();
    cout << node << " ";
}
```

→ Critical section (IMPORTANT):

- Ek time pe sirf ek thread access kare
- Queue shared resource hai → race condition avoid karne ke liye

Steps:

- Queue se front element nikala
 - Print kiya
-

C++

```
#pragma omp parallel for
for (int i = 0; i < graph[node].size(); i++)
```

→ Neighbors ko parallel process karne ke liye loop

C++

```
int neighbor = graph[node][i];
```

→ Current neighbor

C++

```
#pragma omp critical
{
    if (!visited[neighbor]) {
        visited[neighbor] = true;
        q.push(neighbor);
    }
}
```

→ Again critical section:

- Check visited
- Mark visited
- Queue me add

👉 Ye bhi shared data hai → synchronization needed

=====

PARALLEL DFS FUNCTION

=====

C++

```
void parallelDFS(vector<vector<int>>& graph, int node, vector<bool>& visited)
```

- DFS recursive function
- **visited** reference me pass kiya

C++

```
if (visited[node])
    return;
```

- Agar already visit ho chuka hai → return

C++

```
#pragma omp critical
{
    if (!visited[node]) {
        visited[node] = true;
        cout << node << " ";
    }
}
```

- Critical section:

- Node ko visit mark kiya
- Print kiya

C++

```
#pragma omp parallel for
for (int i = 0; i < graph[node].size(); i++)
```

- Har neighbor ko parallel process

C++

```
int neighbor = graph[node][i];
```

- Neighbor node

C++

```
if (!visited[neighbor]) {
    parallelDFS(graph, neighbor, visited);
}
```

- Recursive DFS call

⚠ NOTE:

- Yaha race condition ho sakta hai (visited check parallel hai)
- Real parallel DFS thoda complex hota hai

=====

◆ MAIN FUNCTION

=====

C++
`int main()`

→ Program execution start

C++
`int n = 5;
vector<vector<int>> graph(n);`

→ 5 nodes ka graph banaya

Graph Creation (Undirected)

C++
`graph[0] = {1, 2};
graph[1] = {0, 3, 4};
graph[2] = {0};
graph[3] = {1};
graph[4] = {1};`

→ Adjacency list representation

C++
`double start_time, end_time;`

→ Execution time measure karne ke liye

◆ BFS Execution

C++
`start_time = omp_get_wtime();
parallelBFS(graph, 0);
end_time = omp_get_wtime();`

→ Time measure kiya BFS ka

C++
`cout << "\nBFS Execution Time: " << end_time - start_time << " seconds\n\n";`

→ Time print

◆ DFS Execution

C++

```
vector<bool> visited(n, false);
```

→ DFS ke liye new visited array

C++

```
cout << "DFS Traversal: ";
```

→ Print label

C++

```
start_time = omp_get_wtime();
parallelDFS(graph, 0, visited);
end_time = omp_get_wtime();
```

→ DFS run + time measure

C++

```
cout << "\nDFS Execution Time: " << end_time - start_time << " seconds\n";
```

→ Time print

C++

```
return 0;
```

→ Program end

⚠ IMPORTANT (Viva ke liye)

Tu ye bol sakta hai 🙋

✅ Achha kya hai:

- OpenMP use kiya hai parallelism ke liye
- Critical sections se race condition avoid kiya
- BFS & DFS dono implement kiye

❌ Limitations:

- BFS actually fully parallel nahi hai (queue sequential hai)
- DFS me race condition possibility hai
- Performance gain zyada nahi milega small graphs me

🔥 Short Viva Summary

👉 "Is program me humne BFS aur DFS ko OpenMP ke through parallelize karne ki koshish ki hai. Shared data structures jaise queue aur visited array ko protect karne ke liye critical sections use kiye gaye hain.

However, BFS inherently sequential hai aur DFS me synchronization issues ho sakte hain.”

Agar tu chahe to main:

- ✓ Iska **perfect corrected parallel version**
- ✓ Ya **assignment format (Aim, Theory, Algorithm)**

bhi bana deta hoon 👍

isko kaise aur kaha run kre

Achha question hai 👍 — OpenMP wala code normal C++ ki tarah run nahi hota, thoda special compilation lagta hai. Main step-by-step bata raha hoon 👉

💎 ✓ OPTION 1: LOCAL SYSTEM (BEST METHOD)

💻 Requirements

- C++ compiler (GCC / MinGW / g++)
- OpenMP support

♦ Step 1: Code Save karo

File name:

`bfs_dfs.cpp`

♦ Step 2: Compile karo (IMPORTANT ⚠)

Bash

`g++ -fopenmp bfs_dfs.cpp -o output`

👉 -fopenmp **bahut important hai**

Without this → OpenMP kaam nahi karega

♦ Step 3: Run karo

Bash

`./output`

👉 Windows me:

Bash

output.exe

◆ ✓ OPTION 2: VS Code me run karna

◆ Step 1:

Install:

- C/C++ Extension (by Microsoft)

◆ Step 2:

Ensure compiler installed (MinGW)

◆ Step 3:

Terminal open karo (VS Code ke andar)

Run same command:

Bash

```
g++ -fopenmp bfs_dfs.cpp -o output
```

Run:

Bash

```
./output
```

◆ ✓ OPTION 3: ONLINE COMPILER (LIMITED SUPPORT ⚠)

Sab online compilers OpenMP support nahi karte.

Try kar sakta hai:

- OnlineGDB
- Replit

👉 But:

- Parallel execution properly show nahi karega
- Kabhi-kabhi error bhi aata hai

◆ ✓ OPTION 4: CODE::BLOCKS (if installed)

1. Settings → Compiler
2. "Other options" me add karo:

-fopenmp

3. Build & Run

COMMON ERRORS (EXAM IMPORTANT)

Error:

`omp.h not found`

✓ Fix:

- Compiler OpenMP support nahi karta
- Install proper GCC

Parallel kaam nahi kar raha

✓ Fix:

- -fopenmp flag missing

Output same aa raha sequential jaisa

✓ Reason:

- Graph chhota hai → parallel benefit nahi dikhega

BONUS (Viva Tip)

Examiner puch sakta hai:

👉 "How do you enable OpenMP?"

Tu bol:

"We compile using g++ with the -fopenmp flag which enables OpenMP directives."

Agar tu chahe to main:

- ✓ Screenshot based setup (Windows + VS Code)
- ✓ Ya fully working zip project

bhi bana deta hoon 👍

ubuntu pe krna hai to kaise aur kuch install krna hoga kya

Ubuntu pe run karna actually **sabse easy** hai 👍 (OpenMP mostly already supported hota hai). Main tujhe clean steps de raha hoon 👉

◆ ✓ Step 1: Check compiler installed hai ya nahi

Terminal open kar:

Bash
`g++ --version`

👉 Agar version show ho gaya → OK

👉 Agar error aaya → install karna padega

◆ ✓ Step 2: Agar g++ nahi hai to install karo

Bash
`sudo apt update`
`sudo apt install g++`

👉 Ye **GCC compiler** install karega (OpenMP support ke saath)

◆ ✓ Step 3: Code file banao

Bash
`nano bfs_dfs.cpp`

👉 Apna pura code paste kar

👉 Save: `Ctrl + O` → Enter

👉 Exit: `Ctrl + X`

◆ ✓ Step 4: Compile (MOST IMPORTANT ⚠)

Bash
`g++ -fopenmp bfs_dfs.cpp -o bfs_dfs`

👉 `-fopenmp` = OpenMP enable karta hai

◆ ✓ Step 5: Run karo

Bash
`./bfs_dfs`

◆ 🔥 OPTIONAL: Threads control karna

Default threads = CPU cores ke equal hote hain

Agar tu manually set karna chahta hai:

Bash

```
export OMP_NUM_THREADS=4
./bfs_dfs
```

👉 Yaha 4 threads use honge

💡 🔥 Verify parallel chal raha hai ya nahi

Code me ye line add kar sakta hai:

C++

```
cout << "Threads: " << omp_get_num_threads() << endl;
```

💡 ❌ Common Errors

❌ `omp.h` not found

✓ Fix:

Bash

```
sudo apt install libomp-dev
```

❌ Permission denied

✓ Fix:

Bash

```
chmod +x bfs_dfs
```

💡 🎯 Short Viva Answer

👉 "On Ubuntu, we compile the program using g++ with the `-fopenmp` flag. GCC has built-in support for OpenMP, so no separate installation is usually required."

🔥 Final Summary

👉 Ubuntu pe tujhe bas ye 3 commands yaad rakhni hai:

Bash

```
g++ -fopenmp bfs_dfs.cpp -o bfs_dfs
./bfs_dfs
```

Agar tu chahe to main:

- ✓ Output ka expected result
- ✓ Ya optimized parallel version (teacher ko impress karne wala 😎)

bhi de sakta hoon 🚀

konsi 3

Seedha yaad rakhne layak **ye 3 commands** 📌

Bash

```
g++ -fopenmp bfs_dfs.cpp -o bfs_dfs
./bfs_dfs
```

Aur agar install nahi hai to pehle:

Bash

```
sudo apt install g++
```

🔥 Final 3 Commands (Correct Order)

Bash

```
sudo apt install g++ # (sirf ek baar, agar compiler nahi hai)
g++ -fopenmp bfs_dfs.cpp -o bfs_dfs
./bfs_dfs
```

👉 Bas itna hi 👍

Agar exam me bole "commands batao" to tu confidently bol:

1. Install compiler (if needed)
2. Compile with `-fopenmp`
3. Execute the program 🚀

```
anish@LAPTOP-3JPSGL7M:~/openmp_practical$ ./bfs_dfs
BFS Traversal: 0 1 2 3 4
BFS Execution Time: 0.0292641 seconds

DFS Traversal: 0 1 3 2 4
DFS Execution Time: 0.0156932 seconds
anish@LAPTOP-3JPSGL7M:~/openmp_practical$ explain kr
```

Perfect 👍 tera code **sahi run ho raha hai** — ab main tujhe iska output **simple aur clear way me explain** karta hoon (viva ready 📌)

💠 OUTPUT ANALYSIS


✅ 1. BFS Traversal

BFS Traversal: 0 1 2 3 4

👉 BFS ka full form = **Breadth First Search**

👉 Ye level-by-level traverse karta hai

Tera graph:



BFS Steps:

1. Start from 0
2. Visit neighbors → 1, 2
3. Then visit next level → 3, 4

👉 Final order:

0 → 1 → 2 → 3 → 4

✓ Isliye tera output correct hai ✓

✓ 2. BFS Execution Time

0.0292641 seconds

👉 Ye time hai jo BFS ko run hone me laga

⚠ Important:

- Ye time system pe depend karta hai
- Har run me change ho sakta hai

DFS Traversal

DFS Traversal: 0 1 3 2 4

👉 DFS = **Depth First Search**

👉 Ye ek branch ko depth tak explore karta hai

DFS Steps:

1. Start → 0
2. Go to → 1
3. Go deeper → 3
4. Backtrack → 1
5. Go to → 4 (ya 2 depending on parallel execution)

👉 Tera output:

0 → 1 → 3 → 2 → 4

⚠️ IMPORTANT (VERY IMPORTANT FOR VIVA)

👉 DFS ka output **fix nahi hota** yaha

Kyuki:

- Tu **parallel DFS** use kar raha hai
- Threads alag-alag order me execute hote hain

👉 Isliye kabhi output ho sakta hai:

0 1 3 4 2
ya
0 2 1 3 4

✓ Sab correct hai (parallel execution ki wajah se)

✅ 3. DFS Execution Time

0.0156932 seconds

👉 DFS BFS se faster lag raha hai yaha

✓ Reason:

- Graph small hai
- Overhead kam hai

🔥 FINAL VIVA EXPLANATION (READY TO SPEAK)

Tu directly bol sakta hai 👉

"The BFS traversal visits nodes level by level starting from node 0, so the output is 0 1 2 3 4. The DFS traversal explores depth-wise, and since it is implemented using OpenMP, the order may vary due to parallel execution. The execution time shows how long each traversal took, which depends on system performance and thread scheduling."

💠 🔥 EXTRA SMART POINT (Teacher Impress 😎)

👉 Bol:

"Even though OpenMP is used, BFS is still mostly sequential due to the queue, and DFS may produce non-deterministic output because of parallel threads."

Agar tu chahe to next step me main:

- ✓ Iska **perfect theory + algorithm (assignment format)**
- ✓ Ya **diagram ke saath explanation (PPT ready)**

bhi bana deta hoon 🚀

Write a program to implement Parallel Bubble Sort and Merge sort using OpenMP. Use existing algorithms and measure the performance of sequential and parallel algorithms.

```
#include <iostream>
#include <vector>
#include <omp.h>
#include <cstdlib>

using namespace std;

// ----- SEQUENTIAL BUBBLE SORT -----
void bubbleSortSequential(vector<int>& arr) {
    int n = arr.size();
    for(int i = 0; i < n-1; i++) {
        for(int j = 0; j < n-i-1; j++) {
            if(arr[j] > arr[j+1]) {
                swap(arr[j], arr[j+1]);
            }
        }
    }
}

// ----- PARALLEL BUBBLE SORT -----
void bubbleSortParallel(vector<int>& arr) {
    int n = arr.size();

    for(int i = 0; i < n-1; i++) {

        #pragma omp parallel for
        for(int j = 0; j < n-i-1; j++) {
            if(arr[j] > arr[j+1]) {
                #pragma omp critical
                swap(arr[j], arr[j+1]);
            }
        }
    }
}

// ----- MERGE FUNCTION -----
void merge(vector<int>& arr, int left, int mid, int right) {

    int n1 = mid - left + 1;
    int n2 = right - mid;

    vector<int> L(n1), R(n2);
```

```

for(int i = 0; i < n1; i++)
    L[i] = arr[left + i];

for(int j = 0; j < n2; j++)
    R[j] = arr[mid + 1 + j];

int i = 0, j = 0, k = left;

while(i < n1 && j < n2) {
    if(L[i] <= R[j])
        arr[k++] = L[i++];
    else
        arr[k++] = R[j++];
}

while(i < n1)
    arr[k++] = L[i++];

while(j < n2)
    arr[k++] = R[j++];
}

// ----- SEQUENTIAL MERGE SORT -----
void mergeSortSequential(vector<int>& arr, int left, int right) {
    if(left < right) {
        int mid = left + (right - left) / 2;

        mergeSortSequential(arr, left, mid);
        mergeSortSequential(arr, mid + 1, right);

        merge(arr, left, mid, right);
    }
}

// ----- PARALLEL MERGE SORT -----
void mergeSortParallel(vector<int>& arr, int left, int right) {
    if(left < right) {
        int mid = left + (right - left) / 2;

        #pragma omp parallel sections
        {
            #pragma omp section
            mergeSortParallel(arr, left, mid);

            #pragma omp section
            mergeSortParallel(arr, mid + 1, right);
        }

        merge(arr, left, mid, right);
    }
}

```

```

}

// ----- MAIN FUNCTION -----
int main() {

    int n = 30000; // Increase for better comparison

    vector<int> arr(n);

    for(int i = 0; i < n; i++)
        arr[i] = rand() % 10000;

    vector<int> arr1 = arr;
    vector<int> arr2 = arr;
    vector<int> arr3 = arr;
    vector<int> arr4 = arr;

    double start, end;

    // Sequential Bubble Sort
    start = omp_get_wtime();
    bubbleSortSequential(arr1);
    end = omp_get_wtime();
    cout << "Sequential Bubble Sort Time: " << end - start << " seconds\n";

    // Parallel Bubble Sort
    start = omp_get_wtime();
    bubbleSortParallel(arr2);
    end = omp_get_wtime();
    cout << "Parallel Bubble Sort Time: " << end - start << " seconds\n";

    // Sequential Merge Sort
    start = omp_get_wtime();
    mergeSortSequential(arr3, 0, n-1);
    end = omp_get_wtime();
    cout << "Sequential Merge Sort Time: " << end - start << " seconds\n";

    // Parallel Merge Sort
    start = omp_get_wtime();
    mergeSortParallel(arr4, 0, n-1);
    end = omp_get_wtime();
    cout << "Parallel Merge Sort Time: " << end - start << " seconds\n";

    return 0;
}

```

now explain this

Good — ye code **overall correct hai**, but thoda “theoretical parallel” hai (real performance har case me better nahi aayega). Main tujhe **clear + viva-ready explanation** deta hoon 🙌

OVERVIEW

👉 Program 4 algorithms compare karta hai:

1. Sequential Bubble Sort
2. Parallel Bubble Sort (OpenMP)
3. Sequential Merge Sort
4. Parallel Merge Sort (OpenMP)

👉 Aur inka **execution time measure** karta hai

HEADER FILES

C++
`#include <iostream>`

➡ Output ke liye

C++
`#include <vector>`

➡ Dynamic array

C++
`#include <omp.h>`

➡ OpenMP (parallel programming)

C++
`#include <cstdlib>`

➡ `rand()` function ke liye

1. SEQUENTIAL BUBBLE SORT

C++
`void bubbleSortSequential(vector<int>& arr)`

👉 Classic bubble sort

Logic:

- Har pass me largest element end me chala jata hai

C++
`for(int i = 0; i < n-1; i++)`

➡ Passes

C++
`for(int j = 0; j < n-i-1; j++)`

→ Adjacent elements compare

C++

```
if(arr[j] > arr[j+1])
    swap(arr[j], arr[j+1]);
```

→ Swap if wrong order

✓ Time Complexity: $O(n^2)$

◆ 2. PARALLEL BUBBLE SORT

C++

```
void bubbleSortParallel(vector<int>& arr)
```

👉 Yaha OpenMP use kiya gaya hai

C++

```
#pragma omp parallel for
for(int j = 0; j < n-i-1; j++)
```

→ Inner loop parallel banaya

C++

```
#pragma omp critical
swap(arr[j], arr[j+1]);
```

→ Critical section:

- Ek time pe ek thread hi swap kare

⚠ IMPORTANT (VERY IMPORTANT)

👉 Ye perfect parallel bubble sort nahi hai

Problems:

- Adjacent swaps → dependency hoti hai
- Critical section → parallelism slow ho jata hai

👉 Isliye:

✗ Speed improvement guaranteed nahi hai

◆ 3. MERGE FUNCTION

C++

```
void merge(vector<int>& arr, int left, int mid, int right)
```

👉 Do sorted arrays ko merge karta hai

Steps:

1. Left array (L)
2. Right array (R)
3. Compare karke merge

C++

```
while(i < n1 && j < n2)
```

→ Compare elements

C++

```
arr[k++] = L[i++];
```

→ Smaller element insert

✓ Time Complexity: **O(n)**

◆ ◆ 4. SEQUENTIAL MERGE SORT

C++

```
void mergeSortSequential(vector<int>& arr, int left, int right)
```

👉 Divide & Conquer

Steps:

1. Array ko 2 parts me divide
2. Recursively sort
3. Merge

✓ Time Complexity: **O(n log n)**

◆ ◆ 5. PARALLEL MERGE SORT

C++

```
#pragma omp parallel sections
```

👉 Yaha parallelism apply kiya gaya

C++

```
#pragma omp section
mergeSortParallel(arr, left, mid);
```

C++

```
#pragma omp section
mergeSortParallel(arr, mid + 1, right);
```

→ Left aur right half parallel sort hote hain

👉 Fir merge hota hai

C++

```
merge(arr, left, mid, right);
```

✓ Advantage:

- ✓ Real parallelism yaha milta hai
- ✓ Large data me fast hota hai

◆ MAIN FUNCTION

C++
`int n = 30000;`

👉 Large input (performance compare ke liye)

C++
`arr[i] = rand() % 10000;`

👉 Random numbers generate

C++
`vector<int> arr1 = arr;
vector<int> arr2 = arr;
vector<int> arr3 = arr;
vector<int> arr4 = arr;`

👉 Same data copy kiya for fair comparison

◆ TIME MEASUREMENT

C++
`start = omp_get_wtime();`

➡ Start time

C++
`end = omp_get_wtime();`

➡ End time

C++
`cout << end - start;`

➡ Execution time

◆ OUTPUT EXPECTATION

👉 Generally:

Algorithm	Expected Speed
Sequential Bubble	Slow ✗
Parallel Bubble	Same ya slightly better

Algorithm	Expected Speed
Sequential Merge	Fast ✓
Parallel Merge	Fastest 🚀

🔥🔥 VIVA READY ANSWER

Tu directly bol sakta hai 🙌

"This program compares sequential and parallel implementations of Bubble Sort and Merge Sort using OpenMP. Parallel Bubble Sort uses parallel for but suffers from synchronization overhead due to critical sections. Parallel Merge Sort uses parallel sections to divide work efficiently, providing better performance for large datasets."

💠🔥 IMPORTANT POINTS (Teacher Impress 😎)

🙌 Bol ye:

- Bubble sort is **not suitable for parallelization**
- Merge sort is **naturally parallelizable**
- OpenMP directives used:
 - `parallel for`
 - `parallel sections`
 - `critical`

! FINAL VERDICT (MOST IMPORTANT)

✅ Code logically correct hai

⚠️ But:

- Parallel Bubble Sort efficient nahi hai
- Parallel Merge Sort best part hai code ka

Agar tu chahe to main:

✅ Iska **perfect optimized parallel version**

✅ Ya **assignment format (Aim, Theory, Algorithm, Conclusion)**

bhi bana deta hoon 🚀

```
anish@LAPTOP-3JPSGL7M:~/sort_openmp$ ./sort_openmp
Sequential Bubble Sort Time: 4.96608 seconds
Parallel Bubble Sort Time: 21.1619 seconds
```

```
Sequential Merge Sort Time: 0.0202348 seconds
Parallel Merge Sort Time: 0.027865 seconds
anish@LAPTOP-3JPSGL7M:~/sort_openmp$
```

Ye output actually **bahut important observation** hai — aur honestly bolu to ye **expected behavior** hai



Main tujhe clearly samjhata hoon 🙌

◆ OUTPUT BREAKDOWN

✓ 1. Sequential Bubble Sort

4.96608 seconds

👉 Slow hai (expected)

✓ Reason: Bubble Sort = $O(n^2)$

✓ 30,000 elements → heavy computation

✗ 2. Parallel Bubble Sort

21.1619 seconds ! (bahut slow)

👉 Ye shocking lagta hai, but **ye bilkul correct** hai

🔥 Reason:

✗ 1. Critical Section

C++

```
#pragma omp critical
swap(arr[j], arr[j+1]);
```

→ Har swap ke liye lock lag raha hai

→ Threads wait kar rahe hain

👉 Result:

Parallel → Serial ban gaya 😂

✗ 2. Data Dependency

👉 Bubble sort me:

- `arr[j]` aur `arr[j+1]` dependent hote hain

→ Parallelization difficult hai

❌ 3. Thread Overhead

👉 Threads create + manage karna bhi time leta hai

🔥 FINAL:

👉 Isliye:

Parallel Bubble Sort > Sequential Bubble Sort (time me ❌)

💠 3. Sequential Merge Sort

0.0202348 seconds

👉 Bahut fast ✓

✓ Reason: $O(n \log n)$

💠 4. Parallel Merge Sort

0.027865 seconds

👉 Slightly slower !

🤔 Why slower?

❌ Reason 1: Small Input

👉 30,000 elements → itna bada nahi hai

➡ Parallel overhead > benefit

❌ Reason 2: Thread Creation Cost

👉 Parallel sections create threads

➡ Time lagta hai

🔥 IMPORTANT CONCEPT

👉 Parallel tab fast hota hai jab:

✓ Data bahut bada ho (1 lakh+ / millions)

✓ Work independent ho

🔥 FINAL COMPARISON

Algorithm	Result	Reason
Seq Bubble	Slow	$O(n^2)$
Parallel Bubble	❌ Worst	Lock + dependency
Seq Merge	Fast	Efficient algorithm
Parallel Merge	Slightly slow	Overhead

💎 🔥 VIVA READY ANSWER (VERY IMPORTANT)

Tu ye confidently bol 🙋

"Parallel Bubble Sort performs worse than sequential because of synchronization overhead and data dependency between adjacent elements. Parallel Merge Sort is more efficient but for small input sizes, the overhead of thread management can make it slower than sequential Merge Sort."

💎 🔥 TEACHER IMPRESS LINE 😎

🙋 Bol ye:

"Not all algorithms benefit from parallelization. Bubble sort is inherently sequential, while merge sort is naturally parallelizable."

🔥 BONUS (AGAR MARKS BADHANE HAI)

🙋 Bol:

"If we increase input size significantly, parallel merge sort will outperform sequential merge sort."

⚠️ FINAL VERDICT

✅ Tera code correct hai

❗ Output bhi correct hai

💯 Conceptually perfect experiment hai

Agar tu chahe to main:

✅ Iska **graph (performance comparison)**

✅ Ya **assignment format (Aim, Theory, Conclusion)**

bhi bana deta hoon 🚀

Implement Min, Max, Sum and Average operations using Parallel Reduction.

```
#include <iostream>
#include <vector>
#include <omp.h>
#include <cstdlib>

using namespace std;

int main() {

    int n = 1000000; // Input size

    vector<int> arr(n);

    // Generate random numbers
    for(int i = 0; i < n; i++)
        arr[i] = rand() % 1000;

    int min_val = arr[0];
    int max_val = arr[0];
    long long sum = 0;

    double start, end;

    // Parallel Reduction
    start = omp_get_wtime();

    #pragma omp parallel for reduction(min:min_val) reduction(max:max_val) reduction(+:sum)
    for(int i = 0; i < n; i++) {
        if(arr[i] < min_val)
            min_val = arr[i];

        if(arr[i] > max_val)
            max_val = arr[i];

        sum += arr[i];
    }

    end = omp_get_wtime();

    double avg = (double)sum / n;

    cout << "Minimum Value: " << min_val << endl;
    cout << "Maximum Value: " << max_val << endl;
    cout << "Sum: " << sum << endl;
    cout << "Average: " << avg << endl;
    cout << "Execution Time: " << end - start << " seconds" << endl;
```

```
return 0;
} now explain this
```

Ye code **perfect example** hai **Parallel Reduction** ka 👍 — aur ye actually **correct + efficient implementation** hai (previous wale bubble sort se kaafi better 😊)

Main tujhe **line-by-line + concept + viva explanation** deta hoon 🙋

◆ OVERVIEW

👉 Program calculate karta hai:

- Minimum value
- Maximum value
- Sum
- Average

👉 Using **OpenMP Parallel Reduction**

◆ HEADER FILES

C++
`#include <iostream>`

➡ Output ke liye

C++
`#include <vector>`

➡ Array store karne ke liye

C++
`#include <omp.h>`

➡ OpenMP (parallel programming)

C++
`#include <cstdlib>`

➡ `rand()` use karne ke liye

◆ MAIN FUNCTION

C++
`int n = 1000000;`

➡ 10 lakh elements (large input → parallel benefit milega)

C++

```
vector<int> arr(n);
```

→ Dynamic array create kiya

C++

```
for(int i = 0; i < n; i++)
    arr[i] = rand() % 1000;
```

→ Random values fill ki (0-999)

◆ INITIAL VARIABLES

C++

```
int min_val = arr[0];
int max_val = arr[0];
long long sum = 0;
```

→ Initial values:

- min = first element
- max = first element
- sum = 0

C++

```
double start, end;
```

→ Time measurement

◆ PARALLEL REDUCTION (CORE PART 🔥)

C++

```
#pragma omp parallel for reduction(min:min_val) reduction(max:max_val) reduction(+:sum)
```

👉 Ye sabse important line hai

🔥 Reduction kya karta hai?

👉 Har thread apna **local copy** banata hai:

- min_val
- max_val
- sum

👉 End me sabko combine karta hai

◆ Breakdown:

1

C++

`reduction(min:min_val)`

→ Sab threads ka minimum nikalta hai

2

C++

`reduction(max:max_val)`

→ Sab threads ka maximum nikalta hai

3

C++

`reduction(+:sum)`

→ Sab threads ka sum add karta hai

◆ LOOP

C++

`for(int i = 0; i < n; i++)`

→ Entire array process hota hai

C++

`if(arr[i] < min_val)
 min_val = arr[i];`

→ Minimum update

C++

`if(arr[i] > max_val)
 max_val = arr[i];`

→ Maximum update

C++

`sum += arr[i];`

→ Sum calculate

◆ TIME END

C++

`end = omp_get_wtime();`

→ Execution time record

◆ AVERAGE

C++

```
double avg = (double)sum / n;
```

→ Average = Sum / n

◆ OUTPUT

C++

```
cout << "Minimum Value: " << min_val << endl;
```

→ Min print

C++

```
cout << "Maximum Value: " << max_val << endl;
```

→ Max print

C++

```
cout << "Sum: " << sum << endl;
```

→ Sum print

C++

```
cout << "Average: " << avg << endl;
```

→ Average print

C++

```
cout << "Execution Time: " << end - start << " seconds";
```

→ Time print

🔥 WHY THIS CODE IS BEST

👉 Previous codes me problem tha:

- ❌ critical section
- ❌ locks
- ❌ slow parallel

👉 Yaha:

- ✓ No locks
- ✓ No race condition
- ✓ True parallelism

◆ 🔥 VIVA READY ANSWER

Tu directly bol 👉

Printed using [ChatGPT to PDF](#), powered by PDFCrowd [HTML to PDF API](#).

"This program uses OpenMP reduction to compute min, max, sum, and average in parallel. Each thread maintains a private copy of variables and at the end, OpenMP combines them efficiently, avoiding race conditions and synchronization overhead."

IMPORTANT POINTS

👉 Reduction ka advantage:

- No need of **critical**
- No race condition
- Faster execution

COMPLEXITY

Operation	Complexity
Sequential	$O(n)$
Parallel	$O(n / \text{threads})$

TEACHER IMPRESS LINE

👉 Bol ye:

"Reduction is the most efficient way to perform aggregate operations like sum, min, and max in parallel programming."

FINAL VERDICT

- ✓ Code 100% correct
- ✓ Best OpenMP usage
- ✓ Practical ke liye perfect

Agar tu chahe to next step me main:

- ✓ Iska **sequential vs parallel comparison version**
- ✓ Ya **assignment format (Aim, Theory, Algorithm, Conclusion)**

bhi bana deta hoon 🚀

```

anish@LAPTOP-3JPSGL7M:~/min_max_sum_avg$ ./reduction
Minimum Value: 0
Maximum Value: 999
Sum: 499562283

```

Average: 499.562
 Execution Time: 0.00728151 seconds
 anish@LAPTOP-3JPSGL7M:~/min_max_sum_avg\$

Perfect 👍 — tera output **bilkul correct hai**. Ab main tujhe iska **clear explanation + viva points** deta hoon 🙌

◆ OUTPUT EXPLANATION

✓ 1. Minimum Value

Minimum Value: 0

👉 Tune random values generate ki:

C++
`rand() % 1000`

➡ Range = 0 to 999

✓ Isliye minimum 0 aana perfectly correct hai

✓ 2. Maximum Value

Maximum Value: 999

👉 Same reason:

- Maximum possible value = 999

✓ Output correct

✓ 3. Sum

Sum: 499562283

👉 Ye sabhi 10 lakh numbers ka total hai

✓ Approx expected value:

- Average ≈ 500
- $n = 1,000,000$

👉 Expected sum:

$$500 \times 1,000,000 = 500,000,000$$

✓ Tera result:

499,562,283 (very close)

👉 Means random distribution sahi hai

✅ 4. Average

Average: 499.562

👉 Formula:

Average = Sum / n

👉 Calculation:

499562283 / 1000000 ≈ 499.562

✅ Bilkul correct

✅ 5. Execution Time

0.00728151 seconds

👉 Ye sabse important part hai

✅ Bohot fast ⚡

🔥 WHY IT IS FAST?

👉 Kyuki tu use kar raha hai:

```
C++
#pragma omp parallel for reduction(...)
```

✅ Benefits:

- No locks (critical nahi hai)
- No race condition
- Work divide ho gaya threads me

👉 Isliye:

Parallel Reduction = Highly Efficient 🚀

💎 🔥 VIVA READY EXPLANATION

Tu ye bol sakta hai 👉

"The output shows correct minimum and maximum values within the expected range of 0 to 999. The sum and average are approximately 500 due to uniform random distribution. The execution time is very low because OpenMP reduction efficiently parallelizes the computation without synchronization overhead."

TEACHER IMPRESS POINT 🤖

👉 Ye line bol:

“Reduction avoids the need for critical sections and ensures thread-safe aggregation, making it one of the most efficient parallel constructs in OpenMP.”

FINAL ANALYSIS 🔥

Parameter	Result	Status
Min	0	✅ Correct
Max	999	✅ Correct
Sum	~5e8	✅ Correct
Avg	~500	✅ Correct
Time	Very Low	🚀 Excellent

FINAL VERDICT ✅

- ✅ Code correct
- ✅ Output correct
- ✅ Parallel implementation best
- 100 Practical ke liye perfect

Agar tu chahe to next:

- ✅ Iska **sequential vs parallel comparison version**
- ✅ Ya **full assignment write-up (Aim, Theory, Algorithm, Conclusion)**

bhi bana deta hoon 🚀

Implement HPC application for AI/ML domain.

#include

```
<iostream>
#include <vector>
#include <cmath>
#include <cstdlib>
#include <omp.h>
```

```
using namespace std;
```

```
#define N 10000
#define K 3
#define MAX_ITER 100
```

```

struct Point {
    double x, y;
    int cluster;
};

double distance(Point a, Point b) {
    return sqrt((a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y));
}

int main() {

    vector<Point> points(N);
    vector<Point> centroids(K);

    for(int i = 0; i < N; i++) {
        points[i].x = rand() % 100;
        points[i].y = rand() % 100;
        points[i].cluster = 0;
    }

    for(int i = 0; i < K; i++)
        centroids[i] = points[i];

    double start = omp_get_wtime();

    for(int iter = 0; iter < MAX_ITER; iter++) {

        // 1 Assign clusters (Parallel)
        #pragma omp parallel for
        for(int i = 0; i < N; i++) {

            double minDist = distance(points[i], centroids[0]);
            int clusterID = 0;

            for(int j = 1; j < K; j++) {
                double dist = distance(points[i], centroids[j]);
                if(dist < minDist) {
                    minDist = dist;
                    clusterID = j;
                }
            }

            points[i].cluster = clusterID;
        }

        // 2 Update centroids (Manual reduction)
        vector<double> sumX(K, 0), sumY(K, 0);
        vector<int> count(K, 0);

        #pragma omp parallel
        {

```

```

vector<double> localSumX(K, 0);
vector<double> localSumY(K, 0);
vector<int> localCount(K, 0);

#pragma omp for
for(int i = 0; i < N; i++) {
    int cid = points[i].cluster;
    localSumX[cid] += points[i].x;
    localSumY[cid] += points[i].y;
    localCount[cid]++;
}

#pragma omp critical
{
    for(int i = 0; i < K; i++) {
        sumX[i] += localSumX[i];
        sumY[i] += localSumY[i];
        count[i] += localCount[i];
    }
}

for(int i = 0; i < K; i++) {
    if(count[i] != 0) {
        centroids[i].x = sumX[i] / count[i];
        centroids[i].y = sumY[i] / count[i];
    }
}

double end = omp_get_wtime();

cout << "K-Means Clustering Completed\n";
cout << "Execution Time: " << end - start << " seconds\n";

return 0;
}

```

now explain this

Ye tera **HPC + AI/ML domain ka best example** hai 👍 — tu actually **K-Means Clustering (unsupervised ML algorithm)** ko OpenMP ke saath parallel bana raha hai. Main tujhe **clear, structured + viva-ready explanation** deta hoon 🙌

OVERVIEW

👉 Ye program implement karta hai:

👉 **K-Means Clustering Algorithm (AI/ML)**

👉 Parallelization using **OpenMP (HPC concept)**

Goal:

Data points ko **K clusters** me group karna

CONSTANTS

C++

```
#define N 10000
```

→ Total data points = 10,000

C++

```
#define K 3
```

→ Total clusters = 3

C++

```
#define MAX_ITER 100
```

→ Algorithm 100 iterations tak chalega

STRUCT

C++

```
struct Point {
    double x, y;
    int cluster;
};
```

👉 Har point ke paas:

- x coordinate
 - y coordinate
 - cluster ID
-

DISTANCE FUNCTION

C++

```
double distance(Point a, Point b)
```

→ Euclidean distance calculate karta hai:

C++

```
sqrt((x1 - x2)2 + (y1 - y2)2)
```

👉 Ye decide karta hai point kis centroid ke closest hai

INITIALIZATION

C++


```
vector<Point> points(N);
vector<Point> centroids(K);
```

➡ Points aur centroids store

```
C++
points[i].x = rand() % 100;
points[i].y = rand() % 100;
```

👉 Random data generate (0-99 range)

```
C++
centroids[i] = points[i];
```

👉 Initial centroids = first K points

◆ ◆ **TIMER START**

```
C++
double start = omp_get_wtime();
```

◆ ◆ **MAIN LOOP (K-MEANS LOGIC)**

```
C++
for(int iter = 0; iter < MAX_ITER; iter++)
```

👉 K-Means repeatedly 2 steps karta hai:

🔥 **STEP 1: CLUSTER ASSIGNMENT (PARALLEL)**

```
C++
#pragma omp parallel for
for(int i = 0; i < N; i++)
```

👉 Har point ko parallel process kiya ja raha hai

```
C++
double minDist = distance(points[i], centroids[0]);
```

➡ Initial minimum distance

```
C++
for(int j = 1; j < K; j++)
```

➡ Sab centroids check karo

```
C++
if(dist < minDist)
```

➡ Closest centroid find karo

C++

```
points[i].cluster = clusterID;
```

👉 Point ko nearest cluster assign

✅ Advantage:

✓ Har point independent hai

✓ Perfect parallelization 🚀

🔥 STEP 2: UPDATE CENTROIDS

👉 Ab har cluster ka average nikalna hai

◆ Global arrays

C++

```
vector<double> sumX(K, 0), sumY(K, 0);
vector<int> count(K, 0);
```

◆ Parallel block

C++

```
#pragma omp parallel
```

👉 Har thread apna local data maintain karega

◆ Local variables

C++

```
vector<double> localSumX(K, 0);
vector<double> localSumY(K, 0);
vector<int> localCount(K, 0);
```

👉 Thread-safe computation

◆ Work distribution

C++

```
#pragma omp for
for(int i = 0; i < N; i++)
```

C++

```
localSumX[cid] += points[i].x;
localCount[cid]++;
```

👉 Cluster-wise sum aur count

◆ Combine results

C++
#pragma omp critical

👉 Sab threads ka result merge

C++
sumX[i] += localSumX[i];

◆ Update centroid

C++
centroids[i].x = sumX[i] / count[i];

👉 New centroid = average of points

◆ ◆ TIMER END

C++
double end = omp_get_wtime();

◆ ◆ OUTPUT

C++
cout << "K-Means Clustering Completed\n";
cout << "Execution Time: " << end - start << " seconds\n";

🔥 🔥 HPC + AI/ML CONNECTION

👉 Ye program demonstrate karta hai:

Concept	Use
AI/ML	K-Means clustering
HPC	OpenMP parallelization
Parallelism	Cluster assignment + reduction

◆ 🔥 VIVA READY ANSWER

Tu directly bol 👉

"This program implements K-Means clustering, an unsupervised machine learning algorithm, using OpenMP for parallel execution. The cluster assignment step is parallelized using parallel

for, and centroid updates are handled using manual reduction to ensure thread safety. This demonstrates how HPC techniques can accelerate AI/ML computations.”

🔥 IMPORTANT POINTS

- 👉 Best parallel part:
- ✓ Cluster assignment (independent)
- 👉 Slight limitation:
- ! Centroid update me **critical** use hua hai (overhead)

🔥 TEACHER IMPRESS LINE 😎

👉 Bol:

“K-Means is highly suitable for parallelization because distance calculations for each point are independent, making it ideal for HPC applications.”

🔥 FINAL VERDICT

- ✓ Code correct
- ✓ HPC concept properly applied
- ✓ AI/ML integration strong
- 100 Practical ke liye best example

Agar tu chahe to next:

- ✓ Iska **diagram + visualization explanation**
- ✓ Ya **full assignment write-up (Aim, Theory, Algorithm, Conclusion)**

bhi bana deta hoon 🚀

```
anish@LAPTOP-3JPSGL7M:~/hpc_aiml$ ./program
K-Means Clustering Completed
Execution Time: 0.0124322 seconds
anish@LAPTOP-3JPSGL7M:~/hpc_aiml$
```

Perfect 👍 — ye output **bilkul expected aur correct hai**. Ab main tujhe iska **deep explanation (viva level)** deta hoon 🙌

💠 OUTPUT SAMJHO

Bash

K-Means Clustering Completed
Execution Time: 0.0124322 seconds

◆ 1. "K-Means Clustering Completed"

👉 Iska matlab:

- Algorithm ne **saare iterations (100)** complete kar liye
- Har iteration me:
 1. Points ko clusters assign kiya
 2. Centroids update kiye

✓ K-Means successfully run ho gaya

◆ 2. Execution Time

Bash
0.0124322 seconds

👉 Matlab:

- 10,000 points
- 3 clusters
- 100 iterations

👉 Itna sab process hua sirf ~0.012 sec me ⚡

🔥 WHY IT IS FAST?

✓ Reason 1: Parallelization

C++
#pragma omp parallel for

👉 Har thread alag-alag points handle kar raha hai

✓ Reason 2: Independent Computation

👉 Distance calculation:

Point A → centroid
Point B → centroid

- ➡ Dono independent hai
- ➡ Easily parallel ho jata hai

✓ Reason 3: HPC Advantage

👉 HPC (High Performance Computing) ka main goal:

Divide work → Execute parallel → Reduce time

✓ Ye program exactly wahi kar raha hai

💠 🔥 REAL UNDERSTANDING

👉 Agar tu same code **without OpenMP** run kare:

→ Time increase ho jayega

→ Ho sakta hai ~2x-4x slow ho

💠 💡 BUT EK IMPORTANT BAAT ⚠️

👉 0.012 sec ka matlab ye nahi ki algorithm “super optimized” hai

! Reason:

- Dataset small hai (10k points)
- System fast hai
- Threads efficient hai

👉 Agar:

N = 1,000,000 (10 lakh)

→ Tab parallel ka real power dikhega 🚀

💠 🔥 VIVA READY EXPLANATION

Tu confidently bol 🗣️

“The program successfully performs K-Means clustering using OpenMP. The execution time is very low because the cluster assignment step is parallelized, allowing multiple threads to compute distances simultaneously. This demonstrates how HPC techniques significantly improve performance in AI/ML algorithms.”

💠 🔥 TEACHER IMPRESS LINE 😎

👉 Ye line pakki bol:

“K-Means is computationally intensive due to repeated distance calculations, and parallelization using OpenMP reduces execution time significantly, making it suitable for large-scale AI/ML applications.”

🔥 EXTRA SMART POINT

👉 Bol:

“The centroid update step still uses a critical section, which introduces some overhead, but overall performance gain is achieved due to parallel cluster assignment.”

💠 FINAL ANALYSIS

Parameter	Result	Status
Execution	Completed	✓
Time	~0.012 sec	🚀 Fast
Parallelism	Applied	✓
AI/ML Concept	K-Means	✓

💠 ✓ FINAL VERDICT

- ✓ Code correct
- ✓ Output correct
- ✓ HPC + AI/ML integration strong
- 100 Practical ke liye perfect

Agar tu chahe next:

- ✓ Iska **diagram (cluster visualization)**
- ✓ Ya **complete assignment write-up (Aim, Theory, Algorithm, Conclusion)**

bhi bana deta hoon 🚀

bostonhousednn.ipynb

File

now deep learning Linear regression by using Deep Neural network: Implement Boston housing price prediction problem by Linear regression using Deep Neural network. Use Boston House price prediction dataset.

Great — ab tu **Deep Learning + AI/ML domain** me aa gaya 🚀

Main tujhe **Boston Housing using Deep Neural Network (DNN)** ka **complete practical-level explanation + code + viva points** deta hoon.

💠 PROBLEM UNDERSTANDING

👉 Dataset: Boston Housing Dataset

👉 Goal:

- House price predict karna (Regression problem)

👉 Input:

- Features like crime rate, rooms, tax, etc.

👉 Output:

- House price (continuous value)

◆ WHY DNN FOR LINEAR REGRESSION?

👉 Normally:

- Linear Regression = single equation

👉 But DNN:

- Non-linear patterns bhi learn kar sakta hai
- More powerful for real-world data

◆ COMPLETE CODE (TensorFlow/Keras)

Python

```
# Import Libraries
import numpy as np
import tensorflow as tf
from tensorflow import keras
from sklearn.datasets import load_boston
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler

# Load dataset
data = load_boston()
X = data.data
y = data.target

# Train-test split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2)

# Feature scaling
scaler = StandardScaler()
X_train = scaler.fit_transform(X_train)
X_test = scaler.transform(X_test)

# Build Deep Neural Network
model = keras.Sequential([
    keras.layers.Dense(64, activation='relu', input_shape=(X_train.shape[1],)),
    keras.layers.Dense(32, activation='relu'),
    keras.layers.Dense(1) # Output layer (regression)
])

# Compile model
model.compile(
    optimizer='adam',
    loss='mse',
```



```

    metrics=['mae']
)

# Train model
model.fit(X_train, y_train, epochs=100, batch_size=16, verbose=1)

# Evaluate
loss, mae = model.evaluate(X_test, y_test)

print("Test Loss:", loss)
print("Mean Absolute Error:", mae)

```

◆ STEP-BY-STEP EXPLANATION

✓ 1. Dataset Load

Python
`load_boston()`

👉 Features + price data load

✓ 2. Train-Test Split

Python
`train_test_split(...)`

👉 Model training + testing separate

✓ 3. Feature Scaling

Python
`StandardScaler()`

👉 Important for neural networks

👉 All features same scale

🔥 4. MODEL (DNN)

Python
`Dense(64, activation='relu')`

➡ Hidden layer 1

Python
`Dense(32, activation='relu')`

➡ Hidden layer 2

Python
`Dense(1)`

➡ Output (price prediction)

🔥 5. COMPILE

Python

```
optimizer='adam'
```

👉 Learning optimize karta hai

Python

```
loss='mse'
```

👉 Mean Squared Error (regression)

🔥 6. TRAIN

Python

```
model.fit(...)
```

👉 Model learn karta hai data se

🔥 7. EVALUATE

Python

```
model.evaluate(...)
```

👉 Model performance check

💠 🔥 OUTPUT EXPECTATION

👉 Typical output:

- Loss (MSE)
- MAE (Mean Absolute Error)

Example:

Loss: ~20–30

MAE: ~3–5

💠 🔥 VIVA READY ANSWER

Tu confidently bol 👉

“This program implements a Deep Neural Network for predicting house prices using the Boston Housing dataset. The model consists of multiple dense layers with ReLU activation

and is trained using the Adam optimizer with Mean Squared Error loss. Feature scaling is applied to improve convergence."

🔹 🔥 IMPORTANT POINTS

👉 Why scaling?

- Neural networks sensitive to feature scale

👉 Why ReLU?

- Fast and avoids vanishing gradient

👉 Why MSE?

- Standard regression loss function

🔹 🔥 TEACHER IMPRESS LINE 😎

👉 Ye line bol:

"Although linear regression can solve this problem, using a Deep Neural Network allows capturing non-linear relationships in the data, improving prediction capability."

🔹 🔥 EXTRA (VERY IMPORTANT ⚠)

👉 Real world me:

- `load_boston()` deprecated ho chuka hai
👉 Use:
- `fetch_california_housing()` (modern dataset)

🔹 🔹 FINAL VERDICT

✓ AI/ML concept ✓

✓ Deep Learning ✓

✓ Regression ✓

🏆 Practical ke liye perfect

Agar tu chahe next:

✓ Iska **Jupyter Notebook ready file**

✓ Ya **graph (loss vs epochs)**

✓ Ya **PPT explanation (10 min presentation)**

bhi bana deta hoon 🚀

what is output and explain the output

Good — ab tu **output samajhna chahta hai**, jo viva me sabse important hota hai 👍
Main tujhe **realistic output + uska deep explanation** deta hoon 🙌

◆ TYPICAL OUTPUT (jab tu code run karega)

Training ke time pe tu aisa kuch dekhega:

```
Epoch 1/100
25/25 ————— loss: 450.23 - mae: 15.32
Epoch 2/100
25/25 ————— loss: 120.45 - mae: 7.85
...
Epoch 100/100
25/25 ————— loss: 22.15 - mae: 3.75
```

🙌 Aur end me:

```
Test Loss: 24.30
Mean Absolute Error: 3.90
```

◆ OUTPUT EXPLANATION (STEP BY STEP)

🔥 1. Epochs

Epoch 1/100

🙌 Matlab:

- Model total **100 times** data se learn karega

🙌 Har epoch = ek full pass over dataset

🔥 2. Loss (MSE)

loss: 450 → 120 → 22

🙌 Ye **Mean Squared Error** hai

📌 **Formula:**

$$\text{MSE} = (\text{Actual} - \text{Predicted})^2$$

🙌 Interpretation:

- Start me error high (450)
- Training ke baad reduce ho gaya (~22)

✓ Good sign → model learning kar raha hai

🔥 3. MAE (Mean Absolute Error)

mae: 15 → 7 → 3.7

👉 Formula:

$MAE = |Actual - Predicted|$

👉 Interpretation:

- Final MAE $\approx$ 3.7

✓ Matlab:

👉 Model prediction average me ~3-4 units galat hai

💠 FINAL OUTPUT

Test Loss: 24.30
Mean Absolute Error: 3.90

🔥 Test Loss

👉 Ye unseen data pe error hai

✓ Training loss ke close hona chahiye

👉 Agar bahut zyada ho → overfitting

🔥 MAE (MOST IMPORTANT)

👉 Final result:

MAE $\approx$ 3.9

👉 Matlab:

✓ Model approx **\$3900 error** karta hai (kyunki price in \$1000s hai)

💠 🔥 SIMPLE LANGUAGE ME SAMJHO

👉 Agar actual house price = 25 (i.e. \$25,000)

👉 Model predict kare:

~21 ya ~29

👉 Error $\approx$ 4

GOOD vs BAD MODEL

MAE	Meaning
10+	✗ Poor
5-10	⚠ Average
2-5	✓ Good
<2	🚀 Excellent

👉 Tera expected:

3-4 → GOOD MODEL ✓

VIVA READY ANSWER

Tu directly bol 🙋

"The output shows the training progress through epochs, where the loss and MAE decrease over time, indicating learning. The final test MAE represents the average prediction error. In this case, the model predicts house prices with an average error of around 3 to 4 units, which indicates good performance."

TEACHER IMPRESS LINE 😎

👉 Ye line bol:

"A decreasing loss curve indicates proper learning, and a similar training and testing error suggests that the model is not overfitting."

EXTRA SMART POINT

👉 Bol:

"If the test loss is much higher than training loss, it indicates overfitting, and techniques like regularization or dropout can be used."

FINAL SUMMARY

- ✓ Loss ↓ → Learning ho raha hai
- ✓ MAE ≈ 3-4 → Good accuracy
- ✓ Test ≈ Train → No overfitting

Agar tu chahe to next:

- ✓ Graph (Loss vs Epoch)

- ✓ Overfitting vs Underfitting explanation
- ✓ PPT explanation (10 marks ke liye ready)

bhi bana deta hoon 🚀

samjha nhi house ka price ka kaise

Achha, main simple language me samjhata hoon — tu bas ye concept pakad le, sab clear ho jayega 👍

◆ PROBLEM KA REAL MEANING

👉 Tu model ko ye sikhata hai:

“Ghar ki details de → uska price bata”

◆ DATASET ME KYA HOTA HAI?

Har house ke liye kuch features hote hain:

Example:

Feature	Meaning
RM	Kitne rooms hai
LSTAT	Area kitna poor hai
TAX	Tax rate
CRIM	Crime rate

👉 Aur ek output hota hai:

PRICE (ghar ka daam)

🔥 IMPORTANT POINT

👉 Dataset me price **\$1000 units me hota hai**

Matlab:

Value	Real Price
20	\$20,000
30	\$30,000
50	\$50,000

◆ MODEL KYA KAR RAHA HAI?

👉 Model seekh raha hai:

(Rooms, Area, Tax, Crime) → Price

◆ SIMPLE EXAMPLE

Input (house details):

Rooms = 6
Crime = low
Tax = medium

👉 Model predict karega:

Output = 25

👉 Real meaning:

\$25,000 house price

◆ AB MAE SAMJHO (IMPORTANT)

Tu confuse yaha ho raha hai 👉

MAE = 3.9

👉 Matlab:

Average error = 3.9 units

👉 Real money me:

$3.9 \times 1000 = \$3900$

🔥 FINAL SIMPLE UNDERSTANDING

👉 Agar actual price:

Actual = 25 (\$25,000)

👉 Model bole:

Prediction = 22

👉 Error:

$|25 - 22| = 3$

👉 Real money:

\$3000 ka error

◆ EK AUR SIMPLE EXAMPLE

Actual Price	Predicted	Error
30	27	3

Actual Price	Predicted	Error
20	23	3
40	38	2

👉 Average error ≈ 3

👉 Isliye MAE ≈ 3

🔹 🔥 VIVA READY LINE

Tu ye bol 🗨️

"The model predicts house prices in units of thousands of dollars. The Mean Absolute Error indicates the average difference between predicted and actual prices. For example, an MAE of 3 means the model prediction is off by approximately \$3000."

🔹 🔥 EK LINE ME FINAL

👉 Simple:

Model ghar ka price predict karta hai
MAE batata hai kitna galat predict kiya

Agar abhi bhi doubt hai to bol — main tujhe **diagram ya real graph ke saath** aur clear kar dunga 👍

lekin vo input kya lega run krne ke baad matlab user se lega ya kaha se

Bahut sahi doubt 👍 — ye exam me bhi poocha jata hai.

🔹 ✦ SHORT ANSWER

👉 Current code me model user se input nahi leta

👉 Wo input leta hai:

Dataset se (Boston Housing dataset)

🔹 ✦ STEP-BY-STEP SAMJHO

✦ 1. Dataset se input

Python

```
data = load_boston()
X = data.data # INPUT
y = data.target # OUTPUT (price)
```

👉 Yaha:

- x = house ki details (rooms, tax, etc.)
- y = house ka price

♦ 2. Model training ke time

Python

```
model.fit(X_train, y_train)
```

👉 Model:

- Input leta hai dataset se
- Output (price) learn karta hai

♦ 3. Testing ke time

Python

```
model.evaluate(X_test, y_test)
```

👉 Model:

- Dataset ke unseen data pe test hota hai

🔥 IMPORTANT POINT

👉 Matlab:

User se koi input nahi liya ja raha ❌
Sab dataset se aa raha hai ✅

♦ ♦ AGAR TU USER INPUT LENA CHAHE

👉 Tab tu manually input de sakta hai

Example:

Python

```
# User input (13 features dene padenge)
user_input = [[0.1, 18, 2.31, 0, 0.5, 6.5, 65, 4.0, 1, 296, 15.3, 396, 4.98]]

# Scale karo
user_input = scaler.transform(user_input)

# Prediction
price = model.predict(user_input)

print("Predicted House Price:", price[0][0] * 1000, "USD")
```

♦ 🔥 SIMPLE UNDERSTANDING

Stage	Input kaha se aata hai
Training	Dataset
Testing	Dataset
Real use	User input

REAL WORLD ME KYA HOTA HAI

👉 Real application me:

- User form fill karta hai
- Model predict karta hai

Example:

Rooms = 5
Area = medium
Crime = low

👉 Model:

Price = ₹25 lakh

VIVA READY ANSWER

Tu confidently bol 🙌

“In this implementation, the model takes input from the Boston Housing dataset during training and testing. However, in real-world applications, user input can be provided to the trained model for prediction.”

FINAL LINE

👉 Simple yaad rakh:

Training = Dataset
Prediction = User ya new data

Agar tu chahe to main:

- ✓ Full working UI (HTML form + ML model)
- ✓ Ya simple CLI input version

bhi bana deta hoon 🚀

two.ipynb

 File

Classification using Deep neural network
Binary classification using Deep Neural Networks Example: Classify movie reviews into

positive" reviews and "negative" reviews, just based on the text content of the reviews.
Use IMDB dataset now explain thisd

Great — ab tu **Deep Learning Classification (NLP)** pe aa gaya 🚀

Main tujhe **IMDB Movie Review Classification using DNN** ko simple + exam-ready way me samjhata hoon 🙌

◆ PROBLEM KYA HAI?

👉 Dataset: IMDB Movie Reviews Dataset

👉 Goal:

Review (text) → Positive ya Negative

👉 Example:

Review	Output
"Movie was amazing!"	Positive ✓
"Worst movie ever"	Negative ✗

◆ YE KAUNSA PROBLEM HAI?

👉 **Binary Classification**

- 2 classes:
 - 0 → Negative
 - 1 → Positive

◆ MODEL KYA KARTA HAI?

👉 Model seekhta hai:

Text → Sentiment (0 ya 1)

◆ FLOW (IMPORTANT)

🔥 1. Dataset Load

👉 IMDB dataset already preprocessed hota hai

Python

```
(X_train, y_train), (X_test, y_test) = imdb.load_data(num_words=10000)
```

👉 Yaha:

- `x_train` = reviews (numbers me converted)
 - `y_train` = labels (0/1)
-

🔥 2. Text ko numbers me convert

👉 Words → integers

Example:

"good movie" → [45, 120]

🔥 3. Padding

Python

`pad_sequences(...)`

👉 Sab reviews same length ke banaye jate hain

🔥 4. MODEL (DNN)

Typical model:

Python

```
model = Sequential([
    Embedding(10000, 128),
    Flatten(),
    Dense(64, activation='relu'),
    Dense(1, activation='sigmoid')
])
```

🔥 5. COMPILE

Python

`loss = 'binary_crossentropy'`

👉 Binary classification ke liye best

🔥 6. TRAIN

Python

`model.fit(...)`

👉 Model learn karta hai patterns

7. EVALUATE

Python

`model.evaluate(...)`

 Accuracy check

OUTPUT KYA AATA HAI?

Typical output:

Epoch 1/10
loss: 0.65 - accuracy: 0.62

Epoch 10/10
loss: 0.25 - accuracy: 0.90

Final:

Test Accuracy: 0.88

OUTPUT EXPLANATION

1. LOSS

0.65 → 0.25

 Error kam ho raha hai

 Model learn kar raha hai

2. ACCURACY

0.62 → 0.90

 90% predictions correct

FINAL RESULT

 Agar:

Test Accuracy = 0.88

 Matlab:

100 reviews me se 88 sahi predict

REAL EXAMPLE

Input:

"This movie was fantastic and amazing!"

👉 Model output:

0.95 → Positive ✓

Input:

"I hated this movie"

👉 Output:

0.10 → Negative ✗

🔹 🔥 SIGMOID OUTPUT (IMPORTANT)

👉 Last layer:

Python

```
Dense(1, activation='sigmoid')
```

👉 Output range:

0 to 1

Value	Meaning
> 0.5	Positive
< 0.5	Negative

🔹 🔥 VIVA READY ANSWER

Tu bol 👉

"This program performs binary classification using a Deep Neural Network on the IMDB dataset. The model learns to classify movie reviews as positive or negative based on text content. The final output is a probability between 0 and 1, where values above 0.5 indicate positive sentiment."

🔹 🔥 IMPORTANT POINTS

👉 Why Embedding?

- Words ko vector me convert karta hai

👉 Why sigmoid?

- Binary output ke liye

👉 Why crossentropy?

- Classification loss function

🔥 TEACHER IMPRESS LINE 😎

👉 Ye bol:

"This is a Natural Language Processing problem where text data is converted into numerical form and processed using a Deep Neural Network for sentiment classification."

◆ FINAL SUMMARY

- ✓ Input = text review
- ✓ Output = positive/negative
- ✓ Accuracy = model performance

Agar tu chahe to next:

- ✓ Full working code
- ✓ User input wala sentiment predictor
- ✓ PPT explanation

bhi bana deta hoon 🚀

to yaha kaise output aayega aur input kya lega

Sahi question 👍 — ab main tujhe **bilkul clear (confusion-free)** samjhata hoon:

◆ SHORT ANSWER

👉 Input kya lega?

➡ Dataset se movie reviews (text)

👉 Output kya dega?

➡ Har review ke liye:

0 → Negative ❌
1 → Positive ✅

◆ STEP-BY-STEP SAMJHO

🔥 1. INPUT KYA HAI?

👉 IMDB dataset me already reviews hote hain

Example:

"This movie was awesome and fantastic"
"I hated this movie, very boring"

👉 Ye text directly model me nahi jaata
 ➡ Pehle convert hota hai numbers me:
 [45, 120, 67, 89]

🔥 2. TRAINING KE TIME

Python

```
model.fit(X_train, y_train)
```

👉 Model seekhta hai:

Review	Label
"Good movie"	1
"Bad movie"	0

🔥 3. TESTING KE TIME OUTPUT

Python

```
model.evaluate(X_test, y_test)
```

👉 Output aata hai:

Loss: 0.25
 Accuracy: 0.88

💠 ♦ OUTPUT KA REAL MEANING

✅ Accuracy = 0.88

👉 Matlab:

100 reviews me se 88 correct predict

🔥 4. INDIVIDUAL PREDICTION (IMPORTANT)

👉 Jab tu ek review predict karega:

Python

```
model.predict(X_test[0])
```

👉 Output aayega:

0.92

💠 ♦ ISKA MEANING

Output	Meaning
0.92	Positive 
0.10	Negative 

👉 Rule:

> 0.5 → Positive
< 0.5 → Negative

◆ ✦ SIMPLE REAL EXAMPLE

Input:

"This movie is amazing"

Output:

0.95 → Positive 

Input:

"This movie is worst"

Output:

0.12 → Negative 

◆ 🔥 IMPORTANT CONFUSION CLEAR

👉 User input le raha hai kya?

 Nahi (default code me)

👉 Input aa raha hai:

Dataset se

◆ ✦ AGAR TU USER INPUT LENA CHAHE

Tab tu aisa kar sakta hai:

Python

```
review = input("Enter movie review: ")
# (Preprocessing required here)
prediction = model.predict(processed_review)
if prediction > 0.5:
    print("Positive Review")
else:
    print("Negative Review")
```

◆ 🔥 VIVA READY ANSWER

Tu confidently bol 🙋

“The model takes movie reviews from the IMDB dataset as input. It outputs a probability between 0 and 1 using a sigmoid function. If the value is greater than 0.5, the review is classified as positive; otherwise, it is negative.”

🔥 EK LINE ME FINAL

Input = Review (text)
Output = 0 ya 1 (Negative ya Positive)

Agar tu chahe to next:

- ✓ Full working code (copy paste ready)
- ✓ Live input wala sentiment analyzer
- ✓ Ya diagram (flow chart)

bhi bana deta hoon 🚀

three.ipynb

File

Convolutional neural network (CNN)
Dataset and create a classifier to classify fashion clothing into
categories.

Use MNIST Fashion

Great 🙌 — ab tu **CNN (Convolutional Neural Network)** pe aa gaya hai, jo deep learning ka **sabse important topic** hai (especially exams + viva) 🚀

Main tujhe **Fashion MNIST classifier using CNN** ko simple + clear + exam-ready way me samjhata hoon 🙋

🔹 PROBLEM KYA HAI?

🙋 Dataset: Fashion MNIST Dataset

🙋 Goal:

Image (kapde ka photo) → Category (label)

🔹 DATASET DETAILS

🙋 Total 10 classes:

Label	Category
0	T-shirt
1	Trouser
2	Pullover

Label	Category
3	Dress
4	Coat
5	Sandal
6	Shirt
7	Sneaker
8	Bag
9	Ankle boot

👉 Image size:

28 × 28 (grayscale)

◆ INPUT KYA HAI?

👉 Ek image:

28x28 pixels (numbers form me)

Example:

```
[ [0, 0, 255, ...],
  [34, 120, 90, ...],
  ... ]
```

◆ OUTPUT KYA HAI?

👉 Model output deta hai:

0 to 9 (category number)

Example:

Prediction = 7 → Sneaker 📺

◆ CNN KYA KARTA HAI?

👉 CNN image se automatically features extract karta hai:

- Edges
- Shapes
- Patterns

👉 Phir classify karta hai

◆ MODEL FLOW (IMPORTANT 🔥)

Image → Conv Layer → Pooling → Flatten → Dense → Output

◆ SIMPLE CNN CODE

Python

```
import tensorflow as tf
from tensorflow import keras
from tensorflow.keras import layers

# Load dataset
(X_train, y_train), (X_test, y_test) = keras.datasets.fashion_mnist.load_data()

# Normalize
X_train = X_train / 255.0
X_test = X_test / 255.0

# Reshape (for CNN)
X_train = X_train.reshape(-1, 28, 28, 1)
X_test = X_test.reshape(-1, 28, 28, 1)

# Model
model = keras.Sequential([
    layers.Conv2D(32, (3,3), activation='relu', input_shape=(28,28,1)),
    layers.MaxPooling2D((2,2)),

    layers.Conv2D(64, (3,3), activation='relu'),
    layers.MaxPooling2D((2,2)),

    layers.Flatten(),
    layers.Dense(64, activation='relu'),
    layers.Dense(10, activation='softmax')
])

# Compile
model.compile(optimizer='adam',
              loss='sparse_categorical_crossentropy',
              metrics=['accuracy'])

# Train
model.fit(X_train, y_train, epochs=10)

# Evaluate
loss, acc = model.evaluate(X_test, y_test)

print("Test Accuracy:", acc)
```

◆ OUTPUT KYA AATA HAI?

Training ke time:

Epoch 1/10
loss: 0.60 - accuracy: 0.78

Epoch 10/10
loss: 0.25 - accuracy: 0.90

Final:

Test Accuracy: 0.88

◆ OUTPUT EXPLANATION

 **Accuracy = 0.88**

👉 Matlab:

100 images me se 88 correct classify

Loss ↓

0.60 → 0.25

👉 Error kam ho raha hai

✓ Model learning kar raha hai

PREDICTION EXAMPLE

Python

```
model.predict(X_test[0])
```

👉 Output:

[0.01, 0.02, 0.05, ..., 0.90, ...]

👉 Highest value → predicted class

Example:

0.90 at index 7 → Sneaker 

VIVA READY ANSWER

Tu bol 👉

“This program uses a Convolutional Neural Network to classify images from the Fashion MNIST dataset into 10 categories. The CNN automatically extracts features using convolution and pooling layers, and the final output layer uses softmax to predict the class with highest probability.”

IMPORTANT POINTS

👉 Why CNN?

- Images ke liye best

👉 Why Conv layer?

- Feature extraction

👉 Why Pooling?

- Size reduce karta hai

👉 Why Softmax?

- Multi-class classification

TEACHER IMPRESS LINE

👉 Ye bol:

“CNNs are highly effective for image data because they preserve spatial relationships and automatically learn hierarchical features.”

◆ INPUT vs OUTPUT SUMMARY

Stage	Input	Output
Training	Images dataset	Model
Testing	Images dataset	Accuracy
Prediction	Single image	Category

◆ FINAL ONE LINE

Input = Image (28x28)

Output = Clothing category (0–9)

Agar tu chahe to next:

- ✓ Diagram (CNN working visual)
- ✓ Real image prediction demo
- ✓ PPT (10 marks presentation)

bhi bana deta hoon 🚀

ye kaise output dega

Achha, tu exactly ye samajhna chahta hai: “CNN actual me output kaise deta hai?” — chalo ise step-by-step simple bana dete hain 👍

◆ STEP 1: INPUT KYA JAATA HAI?

👉 Model ko ek **image** milti hai (Fashion MNIST se)

Example:

28 × 28 pixels image (kapde ka photo)

◆ STEP 2: CNN ANDAR KYA KARTA HAI?

👉 CNN layers image ko process karti hain:

Image → Conv → Pool → Conv → Pool → Flatten → Dense

👉 Ye sab milke image ke features nikalte hain (shape, edges, pattern)

◆ STEP 3: FINAL OUTPUT (IMPORTANT 🔥)

Last layer hoti hai:

Python

```
Dense(10, activation='softmax')
```

👉 Ye 10 values deta hai (kyunki 10 classes hai)

🔥 OUTPUT KA FORM

Example output:

```
[0.01, 0.02, 0.05, 0.03, 0.01, 0.01, 0.02, 0.80, 0.03, 0.02]
```

👉 Iska matlab:

Index	Category	Probability
0	T-shirt	0.01
1	Trouser	0.02
...	...	...
7	Sneaker	0.80

◆ 🔥 FINAL DECISION

👉 Model bolta hai:

Sabse bada value = 0.80

👉 Index = 7

👉 Final output:

Prediction = 7 → Sneaker 📺

◆ SIMPLE LANGUAGE ME

👉 CNN bolta hai:

"Is image ke Sneaker hone ke chances sabse zyada hai"

◆ CODE SE OUTPUT KAISA DIKHEGA?

Python

```
pred = model.predict(X_test[0])
print(pred)
```

👉 Output:

```
[0.01 0.02 0.05 ... 0.80 ...]
```


Python

```
import numpy as np
print(np.argmax(pred))
```

👉 Output:

7

◆ REAL EXAMPLE

👉 Input image:

- Shoe 📷

👉 Output:

[0.01, 0.01, 0.02, 0.03, 0.01, 0.01, 0.02, 0.88, 0.01, 0.00]

👉 Final:

7 → Sneaker

◆ 🔥 VIVA READY ANSWER

Tu ye bol 👉

“The CNN outputs a probability distribution over 10 classes using the softmax function. The class with the highest probability is selected as the final prediction.”

◆ 🔥 EK LINE ME FINAL

CNN → 10 probabilities deta hai → max value wala class output hota hai

◆ 🔥 AGAR ABHI BHI CONFUSION HAI

Main tujhe next me:

- ✓ Diagram (visual flow)
- ✓ Real image + prediction demo
- ✓ Step-by-step animation style explanation

bhi dikha sakta hoon — bas bol 👍

ab tak apn ne 7 practicals dekhe list out kro

Haan 👍 ab tak tumne **total 7 practicals** cover kar liye hain. Main unhe clean list me arrange kar deta hoon (exam-ready) 👉

◆ LIST OF PRACTICALS (HPC + AI/ML)

1 Parallel BFS & DFS using OpenMP

- 👉 Graph traversal
 - 👉 Parallel threads use karke nodes visit
-

2 Parallel Bubble Sort & Merge Sort

- 👉 Sorting algorithms
 - 👉 Sequential vs Parallel performance comparison
-

3 Min, Max, Sum, Average using Parallel Reduction

- 👉 OpenMP reduction use kiya
 - 👉 Efficient aggregation without locks
-

4 HPC Application for AI/ML (K-Means Clustering)

- 👉 Unsupervised learning
 - 👉 Parallel clustering using OpenMP
-

5 Linear Regression using Deep Neural Network

- 👉 Boston Housing Dataset
 - 👉 House price prediction (regression)
-

6 Binary Classification using Deep Neural Network

- 👉 IMDB Movie Reviews Dataset
 - 👉 Positive vs Negative sentiment
-

7 CNN using Fashion MNIST Dataset

- 👉 Fashion MNIST Dataset
 - 👉 Image classification (clothing categories)
-



◆ HPC (High Performance Computing)

- BFS & DFS
- Sorting
- Reduction
- K-Means

◆ AI/ML & Deep Learning

- Regression (Boston Housing)
- Classification (IMDB)
- CNN (Fashion MNIST)

◆ 🔥 VIVA READY LINE

Tu bol sakta hai 🗣️

“The practicals cover both HPC concepts using OpenMP and AI/ML techniques including regression, classification, and convolutional neural networks.”

◆ 🔥 FINAL SUMMARY

Total Practicals = 7
HPC = 4
AI/ML = 3

Agar tu chahe to next:

- ✓ In sab ka **short notes (1 page revision)**
- ✓ Ya **important viva questions + answers**

bhi bana deta hoon 🚀

abhi sabhi ke liye viva mai kya kya puch skte hai aise 15 15 sawal har kisi ke do aur answer bhi based on practicals

Perfect 👍 — ab tu **exam/viva mode** me aa gaya hai. Main tujhe **har practical ke liye 15 important viva questions + short answers** deta hoon (total 7 practicals).

👉 Answers short + direct rakhe hain taaki tu easily yaad kar sake.

◆ 1 Parallel BFS & DFS (OpenMP)

Q1. BFS kya hai?

👉 Level-wise traversal of graph.

Q2. DFS kya hai?

👉 Depth-wise traversal (recursion/stack).

Q3. BFS me kaunsa data structure use hota hai?

👉 Queue

Q4. DFS me kya use hota hai?

👉 Stack / Recursion

Q5. OpenMP kya hai?

👉 Parallel programming API for shared memory.

Q6. #pragma omp parallel for kya karta hai?

👉 Loop ko multiple threads me divide karta hai.

Q7. Critical section kya hota hai?

👉 Ek time pe ek thread hi execute kare.

Q8. BFS parallel karna difficult kyu hai?

👉 Queue dependency hoti hai.

Q9. DFS ka output fix hota hai?

👉 Parallel me nahi (non-deterministic).

Q10. Graph kya hota hai?

👉 Nodes + edges ka structure.

Q11. Visited array ka use kya hai?

👉 Duplicate traversal avoid karne ke liye.

Q12. BFS complexity?

👉 $O(V + E)$

Q13. DFS complexity?

👉 $O(V + E)$

Q14. Race condition kya hai?

👉 Multiple threads ek data ko modify kare.

Q15. Parallel ka advantage?

👉 Faster execution (large data me)

📦 2 Parallel Bubble & Merge Sort

Q1. Bubble sort kya hai?

👉 Adjacent elements swap karke sorting.

Q2. Bubble sort complexity?

👉 $O(n^2)$

Q3. Merge sort kya hai?

👉 Divide and conquer algorithm.

Q4. Merge sort complexity?

👉 $O(n \log n)$

Q5. Parallel bubble slow kyu hai?

👉 Data dependency + critical section.

Q6. Merge sort parallel kyu efficient hai?

👉 Independent subproblems.

Q7. parallel sections kya hai?

👉 Different blocks parallel run hote hain.

Q8. Swap operation kya karta hai?

👉 Elements exchange karta hai.

Q9. Stable sort kya hota hai?

👉 Same order maintain karta hai.

Q10. In-place sorting kya hai?

👉 Extra memory use nahi karta.

Q11. Merge function kya karta hai?

👉 Do sorted arrays combine karta hai.

Q12. Parallel overhead kya hai?

👉 Thread creation ka cost.

Q13. Sequential vs Parallel difference?

👉 Single thread vs multi-thread.

Q14. Large data me kya fast hota hai?

👉 Parallel merge sort

Q15. Sorting ka use?

👉 Data organize karne ke liye

🔹 3 Parallel Reduction (Min, Max, Sum, Avg)

Q1. Reduction kya hai?

👉 Aggregation operation (sum, min, max)

Q2. reduction(+:sum) kya karta hai?

👉 Sum ko safely combine karta hai

Q3. Reduction ka advantage?

👉 No race condition

Q4. Min kaise calculate hota hai?

👉 Smallest value select hoti hai

Q5. Max kaise calculate hota hai?

👉 Largest value

Q6. Average formula?

👉 Sum / n

Q7. Parallel reduction fast kyu hai?

👉 Work divide hota hai

Q8. Critical vs reduction?

👉 Reduction faster hai

Q9. Complexity?

👉 $O(n)$

Q10. Thread kya hai?

👉 Execution unit

Q11. Shared memory kya hai?

👉 Sab threads same memory use karte hain

Q12. Data race kya hai?

👉 Wrong result due to parallel write

Q13. Reduction kab use hota hai?

👉 Aggregation problems me

Q14. Sum variable ka type long long kyu?

👉 Overflow avoid karne ke liye

Q15. Output fast kyu aata hai?

👉 Parallel computation

🔹 4 HPC AI/ML (K-Means Clustering)

Q1. K-Means kya hai?

👉 Unsupervised clustering algorithm

Q2. K kya represent karta hai?

👉 Number of clusters

Q3. Centroid kya hota hai?

👉 Cluster ka center

Q4. Distance ka use?

👉 Nearest cluster find karne ke liye

Q5. Iteration kyu hoti hai?

👉 Centroids update ke liye

Q6. Parallelization kaha hota hai?

👉 Cluster assignment

Q7. Complexity?

👉 $O(n \times k \times \text{iterations})$

Q8. Manual reduction kya hai?

👉 Thread-wise sum combine karna

Q9. K-Means ka type?

👉 Unsupervised learning

Q10. Random initialization kyu?

👉 Starting centroids ke liye

Q11. Convergence kya hai?

👉 Jab centroids stable ho jaye

Q12. Overhead kaha aata hai?

👉 Critical section me

Q13. Real-world use?

👉 Customer segmentation

Q14. Euclidean distance kya hai?

👉 Straight line distance

Q15. HPC ka role?

👉 Fast computation

🔹 5 DNN Linear Regression (Boston Housing)

Q1. Regression kya hai?

👉 Continuous value prediction

Q2. Output kya hota hai?

👉 House price

Q3. Dataset kya hai?

👉 Boston Housing Dataset

Q4. MSE kya hai?

👉 Mean Squared Error

Q5. MAE kya hai?

👉 Mean Absolute Error

Q6. Scaling kyu?

👉 Faster learning

Q7. Activation function?

👉 ReLU

Q8. Optimizer?

👉 Adam

Q9. Epoch kya hai?

👉 One full training cycle

Q10. Overfitting kya hai?

👉 Model training data pe hi fit ho jaye

Q11. Underfitting kya hai?

👉 Model learn na kare

Q12. Loss kya hai?

👉 Error measure

Q13. Neural network kya hai?

👉 Brain-inspired model

Q14. Dense layer kya hai?

👉 Fully connected layer

Q15. Output unit?

👉 Single neuron

📦 6 DNN Binary Classification (IMDB)

Q1. Classification kya hai?

👉 Category prediction

Q2. Binary classification?

👉 2 classes

Q3. Dataset?

👉 IMDB Movie Reviews Dataset

Q4. Output kya hai?

👉 0 or 1

Q5. Sigmoid kya hai?

👉 Output 0-1 me deta hai

Q6. Threshold kya hai?

👉 0.5

Q7. Accuracy kya hai?

👉 Correct predictions %

Q8. Embedding kya hai?

👉 Words ko vector me convert karta hai

Q9. Text preprocessing kya hai?

👉 Cleaning + tokenization

Q10. Loss function?

👉 Binary crossentropy

Q11. NLP kya hai?

👉 Natural Language Processing

Q12. Overfitting?

👉 Training me high accuracy, test me low

Q13. Prediction kya deta hai?

👉 Probability

Q14. Dataset input kya hai?

👉 Reviews (text)

Q15. Real use?

👉 Sentiment analysis

📦 7 CNN (Fashion MNIST)

Q1. CNN kya hai?

👉 Image processing neural network

Q2. Dataset?

👉 Fashion MNIST Dataset

Q3. Input kya hai?

👉 28×28 image

Q4. Output kya hai?

👉 10 classes

Q5. Conv layer kya hai?

👉 Feature extraction

Q6. Pooling kya hai?

👉 Size reduce karta hai

Q7. Flatten kya hai?

👉 2D → 1D convert

Q8. Softmax kya hai?

👉 Multi-class probability

Q9. Accuracy kya hai?

👉 Correct classification %

Q10. CNN kyu use karte hai?

👉 Image ke liye best

Q11. Feature kya hai?

👉 Pattern (edges, shapes)

Q12. Training kya hai?

👉 Model learning

Q13. Testing kya hai?

👉 Model evaluation

Q14. Overfitting kya hai?

👉 Model memorize kare

Q15. Output kaise decide hota hai?

👉 Highest probability

FINAL TIP

👉 Agar tu ye sab yaad kar lega:

✓ 90% viva clear ho jayega

Agar tu chahe next:

✓ **Important tricky questions (teacher puchega)**

✓ **One-page revision notes (last day)**

bhi bana deta hoon 🚀