

```

#include<stdio.h>
#include<stdlib.h>
#include<string.h>
#include<sys/types.h>
#include<sys/socket.h>
#include<arpa/inet.h>
#include<errno.h>
#include<fcntl.h>
#include<unistd.h>

void main(){

    struct sockaddr_in server,client;
    int sock,clientSocket;
    char receivedBytes[1024],sendBytes[1024];
    int bytes;
    if((sock = socket(AF_INET,SOCK_STREAM,0)) == -1){
        perror("Invalid Socket Descriptor");
        exit(1);
    }

    server.sin_family = AF_INET;
    server.sin_port = htons(5000);
    server.sin_addr.s_addr = INADDR_ANY;
    bzero(&(server.sin_zero),8);

    if(connect(sock,(struct sockaddr *)&server,sizeof(server)) == -1){
        perror("Unable to connect");
        exit(1);
    }

    while(1){
        printf("\nEnter first number: ");
        gets(sendBytes);
        bytes = send(sock,sendBytes,1024,0);

        printf("\nEnter second number: ");
        gets(sendBytes);
        bytes = send(sock,sendBytes,1024,0);

        printf("\nEnter operand ( + | - | * | / | %) or ( q ) to quit: ");
        gets(sendBytes);
        bytes = send(sock,sendBytes,1024,0);

        if(strcmp(sendBytes,"q") == 0 || strcmp(sendBytes,"Q") == 0){
            printf("\nClient exiting...");
            close(sock);
            exit(1);
        }

        bytes = recv(sock,receivedBytes,1024,0);
        receivedBytes[bytes] = '\0';
        printf("\nResult: %s",receivedBytes);
    }
}
/*
socket()
connect()
recv()
send()
*/

```