



# Day 21 - React Components

~React : Used to create Dynamic Websites (instagram, etc) — Live Websites

1. re-render: when react actually updates the DOM.  
Anytime when the actual DOM manipulation happens.
2. Anytime the parent re-renders, all children re-renders.  
Clicking on one button, re-renders everything.
3. Memo:



Putting the entire Header function in the memo, to break the re-rendering between the parent and the children.



memo only works with dynamic variables.

```
///example
```

```
const Header = React.memo(function Header ({title}) {  
  return <div> {title} </div>  
});
```

```
//here {title} is dynamic.
```

4. Keys:  
Uniquely identifies components.

```

return (
    <Todo
      key={todo.id}
      title={todo.title}
      description={todo.description}
    />
  );

```

5. The practise code:

```

import React, { useState } from "react";

let counter = 4;

function App() {
  const [todos, setTodos] = useState([
    {
      id: 1,
      title: "Go to the gym",
      description: "You need to go to the gym",
    },
    {
      id: 2,
      title: "Go to market",
      description: "You need to go with Mummy",
    },
    {
      id: 3,
      title: "Read that book",
      description: "Read the Cave by Alok Kejriwal!",
    },
  ]);
}

```

```

function addTodo() {
  setTodos([
    ...todos,
    {
      id: counter++,
      title: Math.random().toString(),
      description: Math.random().toString(),
    },
  ]);
}

return (
  <div>
    <button onClick={addTodo}>Add a todo</button>
    {todos.map(function (todo) {
      return (
        <Todo
          key={todo.id}
          title={todo.title}
          description={todo.description}
        />
      );
    })}
  </div>
);
}

function Todo({ title, description }) {
  return (
    <div>
      <h1>{title}</h1>
      <h4>{description}</h4>
    </div>
  );
}

```

```
export default App;
```

6. Question : Why do we write function names with capital letters?

Ans:



In React, it's a convention to start component names with a capital letter. This is because when JSX is compiled, components starting with a lowercase letter are treated as HTML tags.