

Linux File and Directory Management Machine Test

Objectives

1. Create a file called **x**.
2. Create a directory called **content**.
3. Move the **x** file to the **content** directory.
4. Create a file inside the **content** directory called **y**.
5. Create the following directory structure inside the **content** directory: **dir1/dir2/dir3**.
6. Remove the **content** directory along with all its contents.

```
anish@rakusafe: ~  
anish@rakusafe:~$  
anish@rakusafe:~$ sudo touch x  
anish@rakusafe:~$  
anish@rakusafe:~$ sudo mkdir content  
anish@rakusafe:~$ ls  
DevOps-Team  ani.txt          content          home            x  
DevOpsLab    application.log  deploy.sh       linux-test  
LinuxPractice backup          'deploy.sh'$'\341\271\243' logs.txt  
MyLinuxLab   config.env       developer       notes.txt  
ani          config.txt      employee.txt    project.txt  
anish@rakusafe:~$ sudo mv x con  
config.env config.txt content/  
anish@rakusafe:~$ sudo mv x content/  
anish@rakusafe:~$ ls  
DevOps-Team  ani.txt          content          home            linux-test  
DevOpsLab    application.log  deploy.sh       'deploy.sh'$'\341\271\243' logs.txt  
LinuxPractice backup          developer       notes.txt  
MyLinuxLab   config.env       employee.txt    project.txt  
ani          config.txt  
anish@rakusafe:~$ sudo ls -l con  
config.env config.txt content/  
anish@rakusafe:~$ sudo ls -l content/  
total 0  
-rw-r--r-- 1 root root 0 Oct  4 14:18 x  
anish@rakusafe:~$ sudo touch con  
config.env config.txt content/  
anish@rakusafe:~$ sudo touch content/y  
anish@rakusafe:~$ ls  
DevOps-Team  ani.txt          content          home            linux-test  
DevOpsLab    application.log  deploy.sh       'deploy.sh'$'\341\271\243' logs.txt  
LinuxPractice backup          developer       notes.txt  
MyLinuxLab   config.env       employee.txt    project.txt  
ani          config.txt  
anish@rakusafe:~$ sudo ls -l content/  
total 0  
-rw-r--r-- 1 root root 0 Oct  4 14:18 x  
-rw-r--r-- 1 root root 0 Oct  4 14:22 y  
anish@rakusafe:~$
```

```
anish@rakusafe:~$ sudo mkdir -p content/dir1/dir2/dir3
anish@rakusafe:~$ ls
DevOps-Team    ani.txt          content          home
DevOpsLab      application.log  deploy.sh        linux-test
LinuxPractice  backup           'deploy.sh'$'\341\271\243' logs.txt
MyLinuxLab     config.env       developer        notes.txt
ani            config.txt       employee.txt     project.txt
anish@rakusafe:~$ cd content
anish@rakusafe:~/content$ tree
.
├── dir1
│   └── dir2
│       └── dir3
├── x
└── y
4 directories, 2 files
anish@rakusafe:~/content$
```

```
anish@rakusafe: ~
anish@rakusafe:~$
anish@rakusafe:~$
anish@rakusafe:~$
anish@rakusafe:~$
anish@rakusafe:~$
anish@rakusafe:~$
anish@rakusafe:~$
anish@rakusafe:~$ rm -r con
config.env config.txt content/
anish@rakusafe:~$ rm -r content/
rm: descend into write-protected directory 'content/'? ^C
anish@rakusafe:~$ sudo rm -r content/
anish@rakusafe:~$
anish@rakusafe:~$ ls
DevOps-Team    ani.txt          deploy.sh        linux-test
DevOpsLab      application.log  'deploy.sh'$'\341\271\243' logs.txt
LinuxPractice  backup           developer        notes.txt
MyLinuxLab     config.env       employee.txt     project.txt
ani            config.txt       home
anish@rakusafe:~$
```